R. & M. No. 2952 (5,668, 6,290, 5,917) A.R.C. Technical Report



ECHNICAL LIBRARY

ABBOTTAEROSPACE.COM

# MINISTRY OF SUPPLY AERONAUTICAL RESEARCH COUNCIL REPORTS AND MEMORANDA

# Spring Tab Flutter

## PART I

A Theoretical Investigation on Wing-Aileron-Tab Flutter

By

R. A. FRAZER, B.A., D.Sc., and W. P. JONES, M.A. of the Aerodynamics Division, N.P.L.

## PART II

Experiments on Binary Aileron-Tab Flutter

By

C. SCRUTON, B.Sc., J. WILLIAMS, B.Sc., and C. J. W. MILES of the Aerodynamics Division, N.P.L.

Crown Copyright Reserved

LONDON : HER MAJESTY'S STATIONERY OFFICE

1955 PRICE £1 55 0d NET



# Spring Tab Flutter

# Parts I and II

By

R. A. FRAZER, B.A., D.Sc., W. P. JONES, M.A., C. SCRUTON, B.Sc., J. WILLIAMS, B.Sc., and C. J. W. MILES,

of the Aerodynamics Division, N.P.L.

Reports and Memoranda No. 2952 July, 1942

#### CONTENTS

#### PART I

A Theoretical Investigation on Wing-Aileron-Tab Flutter

Page

Summ	lary													
Intro	luction													
(0	i) Scope of the Paper	••	••	••	••	••	••	••	••	• •	••	••	••	3
(7	b) Spring Tabs Considered	••	••	••	••	••	••	••	••	• • •	••	••	••	3
(0	c) The Elastic Cross-Stiffness	••			••	••	••	••	••	••	••	••	••	4
(0	i) Barred Co-ordinates and D	ynami	cal Coe	efficient	s	••	••	••	••	••	• •	••	• •	4
(8	b) The Complete Dynamical S	ystem	••	••	 	••	••	••	••	••	••		••	4 4
	y) Air Load Coefficients	icar Co	-oruma	ttes and	t Coen	icients	••	••	• •	• •	••	••	••	4 1
(8) (1	b) Inertia-Stiffness Diagrams	• •	••	••	••	••	••	••	••	••	••	• •	••	5
(1	Dipercention of Binary Flutt	er		•••	•••	••			••		•••			5
()	i) Prevention of Ternary Flut	ter	••	••	•••	••	••		••	••			•••	5
			Se	ction I	. Gen	eral T	heory							
1. E	lastic Constraints	••	••		••		·		••			• •		6
<b>2.</b> T	he Dynamical Equations	•••	••	••	•••	• •	••		••	••	••			7
3. CI	assical Derivative Theory and	d Vorte	ex The	ory	••	••	••	••	••	••	• •	• •		9
4. Sy	ymmetrical and Antisymmetri	ical Os	cillatic	ons	••	• •	••	••	• •	•••	••	• •	• •	10
5. E	limination of the Elastic Cros	s-Stiffr	iesses	••	••	••	••	••	••	••	••	• •	••	11
6. N	atural Frequencies in Vacuo a	and in	Still A	ir	••		•••			• •	••	••	• •	12
<b>7</b> . T	he Inertial Coefficients	•••	••			••	• •		• •			• •	• ·	13
8. B	inary Inertia—Stiffness Diagr	ams	•••	••	••	•••	••		••	••			•••	15
9. T	ernary Inertia—Stiffness Diag	grams	••		••	••	••	••	•••	••				17
10. Si	mplified Theory of Binary Ai	leron-	Гаb Fl	utter a	nd Cor	npariso	on with	Servo-	ruddei	Flutte	r	•••		18
(1752)														A



## CONTENTS—continued

#### PART I-continued

### Section II. Numerical Applications to Binary Flutter

					1	1								Page
11. Specification of	f Aeroplane	es				••				•••				21 21
12. Flexure–Torsio	n Flutter	• •			• •	••				• •				21
13. Flexure-Ailero	n Flutter					• •				<b>、</b> .	• •	• •		23
14. Torsion-Ailero	n Flutter		• •						••					23
15. Aileron–Tab Fl	lutter with	Spring T	`ab No	. 2			••							23
16. Prevention of A	Aileron–Ta	b Flutter	with S	Spring '	Tab No	o. 2								<b>24</b>
17. Bearing of the	Preceding	Conclusio	ons on	Servo-1	rudder	Flutter	••			• •				27
18. Aileron–Tab F	lutter with	Spring 1	ab No	. 1										28
19. Flutter Preven	tion with S	Spring Ta	ıb No.	1		• • •								28
		Section	TTT	Naman	vical Ad	Hicati	we to '	Town and	Elaitta	<i>ar</i>				
20. Preliminary Re	emarks									,				29
21. Flexure–Ailero	n–Tab Flu	tter											•••	30
22. Torsion–Aileron	n-Tab Flut	tter									••			31
23. Analysis of Dia	igrams													31
3	Section	A IV A	pprovi	mation	s to Som	no Rimo	7401 TAAR	ntia_Sti	ffmars	Diagran	44.0			01
24. Approximate A	Air-Load Co	pefficients	ррю <i>л</i> і 3						<i>jj ness</i> 1	, sugrur				31
25. Binary Flutter				••								• •		32
26. Stability Condi	itions		• •	••		•••								32
References		••	• •	• •	•••	••	•••	• •	· <b></b>	• •	••	• •	••	33
List of Symbols		•••	•••	• •	•••	•••	•••	• •	• •	••	••	••	••	35
Appendix I	••• ••	••	•••	• •	••	••	• •	• •	• •	••	••	•••	• •	37
Appendix II	•••		• •	••	••	••	••	• •	••	••	••	• •	• •	39
Appendix 111	••••••	••	••	••	••	••	••	••	••	••	• •	••	• •	41
Illustrations	•• ••	••	••	••	••	••	••	••	••	••	• •	• •		40-04
	•• ••		••	••	••		••	••	••	••	• •	••	••	00-00
					PAR	T II								
		1	Experin	nents or	n Binar	ry Ailer	ron–Ta	b Flutte	er					
1. Summary	•• ••				• •	••	••	••	••			• •		90

	•																
2.	The Mode	el	••	••	• •	••						•••	•••		• •		90
3.	Results																
	Tests of	Recon	nmend	lations	of Pa	rt I	• •			••			••	••			90
	(a) Th	ne Effec	t of L	ensity	Ratio	Δ	••	••	••	••		••	• •	••	••	•••	90
	(b) Th	ne Effec	t of A	dditio	n of Ma	ass to t	the Aile	eron	• •	••	• •	• •	• •	••	••		91
	. (c) Th	ie Effec	t of tl	ne Loc	ation o	f the T	ab Bal	ancing	Mass	••	••	• •	• •	••	••	••	91
	Tests wi	ith Flui	ld Dar	nping	and So	lid Fri	ction	••	••	••	• •	• •	• •	• •	••	• •	91
4.	Conclusion	ns	••	••	••	••	••	••	· <b>·</b> ·	••	••		••	••	•••	••	91
Τa	able	•••	••		••	•••	• •	••	• •	••	••	••	• •	••	••	••	92
A]	ppendix	••	••	••	••	••	•••	• •	••		• •	••	••	•••	••	•••	92
II	lustrations	••	••	••	••	••	••	••		• •	· ••	••		•••	•••	9	94-95

 $\mathbf{2}$ 



### PART I

### A Theoretical Investigation on Wing-Aileron-Tab Flutter

By

#### R. A. FRAZER, B.A., D.Sc., and W. P. JONES, M.A.

Summary.—A theoretical discussion is given of wing-aileron-tab flutter, with special reference to the influence of spring tab control. Numerical applications of the theory are made to two representative types of spring tab, and with the aid of special stability diagrams certain conclusions are drawn regarding the conditions for flutter prevention.

In relation to binary aileron-tab flutter it is shown that certain restrictions on the aileron-tab density ratio should be observed, and that when a balancing mass for the tab is fitted its arms should be limited to a certain length. Calculations relating to ternary flutter indicate that the possibility of ternary flutter occurring when all the possible binary types are absent is very remote.

Introduction.—(a) Scope of the Paper.—The paper gives a theoretical discussion of wingaileron—tab flutter with special reference to the influence of spring tab control on the flutter. Section I describes the analytical and graphical methods used, which are based on vortex striptheory. Section II deals with the calculated binary flutter characteristics of a particular wing system (referred to as aeroplane S), the basic data for which are derived by simplifying assumptions from those of a modern fighter aeroplane. Section III gives numerical applications to ternary flutter, and approximate methods are considered in Section IV. To avoid unnecessary complication of the main text, the derivation of the numerical data is explained in three appendices.

The main purpose of the paper is to indicate the general rules which should be observed in the design of spring tabs in order that flutter may be avoided. Numerical values for critical speeds are occasionally given, but they are intended only to illustrate tendencies and should not be interpreted as attempts to predict the critical speeds of any existing aeroplane. The graphical methods on which the final conclusions of the paper are based, are briefly explained under headings (h) and (i) of this Introduction. The conclusions reached relate solely to non-preloaded spring tabs.

(b) Spring Tabs Considered.—The possible advantages in control to be gained from spring tabs have been discussed by Gates<sup>1</sup> and Brown<sup>2</sup>. One form of spring tab is shown in Figs. 1a and 1b: the two diagrams correspond respectively to the cases in which preloading of the spring is absent, and present. Another device which has been fitted experimentally to a Spitfire and tested in flight is shown in Fig. 2.

The two devices just mentioned have different elastic characteristics, and will be distinguished as spring tabs Nos. 1 and 2. Both have in common a casing and a spring constrained plunger. With spring tab No. 1 the operating force is applied to the casing, which is mounted in the main wing and connected by a link FM to the tab lever TM; the plunger is attached to the aileron lever AI. With spring tab No. 2, which contains a single compression spring, the casing is mounted in the aileron, and the operating force is applied to a lever BCH. This lever is connected directly to the plunger and also to the tab lever by a link FM.

In the theory two fundamental constants n, N, which are in the nature of gear ratios, are introduced. They are defined by n = (AF - AI)/TM and N = AF/TM in the case of spring tab No. 1, and by n = 0 and  $N = HQ \times CS/HC \times TM$  in the case of spring tab No. 2. If the angular co-ordinates are chosen to be  $\xi$  (aileron angle relative to main wing) and  $\beta$  (tab angle relative to aileron) the constant n is the ratio  $\beta/\xi$  when the tab-aileron system is displaced but the spring is assumed centralised and locked. The constant N is the ratio  $\beta/\xi$  when the system is displaced but the control point H is held undisplaced in the direction of the operating force.

3

(1752)

A 2



(c) The Elastic Cross-Stiffness.—When  $\xi$  and  $\beta$  are adopted as the angular co-ordinates, an elastic cross-stiffness is present with both types of spring tab. This cross-stiffness is the sum of two parts—the first proportional to n times the spring tab stiffness  $\sigma$ , and the second proportional to N times the effective stiffness  $\sigma_0$  of the control circuit.

(d) Barred Co-ordinates and Dynamical Coefficients.—The presence of an elastic coupling is a great inconvenience in flutter analysis, and it is generally preferable to choose angular co-ordinates in such a way that such couplings are avoided. For example, with flexure-torsion flutter, the reference centre for the definition of the flexural co-ordinate is usually chosen to be the flexural centre with this special object in view. In the case of the spring tab it is necessary to use a linear transformation of the co-ordinates  $\xi$  and  $\beta$ . Amongst the infinite number of possible transformations by means of which the cross-stiffness can be removed, there is a particular one which offers the very great advantage that it depends only on the gear ratios n and N, and not on  $\sigma$  and  $\sigma_0$ . The new angular co-ordinates  $\xi$ ,  $\beta$  are connected with  $\xi$ ,  $\beta$  by the relations  $\xi = \xi + \overline{\beta}$  and  $\beta = n\overline{\xi} + N\overline{\beta}$ . The dynamical coefficients resulting from the transformation, which are of course linear combinations of the original coefficients, are referred to as the ' barred coefficients'. One of the barred direct elastic stiffnesses for the aileron-tab combination is directly proportional to  $\sigma_0$ , the other is proportional to  $\sigma$ , and the cross-stiffness is zero. With normal spring tabs the values of the barred aileron and tab moments of inertia, and of the barred product of inertia, are all roughly of the same order. To reduce the barred product of inertia to zero, the tab would have to be provided with a prohibitive degree of mass overbalance.

(e) The Complete Dynamical System.—The complete system (Fig. 3) consists of the port and starboard wing-aileron-tab combinations together with the control column and the interconnections. When the springs are not preloaded the possible varieties of flutter are symmetrical flutter (control column locked) and antisymmetrical flutter (control column free). Each variety can involve wing flexure and torsion and displacements of the tab and aileron, but as usually the simpler binary and ternary types will mainly be considered in numerical applications. With antisymmetrical flutter the stiffness  $\sigma_0$  is not operative. In the case of preloaded spring tabs symmetrical and antisymmetrical oscillations can occur, and more general varieties are perhaps also possible.

(f) Suffix Notation for Dynamical Co-ordinates and Coefficients.—In view of the large number of parameters involved in the theory, it is convenient to adopt a single suffix notation for the angular co-ordinates and a double suffix notation for the coefficients. Thus the usual angles  $\phi$ ,  $\theta$ ,  $\xi$ ,  $\beta$  denoting wing flexure, wing torsion and the aileron and tab angles, are replaced respectively by  $q_1$ ,  $(l/c_0)q_2$ ,  $(l/c_0)q_3$ ,  $(l/c_0)q_4$ , where  $c_0$  denotes the root chord and l is the spanwise distance of the reference section from the root. The typical inertial coefficient then is  $A_{ij}$ , and the corresponding non-dimensional coefficient is  $a_{ij}$ . For example,  $a_{33}$ ,  $a_{44}$ ,  $a_{34}$  are the non-dimensional aileron and tab moments of inertia, and the product of inertia. Similarly  $\bar{a}_{33}$ .  $\bar{a}_{44}$ ,  $\bar{a}_{34}$  are the barred coefficients corresponding to the transformed co-ordinates  $\bar{q}_1(=q_1)$ ,  $\bar{q}_2(=q_2)$ ,  $\bar{q}_3$ ,  $\bar{q}_4$ .

A somewhat similar scheme of notation is used to describe the type and variety of flutter. Thus symmetrical torsion-aileron flutter is indicated concisely as (23s) flutter, antisymmetrical flexure-aileron-tab flutter as (134a) flutter, and so on.

(g) Air-Load Coefficients.—In flutter analysis attention is usually restricted to critical conditions and to a single complex constituent motion. In the present paper, in order to accord with a notation which has now been standardised for matrices<sup>3</sup>, the complex amplitudes corresponding to  $q_1, q_2, q_3, q_4$ , are denoted by  $k_1, k_2, k_3, k_4$ , so that the critical flexural motion for instance is  $q_1 = k_1 e^{2\pi i f t}$ , where f denotes the critical frequency.

Now suppose  $Q_1$ ,  $Q_2$ ,  $Q_3$ ,  $Q_4$  to denote the non-dimensional aerodynamic moment coefficients. On the hypothesis of small oscillations the complex amplitudes of each moment coefficient must be linear in  $k_1$ ,  $k_2$ ,  $k_3$ ,  $k_4$  so that  $Q_1$ , for example, is given by an expression of the form

 $Q_{1} = - \left( \mathscr{A}_{11}k_{1} + \mathscr{A}_{12}k_{2} + \mathscr{A}_{13}k_{3} + \mathscr{A}_{14}k_{4} \right) e^{2\pi i f t},$ 

and similarly for the remaining moments. The complex coefficients  $\mathscr{A}_{ij} = C_{ij} + iB_{ij}$  are termed the *air-load coefficients*. From dimensional considerations it is evident that, if scale effect is



absent (as is assumed), the air-load coefficients can depend only on the value of the non-dimensional frequency parameter referred to some datum length, e.g., on  $\omega \equiv 2\pi f c_0/V$ , where V denotes the critical speed and  $c_0$  the root chord.

In the numerical applications the values of the air-load coefficients for aeroplane S are calculated by simple vortex strip-theory, in which the theoretical two-dimensional coefficients are integrated over the span and allowance is made for the distortion modes.

(h) Inertia-Stiffness Diagrams\*.--When the flutter is binary and no elastic cross-stiffness is present, the influence of the two moments of inertia and of the two direct elastic stiffnesses can be discussed very conveniently by a graphical method similar to that applied for flexure-torsion flutter by Cicala<sup>4</sup>. The method makes use of a ' base curve ' and a ' frequency parameter curve ', (e.g., Fig. 4), which depend only on the air-load coefficients and the product of inertia and are for convenience usually plotted on separate sheets. The sheet with the base curve is referred to as the inertia-stiffness diagram, and is used as follows. The current values of the moments of inertia are plotted in the third quadrant, and through the inertia point I so obtained the stiffness line IP is drawn having for its slope the ratio of the two elastic stiffness coefficients. Then if  $P_1$  is any intersection of IP with the base curve, and if  $IM_1$  and  $PM_1$  are parallel to the co-ordinate axes,  $PM_1$  is inversely proportional to the square of the critical frequency, and so  $\omega^2 PM_1$  is inversely proportional to the square of the corresponding critical speed. The appropriate value of  $\omega^2$  is read from the frequency parameter curve. If two such intersections occur there are two critical speeds, and if no intersections occur flutter is avoided. Examples of binary inertiastiffness diagrams in which the product of inertia also is varied are provided by Figs. 8 to 16. With some additional complications the method can be extended to ternary flutter.

(i) Prevention of Binary Aileron-Tab Flutter.—In the case of (34) flutter and spring tab No. 2, if N is kept constant and the barred product of inertia  $\bar{p}$  ( $\equiv \bar{a}_{34}$ ) is varied, the base curves resemble a set of parallel wedges pointing towards the right and with their vertices in the third quadrant (see Figs. 13, 15 and 16). With practical distributions of mass, the values of  $\bar{a}_{33}$  and  $\bar{a}_{44}$  do not differ greatly from  $\bar{p}$ , and it is found that the inertia point I always lies near the vertex of the appropriate curve. In order that flutter may be prevented absolutely (*i.e.*, for all values of  $\sigma$ and  $\sigma_0$  it is necessary that no stiffness line through I shall intersect the base curve. Since the slope of the stiffness line is always positive, the abscissa of I (namely  $\bar{a}_{44}$ ) is required to be less than the numerically smallest abscissa of the curve. Now it is found that this abscissa plots linearly against  $\bar{p}$  (Fig. 17). Hence if, in this new diagram, the vertical scale is adopted for  $\bar{a}_{44}$ , all points J ( $\bar{p}, \bar{a}_{44}$ ) lying above the line represent inertial conditions for which flutter is possible, whereas all points below the line represent conditions for which flutter is prevented absolutely. The disadvantages of a low aileron-tab density ratio will be clear from the small sketches in Fig. 17 indicating the type of covering. In para. 16 it is also shown by simple arguments that any addition of mass to the main aileron will result in the inertia point J being displaced in a direction which will improve the stability. On the other hand, addition of mass to the tab ahead of the hinge axis will produce an advantageous displacement of J only when the offset of the mass from the hinge axis is restricted within a certain limit.

The general conclusions regarding the absolute prevention of binary aileron-tab flutter with non-preloaded spring tabs of type No. 2 are stated in para. 16. In paras. 18 and 19 it is shown that the same conclusions are also valid for the more general spring tab type No. 1.

(j) Prevention of Ternary Flutter.—The problem of ternary flutter prevention is considered in paras. 20 to 23, but owing to the complicated nature of the inertia-stiffness diagrams simple stability conditions similar to those for binary flutter cannot be obtained. It is shown that both flexure-aileron-tab and torsion-aileron-tab flutter are possible under certain conditions when aileron-tab flutter is absent. Flexure-aileron-tab flutter is eliminated by static balance of the aileron  $(a_{13} = 0)$ , but torsion-aileron-tab flutter is still possible. This also is prevented by balancing the aileron dynamically  $(a_{23} = 0)$ . The possibility of ternary flutter occurring when all the binary types are absent is very remote.

<sup>\*</sup> A description of inertia-stiffness diagrams based on classical derivative theory is given in para. 10.



Acknowledgements.—The writers wish to express their indebtedness to Miss S. Skan, Mrs. J. Muir and Miss J. Francis, of the Aerodynamics Division, who carried out the greater part of the numerical work of the investigation.

#### Section I. General Theory

1. Elastic Constraints.—(a) Spring Tabs.—It is assumed first that the preloaded spring tab No. 1 (see Fig. 1b) is fitted, and that  $\xi = 0$ ,  $\beta = 0$  when the plunger is centralized. When both the aileron and the tab are given small displacements the rearward displacement of the plunger from its initial position is AI $\xi$ , and the corresponding displacement of the casing is AF $\xi$  — TM $\beta$ . Thus the right-hand spring will be picked up if

$$\mathrm{AI}\xi > \mathrm{AF}\xi - \mathrm{TM}eta$$

*i.e.*, if

$$reta > R\xi$$
 ,

where  $r \equiv TM$  and  $R \equiv AF - AI$ . In this case, if  $P_0$  denotes the preloading force in the spring, and  $\sigma$  denotes the stiffness rate, the strain energy is given by

On the other hand, if  $r\beta < R\xi$ , the left-hand spring will be engaged, and the strain energy is then given by

If spring tab No. 2 is fitted (see Fig. 2) the additional spring compression when  $\beta > 0$  is  $(CK \times TM/CS)\beta$ . Hence if  $\sigma$  denotes the stiffness rate and  $P_0$  the preloading force, the strain energy is given by

where  $r \equiv (CK \times TM/CS)$ . On comparison of (1.1) and (1.3) it is seen that the theory for spring tab No. 2 is covered by that for the particular case R = 0 of spring tab No. 1.

(b) Control Circuit.—In Fig. 3 the connections to the control column are represented by segments of cables tensioned by springs, each of stiffness  $\sigma_0$ . To simplify the diagram further, the actual control column is replaced by a nominal column  $C_0$  mounted in the plane of the wings, and the movements are shown transmitted to the tabs through levers  $L_p$ ,  $L_s$ .

The flexural and torsional wing displacements do not (in general) contribute to the strain energy of the control connections. Thus the effective variables to be considered are  $\xi_p$ ,  $\beta_p$  (the port aileron and tab angles),  $\xi_s$ ,  $\beta_s$  (the corresponding starboard angles), and lateral displacement Y of the points of attachment of the control cables to  $C_0$ .

Suppose first that spring tabs No. 1 are fitted. Then in a general displacement of the complete system the rearward displacement of the point H in Fig. 1b for the port wing is  $AF\xi_p - TM\beta_p$ . Hence the corresponding displacement of the point  $H_p'$  of the lever  $L_p$  in Fig. 3, measured inwards along the span is

$$R'\xi_{p} - \imath'\beta_{p}$$
 ,

where  $R' \equiv v AF$ ,  $r' \equiv v TM$ , and v is a gearing constant. Similar considerations apply for the starboard wing. It readily follows that the strain energy of the control connections (excluding spring tabs) is given by

$$2W_{2} = 2\sigma_{0} \left\{ (R'\xi_{p} - r'\beta_{p})^{2} + (R'\xi_{s} - r'\beta_{s})^{2} + 2Y^{2} \right\} + 4\sigma_{0}Y \left\{ (R'\xi_{p} - r'\beta_{p}) - (R'\xi_{s} - r'\beta_{s}) \right\}. \qquad \dots \qquad \dots \qquad \dots \qquad (1.4)$$

The same expression applies for spring tabs No. 2 (Fig. 2), except that for this case  $R' \equiv \nu HQ$  and  $\nu' \equiv \nu (HC \times TM/CS)$ .



(c) Complete System.—The total strain energy, obtained by the addition of  $W_1$  and  $W_2$  and the usual terms arising from wing flexure and wing torsion, is given by

$$2W = l_{\phi}/(\phi_{p}^{2} + \phi_{s}^{2}) + m_{\theta}(\theta_{p}^{2} + \theta_{s}^{2}) + \sigma \left\{ \left( r\beta_{p} - R\xi_{p} \pm \frac{P_{0}}{\sigma} \right)^{2} + \left( r\beta_{s} - R\xi_{s} \pm \frac{P_{0}}{\sigma} \right)^{2} \right\} + 2\sigma_{0} \{ (R'\xi_{p} - r'\beta_{p})^{2} + (R'\xi_{s} - r'\beta_{s})^{2} + 2Y^{2} \} + 4\sigma_{0}Y \{ R'\xi_{p} - r'\beta_{p} \} - (R'\xi_{s} - r'\beta_{s}) \} . \qquad (1.5)$$

In each of the round brackets containing ambiguities of sign, the positive or negative sign is to be taken according as  $r\beta > R\xi$  or  $< R\xi$  for the relevant wing.

The complete set of elastic moments on the port wing-aileron-tab combination, obtained by differentiation of the strain energy function, can be expressed by matrices as

where

$$\begin{split} \chi_{p} &\equiv \{\phi_{p}, \theta_{p}, \xi_{p}, \beta_{p}\}, \\ E &\equiv \begin{bmatrix} l_{\phi} & 0 & 0 & 0 \\ 0 & m_{\theta} & 0 & 0 \\ 0 & 0 & \sigma R^{2} + 2\sigma_{0}R'2 & -\sigma Rr - 2\sigma_{0}R'r' \\ 0 & 0 & -\sigma Rr - 2\sigma_{0}R'r' & \sigma r^{2} + 2\sigma_{0}r'^{2} \end{bmatrix}, \\ \tilde{\omega} &\equiv \{0 & 0 & -R & r\}, \\ \vartheta &\equiv \{0 & 0 & R' & -r'\}. \end{split}$$

The corresponding starboard elastic moments are

$$\frac{\partial W}{\partial Y} = 2\sigma_0 R'(\xi_p - \xi_s) - 2\sigma_0 r'(\beta_p - \beta_s) + 4\sigma_0 Y$$
  
=  $2\sigma_0 \vartheta'(\chi_p - \chi_s) + 4\sigma_0 Y$ , ... (1.8)

where  $\vartheta'$  denotes the transposed of  $\vartheta$ , *i.e.*, the row [0, 0, R', -r'].

(d) Spring Tab Gear Ratios.—The constants defined by

n

$$\equiv R/r \qquad \qquad N \equiv R'/r' \qquad \dots \qquad \dots \qquad \dots \qquad (1.9)$$

play an important part in the theory. They will be referred to as the spring tab gear ratios.

The first constant n measures the ratio of tab angle to aileron angle when the system is moved but the spring is assumed centralized and locked. The second constant N measures the ratio of tab angle to aileron angle when the system is moved but the control point H is held undisplaced in the direction of the operating force (see Figs. 1 and 2). With spring tab No. 2, the first gear ratio n = 0.

2. The Dynamical Equations.—It will first be assumed that the plungers of the spring tabs are in central position when the system is in equilibrium.



Let  $U_p \equiv \{L, M, H, T\}_p$  and  $U_s \equiv \{L, M, H, T\}_s$  denote the columns of the increments of aerodynamical moment on the port and starboard sides in the disturbed motion : also let A denote the inertia matrix appropriate to each wing system, and E,  $\tilde{\omega}$ ,  $\vartheta$  be the matrices defined for equations (1.6). Then the dynamical equations are as follows.

Port Wing

Starboard Wing

$$\left(A\frac{d^2}{dt^2}+E\right)\chi_s\pm P_0\tilde{\omega}-2\sigma_0\vartheta Y=U_s\ldots\ldots\ldots\ldots\ldots\ldots\ldots(2.2)$$

Control Column (of effective mass  $M_0$ )

$$M_{0}\frac{d^{2}Y}{dt^{2}} + 2\sigma_{0}\vartheta'(\chi_{p} - \chi_{s}) + 4\sigma_{0}Y = 0. \quad .. \quad .. \quad .. \quad .. \quad (2.3)$$

To express these equations in the non-dimensional form a new time variable  $\tau$ , and modified dynamical co-ordinates q are introduced, defined by

$$\tau \equiv tV/c_{0}; \qquad q_{0} \equiv Y/l q_{1} \equiv \phi; \qquad q_{2} \equiv (c_{0}/l)\theta; \qquad q_{3} \equiv (c_{0}/l)\xi; \qquad q_{4} \equiv (c_{0}/l)\beta$$
 . . . (2.4)

The last four relations can be expressed by matrices as

On application of the preceding transformations to (2.1), premultiplication of the resulting equations by  $\mu$  to retain symmetry of the inertial and elastic matrices, and division throughout by  $\rho V^2 lc_0^2$ , we obtain

$$(aD^2 + e)q_p \pm p_0\tilde{\omega} + n_0\vartheta q_0 = Q_p, \qquad \dots \qquad \dots \qquad \dots \qquad \dots \qquad (2.6)$$

in which

$$D = \frac{d}{d\tau}; \qquad a = \mu A \mu / \rho l c_0^4; \qquad e = \mu E \mu / \rho V^2 l c_0^2$$
$$p_0 = P_0 / \rho V^2 l^2 c_0; \qquad n_0 = 2\sigma_0 / \rho V^2 l c_0,$$

and

$$Q_{p} \equiv \frac{\mu U_{p}}{\rho V^{2} l^{2} c_{0}} = \left\{ \frac{L}{\rho V^{2} l^{3}}, \ \frac{M}{\rho V^{2} l^{2} c_{0}}, \ \frac{H}{\rho V^{2} l^{2} c_{0}}, \ \frac{T}{\rho V^{2} l^{2} c_{0}} \right\}_{p}.$$

A similar treatment of (2.2) yields

$$(aD^2 + e)q_s \pm p_0\tilde{\omega} - n_0\vartheta q_0 = Q_s, \qquad \dots \qquad \dots \qquad \dots \qquad (2.7)$$

while (2.3), expressed non-dimensionally, can be written

where 
$$m_0 \equiv M_0/\rho c_0^2 l$$
.  $(m_0 D^2 + 2c_0 n_0)q_0 + n_0 \vartheta'(q_p - q_s) = 0$ , ... (2.8)

In (2.6) the upper or the lower sign for  $\tilde{\omega}$  must be taken according as  $rq_{4p} - Rq_{3p} > 0$  or < 0. Similarly in (2.7) the upper or lower signs are taken according as  $rq_{4s} - Rq_{3s} > 0$  or < 0. With non-preloaded springs these restrictions do not arise since  $p_0 = 0$ . The dynamical equations with the simplification  $p_0 = 0$  are also valid for small disturbed motions and preloaded or non-preloaded springs, if the controls are assumed to be non-centralized and the force applied to the control column is kept steady. In this case the dynamical co-ordinates and the aerodynamical moments represent the deviations from the equilibrium values.

TECHNICAL LIBRARY

ABBOTTAEROSPACE.COM

The full expressions for the non-dimensional inertial and elastic coefficients  $a_{ij}$ ,  $e_{ij}$  are given by

$$a \equiv \begin{bmatrix} A_{11}/\rho l^{3}c_{0}^{2} & A_{12}/\rho l^{2}c_{0}^{3} & A_{13}/\rho l^{2}c_{0}^{3} & A_{14}/\rho l^{2}c_{0}^{3} \\ A_{21}/\rho l^{2}c_{0}^{3} & A_{22}/\rho lc_{0}^{4} & A_{23}/\rho lc_{0}^{4} & A_{24}/\rho lc_{0}^{4} \\ A_{31}/\rho l^{2}c_{0}^{3} & A_{32}/\rho lc_{0}^{4} & A_{33}/\rho lc_{0}^{4} & A_{34}/\rho lc_{0}^{4} \end{bmatrix}, \qquad \dots \dots \dots \dots \dots (2.9)$$

$$e \equiv \begin{bmatrix} l_{\phi}/\rho V^{2}l^{3} & 0 & 0 & 0 \\ 0 & m_{\theta}/\rho V^{2}lc_{0}^{2} & 0 & 0 \\ 0 & 0 & (\sigma R^{2} + 2\sigma_{0}R'^{2})/\rho V^{2}lc_{0}^{2} & (\sigma r^{2} + 2\sigma_{0}r'^{2})/\rho V^{2}lc_{0}^{2} \end{bmatrix}. (2.10)$$

3. Classical Derivative Theory and Vortex Theory.—The aerodynamic moments can be expressed either by derivative coefficients or by the more general air-load coefficients of vortex theory. It is necessary to explain the different viewpoints.

(a) Classical Derivative Theory.—Here the moment coefficients Q are represented by expressions which are linear in the accelerations, velocities, and displacements. Thus say

$$-Q = (\hat{a}D^2 + \hat{b}D + \hat{c})q$$

where  $D \equiv d/d\tau$  and  $\hat{a}$ ,  $\hat{b}$ ,  $\hat{c}$  are the matrices of the constant derivative coefficients. An important consequence of this assumption is the linearization of the dynamical equations. The most general disturbed motion can then be represented by a superposition of a finite number of exponential constituent motions  $q = k e^{\lambda \tau}$ , and the relevant values of  $\lambda$  are the roots of the usual determinantal equation. Moreover, the free constants are determined uniquely by the displacements and velocities which define the initial disturbance. In this theory the aerodynamic moments corresponding to the typical constituent are given by

$$-Q = (\hat{a}\lambda^2 + \hat{b}\lambda + \hat{c})k\,\mathrm{e}^{\lambda\tau} \equiv \mathscr{A}k\,\mathrm{e}^{\lambda\tau},\,\mathrm{say.}\qquad\ldots\qquad\ldots\qquad\ldots\qquad(3.1)$$

In particular, with a simple harmonic constituent of frequency f, the appropriate value of  $\lambda$  is  $i\omega$ , where  $\omega$  denotes the frequency parameter  $\omega = 2\pi f c_0/V$ , and then

(b) Vortex Theory.—In this theory only the critical type of motion  $q = k e^{i\omega \tau}$  is usually considered. Then

where  $\mathscr{A}$  is the matrix of the 'air-load coefficients'. These coefficients are functions of  $\omega$  only.

A theory restricted to simple harmonic oscillations is sufficient for calculations of critical speeds, but is inadequate for a proof of the familiar resolution theorems concerning symmetrical and antisymmetrical oscillations. Nor can it be applied with problems such as the discussion of the stability of steady oscillations in the case of preloaded spring tabs. The appropriate generalizations will be indicated without any attempt at formal proof.



The essential necessary assumptions are that the most general motion is expressible by the superposition of exponential constituents  $q = k e^{\lambda r}$ , where  $\lambda \equiv \mu + i\omega$  is in general complex, and that the moment coefficients corresponding to that constituent are

in which  $\mathscr{A}$  depends on  $\lambda$  only. The damping parameter  $\mu$  and the frequency parameter  $\omega$  are here defined in terms of the true damping factor  $\mu_0$  and the true frequency f by the relations  $\mu \equiv \mu_0 c_0/V$  and  $\omega \equiv 2\pi f c_0/V$ .

Now consider the small motions of a quite general aerodynamic system given by

$$(aD^2 + e)q = Q$$
,

where, as previously,  $D \equiv d/d\tau$ . The trial solution  $q = k e^{\lambda \tau}$ , in conjunction with (3.4) here leads to the condition

$$(a\lambda^2 + e + \mathscr{A})k = 0$$
,

so that the permissible values of  $\lambda$  are given by the determinantal equation

$$|a\lambda^2 + e + \mathscr{A}| = 0. \qquad \dots \qquad \dots \qquad \dots \qquad (3.5)$$

The corresponding equation obtained by classical derivative theory would be

$$|(a+\hat{a})\lambda^{2}+b\lambda+e+\hat{c}|=0. \qquad \dots \qquad \dots \qquad \dots \qquad (3.6)$$

If the system has *n* degrees of freedom (3.6) has 2n roots; on the other hand, (3.5) has an infinite number, since  $\mathscr{A}$  is in general a matrix of transcendental functions of  $\lambda$ . Hence, according to classical theory, a disturbed motion is fully determined by 2n conditions, *e.g.*, *n* displacements and *n* velocities at a given starting instant. Whereas, in vortex theory, the term ' initial disturbance' is strictly speaking meaningless. For example, suppose a wing to be moved inexorably in any manner before t = 0, and to be released at t = 0 with known velocities and displacements. Then, according to classical theory, the ensuing motion is quite independent of the movements before t = 0. On the other hand, vortex theory would take into account the antecedent air disturbances.

In the present paper vortex theory is adopted in preference to the simpler classical theory, since in the particular numerical applications considered all the air-load coefficients required can be calculated directly.

4. Symmetrical and Antisymmetrical Oscillations.—With non-preloaded spring tabs, or with preloaded spring tabs oscillating about a non-central equilibrium position, equations (2.6), (2.7) and (2.8) are applicable with the simplification  $p_0 = 0$ . In this case, if a typical constituent motion is denoted by  $\{k_p, k_s, k_0\}e^{\lambda\tau}$  and the aerodynamic moments are defined by (3.4), the equations require that

$$(a\lambda^2+e+\mathscr{A})k_p+n_0artheta k_0=0\ ,\ (a\lambda^2+e+\mathscr{A})k_s-n_0artheta k_0=0\ ,\ (m_0\lambda^2+2c_0n_0)k_0+nartheta'(k_p-k_s)=0\ .$$

These may be written

$$(a\lambda^2 + e + \mathscr{A})(k_p + k_s) = 0$$
,  
 $(a\lambda^2 + e + \mathscr{A})(k_p - k_s) + 2n_0\vartheta k_0 = 0$ ,  
 $(m_0\lambda^2 + 2c_0n_0)k_0 + n\vartheta'(k_p - k_s) = 0$ ,

and elimination of the complex amplitudes leads to the determinantal equation

$$\begin{vmatrix} a\lambda^2 + e + \mathscr{A} & 0 & 0 \\ 0 & a\lambda^2 + e + \mathscr{A} & 2n_0\vartheta \\ 0 & n\vartheta' & m_0\lambda^2 + 2c_0n_0 \end{vmatrix} = 0.$$



The permissible values of  $\lambda$  are thus given either by

$$|a\lambda^2 + e + \mathscr{A}| = 0 \qquad \dots \qquad \dots \qquad (4.1)$$

in conjunction with  $k_p = k_s$  and  $k_0 = 0$  (symmetrical oscillations): or by

$$\begin{vmatrix} a\lambda^2 + e + \mathscr{A} & 2n_0\vartheta \\ n_0\vartheta' & m_0\lambda^2 + 2c_0n_0 \end{vmatrix} = 0 \qquad \dots \qquad \dots \qquad (4.2)$$

in conjunction with  $k_{p} = -k_{s}$  (antisymmetrical oscillations).

When, as will be assumed throughout, the inertia of the control column can be neglected  $(m_0 = 0)$ , (4.2) simplifies to

$$|a\lambda^2 + \varepsilon + \mathscr{A}| = 0 \qquad \dots \qquad \dots \qquad (4.3)$$

where

 $\varepsilon \equiv e - \frac{n_0}{c_0} \vartheta \vartheta'.$ 

The matrix  $\varepsilon$ , giving the elastic stiffnesses appropriate to the antisymmetrical oscillations, is then defined similarly to  $\varepsilon$  (see (2.10)) but with the terms dependent on  $\sigma_0$  omitted.

In the more complicated case where the spring tabs are preloaded and oscillate about the central position, both symmetrical and antisymmetrical oscillations can occur, but a formal proof that these yield the most general motion has not yet been devised. The symmetrical oscillations (in which  $q_p = q_s$ ,  $q_0 = 0$  and the terms involving  $p_0$  have the same signs) are given by

$$(aD^2 + e)q \pm p_0\tilde{\omega} = Q$$
 ,

where the upper or the lower sign is taken according as  $rq_4 - Rq_3 > 0$  or < 0. The antisymmetrical oscillations are given similarly by

$$(aD^2 + \varepsilon)q \pm p_0\tilde{\omega} = Q$$
.

5. Elimination of the Elastic Cross-Stiffness.—For a discussion of the stability it is convenient to remove the cross-stiffnesses which are present in the elastic matrices e and e. This requires a change of the aileron and tab co-ordinates  $q_3$ ,  $q_4$  to new ' barred ' co-ordinates  $q_3$ ,  $q_4$ , as explained in the Introduction. If a general transformation is assumed, say

it is readily shown that the cross-stiffness will be absent in the transformed Langrangian equations provided

$$\sigma r^2(nu-w)(nv-z) + 2\sigma_0 r'^2(Nu-w)(Nv-z) = 0$$
, ... (5.1)

where  $n \ (\equiv R/r)$  and  $N \ (\equiv R'/r')$  denote the gear ratios (see (1.9)). This condition is satisfied for all values of  $\sigma$  and  $\sigma_0$  if the free constants are chosen to be u = v = 1, w = n, z = N. The relations connecting the original and the modified co-ordinates then are

to which for symmetry may be added  $q_1 = \bar{q}_1$ ,  $q_2 = \bar{q}_2$ . When this transformation is applied, the equations for symmetrical oscillations become

$$(aD^2 + \bar{e} + \bar{\mathscr{A}})\bar{q} = 0$$
, ... (5.3)

where the new inertial coefficients  $\bar{a}_{ij}$  are given by

$$\begin{bmatrix} a_{11} & a_{12} & a_{13} + na_{14} & a_{13} + Na_{14} \\ a_{21} & a_{22} & a_{23} + na_{24} & a_{23} + Na_{24} \\ a_{31} + na_{41} & a_{32} + na_{42} & a_{33} + n(a_{34} + a_{43}) + n^2a_{44} & a_{33} + Na_{34} + na_{43} + nNa_{44} \\ a_{31} + Na_{41} & a_{32} + Na_{42} & a_{33} + na_{34} + Na_{43} + nNa_{44} & a_{33} + N(a_{34} + a_{43}) + N^2a_{44} \end{bmatrix}, (5.4)$$

ABBOTTAEROSPACE.COM

ECHNICAL LIBRARY

the new elastic coefficients  $\bar{e}_{ij}$  are given by

$$\begin{bmatrix} l_{\phi}/\rho V^{2}l^{3} & 0 & 0 & 0 \\ 0 & m_{\theta}/\rho V^{2}lc_{0}^{2} & 0 & 0 \\ 0 & 0 & 2\sigma_{0}r'^{2}(N-n)^{2}/\rho V^{2}lc_{0}^{2} & 0 \\ 0 & 0 & 0 & \sigma r^{2}(N-n)^{2}/\rho V^{2}lc_{0}^{2} \end{bmatrix}, \dots (5.5)$$

and the new air-load coefficients  $\bar{\mathscr{A}}_{ij} \equiv \bar{C}_{ij} + i\bar{B}_{ij}$  are defined similarly to (5.4).

The results just stated are also applicable for the antisymmetrical oscillations except that  $\sigma_0 = 0$  in (5.5).

From (3.3) and (5.3) it is seen that for critical conditions of the system

$$|-\bar{a}\omega^{2}+\bar{e}+\bar{C}+i\bar{B}|=0.$$
 (5.6)

For the further treatment of (5.6) it is convenient to introduce the further symbols

$$Z'/\omega^{2} \equiv Z + \bar{a}_{33} = 2\sigma_{0}r'^{2}(N-n)^{2}/4\pi^{2}\rho lc_{0}^{4}f^{2},$$
  

$$W'/\omega^{2} \equiv W + \bar{a}_{44} = \sigma r^{2}(N-n)^{2}/4\pi^{2}\rho lc_{0}^{4}f^{2},$$
(6.6)

$$x \equiv X' + \bar{D}_{11};$$
  $y \equiv Y' + \bar{D}_{22};$   $z \equiv Z' + \bar{D}_{33};$   $w \equiv W' + \bar{D}_{44}...$  (5.10)

The determinant (5.6), expressed at length, is then

$$\begin{vmatrix} x + i\bar{B}_{11} & \bar{D}_{12} + i\bar{B}_{12} & \bar{D}_{13} + i\bar{B}_{13} & \bar{D}_{14} + i\bar{B}_{14} \\ \bar{D}_{21} + i\bar{B}_{21} & y + i\bar{B}_{22} & \bar{D}_{23} + i\bar{B}_{23} & \bar{D}_{24} + i\bar{B}_{24} \\ \bar{D}_{31} + i\bar{B}_{31} & \bar{D}_{32} + i\bar{B}_{32} & z_{33} + i\bar{B}_{33} & \bar{D}_{34} + i\bar{B}_{34} \\ \bar{D}_{41} + i\bar{B}_{41} & \bar{D}_{42} + i\bar{B}_{42} & \bar{D}_{43} + i\bar{B}_{43} & w + i\bar{B}_{44} \end{vmatrix}$$
(5.11)

The preceding definitions, and equations are also applicable for antisymmetrical oscillations, with the simplification Z' = 0. They can also be applied for divergence speeds, which correspond to  $\omega = 0$ . In this case there is the simplification  $B_{ij} = 0$ .

6. Natural Frequencies in Vacuo and in Still Air.—In the present theory a distinction is drawn between the natural frequencies  $f_v$  appropriate to oscillations in vacuo and the frequencies  $f_a$  appropriate to oscillation in still ' perfect air'. The equation giving the frequencies  $f_v$  can be

deduced from (5.11) by omission of the air-load coefficients and division of the rows by  $\omega^2$ . If X, Y, Z, W are as defined by (5.8), the required equation is

TECHNICAL LIBRARY

$$\begin{vmatrix} X_{v} & -\tilde{a}_{12} & -\tilde{a}_{13} & -\tilde{a}_{14} \\ -\tilde{a}_{21} & Y_{v} & -\tilde{a}_{23} & -\tilde{a}_{24} \\ -\tilde{a}_{31} & -\tilde{a}_{32} & Z_{v} & -\tilde{a}_{34} \\ -\tilde{a}_{41} & -\tilde{a}_{42} & -\xi_{43} & W_{v} \end{vmatrix} = 0 \dots (6.1)$$

ABBOTTAEROSPACE.COM

To obtain the corresponding equation for oscillations in still air, use is made of the asymptotic expressions for the air-load coefficients. When  $\omega \to \infty$   $(V \to 0)$  it is found that

$$\bar{C}_{ij}/\omega^2 \rightarrow -\bar{\gamma}_{ij}$$
;  $\bar{B}_{ij}/\omega^2 \rightarrow 0$ , ... (6.2)

where  $\bar{\gamma}_{ij}$  are positive constants such that  $\bar{\gamma}_{ij} = \bar{\gamma}_{ji}$ , which represent the aerodynamic (or 'apparent additional ') moments and products of inertia of the system in still air. The limiting form of (5.11), when the rows are divided by  $\omega^2$  and  $\omega \to \infty$ , is

$$\begin{vmatrix} X_{a} - \bar{\gamma}_{11} & -\bar{a}_{12} - \bar{\gamma}_{12} & -\bar{a}_{13} - \bar{\gamma}_{13} & -\bar{a}_{14} - \bar{\gamma}_{14} \\ -\bar{a}_{21} - \bar{\gamma}_{21} & Y_{a} - \bar{\gamma}_{22} & -\bar{a}_{23} - \bar{\gamma}_{23} & -\bar{a}_{24} - \bar{\gamma}_{24} \\ -\bar{a}_{31} - \bar{\gamma}_{31} & -\bar{a}_{32} - \bar{\gamma}_{32} & Z_{a} - \bar{\gamma}_{33} & -\bar{a}_{34} - \bar{\gamma}_{34} \\ -\bar{a}_{41} - \bar{\gamma}_{41} & -\bar{a}_{42} - \bar{\gamma}_{42} & -\bar{a}_{43} - \bar{\gamma}_{43} & W - \bar{\gamma}_{44} \end{vmatrix} = 0.$$
(6.3)

7. The Inertial Coefficients.—In past theoretical investigations the control surfaces have usually been treated as rigid and provided with two pivots only. However, on modern aeroplanes control surfaces with three or more pivots, or even with a continuous 'piano' type of hinge, are not uncommon. In the present analysis it is supposed that both the aileron and the tab are provided with hinges which are effectively continuous along the span and capable of bending deformation with the wing. On the other hand, since some limitation is necessary on the number of degrees of freedom, the control surfaces are treated as rigid in torsion. The assumption of continuous hinges ensures continuous connection between the control surfaces in all wing sections, and is necessary for a satisfactory calculation of the air-load coefficients.

Now suppose the port wing, for example, to be given a general displacement  $\phi$ ,  $\theta$ ,  $\xi$ ,  $\beta$  and let  $z_{w-a-t}$ ,  $z_{a-t}$ ,  $z_t$  denote, respectively the vertical displacements of a general point of the main wing, of the main aileron, and of the tab. The terms 'main wing' and 'main aileron' here mean the parts of the wing that remain when the aileron and tab are removed, and the part of the aileron that remains when the tab is removed. Then

where, as usual  $\eta = y/l$ , and  $f(\eta)$ ,  $F(\eta)$  are the flexural and torsional distortion modes of the wing proper. These functions are assumed chosen such that  $f(\eta) = F(\eta) = 1$  at the reference section  $\eta = 1$ .

Again, the twist of the wing proper at section  $\eta$  is  $\theta F(\eta)$ . Hence the local aileron angle (*i.e.*, the inclination to the wing at section  $\eta$ ) is

$$\xi_{\eta} = \xi + \theta \{1 - F(\eta)\}.$$

It follows that, if the aileron hinge axis lies at distance  $d_a$  behing  $OY^*$ ,

Moreover, if the tab hinge axis lies at distance  $d_t$  behind OY

\* It is here assumed for simplicity that the hinge-line is parallel to OY.



It should be noted that when  $\xi = 0$  (aileron locked central at the reference section) (7.2) does not reduce to (7.1). Thus, in the discussion of flexure-torsion flutter, the distortion modes must be taken as given by (7.1) for points of the main wing, and by (7.2) with  $\xi = 0$  for points of the aileron.

The inertial coefficients can be deduced from (7.1), (7.2), (7.3) in the usual way by expansion of the kinetic energy function

$$2T = \Sigma m \dot{z}_{w-a-i}^2 + \Sigma m \dot{z}_{a-i}^2 + \Sigma m \dot{z}_t^2,$$

where the summations are taken over the appropriate parts of the system. To express the results conveniently, let  $\Sigma$ ,  $\Sigma$ ,  $\Sigma$  denote respectively summations taken over the *complete* wing (including aileron and tab), over the complete aileron (including tab), and over the tab only. Then the inertial coefficients are found to be

$$A_{11} = \sum_{w} ml^{2}f^{2}; \qquad A_{22} = \sum_{w} mx^{2}F^{2} + \sum_{a} m\left\{(x - d_{a} + d_{a}F)^{2} - x^{2}F^{2}\right\};$$

$$A_{33} = \sum_{a} m(x - d_{a})^{2}; \qquad A_{44} = \sum_{t} m(x - d_{t})^{2};$$

$$A_{12} = A_{21} = \sum_{w} mlxfF - \sum_{a} mlf(x - d_{a})(F - 1);$$

$$A_{13} = A_{31} = \sum_{a} ml(x - d_{a})f; \qquad A_{14} = A_{41} = \sum_{t} ml(x - d_{t})f;$$

$$A_{23} = A_{32} = \sum_{a} m(x - d_{a})(x - d_{a} + d_{a}F); \qquad A_{24} = A_{42} = \sum_{t} m(x - d_{t})(x - d_{a} + d_{a}F);$$

$$A_{34} = A_{43} = \sum_{t} m(x - d_{a})(x - d_{t}) \ldots (7.4)$$

The corresponding non-dimensional coefficients  $a_{ij}$  are given by equation (2.9).

In practice both the aileron and the tab would be 'mass-balanced' on some basis. In the present paper an aileron is described as *uniformly statically balanced* if the centre of mass of the aileron in *every section* lies on the aileron hinge-line. A similar definition applies for the tab. If both conditions are satisfied the combination is said to be uniformly statically balanced. From (7.4) it is seen that with such a system  $A_{13} = A_{14} = 0$ ,  $A_{23} = A_{33}$ , and  $A_{24} = A_{34} = A_{44}$ . The inertia matrix then has the simple form

$$a = \begin{bmatrix} a_{11} & a_{12} & 0 & 0 \\ a_{21} & a_{22} & a_{33} & a_{44} \\ 0 & a_{33} & a_{33} & a_{44} \\ 0 & a_{44} & a_{44} & a_{44} \end{bmatrix} .$$
 (7.5)

The corresponding barred inertial coefficients are

$$\bar{a} = \begin{bmatrix} a_{11} & a_{12} & 0 & 0 \\ a_{21} & a_{22} & a_{33} + na_{44} & a_{33} + Na_{44} \\ 0 & a_{33} + na_{44} & a_{33} + n(n+2)a_{44} & a_{33} + (Nn+N+n)a_{44} \\ 0 & a_{33} + Na_{44} & a_{33} + (nN+n+N)a_{44} & a_{33} + N(N+2)a_{44} \end{bmatrix} .$$
(7.6)

It is readily verified that the aileron-tab barred inertias then satisfy the relation

in which  $\bar{p} \equiv \bar{a}_{34} = \bar{a}_{43}$ . If on the other hand the tab balancing is such that the aileron-tab product of inertia  $a_{34} = a_{43} = 0$ , the barred inertias for the combination are

$$\left. \begin{array}{c} \bar{a}_{33} = \bar{a}_{33} + n^2 a_{44} \\ \bar{p} = \bar{a}_{33} + n N a_{44} \\ \bar{a}_{44} = \bar{a}_{33} + N^2 a_{44} \end{array} \right\} . \qquad \dots \qquad \dots \qquad \dots \qquad \dots \qquad \dots \qquad \dots \qquad (7.8)$$



8. Binary Inertia-Stiffness Diagrams.—The graphical treatment of binary problems will be explained in relation to aileron-tab flutter.

The determinantal equation appropriate to (34s) flutter\* is (see 5.11))

which yields

$$zw = \bar{D}_{34}\bar{D}_{43} + \bar{B}_{33}\bar{B}_{44} - \bar{B}_{34}\bar{B}_{43} \equiv E_{34}, \qquad \dots \qquad \dots \qquad \dots \qquad \dots \qquad (8.2)$$

These equations can be solved for z and w to give the pairs of values

$$\begin{aligned} z_1 &= Z_1' + \bar{D}_{33} = (F_{34} + \sqrt{G_{34}})/2\bar{B}_{44} , \\ w_1 &= W_1' + \bar{D}_{44} = (F_{34} - \sqrt{G_{34}})/2\bar{B}_{33} , \end{aligned} \right\} \qquad \dots \qquad \dots \qquad (8.4)$$

$$\begin{array}{c} z_2 = Z_2' + \bar{D}_{33} = (F_{34} - \sqrt{G_{34}})/2\bar{B}_{44} , \\ w_2 = W_2' + \bar{D}_{44} = (F_{34} - \sqrt{G_{34}})/2\bar{B}_{33} , \end{array} \right\} \qquad \dots \qquad \dots \qquad \dots \qquad (8.5)$$

in which

The roots  $Z_1'$ ,  $W_1'$  and  $Z_2'$ ,  $W_2'$  represent the critical values of the elastic stiffness coefficients  $\bar{e}_{33}$ ,  $\bar{e}_{44}$  appropriate to any chosen frequency parameter  $\omega$ . The locus described by those roots in the (Z', W')-plane as  $\omega$  is varied is the analogue of the familiar 'test conic' of classical derivative theory. In fact, according to that theory, the air-load coefficients— $C_{ij}$ ,  $B_{ij}$  are, respectively, expressions of the forms  $-\hat{a}_{ij}\omega^2 + \hat{c}_{ij}$ ,  $\hat{b}_{ij}\omega$  (see (3.2)), and it is easy to show that the (Z', W') locus then is a conic section.

The test conic (or its vortex theory analogue) is convenient when it is desired to find the influence of changes of the elastic stiffnesses on the critical speed and *all the inertias are assigned*. An alternative graphical representation will now be described in which not only the elastic stiffnesses but also both *moments of inertia* are left free to be varied. Inertia-stiffness diagrams of this type have been applied by Cicala<sup>4</sup> to flexure-torsion flutter, and are particularly valuable in the discussion of measures for the prevention of flutter. Use is made of (5.8), (5.9), (8.4). (8.5), which give for the critical values of Z and W

or

$$Z_{1} = (z_{1} - C_{33})/\omega^{2}, \qquad W_{1} = (w_{1} - C_{44})/\omega^{2},$$

$$Z_{2} = (z_{2} - \bar{C}_{33})/\omega^{2}, \qquad W_{2} = (w_{2} - \bar{C}_{44})/\omega^{2}$$

$$\vdots \qquad \dots \qquad \dots \qquad (8.7)$$

These critical values depend only on the air-load coefficients and on the product of inertia  $\bar{p} \equiv \bar{a}_{34} = \bar{a}_{43}$ . Accordingly, if Z and W are plotted as ordinate and abscissa, the locus of the critical points, when  $\omega$  is varied, will be independent of the elastic stiffness coefficients and the moments of inertia. In Fig. 4a, which illustrates such a diagram, the critical locus is called the 'base curve'. Two points of the curve will (in general) correspond to a given value of  $\omega$ .

To prepare the diagram for use, the current values of the moments of inertia are plotted in the third quadrant, and through the 'inertia point' I so obtained the 'stiffness line' IP is drawn, having for slope the stiffness ratio  $Z'/W' = 2\sigma_0 r^2/\sigma r^2$  (see (5.5) and (5.7)). Let P<sub>1</sub>, P<sub>2</sub> be the points

<sup>\*</sup> For notation see Introduction (f).



of intersection of this line with the base curve. Then from (5.8) and (8.7) it follows that the critical frequencies  $f_1$ ,  $f_2$  corresponding to these two points are given by

$$Z_{1} + \tilde{a}_{33} \equiv 2\sigma_{0}r'^{2}(N-n)^{2}/4\pi^{2}\rho lc_{0}^{4}f_{1}^{2} = P_{1}M_{1},$$

$$Z_{2} + \tilde{a}_{33} \equiv 2\sigma_{0}r'^{2}(N-n)^{2}/4\pi^{2}\rho lc_{0}^{4}f_{2}^{2} = P_{2}M_{2},$$

$$(8.8)$$

or, alternatively, by  $W_1 + \tilde{a}_{44} = \text{IM}_1$  and  $W_2 + \tilde{a}_{44} = \text{IM}_2$ .

The critical speeds  $V_1$ ,  $V_2$  corresponding to  $f_1$ ,  $f_2$  respectively, can be deduced from the relations

$$Z_{1}' \equiv 2\sigma_{0}r'^{2}(N-n)^{2}/\rho V_{1}^{2}lc_{0}^{2} = \omega_{1}^{2}P_{1}M_{1},$$

$$Z_{2}' \equiv 2\sigma_{0}r'^{2}(N-n)^{2}/\rho V_{1}^{2}lc_{0}^{2} = \omega_{2}^{2}P_{2}M_{2},$$
(8.9)

where  $\omega_1$ ,  $\omega_2$  are the values of the frequency parameter appropriate to the points  $P_1$ ,  $P_2$ . The required values of  $\omega$  (or its square) can either be read off directly from a scale of  $\omega$  marked on the base curve, or a supplementary 'frequency parameter diagram' (Fig. 4b) can be used, in which  $\omega$  is plotted as ordinate against the abscissa of the base curve. In Figs. 4 the dotted portions of the base curve and frequency parameter curve are assumed to correspond.

With antisymmetrical flutter Z' = 0, and the stiffness line is parallel to the axis OW. The critical speeds corresponding to the two intersections  $P_1'$ ,  $P_2'$  are then given by

$$\frac{\sigma r^2 (N-n)^2 / \rho V_1^2 l c_0^2}{\sigma r^2 (N-n)^2 / \rho V_2^2 l c_0^2} = \omega_1'^2 I P_1', \qquad (8.10)$$

Some of the simpler properties of a base curve may be noted. As already remarked each value of  $\omega$  generates a pair of points of the curve. Such pairs may be described as 'conjugates': for example, the points B, B' in Fig. 4a corresponding to B, B' in Fig. 4b are conjugates. However, the conjugates corresponding to the peak A in Fig. 4b coalesce into a single point A on the base curve<sup>\*</sup>. From (8.4), (8.5) and (8.7) it is seen that the chord connecting a pair of conjugates has the slope  $-\overline{B}_{33}/\overline{B}_{44}$ , which is independent of the product of inertia  $\overline{p}$ . When  $\omega$  is kept constant but  $\overline{p}$  is varied, the centres of the chords connecting conjugate points are collinear, and the locus of the conjugate points is a conic section.

A complete survey of the flutter characteristics for all possible inertias and stiffnesses would require a specification of the base curves and frequency parameter curves for all values of  $\bar{p}$ ranging from  $+\infty$  to  $-\infty$ . A few additional theorems may be mentioned, which aid a general description of this complete family of curves. The first of these concerns the asymptotic form of the base curve. When  $|\bar{p}| \to \infty$ 

$$Z|\bar{p} \to \{\bar{B}_{34} + \bar{B}_{43} \pm \sqrt{(-\bar{\Delta})}\}/2\bar{B}_{44}, \\W|\bar{p} \to \{\bar{B}_{34} + \bar{B}_{43} \pm \sqrt{(-\bar{\Delta})}\}/2\bar{B}_{33}, \} \qquad \dots \qquad \dots \qquad \dots \qquad \dots \qquad (8.11)$$

in which

The function  $\Delta$  will be recognized as the discriminant of the dissipation function, and its sign is (in general) positive when  $\omega$  is very large. The maximum value of  $\omega$  attained on the asymptotic base curve is accordingly given by the condition  $\Delta = 0$ , which is independent of the gear ratios N, n. This value does not, of course, represent the greatest  $\omega$  attained as  $\bar{p}$  varies from  $+\infty$  to  $-\infty$ . The maximum maximorum value is, in fact, given by the two conditions  $G_{34} = 0$ ,  $\partial G_{34}/\partial \bar{p} = 0$ , which yield after considerable reduction

$$\bar{\Delta} - (\bar{C}_{34} - \bar{C}_{43})^2 = (N - n)^2 \{ \Delta - C_{34} - C_{43} \}^2 = 0 \quad \dots \quad \dots \quad \dots \quad \dots \quad \dots \quad (8.13)$$

\* The maximum value of  $\omega$  is given by the condition  $G_{34} = 0$ .



From the first of these it follows that the greatest  $\omega$  attained is independent of N and n. The corresponding value of  $\bar{p}$  is, however, not invariant. Similar considerations apply for the minima of  $\omega$ , which are in general definite and distinct from  $\omega = 0$  in the case of aileron-tab flutter. On the other hand, with some types of flutter, the range of  $\omega$  extends continuously down to  $\omega = 0$ . It is to be noted also that with (34) flutter the base curves will have horizontal and vertical asymptotes corresponding to the small definite values of  $\omega$  for which  $\bar{B}_{33} = 0$  and  $\bar{B}_{44} = 0$ . The situations of these asymptotes are independent of  $\bar{p}$ , but vary with N and n.

An inertia-stiffness diagram can be extended to provide also a graphical representation of natural frequencies. The base curves  $H_v$ ,  $H_a$  corresponding respectively to oscillations *in vacuo* and in still air (*see* para. 6) are the two rectangular hyperbolae

$$(H_v) \ldots ZW = p^2 \ldots (8.15)$$

$$(H_a) \ldots (Z - \bar{\gamma}_{33})(W - \bar{\gamma}_{44}) = (\bar{p} + \bar{\gamma}_{34})^2 \ldots \ldots \ldots \ldots \ldots \ldots (8.16)$$

These curves are used in the way already explained for critical frequencies. Since  $\bar{a}_{33}\bar{a}_{44} > \bar{p}^2$  no inertia point I can lie above the lower branch of  $H_v$ .

Finally it may be remarked that if the air-load coefficients accord with classical derivative theory, so that, say,  $\bar{C}_{ij} = -\hat{a}_{ij}\omega^2 + c_{ij}$  and  $\bar{B}_{ij} = b_{ij}\omega$ , the base curve will be a conic section. This curve is an ellipse or a hyperbola according as V > or < 0, where

Examples of binary inertia-stiffness diagrams are given in Section II.

9. Ternary Inertia-Stiffness Diagrams.—The (134) type of flutter will be taken as an example. In this case the determinantal equation (5.11) is

$$\begin{vmatrix} x + i\bar{B}_{11} & \bar{D}_{13} + i\bar{B}_{13} & \bar{D}_{14} + i\bar{B}_{14} \\ \bar{D}_{31} + i\bar{B}_{31} & z + i\bar{B}_{33} & \bar{D}_{34} + i\bar{B}_{34} \\ \bar{D}_{41} + i\bar{B}_{41} & \bar{D}_{43} + i\bar{B}_{43} & w + i\bar{B}_{44} \end{vmatrix} = 0 . \qquad (9.1)$$

This gives on expansion

$$xzw - E_{34}x - E_{41}z - E_{13}w + F_{34}\bar{B}_{11} + F_{41}\bar{B}_{33} + F_{13}\bar{B}_{44} + K_0 = 0, \qquad \dots \qquad (9.2)$$

and

 $\bar{B}_{11}zw + \bar{B}_{33}wx + \bar{B}_{44}xz - F_{34}z - F_{41}z - F_{13}w + 2\bar{B}_{11}\bar{B}_{33}\bar{B}_{44} - E_{34}\bar{B}_{11} - E_{41}\bar{B}_{33} - E_{13}\bar{B}_{44} + H_0 = 0, \quad (9.3)$ 

where  $E_{ij}$ ,  $F_{ij}$  are defined by relations similar to (8.2), (8.3) and

$$K_{0} + iH_{0} = (\bar{D}_{13} + i\bar{B}_{13})(\bar{D}_{34} + i\bar{B}_{34})(\bar{D}_{41} + i\bar{B}_{41}) + (\bar{D}_{31} + i\bar{B}_{31})(\bar{D}_{43} + i\bar{B}_{43})(\bar{D}_{14} + i\bar{B}_{14}) \dots \dots \dots \dots \dots \dots \dots \dots (9.4)$$

The critical values of x, z, w, for any assigned value of  $\omega$ , are thus given by the curve of intersection of the cubic and quadric surfaces (9.2), (9.3).

For the ternary case

$$X = (x - C_{11})/\omega^{2} = X'/\omega^{2} - \bar{a}_{11}$$

$$Z = (z - \bar{C}_{33})/\omega^{2} = Z'\omega^{2} - \bar{a}_{33}$$

$$W = (w - \bar{C}_{44})/\omega^{2} = W'/\omega^{2} - \bar{a}_{44}$$

$$17$$
(9.5)

в

(1752)



The direct analogue of Fig. 4a would be a three-dimensional representation, consisting of a ' base surface' defined by the critical values of X, Z, W, an inertia point situated in the appropriate octant, and a stiffness line determined by the values of the three elastic stiffness coefficients. This representation must, of course, be replaced by a plane diagram.

The ternary plane diagram is shown in Fig. 5. The curve marked  $X = \infty$  corresponds to an infinite value of X' and thus to  $l_{\phi} = \infty$ . It is accordingly identical with the base curve in Fig. 4a. The remaining base curves in the ternary diagram correspond to assigned values of X, which are marked against the curves. In the third quadrant two inertia points I  $(\bar{a}_{44}, \bar{a}_{33})$  and I'  $(\bar{a}_{44}, \bar{a}_{33} + \bar{a}_{11})$  are plotted, and stiffness lines IP, I'P' are drawn through these points having respectively the slopes Z'/W' and X'/W'. Now suppose P<sub>1</sub> to be the critical point of IP which is appropriate to all three assigned elastic stiffnesses. Then

$$\mathbf{P}_1'\mathbf{N} = \mathbf{I'N}\left(\frac{X'}{W'}\right) = \mathbf{I'N}\left(\frac{X+\tilde{a}_{11}}{W+\tilde{a}_{44}}\right) = X + \tilde{a}_{11} \,.$$

But  $P_1'N = P_1'M + \tilde{a}_{11}$ . It follows that  $P_1$  must be chosen to lie on that base curve X = kfor which the condition  $P_1'M = k$  is satisfied. The critical speed is then obtained from any one of the relations  $X' = \omega^2 P_1 N$ ,  $Z' = \omega^2 P_1 M$ ,  $W' = \omega^2 I M$ . The required values of  $\omega$  (or  $\omega^2$ ) can be found from a supplementary frequency parameter diagram.

10. Simplified Theory of Binary Aileron-Tab Flutter and Comparison with Servo-rudder Flutter.-To conclude Section I the treatment of (34) flutter will be reviewed independently in the light of classical derivative theory and without the use of non-dimensional coefficients. The equations obtained will be compared with those given for binary servo-rudder flutter by Duncan and Collar<sup>5</sup> in R. & M. 1527. The springs are assumed to be non-preloaded.

(a) Aileron-Tab Flutter.—As in paras. 1 and 2, let  $\beta$  denote the tab angle and  $\xi$  the aileron angle. Then the simplified dynamical equations appropriate to symmetrical flutter, stated in a notation similar to that used in R. & M. 1527, are as follows.

Tab Hinge Moments.

$$d_{2}\ddot{\beta} + e_{2}V\dot{\beta} + (f_{2}V^{2} + t_{\beta})\beta + p\ddot{\xi} + j_{2}V\dot{\xi} + (k_{2}V^{2} + t_{\xi})\xi = 0. \quad .. \quad (10.1)$$

Aileron Hinge Moments.

$$p\ddot{\beta} + e_3V\dot{\beta} + (f_3V^2 + h_\beta)\beta + g_3\ddot{\xi} + j_3V\dot{\xi} + (k_3V^2 + h_\xi)\xi = 0. \quad \dots \quad \dots \quad (10.2)$$

In these  $d_2$ ,  $f_2$ , p denote the inertial constants, e, f, j, k are the aerodynamical derivatives, and (see para. 1(c))

$$t_{\beta} = \sigma r^{2} + 2\sigma_{0} r^{\prime 2}; \quad t_{\xi} = h_{\beta} = -\sigma Rr - 2\sigma_{0} R^{\prime} r^{\prime}; \quad h_{\xi} = \sigma R^{2} + 2\sigma_{0} R^{\prime 2}. \quad \dots \quad \dots \quad (10.3)$$

The equations for antisymmetrical flutter are similar except that  $\sigma_0 = 0$ .

If, as in para. 5 a general transformation

<del>.</del> .

$$\begin{split} \beta &= z\bar{\beta} + w\bar{\xi} \\ \xi &= v\bar{\beta} + u\bar{\xi} \end{split} \qquad \dots \qquad \dots \qquad \dots \qquad \dots \qquad \dots \qquad \dots \qquad (10.4)$$

is applied, the cross-stiffness is found to be absent from the new dynamical equations provided

On substitution from (10.3) this condition becomes

$$\sigma(zr - vR)(wr - uR) + 2\sigma_0(zr' - vR')(wr' - uR') = 0.$$

The particular transformation given by z = R'/r' = N, w = R/r = n, v = u = 1, is independent of the elastic stiffnesses, and yields the set of barred coefficients given in Table A below.



#### TABLE A

Barred Dynamical Coefficients

New coefft.	Value in terms of original coefficient	New coefft.	Value in terms of original coefficient
$\bar{d}_2$	$d_2N^2 + 2pN + g_3$	Ī	$d_2nN + p(n+N) + g_3$
$\overline{e}_2$	$e_2N^2 + (j_2 + e_3)N + j_3$	$\overline{e}_3$	$e_2nN + j_2n + e_3N + j_3$
$ar{f}_2$	$\int f_2 N^2 + (k_2 + f_3) N + k_3$	$\bar{f}_3$	$\int f_2 nN + k_2 n + f_3 N + k_3$
$\bar{\mathcal{P}}$	$d_2nN + p(n+N) + g_3$	$\overline{g}_3$	$d_2n^2 + 2pn + g_3$
$\overline{j}_2$	$e_2nN + j_2N + e_3n + j_3$	$\overline{j}_3$	$e_2n^2 + (j_2 + e_3)n + j_3$
$\overline{k}_2$	$f_2nN + k_2N + f_3n + k_3$	$\bar{k}_3$	$\int_{2} n^{2} + (k_{2} + f_{3})n + k_{3}$
$\bar{t_{eta}}$	$t_{\beta}N^2 + 2h_{\beta}N + h_{\xi} = \sigma r^2 (N-n)^2$	$ar{h}_eta$	0
$\overline{t}_{\xi}$	0	$ar{h}_{\xi}$	$t_{\beta}n^2 + 2h_{\beta}n + h_{\xi} = 2\sigma_0 r'^2 (N-n)^2$

The stability can now be discussed either by a test conic, or by means of an intertia-stiffness diagram. In either case use is made of the condition for simple harmonic oscillations. This can be written

$$\begin{vmatrix} -\bar{d}_{2}\omega^{2} + \bar{f}_{2} + i\omega\bar{e}_{2} + W', & -\bar{p}\omega^{2} + \bar{k}_{2} + i\omega\bar{f}_{2} \\ -\bar{p}\omega^{2} + \bar{f}_{3} + i\omega\bar{e}_{3}, & -\bar{g}_{3}\omega^{2} + \bar{k}_{3} + i\omega\bar{f}_{3} + Z' \end{vmatrix} = 0, \dots \dots (10.6)$$

where  $\cdot$ 

$$W' \equiv \tilde{t}_{\beta}/V^2 = \sigma r^2 (N-n)^2/V^2$$
,  
 $Z' \equiv \bar{h}_{\xi}/V^2 = 2 \hat{\sigma}_0 r'^2 (N-n)^2/V^2$ 

and  $\omega \equiv 2\pi f/V$ , where f denotes the critical frequency<sup>\*</sup>.

To obtain the test conic,  $\omega$  is eliminated between the two real equations implicit in (10.6), and  $W' + \tilde{f}_2$ ,  $Z' + \tilde{k}_3$  are treated as co-ordinates in a plane. The stiffness line has the slope  $Z'/W' = 2\sigma_0 r'^2/\sigma r^2$ , and the stiffness point has the co-ordinates  $\tilde{f}_2$ ,  $\tilde{k}_3$ .

To obtain the inertia-stiffness diagram use is made of the substitutions

The two real equations implicit in (10.6) then are

$$\begin{array}{c} (\omega^2 W + f_2)(\omega^2 Z + \bar{k}_3) = E \\ (\omega^2 W + \bar{f}_2)\bar{f}_3 + (\omega^2 Z + \bar{k}_3)\bar{e}_2 = F \end{array} \right\}, \qquad \dots \qquad \dots \qquad \dots \qquad (10.8)$$

where

$$\begin{split} E &\equiv (-\ \bar{p}\,\omega^2 + \ \bar{k}_2)(-\ \bar{p}\,\omega^2 + \ \bar{f}_3) \,+\, \omega^2(\bar{e}_2\bar{j}_3 - \ \bar{e}_3\bar{j}_2) \;, \\ F &\equiv (-\ p\,\omega^2 + \ \bar{k}_2)(\bar{e}_3 + \ (-\ p\,\omega^2 + \ \bar{f}_3)\bar{j}_2 \;. \end{split}$$

\* Note that in the present form of analysis the 'frequency parameter'  $\omega$  is not non-dimensional.

19

(1752)

Equations (10.8) can be solved to give

$$\omega^{2}Z = -\bar{k}_{3} + \frac{F \pm \sqrt{G}}{2\bar{\ell}_{2}} \\ \omega^{2}W = -\bar{f}_{2} + \frac{F \pm \sqrt{G}}{2\bar{j}_{3}} \end{cases}, \qquad \dots \qquad \dots \qquad \dots \qquad \dots \qquad \dots \qquad (10.9)$$

in which  $G \equiv F^2 - 4\bar{e}_2\bar{j}_3E$ . These results correspond to equations (8.4) to (8.7). The locus of points W, Z is the base curve, the inertia point I has the co-ordinates  $-d_2, -\bar{g}_3$ , and the slope of the stiffness line is  $2\sigma_0 r'^2/\sigma r^2$ . With antisymmetrical flutter  $\sigma_0 = 0$ . The diagram is used as explained in para. 8 for Figs. 4a and b, except that in the present case  $\omega = 2\pi f/V$ .

ABBOTTAEROSPACE.COM

TECHNICAL LIBRARY

(b) Servo-rudder Flutter.—Equations (10.1) and (10.2) are applicable for servo-rudder flutter provided  $\beta$ ,  $\xi$  are taken to denote, respectively, the displacement of the servo-rudder relative to the main rudder, and the displacement of the main rudder relative to the fuselage. The expressions given in R. & M. 1527 for the elastic stiffnesses, converted to the notation of the present report, are\*

$$egin{aligned} t_eta &= (ef/q) + (e\sigma_\zeta/q) + \sigma_\xi \ , \ h_\xi &= v^2(ef/q) + (f\sigma_\zeta/q) \ , \ t_\xi &= h_eta &= - v(ef/q) \ . \end{aligned}$$

In these,  $\nu$  is a non-dimensional constant defined solely by the geometry of the servo-control mechanism,  $e, f, \sigma_{\xi}, \sigma_{\xi}$  are independent elastic stiffnesses, and  $q \equiv f + \nu^2 e + \sigma_{\xi}$ . Equation (10.5) here leads to the condition

The particular transformation of co-ordinates adopted in R. & M. 1527 leaves the rudder co-ordinate unchanged and is given by z = 1, v = 0, u = 1 with

The new direct stiffnesses are then

$$ar{t}_eta = t_eta = (ef/q) + (e\sigma_\xi/q) + \sigma_\xi$$
  
 $h_eta = f\{(
u^2 e + \sigma_\xi)\sigma_\xi + e\sigma_\xi\}/(ef + e\sigma_\xi + q\sigma_\xi)$ .

This transformation, although relatively simple, has the disadvantage that the value of w given by (10.11) depends on the elastic stiffnesses. Hence if a test conic is calculated by means of the transformed dynamical co-ordinates appropriate to a given w, it should strictly only be used for stiffness variations restricted by the condition  $(10.11)^{\dagger}$ .

In general, a transformation which satisfies (10.10) and is independent of all four stiffnesses  $e, f, \sigma_{\xi}, \sigma_{\zeta}$ , does not exist. However, in the important special case where  $\sigma_{\zeta} = 0$  (direct spring constraint at rudder hinge axis absent) the required conditions are satisfied by z = v, w = 0, v = u = 1, and these yield

It will be seen that the theory is then the same as that for aileron-tab flutter with n = 0. The correspondence is indicated below.

Servo-rudder Flutter	Aileron–Tab Flutter
$\sigma_{\xi} = 0$ $\nu (= \text{OA/AS in R. \& M. 1527})$ $\sigma_{\xi}$ ef/q	$ \begin{array}{l} R = 0 \; (n = 0) \\ N \; (= R'/r') \\ \sigma r^2 \\ 2 \sigma_0 r'^2 \end{array} $

\* The symbols  $\beta$ ,  $\xi$ ,  $t_{\beta}$ ,  $h_{\xi}$ ,  $t_{\zeta}$ ,  $\nu$ , correspond to  $\xi$ ,  $\zeta$ ,  $h_{\xi}$ ,  $m_{\zeta}$ ,  $h_{\zeta}$ , n, of R. & M. 1527.

† This difficulty appears to have been overlooked in R. & M. 1527.



TECHNICAL LIBRARY

ABBOTTAEROSPACE.COM

11. Specification of Aeroplane S.—The numerical applications relate to a particular system which will be referred to as 'aeroplane S'. The dimensions, stiffnesses, and inertias are derived in Appendices 1 and 2 by simplifications from data supplied for the Spitfire. Appendix 3 deals with the calculation of the air-load coefficients. A brief specification of the system follows.

(a) Plan-form and dimensions.—The tapered Spitfire wing-aileron-tab combination is replaced by a rectangular combination of constant section, but the effective areas, spans, and mean chords of the components are left unaltered (see Appendix I and Fig. 6).

(b) Flexural axis and distortion modes.—The straight flexure axis is assumed to lie at 0.3c from the leading edge\*. To avoid unessential complications, both the flexural and the torsional displacements are taken to vary linearly with the distance y from the wing root. The two displacements are, respectively, chosen proportional to the distance from the sections y = 0.35s and y = 0.2s, and the displacements inboard of these sections are neglected. These simplified linear modes offer a fair first approximation to the curved modes adopted by Duncan and Lyon<sup>6</sup> for a typical cantilever wing.

(c) Positions of spring tab and reference section.—In the Spitfire tests spring tab No. 2 (n = 0) was used, and two alternative lengths of the tab lever TM were available. The short lever corresponded to N = 5.61 and the long lever to N = 3.03. The link FM was fitted at about two-thirds of the tab span from the inboard end of the tab. In the calculations the link is for convenience assumed to be placed at the inboard end, and the corresponding wing section is chosen as the reference section (see Fig. 6). Rounded values are adopted for the gear ratios, namely N = 6 and 3: the cases N = 2 and 10 are also investigated.

(d) Elastic and inertial coefficients.—The results of the calculations are analysed mainly by means of inertia-stiffness diagrams. In the practical interpretation of these diagrams, the values, of the stiffnesses and inertias deduced from the *Spitfire* are accepted as the standard of reference, but allowance is made for possible variations due to changes of spring-tab design or to modifications of the weight of outer cover. The numerical values of the elastic stiffnesses are given in Tables 4 and 5, and the inertial coefficients are summarised in Tables 6, 7, and 8 and Fig. 7.

(e) Air-load coefficients.—Both the aileron and the tab are assumed to be hinged continuously along their leading edges. The air-load coefficients are given in Tables 9.

12. Flexure-Torsion (12) Flutter.—The tab and aileron are here assumed to be locked in central position to the wing in the reference section. In this first example the steps involved in the calculation of the base curve will be explained in some detail. The case is relatively simple, since barred coefficients are not introduced, and the distinction between symmetrical and anti-symmetrical flutter does not arise.

The equation corresponding to (8.1) is here

$$egin{array}{cccc} |x+iB_{11} & D_{12}+iB_{12} \ |D_{21}+iB_{21} & y+iB_{22} \end{array} | = 0$$
 ,

where

and

$$x = \omega^2 X + C_{11};$$
  $y = \omega^2 Y + C_{22}.$ 

 $D_{21} = -p\omega^2 + C_{21};$   $D_{12} = -p\omega^2 + C_{12};$   $p = a_{12} = a_{21},$ 

$$\begin{aligned} X' &= l_{\phi} / \rho V^2 l^3 , \qquad X' / \omega^2 = X + a_{11} = l_{\phi} / 4\pi^2 \rho l^3 c_0^2 f^2 , \\ Y' &= m_{\theta} / \rho V^2 l c_0^2 , \qquad Y' / \omega^2 = Y + a_{22} = m_{\theta} / 4\pi^2 \rho l c_0^4 f^2 . \end{aligned}$$

<sup>\*</sup> From later information it appeared that the flexural axis on the *Spitfire* lay unusually far forward at about 0.27c. The difference is unlikely to invalidate the conclusions of this report, which are intended to be purely qualitative.

The critical pairs of values of X, Y, corresponding to (8.4), (8.5), (8.6), (8.7), may be written

ABBOTTAEROSPACE.COM

TECHNICAL LIBRARY

$$X = \left(\frac{F_{12} \pm \sqrt{G_{12}}}{2B_{22}} - C_{11}\right) / \omega^{2}$$
  

$$Y = \left(\frac{F_{12} \mp \sqrt{G_{12}}}{2B_{11}} - C_{22}\right) / \omega^{2}$$
... .. (12.1)

in which

$$\begin{split} E_{12} &\equiv D_{12} D_{21} + B_{11} B_{22} - B_{12} B_{21} \, . \\ F_{12} &\equiv D_{12} B_{21} + D_{21} B_{12} \, , \\ G_{12} &\equiv F_{12}^{\ 2} - 4 B_{11} B_{22} E_{12} \, . \end{split}$$

Now suppose that the base curve corresponding to j = 0.1 is required. From Table 7 it is seen that the appropriate value of the product of inertia is p = 2.19. Also the air-load coefficients required are given by the first four columns in Tables 9A and 9B. The calculations of the functions  $F_{12}$ ,  $E_{12}$ ,  $G_{12}$  are most conveniently arranged in tabular form\*, with the first column reserved for the entries  $\omega$ . To obtain a preliminary rough description of the base curve, the values  $\omega = 1, 2, 3, 4, 5$  can first be tried, and spaces can be left for intermediate values, if required later. In the case considered each of the first four trial values of  $\omega$  leads to a positive value for  $G_{12}$ , and consequently to a real pair of points on the base curve (see (12.1)). However  $G_{12} < 0$ when  $\omega = 5.0$ . The actual maximum permissible  $\omega$  can be determined by interpolation from a graph of  $G_{12}$  against  $\omega$ . An extension of the calculations to a few lower values of  $\omega$  (e.g.,  $\omega = 0.4$ and 0.2) yields a perfectly satisfactory plot of the base curve. The total time occupied is a matter of a few hours—provided, of course, the values of the air-load coefficients are known.

Figs. 8a and 8b show the base curves and frequency parameter curves for  $p = 0, 1 \cdot 10, 2 \cdot 19, 4 \cdot 39$  (corresponding to  $j = 0, 0 \cdot 05, 0 \cdot 1$  and  $0 \cdot 2$ ). To illustrate the use of these diagrams in the prediction of critical speeds and critical frequencies, the two moments of inertia are assumed to be  $a_{11} = 27 \cdot 5$  and  $a_{22} = 1 \cdot 09$ , as for aeroplane S in Table 7. These values are plotted in the third quadrant, to give the marked inertia point I. Next, the elastic stiffnesses for aeroplane S taken from Table 5 are  $l_{\phi}/\rho l^3 = 3 \cdot 74 \times 10^6$  and  $m_{\theta}/\rho l c_0^2 = 1 \cdot 16 \times 10^6$ , which yield the value  $Y'/X' = 1 \cdot 16/3 \cdot 74 = 0 \cdot 31$  for the slope of the stiffness line IP. The critical frequencies  $f_1, f_2$ , when  $j = 0 \cdot 1$  for example, can then be found from the relations

$$Y_1 + a_{22} \equiv m_0/4\pi^2 
ho lc_0^4 f_1^2 = P_1 M_1 = 19 \cdot 09 \;,$$
  
 $Y_2 + a_{22} \equiv m_0/4\pi^2 
ho lc_0^4 f_2^2 = P_2 M_2 = 2 \cdot 68 \;.$ 

which yield (when  $c_0 = 5.87$ )  $f_1 = 6.68$  c.p.s. and  $f_2 = 17.84$ . To obtain the critical speeds  $V_1$ ,  $V_2$ , the ordinates  $\omega_1 = 0.09$  and  $\omega_2 = 0.675$  are read from the curve for j = 0.1 in Fig. 8b. Then

$$\begin{split} Y_{1}' &\equiv m_{\theta}/\rho V_{1}{}^{2}lc_{0}{}^{2} = \omega_{1}{}^{2}\mathrm{P}_{1}\mathrm{M}_{1} \doteq (0 \cdot 09)^{2} \times 19 \cdot 09 ,\\ Y_{2}' &\equiv m_{\theta}/\rho V_{2}{}^{2}lc_{0}{}^{2} = \omega_{2}{}^{2}\mathrm{P}_{2}\mathrm{M}_{2} = (0 \cdot 675)^{2} \times 2 \cdot 68 ,\\ V_{1} &= 2740 \text{ ft/sec (1870 m.p.h.),}\\ V_{2} &= 976 \text{ ft/sec (665 m.p.h.)} \end{split}$$

giving

In the present case the equations giving the natural frequencies are

where by (23.16)  $\gamma_{11} = 2.606$ ,  $\gamma_{22} = 0.1167$ ,  $\gamma_{12} = 0.4079$ . These represent the aerodynamic inertias.

<sup>\*</sup> The parameter p should first be left general in the tabulation of F and E if curves are required for a range of values of the product of inertia,



TECHNICAL LIBRARY

ABBOTTAEROSPACE.COM

13. *Flexure-Aileron* (13) *Flutter.*—The tab is here assumed to be locked in central position to the aileron. Figs. 9 and 10 show the appropriate diagrams, which will be almost self-explanatory after the details given in para. 12.

In Fig. 9a the two inertia points  $I_1$ ,  $I_2$  represent respectively an unbalanced (complete) fabric aileron and an unbalanced aluminium aileron. An indication of the type of covering is provided by the small rectangles drawn against the inertia points : a plain rectangle signifies fabric, and a shaded rectangle aluminium.

The stiffness lines drawn through  $I_1$  and  $I_2$  and marked by arrows are appropriate to symmetrical flutter, and have the slope (see Table 5)

$$rac{Z'}{X'} = rac{(2 \sigma_0 R'^2 / 
ho l c_0{}^2)}{(l_{\phi} / 
ho l^3)} = rac{4227}{3 \cdot 74 imes 10^6} = 0 \cdot 0112_5 \ .$$

The stiffness lines for antisymmetrical flutter (not shown in Fig. 9a) are horizontal. In Fig. 10a, which illustrates the advantages of static balance and static overbalance, the curves are shown to a greatly reduced scale.

14. Torsion-Aileron (23) Flutter.—The appropriate diagrams are Figs. 11a and 11b (for, unbalanced or statically balanced ailerons), and Figs. 12a and 12b (for dynamically balanced ailerons,  $a_{23} = 0$ ). In Fig. 11a the code rectangles drawn against the inertia points are similar to those in Fig. 9a, except that a balancing arm is shown when the aileron is uniformly statically balanced. The points  $I_1$ ,  $I_2$  relate to fabric covering, and  $I_3$ ,  $I_4$  to aluminium. In Table 7 the product of inertia appropriate to a balanced aileron with aluminium covering is given as 0.0395. To avoid unnecessary calculations, the base curve already available for  $a_{23} = 0.037$  is adopted for this case, and the density of the aluminium is assumed reduced by about 6 per cent. Thus  $I_4$  is shown plotted with an ordinate 0.037 instead of 0.0395.

The numerical results appended to Fig. 11a are of some interest. Antisymmetrical flutter occurs with both types of covering, whether the aileron is statically balanced or not. The balancing is definitely advantageous here because it raises the lower critical speed and also tends to compress the speed range leading to flutter. Symmetrical flutter is present only with the metal covering. In this case the static balancing is markedly disadvantageous in the sense that it greatly reduces the lower critical speed, but is advantageous in the sense that it greatly compresses the speed range for flutter. Briefly, static balancing tends to suppress the antisymmetrical flutter at high speeds and the symmetrical flutter at low speeds. To effect this pressing out process completely, it is necessary to proceed to true dynamic balance  $(a_{23} = 0)$ , which involves static overbalance. This is shown by Fig. 12a.

15. Aileron-Tab (34) Flutter with Spring Tab No. 2.—The diagrams relating to aileron-tab flutter were calculated by the formulae given in para. 8. For simplicity those appropriate to spring tab No. 2 were considered first.

Results for N = 2.—Table 8 shows that when N = 2 the practical range of values for  $\bar{p}$  is from about 0.005 to 0.04. It was, however, thought desirable in this first case to extend the calculations to a few higher values of  $\bar{p}$ , in order to indicate the changes as the asymptotic condition  $\bar{p} \to \infty$  is approached. Figs. 13a and 13b show, to a large scale, the parts of the curves for  $\bar{p} = 0$  to 0.0125 which are of practical interest. The complete curves for  $\bar{p} = 1.0$ , 10.0 and  $\infty$  are shown to a greatly reduced scale in Figs. 14a and 14b.



The inertia point  $I_1$  in Fig. 13a is appropriate to a fabric aileron and fabric tab (both unbalanced) with  $\bar{p} = 0.0054$ , while  $I_2$  refers to a fabric aileron and aluminium tab (both balanced) with  $\bar{p} = 0.0128$ . As in Fig. 4a the slope of the stiffness line for symmetrical flutter is given by  $Z'/W' = 2\sigma_0 r'^2/\sigma r^2$ ; this is independent of N. If the elastic coefficients for aeroplane S are adopted (Table 5) the slope works out as 29.27, and the line is accordingly nearly parallel to OZ. The stiffness lines corresponding to antisymmetrical flutter (not marked in Fig. 13a) are, of course, parallel to OW.

In practical cases the values of  $\bar{a}_{33}$ ,  $\bar{a}_{44}$  and  $\bar{p}$  for any given aileron-tab combination do not differ widely, and the inertia point always lies close to the vertex of the base curve. In Fig. 13a both  $I_1$  and  $I_2$  lie wholly to the right of their appropriate base curves, so that in these cases flutter could not occur for any values of the elastic stiffnesses.

The curves in Fig. 14a and 14b are mainly of theoretical interest. One complicating feature is the presence of the vertical and horizontal asymptotes. These are common to all the curves, and correspond to the values  $\omega = 0.085$  and 0.06 for which the two direct damping air-load coefficients  $\bar{B}_{33}$  and  $\bar{B}_{44}$  respectively vanish<sup>\*</sup>. From an inspection of the directions along which  $\omega$  decreases along the base curves (as indicated by the arrows), it is seen that for the smaller values of  $\bar{p}$  (e.g.,  $\bar{p} = 0$  to 1.0) the point of the base curve corresponding to maximum  $\omega$  is situated on the small sharp indentation of the curve near the origin. The wedge-shaped curves in Fig. 12a are, of course, merely the indentations shown on enlarged scale. As  $\bar{p}$  increases from zero, the indentation becomes more and more rounded, and moves away from the origin towards one of the asymptotes<sup>†</sup>. Eventually it *passes through* the asymptote and thus arrives, greatly modified, in the third quadrant. The curled parts of the branch shown in the third quadrant for  $\bar{p} = 10$ , though to some extent diagrammatic, illustrate one stage of development.

It is of some interest to compare the curves in Fig. 14a with those which would be obtained on the basis of classical derivative theory. The theoretical air-load coefficients used to construct Fig. 14a can be represented approximately, over the restricted range  $\omega = 1.0$  to 5.0, by the expressions

where

$$B_{ij} = \hat{b}_{ij}, \qquad \bar{C}_{ij} = \hat{c}_{ij} - \hat{a}_{ij}\omega^2$$

$10^2 \hat{b} =$	0.896	1.00];	$10^{2} \hat{c} =$	[1;46	2.85];	$10^4 \hat{a} =$	$\lceil 5 \cdot 56 \rceil$	5.72]
	0.912	1.03		$1 \cdot 48$	2.97		5.72	5.90

If these values are adopted for the derivative coefficients the expression defined by (8.17) is found to be negative, so that the new base curves will be hyperbolic. This is illustrated by the dotted curve marked C in Fig. 14a, which is the single hyperbolic branch forming the complete new base curve corresponding to  $\dot{p} = 0$ . The nose of this hyperbola fits closely into the indentation of the original base curve, as is seen better from Fig. 13a where points calculated for C are represented by black spots.

Results for N = 3, 6, 10.—The diagrams for these cases (Figs. 15 and 16) are similar to Figs. 13 and require no separate explanation. For the relevant practical values of the inertias, reference should be made to Table 8. The natural frequencies calculated for N = 3 by formulae similar to (12.2) and (12.3) are given in Table 2.

16. Absolute Prevention of Aileron-Tab Flutter with Spring Tab No. 2.—With diagrams of the types shown in Figs. 13a, 15a and 16a flutter is prevented absolutely (*i.e.*, for all stiffness ratios) when the inertia point I lies to the right of the vertex of the base curve. The condition to be satisfied is accordingly

\* See remarks following (8.14).

<sup>&</sup>lt;sup>†</sup> The particular asymptote has not been determined.



where  $W_{\text{max}}$  denotes the maximum abscissa of the base curve appropriate to the particular values of  $\oint$  and N considered<sup>\*</sup>. The values of  $W_{\text{max}}$  for the various cases are given in Table 3, and plotted against  $\oint$  in Fig. 17. To simplify the diagram the actual entries from Table 3 are not marked, but it is found that the points corresponding to any given N lie very closely on straight lines passing just above the origin. If now the vertical scale in the diagram is adopted for  $\bar{a}_{44}$ , it follows from (16.1) that all points J ( $\bar{\phi}$ ,  $\bar{a}_{44}$ ) lying below the line appropriate to a given N represent inertial conditions for which flutter is prevented absolutely. To illustrate this, seven particular points are marked in Fig. 17, all referring to N = 6. The pair  $J_1$ ,  $J_2$  relate to an aluminium aileron-tab combination,  $J_2$ ,  $J_4$  to a fabric-aluminium combination, and  $J_5$ ,  $J_6$ ,  $J_7$  to a fabric-steel combination. An inspection of the positions of these points relative to the line for N = 6 shows that a low value for the aileron-tab density coefficient  $\varDelta$  is extremely disadvantageous. In Appendix II, the mass and density coefficients are defined as follows. If  $\mu_a'$  (slugs) denotes the mass of the unbalanced aileron with the tab removed, and  $\mu_i$  denotes the mass of the unbalanced tab, then

 $\sigma_{a} \text{ (aileron mass-coefficient)} \equiv \mu_{a}' / (s_{a}c_{a}^{2} - s_{t}c_{t}^{2}) ,$   $\sigma_{t} \text{ (tab mass-coefficient)} \equiv \mu_{t} / s_{t}c_{t}^{2} ,$   $\varepsilon_{a} \text{ (aileron density ratio)} \equiv \rho / \sigma_{a} ,$   $\varepsilon_{t} \text{ (tab density ratio)} \equiv \rho / \sigma_{t} ,$   $\Delta \text{ (aileron-tab density ratio)} \equiv \rho_{a} / \sigma_{t} = \varepsilon_{t} / \varepsilon_{a} .$  (16.2)

The values for fabric, aluminium, and steel components are estimated respectively as  $\sigma = 0.03837$ , 0.1151, 0.3125 (or  $\varepsilon = 0.06197$ , 0.01675, 0.006197 with standard air). These give  $\Delta = 1.0$ , 0.27, 0.1 for fabric-fabric, fabric-aluminium, and fabric-steel combinations.

The disadvantages of a low aileron-tab density ratio are confirmed if, as an approximation on the safe side, the straight lines in Fig. 17 are replaced by lines actually passing through the origin and the true and approximate values of  $W_{\rm max}$  are made to agree closely for the highest value of  $\bar{p}$  to be considered. Then  $W_{\rm max}$  becomes proportional to  $\bar{p}$ , so that

$$-W_{\rm max}/\bar{p} = M$$
, ... .. .. .. .. .. (16.3)

where M is a positive constant depending on N only<sup>†</sup>. The values adopted for M are stated below Table 3, which also compares the true and approximate values of  $W_{\text{max}}$ . From (16.1) and (16.3) it follows that the stability condition can be replaced safely by

The values of the ratio  $\bar{a}_{44}/\bar{p}$ , as calculated for unbalanced tabs from the formulae in Table 6 are shown plotted against  $\Delta$  in Fig. 18. The points shown as heavy black spots on the curves have for ordinates the appropriate values of M. Hence the safe values for the density ratio lie to the right of the black spots. The danger associated with a low density ratio is immediately obvious.

The influence of mass balancing on the stability will next be considered. First, assume any datum inertial condition for the combination, and suppose a mass m to be added to the aileron (but *not* to the tab) at any distance X from the aileron hinge axis. Then the aileron moment of inertia  $A_{33}$  will be increased by  $mX^2$ , and the other two inertial constants will remain unchanged. From the relations

$$ar{A}_{_{33}} = A_{_{33}}$$
,  $ar{A}_{_{44}} = A_{_{33}} + 2NP + N^2A_{_{44}}$ ,  $ar{P} = A_{_{33}} + NP$ , ... (16.5)

it follows that  $\delta \bar{A}_{44} = mX^2$  and  $\delta \bar{P} = mX^2$ , so that both these increments are positive and  $\delta \bar{A}_{44}/\delta \bar{P} = 1$ . Thus also  $\delta \bar{a}_{44}/\delta \bar{P} = 1$ . Now it is important to note that the gradients of all the lines in Fig. 17 exceed unity. Hence, in the particular mass variation considered, the inertia

 $\dagger$  It may be noted the M plots almost linearly against N.

<sup>\*</sup> Note that this abscissa is negative in the cases considered.



point J in the diagram will be moved *downwards* in relation to its appropriate line (*i.e.*, J approaches closer to the line if initially in the unstable region, and away from the line if initially in the stable region). Hence any addition of mass to the main aileron, and in particular balancing or overbalancing, is beneficial.

Next, suppose the mass *m* to be added to the tab instead of to the aileron. Its position is assumed to be at distance  $\lambda \equiv \lambda_i c_i$  forward of the tab hinge axis and at distance  $\Lambda \equiv D - \lambda$  behind the aileron hinge axis, where *D* denotes the distance between the axes. Then it is readily shown that

$$\begin{split} \delta \bar{A}_{44} &= m(N\lambda - \Lambda)^2 \\ \delta \bar{P} &= m\Lambda(\Lambda - N\lambda) \; . \\ \frac{\delta \bar{A}_{44}}{\delta \bar{P}} &= \frac{\delta \bar{a}_{44}}{\delta \bar{D}} = 1 - N\left(\frac{\lambda}{\Lambda}\right) \end{split}$$

Hence

The increment  $\delta \bar{A}_{44}$  is always positive, but  $\delta \bar{P}$  is positive only when

$$\frac{\Lambda}{\lambda} \equiv \frac{(D/c_i) - \lambda_i}{\lambda_i} > N . \qquad \dots \qquad \dots \qquad \dots \qquad \dots \qquad \dots \qquad (16.6)$$

The gradient  $\delta \bar{A}_{44}/\delta \bar{P}$  is then less than unity, and the displacement of the inertia point J is accordingly in the safe direction. The condition (16.6) requires the tab balancing mass to lie behind the point which divides the distance between the aileron and tab hinge axes in the ratio N. When, on the other hand  $\Lambda < N\lambda$ ,  $\delta \bar{P}$  is negative and  $\delta \bar{A}_{44}$  is positive as before. J then moves upwards and to the left, and the displacement is in the unsafe direction. In particular, massbalancing of the tab alone may be expected to be disadvantageous if (16.6) is violated.

If  $c_a/c_i = 4.35$ , as for aeroplane S, the limiting values of  $\lambda_i$  given by (16.6) for N = 2, 3, 6, 10 are respectively about 1.11, 0.83, 0.48, 0.3. The ineffectiveness of the tab balance when  $\lambda_i = 1.0$  and N = 6, and its effectiveness when  $\lambda_i = 0.3$ , are illustrated by the relative positions of the points  $J_1$ ,  $J_1'$  and  $J_2$  in Fig. 17.

The following general conclusions are drawn regarding the absolute prevention of binary aileron-tab flutter with non-preloaded spring tab No. 2.

- (a) The density ratio  $\triangle$ , as defined by (16.2), should if possible exceed 0.5, and is preferably of the order unity.
- (b) Any addition of mass to the main aileron only (e.g., an aileron balancing or overbalancing mass) is advantageous.
- (c) The tab-balancing mass, if present, must be placed behind the position which divides the distance between the aileron and tab hinge axes in the spring tab gear ratio N.
- (d) If condition (c) cannot be satisfied, tab mass balance should not be attempted.

Condition (d), which requires the omission of tab mass balance in certain cases, may at first sight appear surprising. The ineffectiveness of the balancing in those cases is, of course, attributable to the presence of the elastic cross-stiffness due to the spring tab. The importance of this elastic coupling is strikingly illustrated by a comparison of the base curves already considered (e.g., Fig. 13a) with those shown in Fig.19 for the same aileron-tab combination, but with the cross-stiffness removed. The new curves are appropriate to the unbarred dynamical coefficients, and are thus applicable for an aileron with the normal type of control, but carrying an elastically hinged tab. It is seen that as the product of inertia  $a_{34}$  reduces the oval base curves shrink continuously, and disappear when  $a_{34} < 0.44 \times 10^{-4}$  about. Hence mass balance in this case has its normal stabilising influence.

Another relevant illustration is provided by a simpler problem—the flexure-torsion flutter of a cantilever wing. If, in the analysis of this motion, the reference centre R is chosen *behind* the flexural centre F instead of at F as normally, a negative cross-stiffness is introduced, as with the spring tab. The flexural and torsional co-ordinates defined in relation to R here correspond



to the unbarred aileron and tab co-ordinates, and the conventional wing co-ordinates referred to F correspond to the barred aileron and tab co-ordinates. It is easy to see that in this case mass balance of the wing about R (corresponding to tab mass balance) is not necessarily always advantageous. For example, if the balancing mass is added behind F, the product of inertia *relative to* F *is increased*, and the critical speed is therefore likely to be reduced.

17. Bearing of the Preceding Conclusions on Servo-rudder Flutter.—In para. 10 a correspondence was established between binary tab-aileron flutter and binary servo-rudder flutter. It is therefore of some importance to consider the bearing of the conclusions drawn in para. 16 on servorudder flutter.

Numerical data appropriate to a particular full-scale aeroplane are given in para. 8 of R. & M. 1527<sup>5</sup>. Expressed in the notation of para. 10 the data are as follows.

Servo- rudder	Value for full scale	Main rudder	Value for full scale
$d_2$	0.037 (standard)	Þ	0.22 (standard)
$e_2$	0.008	$e_3$	0.09
$f_2$	0.0038	$f_3$	0.088
þ	0.22 (standard)	g <sub>3</sub>	6.0
$\frac{1}{j_2}$	0.025	$j_3$	0.80
$k_2$	0.0013	k <sub>3</sub>	+ 0.072
$t_{\beta}$	+126.3	$h_{\beta}$	-305.76
te	-305.76	$h_{\xi}$	+834.7
-		1	

TABLE A (para. 17)

Dynamical Coefficients for Servo-rudder System (units: slug/ft/sec)

The standard values of $a_2$ and $g_3$ are stated to have been derived from experiments in air,
and $p$ was calculated. For the special servo-linkage considered $\sigma_{\xi} = 0$ and $\nu = 2.73$ : hence the
transformation formulae in Table A of para. 10 are applicable with $n = 0$ and $N (= r) = 2.73$ .
The barred elastic stiffnesses for rudder-bar locked work out as $\bar{t}_{\theta} = 106 \cdot 56$ , $\bar{h}_{\varepsilon} = 834 \cdot 7$ ,
$\bar{t}_{\varepsilon} = \bar{h}_{\theta} = 0$ . With rudder-bar free $\bar{h}_{\varepsilon} = 0$ . The barred inertias corresponding to various inertial
conditions of the system are as follows.

# TABLE B (para. 17)Values of Barred Inertias

# $(\lambda$ denotes length of balancing arm in inches)

Inertial condition of system	$\bar{d}_2$	$ar{ otag}$	$\bar{g}_3$
Standard Servo-rudder statically balanced* ( $\lambda = 6$ )	7·477 7·615	$6.601 \\ 6.912$	6.0 $6.724$
Servo-rudder dynamically balanced ( $\lambda = 6$ ) Servo-rudder dynamically balanced ( $\lambda = 10.2$ )	7·667 7·488	$7.047 \\ 6.525$	$7.047 \\ 6.525$

\* New inertias calculated from data given in Ref. 7.

27



It may be added that the values of  $e_2$  and  $f_2$  estimated by vortex strip-theory, and the use of approximate representations for the air-load coefficients, worked out as 0.0065 and 0.00314 (compared with the tabulated values 0.008 and 0.0038). In this calculation the triangular fin was replaced by a rectangular fin of approximately equal area, and a correction factor  $1.4/\pi$  was applied to the derivatives to allow for the small aspect ratio 1.47 of the fin-rudder-servo combination.

Figs. 20a and 20b show the base curves and the frequency-parameter curves corresponding to values of  $\bar{p}$  ranging from 6.601 to 7.2. With the standard inertias (point  $I_1$ ) the critical speeds for rudder-bar locked and rudder-bar free roughly estimated from the diagrams are respectively 285 ft/sec and 290 ft/sec. The corresponding speeds given in R. & M. 1527 are 292 and 286. When the tab is statically balanced (point  $I_2$ ) or dynamically balanced by the short arm (point  $I_3$ ) no flutter occurs. This is also shown by the points  $J_1$ ,  $J_2$ ,  $J_3$  in Fig. 21, which corresponds to Fig. 17.

The values of the constants in (16.6) for the particular aeroplane considered are D = 34.55 in.,  $c_i = 10.2$  in., and N = 2.73. The maximum advisable length of the servo-balancing arm is then given by  $\lambda = D/(N + 1) = 9.26$  in. The point  $J_3'$  in Fig. 21, corresponding to  $\lambda = 10.2$ , illustrates the case in which mass balance fails.

18. Aileron-Tab Flutter with Spring Tab No. 1.—With spring tabs No. 1 the gear ratio defined by n is not zero, and the 'barred' inertial and aerodynamic coefficients for this case accordingly differ from those given for spring tabs No. 2. Formulae for the new inertial coefficients are given by (5.4) and the appropriate aerodynamic coefficients are defined similarly. The two gear ratios n and N are always subject to the restriction N > n. The numerical values of the inertial coefficients for N = 3 and n = 0.5, 1.0 and 2.0 are given in Table 10, and the corresponding elastic stiffnesses are obtained from (5.5) and Table 5.

19. Flutter Prevention with Spring Tab No. 1.—The inertia-stiffness diagrams for spring tabs No. 1 closely resemble those for spring tabs No. 2 which are shown in Figs. 15a and 15b. In view of this similarity, the actual diagrams for spring tabs No. 1 are omitted, but the maximum abscissa  $W_{\text{max}}$  for each curve is plotted against  $\bar{p}$  in Fig. 22. The values of the gear ratios assumed in the calculations are N = 3 and n = 0.5, 1.0 and 2.0. The case n = 0 corresponds to spring tabs of No. 2 type. For each value of n,  $W_{\text{max}}$  plots linearly against  $\bar{p}$ , so that  $-W_{\text{max}}/\bar{p}$  tends to a constant value M for large values of  $\bar{p}$ , where M is a function of N and n only. As for spring tabs No. 2, the stability condition  $\bar{a}_{44} < -W_{\text{max}}$  is then replaced by

$$\frac{a_{44}}{\overline{p}} < M \qquad \dots \qquad \dots \qquad \dots \qquad \dots \qquad \dots \qquad \dots \qquad (19.1)$$

where M > 1.

This inequality can be written alternatively

where  $\bar{a}_{44} - \bar{p}$  is independent of  $a_{33}$  and therefore unaffected by addition to mass to the main aileron. It should be noted that in practice  $\bar{a}_{44} > \bar{p}$  since by (5.4)

$$\bar{a}_{44} - \bar{p} = (N - n)(p + Na_{44})$$
.

The expression on the right is necessarily positive unless the tab is considerably over-mass-balanced.

It will now be shown that the conclusions drawn in para. 16 regarding the effects of massbalancing apply to both types of spring tab. Firstly, if a mass m is added to the main aileron at a distance X from the aileron hinge axis, the resulting increments of the inertial constants are

$$\begin{split} \delta A_{33} &= mX^2 , \qquad \delta P = 0 , \qquad \delta A_{44} = 0 , \\ \delta \bar{A}_{33} &= mX^2 , \qquad \delta \bar{P} = mX^2 , \qquad \delta \bar{A}_{44} = mX^2 . \end{split}$$



In this case, the stability condition (19.2), for the modified system, can be written

$$ar{A_{44}} - ar{P} < (M-1)(ar{P}+mX^2)$$
 ,

and it is then clear that the addition of the mass m is beneficial.

Secondly, suppose a mass *m* to be added to the tab at a distance  $\lambda (\equiv \lambda_i c_i)$  forward of the tab hinge axis and at a distance  $\Lambda (\equiv D - \lambda)$  behind the aileron hinge axis. Then the additions to the inertias are

$$\begin{split} \delta A_{33} &= m\Lambda^2 , \qquad \delta P = - m\Lambda\lambda , \qquad \qquad \delta A_{44} = m\lambda^2 \\ \delta \bar{A}_{33} &= m\Lambda^2 , \qquad \delta \bar{P} = m(\Lambda - n\lambda)(\Lambda - N\lambda), \qquad \delta \bar{A}_{44} = m(\Lambda - N\lambda)^2. \end{split}$$

The stability condition (19.2) for the modified system can here be expressed as

$$ar{A}_{44} - ar{P} = m\lambda(N-n)(\Lambda-N\lambda) < (M-1)(ar{P}+\deltaar{P})$$
.

Now both  $m\lambda(N - n)(\Lambda - N\lambda)$  and  $\delta \overline{P}$  are positive provided  $\Lambda > N\lambda$ , and hence, in this case also, mass-balancing of the tab is beneficial.

It may be noted that since spring tab No. 2 can be regarded as a particular spring tab of No. 1 type for which n = 0, the stability conditions for both types may be expected to be similar as just shown.

#### Section III.—Numerical Applications to Ternary Flutter

20. Preliminary Remarks.—In this section flexure–aileron–tab (134) and torsion–aileron–tab (234) flutter are investigated for a wing fitted with spring tab No. 2. Inertial values corresponding to a fabric aileron and tab are used in the calculations, and a value N = 2 is taken for the spring tab gear ratio. A qualitative analysis of ternary flutter under the following inertial conditions is made :—

- (i) flutter of (134) type with
  - (a) aileron unbalanced
    - (b) aileron statically balanced  $(a_{13} = 0)$ ,
- (ii) flutter of (234) type with
  - (a) aileron unbalanced
  - (b) aileron statically balanced  $(a_{13} = 0)$
  - (c) aileron dynamically balanced  $(a_{23} = 0)$ .

The corresponding inertia stiffness diagrams show that

- (a) flutter of the (134) and (234) types is possible when the aileron is unbalanced although binary (34) flutter is absent
- (b) flutter of (134) type is eliminated by static balancing  $(a_{13} = 0)$ , but (234) type flutter is still possible
- (c) flutter of (234) type is prevented by balancing the aileron dynamically  $(a_{23} = 0)$ .

The ternary inertia-stiffness diagrams are usually complicated, and no simple criterion for ternary flutter prevention analogous to that given for binary (34) flutter in para. 16 and para.19 can be deduced. However, the least favourable conditions for flutter can be recognised from an examination of the relatively simple binary curves from which the positions of the asymptotes for the ternary diagrams are determined. When the vertical asymptotes are far to the left and the horizontal asymptotes are well below the first inertia point I, the possibility of flutter is very remote. This condition implies that all types of binary flutter must be eliminated.

The notation used in the following analysis is listed in Section II except for some symbols which are introduced in para. 21 to simplify the computational work.

21. Flexure-Aileron-Tab (134) Flutter.—The equations of motion for (134) type flutter are given by (9.2) and (9.3) and they can be expressed in the binary form of para. 8 by writing

ABBOTTAEROSPACE.COM

TECHNICAL LIBRARY

$$z' = z - \frac{\bar{E}_{13}}{x}, \qquad w' = w - \frac{\bar{E}_{14}}{x}$$

$$C_{33}' = \bar{C}_{33} - \frac{\bar{E}_{13}}{x}, \qquad C_{44} = \bar{C}_{44} - \frac{\bar{E}_{14}}{x}$$

$$B_{33}' = \bar{B}_{33} - \frac{\bar{F}_{13}}{x} + \frac{\bar{B}_{11}\bar{E}_{13}}{x^2}$$

$$B_{44}' = \bar{B}_{44} - \frac{\bar{F}_{14}}{x} + \frac{\bar{B}_{11}\bar{E}_{14}}{x^2}$$

$$E_{34}' = E_{34} - \frac{K_1}{x} + \frac{E_{13}\bar{E}_{13}}{x^2}$$

$$F_{34}' = F_{34} - \frac{H_0 + 2\bar{B}_{11}\bar{B}_{33}\bar{B}_{44}}{x}$$

$$+ \frac{K_1\bar{B}_{11} + E_{13}F_{14} + E_{14}F_{13}}{x^2} - \frac{2\bar{B}_{11}E_{13}E_{14}}{x^3}$$

$$K_1 = K_0 + \bar{B}_{11}F_{34} + \bar{B}_{33}F_{14} + \bar{B}_{44}F_{13}$$

On substitution, equations (9.2) and (9.3) reduce to

$$z'w' = E_{34}' B_{44}'z' + B_{33}'w' = F_{34}'$$
 ... ... ... ... ... ... (21.2)

and give

$$z' = \omega^{2}Z + C_{33}' = \frac{F_{34}' \pm \sqrt{G_{34}'}}{2B_{44}'}$$

$$w' = \omega^{2}W + C_{44}' = \frac{F_{34}' \pm \sqrt{G_{34}'}}{2B_{33}'}$$
... ... (21.3)

where

$$G_{34}' = F_{34}'^2 - 4B_{33}'B_{44}'E_{34}'.$$

The method of calculation adopted is to regard the value of  $X (= (x - C_{11})/\omega^2)$  as assigned and to derive by (21.3) pairs of values of Z and W corresponding to a range of values of  $\omega$  for which  $G_{34}$  is positive (see para. 9 and Fig. 5). The graph of Z against W is the required base curve appropriate to the given value of X.

The base curves are usually complicated by the presence of asymptotes. From (21.2) and (21.3) it is seen that when  $\omega$  is such that  $B_{33}'$  is zero, w' becomes infinite and z' = 0. Accordingly,  $W \to \infty$  at  $Z = -C_{33}'/\omega^2$  (where  $\omega$  has the appropriate value or values), and similarly  $Z \to \infty$  at  $W = -C_{44}'/\omega^2$  when  $B_{44}' = 0$ . Alternatively the positions of the asymptotes and the corresponding  $\omega$  values can be deduced from the base curves and frequency parameter diagrams relevant to the various associated types of binary flutter. For instance, equations (9.2) and (9.3) reduce to

$$xz = E_{13}$$
 ,  $B_{33}x + B_{11}z = F_{13}$ 

which define flutter of the flexure-aileron (13) type. The values of Z and  $\omega$  at which  $W \to \infty$  for a particular value of X can therefore be read off the curves, in Figs. 9a and 9b corresponding to the appropriate value of  $a_{13}$ . For example, if  $a_{13} = 0.0836$ , and -7.0 < X < -2.0, the values of Z are greater than  $-a_{33}$  and therefore lead to asymptotes above the inertia point in the ternary diagram (see Fig. 23a, 23b).



Diagrams for (134) type flutter are given for the following conditions :---

(a) aileron unbalanced (Figs. 23a, 23b),

and

(b) aileron statically balanced (Fig. 24).

The diagrams show that flutter can occur in the first case but not in the second, as then the relevant curves have no branches to the right and above the inertia point  $(-\bar{a}_{44}, -\bar{a}_{33})$ . Tables 11, 12, 13 give the values of Z and W for a range of values of  $\omega$  and X for each inertial condition, but some of the results are omitted in the diagrams.

22. Torsion-Aileron-Tab (234) Flutter.—The simplified equations of motion for this type of flutter are similarly obtained by writing y for x and replacing the suffix 1 by 2 wherever it occurs in para. 21. Inertia-stiffness diagrams of Z against W are plotted for assigned values of Y for the following cases :—

- (a) aileron unbalanced (Figs. 25a, 25b, 25c)
- (b) aileron statically balanced (Figs. 26a, 26b)
- (c) aileron dynamically balanced (Fig. 27).

Flutter is possible under conditions (a) and (b) but not under (c). The calculated values of Z and W are given for various values of  $\omega$  and Y in Tables 14, 15, 16, 17, 18 and most of these results are included in the diagrams.

23. Analysis of Diagrams.—A graphical method of analysing the ternary inertia-stiffness diagrams is described in para. 9, but it is not always easy to apply. It is sometimes more convenient to find the values of  $l_{\phi}$  which lead to flutter for various values of X. It is shown in para. 9 and Fig. 5 that flutter occurs when X = k, if  $l_{\phi}$  is such that

$$\frac{X'}{W'} = \frac{(k + \bar{a}_{11})}{W_1 + \bar{a}_{44}} = \frac{l_\phi c_0^2}{\sigma r^2 N^2 l^2} \qquad \dots \qquad \dots \qquad \dots \qquad \dots \qquad \dots \qquad \dots \qquad (23.1)$$

where  $W_1$  is the abscissa of the point of intersection  $P_1$  of the Z'/W' stiffness line with the curve for X = k, and where Z', W' are assumed to be known. Values of  $l_{\phi}$  can be calculated by (23.1) for various values of k for which curves have been drawn. The value of k corresponding to the flexural stiffness  $l_{\phi}$  of the wing can then be deduced from a curve of  $l_{\phi}$  against k. The corresponding frequency parameter can be obtained by a supplementary curve of  $\omega_1$  against k or  $l_{\phi}$ , where  $\omega_1$ is the value of the frequency parameter at  $P_1$ . The critical flutter speed would then be given by  $X' = \omega^2(k + \bar{a}_{11})$ . However, critical speeds are not estimated in this section as the intervals between the values of X, Y and  $\omega$  chosen in the calculations are not sufficiently small to allow a quantitative analysis of the diagrams.

### Section IV.—Approximations to some Binary Inertia-Stiffness Diagrams

24. Approximate Air-Load Coefficients.—Good approximations to the inertia-stiffness diagrams for flexure-torsion, flexure-aileron, torsion-aileron and aileron-tab flutter are obtained by using approximate air-load coefficients of the form  $C_{ij} = \hat{c}_{ij} - \hat{a}_{ij}\omega^2$ ,  $B_{ij} = \hat{d}_{ij} + \hat{b}_{ij}\omega^2$  as listed in Table 19. The constants  $\hat{a}_{ij}$  and  $\hat{b}_{ij}$  represent the limiting values of  $-c_{ij}/\omega^2$  and  $B_{ij}/\omega$  as  $\omega \to \infty$ , and  $\hat{c}_{ij}$ ,  $\hat{d}_{ij}$  are chosen to yield the true values of the air-load coefficients at  $\omega = 2$ . The coefficients  $\hat{a}_{ij}$  correspond to the aerodynamic inertias and their numerical values are given by formula (16) of Appendix III. Approximations were also tried on the basis of classical derivative theory in which  $d_{ij}$  is assumed to be zero, and in which allowance is made for the aerodynamic inertias. They were found to be unsatisfactory except in the case of aileron-tab flutter where ' barred ' air-load coefficients which depend on the gear ratio N are used (see para. 5).



25. Binary Flutter.—In the calculations the inertial values corresponding to a fabric aileron and a fabric tab are assumed (see Tables 7 and 8). Approximations to the curves for the following cases are considered :—

- (i) flexure–torsion ( $a_{12} = 2 \cdot 19; j = 0 \cdot 1$ ),
- (ii) flexure-aileron ( $a_{13} = 0.0836$ , unbalanced),
- (iii) torsion-aileron ( $a_{23} = 0.0307$ , unbalanced,  $a_{23} = 0.0107$ , balanced)
- (iv) aileron tab ( $\bar{a}_{34} = 0.0054$ ; N = 2;  $\bar{a}_{34} = 0.006$ , N = 6).

Comparisons of the true curves and their approximations are made in Figs. 28 to 32. In all cases good approximations are obtained for values of  $\omega > 1$ . For lower values of  $\omega$ , the approximate derivatives are less accurate, and lead to errors in the approximate forms of the various curves. For this reason, approximations were not made for the cases where the wing and the aileron are mass-balanced as the true maximum value of  $\omega$  for both flexure-torsion ( $a_{12} = 0$ ) and flexure-aileron ( $a_{13} = 0$ ) flutter is about 0.25 (see Figs. 8b and 10b).

The approximate curves for aileron-tab flutter are shown in Figs. 31 and 32. They are in good agreement with the true curves for both values of N. Equally good agreement is obtained by the use of air-load coefficients of the classical type, namely,  $C_{ij} = \hat{c}_{ij}$ , and  $B_{ij} = \hat{b}_{ij}\omega$ , where allowance is made for the aerodynamic inertia  $a_{ij}$  by adding it to the true value of the product of inertia in vacuo. It may be recalled that the inertia-stiffness diagram depends only on the product of the aileron-tab inertia-stiffness diagrams are small compared with  $\hat{b}_{33}$ , they can be neglected without appreciable loss of accuracy when  $\omega > 1$ .

26. Stability Condition.—In para. 16, it is stated that (34) flutter is prevented when  $\hat{a}_{44} < M\bar{p}$ , where

It can be readily proved that  $-W_{\max} \rightarrow M\bar{p}$  when  $\bar{p}$  is large, if it is assumed that the air-load coefficients are of the classical type. For N = 2, the approximate values of the aileron-tab ' barred ' coefficients obtained by the use of (5.4) and Table 19 are

|0.9246 | 1.049|

and

where the terms  $d_{ij}$  have been neglected.

The abscissa W is given by

$$W = \left[-\bar{C}_{44} + \frac{F \pm \sqrt{G}}{2\bar{B}_{33}}\right] / \omega^2.$$

Let  $\alpha = p'\omega^2 = (\bar{p} + \bar{a}_{34})\omega^2$  where p' represents the effective 'barred 'inertia, then

\*  $\overline{a}$  here denotes a matrix of the aerodynamic inertias.



where

$$\begin{split} f &= \frac{F}{\omega} = - \alpha (\bar{b}_{34} + \bar{b}_{43}) + \bar{c}_{34} \bar{b}_{43} + \bar{c}_{43} \bar{b}_{34} ,\\ e &= E = \alpha^2 - \alpha \left( \bar{c}_{34} + \bar{c}_{43} - \frac{\bar{b}_{33} \bar{b}_{44} - b_{34} b_{43}}{p'} \right) + \bar{c}_{34} \bar{c}_{43} ,\\ g &= \frac{G}{\omega} = f^2 - 4 \bar{b}_{33} \bar{b}_{44} e \equiv g_0 \alpha^2 + g_1 \alpha + g_2 \,. \end{split}$$

For large values of p', the above expressions become functions of  $\alpha$  only, since the term  $\bar{b}_{33}\bar{b}_{44} - \bar{b}_{34}\bar{b}_{43}$  is then small compared with  $p'(\bar{c}_{34} + \bar{c}_{43})$ . When W is a maximum  $\delta W/\delta \alpha = 0$ , and then (26.2) gives

$$\left(1-\alpha\frac{\delta}{\delta\alpha}\right)(f\pm\sqrt{g})=2\bar{b}_{33}\bar{c}_{44},\qquad\ldots\qquad\ldots\qquad\ldots\qquad(26.3)$$

which leads to the quadratic equation

$$g = \frac{(g_1 \alpha + 2g_2)^2}{4D^2} = g_0 \alpha^2 + g_1 \alpha + g_2, \qquad \dots \qquad \dots \qquad \dots \qquad (26.4)$$

where  $D = 2\bar{b}_{33}\bar{c}_{44} - \bar{c}_{34}\bar{b}_{43} - \bar{c}_{43}\bar{b}_{34}$ . From equation (26.4) the values of  $\alpha (= p'\omega^2)$  are then readily determined. When p' is large  $\alpha \to 0.0343$ ; for p' = 0.006,  $\alpha = 0.0353$ ; hence, since  $\pm 2D\sqrt{g} = g_1\alpha + 2g_2$  when W is a maximum equation (26.2) gives after some reduction

$$W_{\text{max}} = -\frac{p'}{2\bar{b}_{33}} \left( \bar{b}_{34} + \bar{b}_{43} - \frac{g_1}{2D} \right) - \frac{(D^2 - g_2)p'}{2\bar{b}_{33}D\alpha} + \bar{a}_{44}$$
  
=  $-0.981p' - \frac{0.00203p'}{\alpha} + 0.0_35651 \dots \dots \dots \dots \dots (26.5)$   
=  $-1.04\bar{p} - 0.0_58$ .

The slight variation in  $\alpha$  with p' does not affect the slope of this line appreciably so that when  $p' \ge 0.006$ , which represents roughly the lower limit of the 'barred' effective product of inertia in practice, the value of the stability factor M is 1.04 as compared with a true value of 1.05 obtained graphically for N = 2. (See Table 3 and Figs. 13a, 13b).

#### REFERENCES

No.	Author	Title, etc.						
1	S. B. Gates	Notes on the spring tab. R.A.E. Report B.A.1665. A.R.C. 5058. April, 1941.						
<b>2</b>	W. S. Brown	Spring tab controls. R. & M. 1979. September, 1941.						
3	R. A. Frazer, W. J. Duncan and A. R. Collar.	Elementary Matrices. Cambridge University Press. 1938						
4	P. Cicala	The torsional-bending oscillations of a wing in a uniform current. L'Aerotechnica. Vol. 16, No. 11, p. 785. November, 1936. Translated as A.R.C. 3030.						
5	W. J. Duncan and A. R. Collar	Binary servo-rudder flutter. R. & M. 1527. February, 1933.						
6	W. J. Duncan and H. M. Lyon	Calculated flexural-torsional flutter characteristics of some typical cantilever wings. R. & M. 1782. April, 1937.						
7	H. Boden	Moments of inertia of rudder surfaces and stiffnesses of fuselage and tail parts of Gloster C.16/28 Troop Carrier. R.A.E. Report M.T.5546A. A.R.C. 1667. March, 1935.						
8	R. A. Frazer	Flexure-torsion flutter derivatives for semi-rigid wings. R. & M. 1952. May, 1941.						
9	R. A. Frazer and S. W. Skan	A comparison of the observed and predicted flexure-torsion flutter characteristics of a tapered model wing. R. & M. 1943. August, 1941.						
10	W. P. Jones	Aerodynamic forces on an oscillating aerofoil-aileron-tab combination. R. & M. 1948. September, 1941.						

33

с

(1752)



## LIST OF SYMBOLS

c

Notes: For the significance of barred symbols *see* Introduction (d). Symbols with double suffices, unless specially defined, denote the elements of a corresponding square matrix. Numbers in round brackets indicate equations.

A	Matrix of inertial constants	para. 2
а	Matrix of non-dimensional inertial coefficients	(2.9)
a (as suffix)	Relating to the aileron	
â		para. $3(a)$
$\mathscr{A}(\equiv C + iB)$	Matrix of air-load coefficients	(3.3)
В	See A	(3.3)
$B_a$ , $B_t$	Statically balanced aileron, statically balanced tab	Appendix II
$\hat{b}$	Matrix of damping derivatives	para. 3 ( <i>a</i> )
β	Tab angle relative to aileron	Figs. 1a and 1b
С	See A	(3.3)
<i>C</i> , <i>C</i> <sub>0</sub>	Local chord of wing, root chord	
$C_a, C_t$	Aileron and tab chords	Appendix I
ĉ	Matrix of aerodynamic stiffness derivatives	para. 3 ( <i>a</i> )
D	Square matrix $-  a \omega^2 + C$ ; also denotes $rac{d}{d  au}$	para. 2 (5, 9)
$d_a, d_t$	Distances of aileron and tab hinge axes behind $OY$	(7.2), (7.3)
·· Д	Aileron-tab density ratio $\sigma_a/\sigma_t$ ; discriminant	(16.2), (8.12)
E	Matrix of elastic stiffnesses	(1.6)
$E_{ij}$	Defined generally as in $(8.2)$	
е.	Matrix of non-dimensional elastic coefficients	(2.10)
3	Defined as $e$ , but with $\sigma_0 = 0$	(4.3)
$\varepsilon_a, \ \varepsilon_t$	Aileron and tab density ratios $\rho/\sigma_a$ , $\rho/\sigma_t$	(16.2)
$\eta =$	y/l	
$F(\eta)$ , $f(\eta)$	Torsional and flexural distortion modes	(7.1)
${F}_{ij}$	Defined generally as in $(8.3)$	
f	Frequency; critical frequency	
$f_a, f_v$	Natural frequency in still air and in vacuo	para. 6
$G_{ij}$	Defined generally as in $(8.6)$	
γ	Matrix of aerodynamic inertial coefficients	(6.2), Appendix III
$H_{1}$ , $H_{2}$ , $H_{3}$	Constants in calculation of inertias	Table 6
H	Aileron hinge moments	para. 2
$H_{0}$	Used in calculation of ternary diagrams	(9.4)

.

.

# THE DOCUMENT PROVIDED BY THE ABBOTT AEROSPACE

## LIST OF SYMBOLS-continued

$h_{\beta}, h_{\xi}$		Elastic stiffnesses in simplified theory	para. 10
Ι		Inertia point in inertia-stiffness diagram	para. 8
J		Inertia point in stability diagram	para. 16
j		Distance of c.g. behind $OY$ as function of chord	
$K_{0}$		Used in calculation of ternary diagrams	(9.4)
$k \equiv \{k_1,  k_2,  k_3,  k_4\}$		Column of complex amplitudes of motion	(3.1)
L		Aerodynamic flexural moment on wing	para. 2
l		Distance reference section from wing root	
$l_{\phi}$		Flexural stiffness of wing	
Л		Distance of tab-balancing mass behind aileron hinge axis	(16.6)
λ		Distance of tab-balancing mass ahead of tab hinge axis	(16.6)
λ		Complex exponential time factor	para. 3
$\lambda_a, \lambda_t$		Distances of aileron and tab-balancing masses ahead of hinge axes, as fractions of aileron and tab chords	Appendix II
M		Aerodynamic torsional moment on wing	para. 2
M		Slope of lines in stability diagram	(16.3)
$M_{0}$		Equivalent mass of control column	(1.7)
$\mathcal{M}_0$	=	${M}_{ m o}/ ho c_{ m o}{}^2 l$	(2.8)
$\mathcal{M}_{ heta}$		Torsional stiffness of wing	
μ		Damping factor; matrix of transformation	para. 3 (b), (2.5)
N		Second spring-tab gear ratio $R'/r'$	para. 1 ( <i>d</i> )
n		First spring-tab gear ratio $R/r$	para. 1 $(d)$
$\mathcal{N}_0$		$2\sigma_{0}/ ho V^{2}lc_{0}$	(2.6)
v		A gearing constant of control circuit	para. 1 ( <i>b</i> )
$\xi, \xi_\eta$		Aileron angle in reference section; local aileron angle	para. 7
$P_{\mathfrak{o}}$		Preloading force of spring tab	para. 1 ( <i>a</i> )
Þ		Generic symbol for product of inertia: also used as suffix to denote port side	
⊅o	=	$P_0/ ho V^2 l^2 c_0$	(2.6)
ũ		Column $\{0, 0, -R, r\}$	(1.6)
$\equiv \{Q_1, Q_2, Q_3, Q_4\}$		Column of aerodynamic moment coefficients	(2.6)
$q \equiv \{q_1, q_2, q_3, q_4\}$		Column { $\phi$ , $(c_0/l)\theta$ , $(c_0/l)\xi$ , $(c_0/l)\beta$ }	(2.4)
$q_0$		Angular co-ordinate of control column	(2.4)
		35	

(1752)

Q

C 2
TECHNICAL LIBRARY ABBOTTAEROSPACE.COM

## LIST OF SYMBOLS-continued

R	=	AF - AI in Figs. 1; for spring tab No. 2 $R = 0$	para. 1 ( <i>a</i> )
R'		vAF in Figs. 1; vHQ in Fig. 2	para. 1 $(b)$
¥		TM in Figs. 1; CK $ imes$ TM/CS in Fig. 2	para. 1 ( <i>a</i> )
γ'		<code><math> u</math>TM in Figs. 1; <math> u</math>HC <math> imes</math> TM/CS in Fig. 2</code>	para. 1 ( <i>b</i> )
ρ		Air density	
S		Wing span: also used as suffix to denote starboard	
S <sub>a</sub> , S <sub>t</sub>		Aileron and tab spans	
σ		Stiffness rate of spring tab	para. 1 ( <i>a</i> )
$\sigma_0$		Stiffness rate of control cables	para. 1 $(b)$
$\sigma_a, \sigma_t$		Aileron and tab mass coefficients	(16.2)
T		Aerodynamic tab hinge moment	
t		Time variable	
$t_{eta}$ , $t_{\xi}$		Elastic stiffnesses	para. 10
τ		Non-dimensional time variable $tV/c_0$	(2.4)
θ		Torsional co-ordinate of wing	
$\theta_{\eta}$		Local angle of twist at section $\eta$	Appendix III
$\vartheta$		Column {0, 0, $R'$ , $-r'$ }	(1.6)
θ'		Transposed of $\vartheta$	(1.8)
U		Column of moments $\{L, M, H, T\}$	para. 2
$U_{a}, U_{t}$		Unbalanced aileron, unbalanced tab	Appendix II
V		Airspeed ; critical speed	
X, Y, Z, W		Co-ordinates in inertia-stiffness diagrams	(5.8)
$X_a, Y_a, Z_a, W_a$		Values of $X$ , $Y$ , $Z$ , $W$ for oscillations in still air	(6.3)
$X_v$ , $Y_v$ , $Z_v$ , $W_v$		Values of $X$ , $Y$ , $Z$ , $W$ for oscillations in vacuo	(6.1)
X', Y', Z', W'		Barred direct elastic stiffness coefficients	(5.7)
x, y, z, w		$X' + D_{11}$ , etc. ; also spatial co-ordinates	(5.10)
$\phi$		Flexural co-ordinate of wing	
x		Column of angles $\{\phi, \theta, \xi, \beta\}$	(1.6)
ω		Non-dimensional frequency parameter $2\pi fc_{o}/V$	(3.2)
$\nabla$		A modified discriminant	(8.17)



#### APPENDIX I

Dimensions, Distortion Modes, and Elastic Stiffnesses of Aeroplane S

The numerical constants adopted for the wing-aileron-tab combination were based—with drastic simplifications—on design data supplied for the *Spitfire*.

1. Dimensions.—The relevant data for the Spitfire are as follows.

Dimensions of Spitfire (Areas in ft<sup>2</sup> and lengths in ft)

· · · · ·	0	,
Gross wing area		242
Area of each aileron		$9 \cdot 45$
Area of each tab		0.68
Overall span		37
Span of each aileron $(s_a)$	1	$6 \cdot 85$
Span of each tab $(s_t)$		$2 \cdot 14$
Root chord of wing		8.33
Tip chord		$4 \cdot 2$
Aileron chord/wing chord	d $(c_a/c)$	$0 \cdot 235$
Tab chord/aileron chord	$(c_t/c_a)$	$0 \cdot 23$

For aeroplane S the geometrical characteristics were modified in accordance with the following assumptions:

- (a) The tapered *Spitfire* wing was replaced by a rectangular wing-aileron-tab combination of constant section
- (b) The effective areas of each component and the values of  $s_a$ ,  $s_t$ ,  $c_a/c$ ,  $c_t/c_a$  were left unaltered.
- (c) The ratio of wing area outboard of aileron to aileron area was left unaltered.

(d) The wing dihedral was removed, and the flexural axis was assumed to lie as normally at 0.3c from the leading edge.

(e) The aileron and the tab were assumed to be hinged continuously along their leading edges.

Thus, for aeroplane S

$s_a = 6 \cdot 85$ ;	$c_a = 9 \cdot 45/6 \cdot 85 = 1 \cdot 38$
$s_t = 2 \cdot 14;$	$c_i = 0.68/2.14 = 0.32$ (rounded)
$c = 1 \cdot 38 / 0 \cdot 235 = 5 \cdot 87$ ;	$s=217/(2 imes5{\cdot}87)=18{\cdot}5{*}.$

For the *Spitfire* the ratio of wing area outboard of aileron to aileron area was estimated as 0.695. Hence for aeroplane S the wing span extending beyond the aileron was taken as  $(0.695 \times 9.45)/5.87 = 1.12$  ft.

The finally accepted rounded dimensions are as shown in Fig. 6.

2. Reference Section and Distortion Modes.—The tab connection is for convenience assumed to be situated at the inner end of the tab, and the corresponding wing section is adopted as the reference section. The choice of this position for the tab connection simplifies the calculations, and it would also greatly simplify the construction of a model should wind-tunnel tests be required to check the theory.

<sup>\*</sup> The effective wing area was taken to be 217 ft<sup>2</sup>, 25 ft<sup>2</sup> being allowed for the centre section,



The simplified linear distortion modes adopted are (see (7.1) and para 11(b))

$$f(\eta) = \frac{0.57\eta - 0.35}{0.22} \text{ for } \eta > \frac{0.35}{0.57} \text{ and } f(\eta) = 0 \text{ for } \eta \le \frac{0.35}{0.57},$$
  
$$F(\eta) = \frac{0.57\eta - 0.2}{0.37} \text{ for } \eta > \frac{0.2}{0.57} \text{ and } F(\eta) = 0 \text{ for } \eta \le \frac{0.2}{0.57}.$$

3. Elastic Stiffnesses.—(a) Wing Stiffnesses.—The figures supplied for the elastic stiffnesses of the Spitfire measured at mid-aileron span are as follows :—

Flexural stiffness

 $3{\cdot}6 imes10^{6}$  lb ft/radian

Torsional stiffness (symmetrical torques) $0.488 \times 10^6$  lb ft/radianTorsional stiffness (antisymmetrical torques) $0.406 \times 10^6$  lb ft/radian.

The distance from the effective wing root to mid-aileron span is taken to be 11.42 ft.

The elastic stiffnesses for aeroplane S are chosen so that the values of the stiffness rates measured at mid-aileron span agree with those for the *Spitfire*. Now for aeroplane S the reference section and the mid-aileron span section lie at distances 0.22s and 0.405s respectively from the axis for linear flexure, and at distances 0.37s and 0.555s from the axis for linear twist. Moreover l (distance of reference section from wing root) = 10.54 ft. Hence, if  $l_{\phi}$ ,  $m_{\theta}$  denote the elastic stiffnesses defined on the usual basis for aeroplane S

$$l_{\phi} = l^{2} \left( \frac{\text{load at reference section}}{\text{linear deflection at reference section}} \right)$$

$$(0.405l)^{2} \left( \text{load at mid-aileron span} \right)$$

$$= \left(\frac{1}{0 \cdot 22}\right) \left(\frac{1}{\text{linear deflection at mid-aileron span}}\right).$$

Or, on substitution of the value appropriate to the Spitfire

$$l_{\phi} = \left(rac{0\cdot405 imes10\cdot54}{0\cdot22 imes11\cdot42}
ight)^2 imes 3\cdot6 imes10^6 = 10\cdot4 imes10^6$$
 lb ft/radian.

Similarly, for symmetrical conditions of loading

$$m_{ heta} = \left(rac{0\cdot 555}{0\cdot 37}
ight)^{2} imes 0\cdot 488 imes 10^{6} = 1\cdot 1 imes 10^{6}$$
 ,

while for antisymmetrical loading  $m_{\theta} = 0.915 \times 10^6$ . The rounded values finally adopted are

 $l_{\phi}=10\cdot4 imes10^{6}$ ;  $m_{0}=1\cdot0 imes10^{6}$  (for both types of loading),

giving

$$l_{\phi}/
ho l^3=3\cdot 74 imes 10^6$$
 ;  $m_0/
ho lc^2=1\cdot 16 imes 10^6$  .

(b) Control Stiffnesses.—The following dimensions relate to the spring tab No. 2 which was tested on the Spitfire. Two alternative lengths for the tab lever TM were provided: these are denoted below by  $(TM)_1$  and  $(TM)_2$ 

CK = 2.30 in.; CS = 1.7 in.; HQ = 2.85 in.; HC = 1.6 in.;

$$(TM)_1 = 0.54$$
 in.;  $(TM)_2 = 1.0$  in.

These yield the two sets of values

$$r = 0.0609 \text{ (ft)};$$
  $N (\equiv R'/r') = 5.61 \text{ (short lever)}$   
 $r = 0.113 \text{ (ft)};$   $N (\equiv R'/r') = 3.03 \text{ (long lever)},$   
38

THIS DOCUMENT PROVIDED BY THE ABBOTT AEROSPACE

Five different springs (Nos. 1 to 5) were provided for the spring tab, but it is understood that only spring No. 1 was tested in flight. The specified spring rates and preloadings are as below.

Spring No.	Stiffness rate (lb/in.)	Preloading $P_0$ (lb)
1 2 3 4 5	$     77*     40     23     11 \cdot 5     6 $	23.821.818.613.79.0

In numerical applications it may be assumed that the practical values can range up to 100 (lb/in.) for the stiffness rate and up to 40 lb for  $P_0$ .

The value of the control circuit stiffness was obtained from a loading test carried out by the R.A.E. on the *Spitfire* aileron, under conditions appropriate to symmetrical flutter. This test gave  $2R'^2\sigma_0 = 3650$ . The numerical values of the elastic stiffnesses with  $\sigma$  taken as 89 lb/in. (1068 lb/ft) are as given in Tables 4 and 5.

#### APPENDIX II

#### Inertial Coefficients

1. Main Wing Inertias.—General expressions for the inertial coefficients are given in para. 7. The flexural and torsional natural frequencies given for the Spitfire are 10 and 28 c.p.s. respectively and the same frequencies are adopted for aeroplane S. Thus, since  $l_{\phi} = 10.4 \times 10^6$  and  $m_{\theta} = 1.0 \times 10^6$  (see para. 3, Appendix I),

 $A_{11} = 10.4 \times 10^{6}/4\pi^{2}10^{2} = 2640$  slug ft<sup>2</sup>, giving  $a_{11} = 27.5$ 

 $A_{22} = 1.0 \times 10^{6}/4\pi^{2}28^{2} = 32.3$  slug ft<sup>2</sup>, giving  $a_{22} = 1.09$ .

The value of  $A_{12}$  appropriate to the *Spitfire* was not specified, and this coefficient is—so far as possible—left general in the calculations. If  $A_{11} = 2640$  as above, and if the wing masses for aeroplane S are assumed to be distributed uniformly along the span, then the total wing mass is about 12.5 slugs. In this case the estimated value of  $A_{12}$  is about 1170j (giving  $a_{12} = 21.9j$ ) where *jc* denotes the distance of the centre of mass in each section behind *OY*. The condition  $A_{11}, A_{22} > A_{12}^2$  requires that j < 0.25.

2. Inertias of Control Surfaces.—For the evaluation of the remaining inertial coefficients, the dimensions and distortion modes are assumed to be given as in Appendix I, and the masses of both the aileron and the tab (excluding any balancing masses) are taken to be distributed uniformly along the span and to be proportional to the distance from the trailing edge. Thus the mass per unit span (slug/ft) of an element of width dx situated at distance x from OY is taken to be  $2\sigma_a(0 \cdot 7c - x)dx$  in the case of the aileron, and  $2\sigma_t(0 \cdot 7c - x)dx$  in the case of the tab, where  $\sigma_a$  and  $\sigma_t$  are density constants. In order to define the aileron density in practical terms, it is convenient first to imagine the actual tab to be replaced by one constructed of the same material as the main aileron. Then, if  $\mu_a$  (slugs) denotes the mass of the complete homogeneous aileron so obtained, and if  $\mu_t$  denotes the mass of the actual tab

$$\sigma_a \equiv \mu_a / S_a C_a^2; \qquad \sigma_t \equiv \mu_t / S_t C_t^2.$$

Alternatively,  $\sigma_a$  may be defined as  $\mu_a/(s_a c_a^2 - s_i c_i^2)$ , where  $\mu_a'$  is the mass of the aileron with its tab removed. For the purposes of these definitions balancing masses are to be excluded from  $\mu_a$  and  $\mu_t$ .

<sup>\*</sup> Direct measurement of the stiffness rate of spring No. 1 at the N.P.L. gave 89 lb/in.

#### THIS DOCUMENT PROVIDED BY THE ABBOTT AEROSPACE TECHNICAL LIBRARY ABBOTTAEROSPACE.COM

The following additional symbols are introduced

 $\varepsilon_a \text{ (aileron density ratio)} \equiv \rho/\sigma_a$  $\varepsilon_i \text{ (tab density ratio)} \equiv \rho/\sigma_i$ 

 $\Delta$  (aileron-tab density ratio)  $\equiv \sigma_a/\sigma_t = \varepsilon_t/\varepsilon_a$ .

The values  $\sigma_a = \sigma_t = 0.03837_5$  (slug/ft<sup>3</sup>), giving  $\varepsilon_a = \varepsilon_t = 0.06197$  and  $\Delta = 1$ , correspond to a fabric covered combination. If the dimensions are as given for the *Spitfire*, the total weight of the combination (without balancing masses) is about 16 lb. The actual combination used for the *Spitfire* tests consisted of an aluminium tab and a fabric covered aileron, and the density constants corresponded more nearly to  $\sigma_t = 3.7\sigma_a = 0.1151$  (slug/ft<sup>3</sup>), giving  $\varepsilon_a = 0.06197$ ,  $\varepsilon_t = 0.01675$ ,  $\Delta = 0.2703$ . When these values are adopted the estimated weights are 1.31 lb for the *balanced* tab and about 29 lb for the *balanced* aileron, as against 1.3 lb and 26.5 lb obtained from direct weighing of the components at the N.P.L. The density constants appropriate to a fabric-steel combination would be about  $\varepsilon_a = 0.06197$ ,  $\varepsilon_t = 0.006197$ ,  $\Delta = 0.1$ .

In the theoretical investigation, any balancing masses present are (unless the contrary is stated) understood to be distributed along the span so as to render the relevant control surface *uniformly statically balanced* (see para. 7). The masses are assumed to lie at distances  $\lambda_a c_a$  and  $\lambda_i c_i$  ahead of the aileron and tab hinge axes, respectively. For brevity, the three cases considered are distinguished as follows

Case	$(U_a,$	$U_t$	unba	alanced	aileron,	unbalanced	tab,
------	---------	-------	------	---------	----------	------------	------

- Case  $(B_a, U_t)$  balanced aileron, unbalanced tab,
- Case  $(B_a, B_t)$  balanced aileron, balanced tab.

Table 6 and Fig. 7 give the calculated inertial coefficients with  $\varepsilon_t$ ,  $\Delta$ ,  $\lambda_a$  and  $\lambda_t$  left general, when the dimensions of the combination and the distortion modes are as specified in paras. 1 and 2 of Appendix I. For the practical ranges of  $\lambda_a$  and  $\lambda_t$ , the values of  $a_{33}$  appropriate to cases (B<sub>a</sub>, U<sub>t</sub>) and (B<sub>a</sub>, B<sub>t</sub>) differ only slightly. The contribution of the tab balancing mass to  $a_{33}\varepsilon_t \times 10^3$  is given by  $H_2 - H_1$  (in Table 6): the values of this correction are shown below.

$\lambda_{a}$ -	λ,								
	0.1	0.3	0.5	1.0	1.5				
$0.25 \\ 0.5 \\ 0.75$	$0.08122 \\ 0.1016 \\ 0.1220$	0.02423 0.03060 0.03697	0.01293 0.01650 0.02007	0.004652 0.006124 0.007597	$0.002085 \\ 0.002859 \\ 0.003630$				

Values o	of $H_2$ –	$-H_1$
----------	------------	--------

Table 7 summarises the estimated coefficients for the special cases of fabric covering  $(\varepsilon = 0.06197)$  and metal covering  $(\varepsilon = 0.01675)$ . When balancing masses are fitted, their positions are standardised in this table as  $\lambda_a = 0.5$  and  $\lambda_t = 1.0$ . The values of the corresponding barred coefficients  $\bar{a}_{33}$ ,  $\bar{a}_{34}$ ,  $\bar{a}_{44}$ , calculated for spring tab No. 2 with N = 2, 3, 6 are given in Table 8.



#### APPENDIX III

#### Air-Load Coefficients

The air-load coefficients for a semi-rigid wing-aileron-tab combination can be calculated by a method similar to that adopted for flexure torsion flutter in R. & M. 1952<sup>8</sup> and R. & M. 1943<sup>9</sup>. The basis of the method may be described as 'vortex strip theory'.

For the present application the necessary values of the two-dimensional coefficients were calculated by the formulae obtained in R. & M. 1948<sup>10</sup>. In that paper the reference point adopted lies at mid-chord, and the complex amplitudes of the air force and moments per unit span are given in terms of the air-load coefficients by the relation

$$\begin{bmatrix} cZ\\ M\\ H\\ T \end{bmatrix} = -\pi\rho c^2 V^2 \begin{bmatrix} Z_{12} & Z_{34} & Z_{56} & Z_{78}\\ M_{12} & M_{34} & M_{56} & M_{78}\\ H_{12} & H_{34} & H_{56} & H_{78}\\ T_{12} & T_{34} & T_{56} & T_{78} \end{bmatrix} \begin{bmatrix} z'/c\\ \theta'\\ \xi'\\ \beta' \end{bmatrix}, \dots \dots \dots (1)$$

where z',  $\theta'$ ,  $\xi'$ ,  $\beta'$  denote the complex amplitudes of the motion. The air-load coefficients  $Z_{ij}$ ,  $M_{ij}$ , etc., are all functions of the frequency parameter\*  $\omega$ , the functional form being typified by

in which d, e, f, p, q are constants depending only on the geometry of the aerofoil system, and C is a known function expressible in terms of Hankel functions of argument  $\omega/2$ . When  $\omega$  is very great  $C \to 0.5$ , and when  $\omega$  is small  $C \to 1 + \frac{1}{2}i\omega \log \omega$ .

A relation similar to (1) applies when the reference point lies at distance h'c forward of midchord, except that  $M_{12}$ ,  $M_{34}$ ,  $M_{56}$ ,  $M_{78}$  must then be replaced respectively by

$$M_{12} + h'Z_{12}, \quad M_{34} + h'(Z_{34} + M_{12}) + h'^2Z_{12}, \quad M_{56} + h'Z_{56}, \quad M_{78} + h'z_{78},$$

and  $Z_{34}$ ,  $H_{34}$ ,  $T_{34}$  by

$$Z_3 + h' Z_{12}$$
,  $H_{34} + h' H_{12}$ ,  $T_{34} + h' T_{12}$ .

Next consider a semi-rigid wing with aileron and tab. As in para. 7 the distortion modes are assumed to be

for points of the main wing

$$a_{a-t} = \phi lf(\eta) + [x + d_a \{F(\eta) - 1\}]\theta + (x - d_a)\xi, \qquad \dots \qquad \dots \qquad (4)$$

for points of the main aileron, and

 $\mathcal{Z}$ 

for points of the tab.

Let  $P_{w-a-t}$ ,  $P_{a-t}$ ,  $P_t$  denote typical forces applied at  $(x, \eta)$  to the main wing, the main aileron, and the tab, respectively. By the principle of virtual work, the first force is equivalent to a force P' applied at x' in the reference section  $\eta = 1$ , if

$$P'(\phi l + \theta x') = P_{w-a-i} \left\{ \phi lf(\eta) + \theta x F(\eta) \right\}.$$

<sup>\*</sup> In preceding reports the frequency parameter is usually denoted by  $\lambda.$ 



Hence the flexural moment L and the torsional moment M equivalent to  $P_{w-a-t}$  are

Similarly the three moments equivalent to  $P_{a-t}$  can be written

 $L = lf(\eta)P_{a-t}; \quad M = F(\eta)xP_{a-t} + \{1 - F(\eta)\}(x - d_a)P_{a-t}; \quad H = (x - d_a)P_{a-t}, \dots$ (7) while the moments equivalent to  $P_t$  are similar to (7) with  $T = (x - d_t)P_t$  in addition.

From the preceding relations it follows that if a complete distribution of loads represented by  $lZ_{\eta}d\eta$ ,  $lM_{\eta}d\eta$ ,  $lH_{\eta}d\eta$ ,  $lT_{\eta}d\eta$  is applied to a wing element of width  $ld\eta$ , then the total equivalent moments on the system are given by

$$L = l^{2} f(\eta) Z_{\eta} d\eta , ... .. .. .. .. .. .. .. (8)$$
  
$$M = l F(\eta) M d\eta + l(1 - F(\eta)) H d\eta ... ... .. .. .. .. (9)$$

$$M = i \Gamma(\eta) M_{\eta} u \eta + i \{1 - \Gamma(\eta)\} M_{\eta} u \eta , \qquad \dots \qquad \dots \qquad \dots \qquad (9)$$

If the wing section considered does not contain the tab then (11) is to be ignored, and if it does not contain the aileron then (10) and (11) are to be ignored.

Now suppose the system of forces applied to the wing element to be the air-loads. Then the complex amplitudes of these loads per unit span are given by

$$\begin{bmatrix} cZ_{\eta} \\ M_{\eta} \\ H_{\eta} \\ T_{\eta} \end{bmatrix} = -\pi\rho c^{2}V^{2} \begin{bmatrix} Z_{12}' & Z_{34}' & Z_{56}' & Z_{78}' \\ M_{12}' & M_{34}' & M_{56}' & M_{78}' \\ H_{12}' & H_{34}' & H_{56}' & H_{78}' \\ T_{12}' & T_{34}' & T_{56}' & T_{78}' \end{bmatrix} \begin{bmatrix} z_{\eta}'/c \\ \theta_{\eta}' \\ \xi_{\eta}' \\ \beta_{\eta}' \end{bmatrix} , \dots (12)$$

where the accented symbols in the square matrix denote the two dimensional air-load coefficients appropriate to a reference centre at h'c forward of mid-chord, and  $z_{\eta'}$ ,  $\theta_{\eta'}$ ,  $\xi_{\eta'}$ ,  $\beta_{\eta'}$  denote the amplitudes of the local flexural displacement  $z_{\eta}$ , the local angle of twist  $\theta_{\eta'}$ , and the local aileron and tab angles  $\xi_{\eta}$ ,  $\beta_{\eta}$ . From equations (2.4) and para. 7 of the main text it is readily shown that these local displacements are expressible in terms of the dynamical co-ordinates q by the relations

$\begin{bmatrix} z_{\eta}/c \end{bmatrix} = \frac{l}{c}$	$f(\eta)$	0	$0 \rceil 0 \lceil q_1 \rceil \dots $	3)
$\theta_{\eta}$ C	0	$F(\eta)$	$0 \mid 0 \mid q_2 \mid$	
$\xi_{\eta}$	0	$1 - F(\eta)$	$1 \left[ 0 \right] q_{3}$	
$\beta_{\eta}$	0	0	$0 \downarrow 1 \lfloor q_4 \rfloor$	
$ = (l_i) $	c)Wq sat	ıy.		

Hence, in the notation (3.3) for complex amplitudes

$$[z_{\eta}'/c, \theta_{\eta}', \xi_{\eta}', \beta_{\eta}'] = (l/c)Wk . \qquad .. \qquad .. \qquad .. \qquad .. \qquad .. \qquad (14)$$

From (12) and (14) it follows that

$$\begin{bmatrix} cZ_{\eta} \\ M_{\eta} \\ H_{\eta} \\ T_{\eta} \end{bmatrix} = -\pi\rho clV^{2} \begin{bmatrix} fZ_{12}' & FZ_{34}' + (1-F)Z_{56}' & Z_{56}' & Z_{78}' \\ fM_{12}' & FM_{34}' + (1-F)M_{56}' & M_{56}' & M_{78}' \\ fH_{12}' & FH_{34}' + (1-F)H_{56}' & H_{56}' & H_{78}' \\ fT_{12}' & FT_{34}' + (1-F)T_{56}' & T_{56}' & T_{78}' \end{bmatrix} \begin{bmatrix} k_{1} \\ k_{2} \\ k_{3} \\ k_{4} \end{bmatrix}.$$
(15)

If the wing section considered does not contain the tab, the last row and last column in the square matrix in (15) will be null. If the section does not contain the aileron, the last two rows and columns will be null and also  $Z_{56}' = M_{56}' = 0$ .



Expressions for the total effective moments on the system can now be derived by integration of the air-loads. Let  $\int d\eta$ ,  $\int d\eta$ ,  $\int d\eta$  denote integration with respect to  $\eta$  over the complete wing span, over the complete aileron span, and over the tab span only. Then the complex amplitude of the flexural moment is given by

and the remaining moments can be evaluated similarly. The elements of the final matrix  $\mathscr{A}$  of the air-load coefficients are

$$\begin{split} \mathscr{A}_{11} &= \pi \int_{w}^{f^{2}} f^{2} Z_{12}' d\eta \\ \mathscr{A}_{13} &= \pi \int_{w}^{f} f^{2} Z_{34}' d\eta + \pi \int_{a}^{f} f(1-f) Z_{56}' d\eta \\ \mathscr{A}_{13} &= \pi \int_{w}^{f} f^{2} Z_{56}' d\eta \\ \mathscr{A}_{14} &= \pi \int_{t}^{f} f^{2} T_{78}' d\eta \\ \mathscr{A}_{21} &= \pi \int_{w}^{f} F^{2} M_{34}' + \pi \int_{a}^{f} f(1-F) H_{12}' d\eta \\ \mathscr{A}_{22} &= \pi \int_{w}^{f} F^{2} M_{34}' + \pi \int_{a}^{f} F(1-F) (M_{56}' + H_{34}') d\eta + \pi \int (1-F)^{2} H_{56}' d\eta \\ \mathscr{A}_{23} &= \pi \int_{a}^{f} F M_{56}' d\eta + \pi \int (1-F) H_{56}' d\eta \\ \mathscr{A}_{24} &= \pi \int_{t}^{f} F M_{78}' d\eta + \pi \int (1-F) H_{78}' d\eta \\ \mathscr{A}_{31} &= \pi \int_{a}^{f} f H_{12}' d\eta \\ \mathscr{A}_{32} &= \pi \int_{a}^{f} F H_{34}' d\eta + \pi \int_{a}^{f} (1-F) H_{56}' d\eta \\ \mathscr{A}_{33} &= \pi \int_{a}^{f} H_{12}' d\eta \\ \mathscr{A}_{34} &= \pi \int_{t}^{f} f T_{12}' d\eta \\ \mathscr{A}_{41} &= \pi \int_{t}^{f} f T_{12}' d\eta \\ \mathscr{A}_{43} &= \pi \int_{t}^{f} F T_{34}' d\eta + \pi \int_{t}^{f} (1-F) T_{56}' d\eta \\ \mathscr{A}_{43} &= \pi \int_{t}^{f} T_{56}' d\eta \\ \mathscr{A}_{44} &= \pi \int_{t}^{f} T_{78}' d\eta , \end{split}$$

In the particular case of a rectangular wing-aileron-tab combination, the coefficients  $Z_{ij}'$ ,  $M_{ij}'$ . etc., are independent of  $\eta$ , and may be brought in front of the integrals. In this case the actual integrals required in the calculations of the air-load coefficients are

ABBOTTAEROSPACE.COM

TECHNICAL LIBRARY

$$\begin{split} J_{11} &= \pi \int_{w} f^{2} \, d\eta \; ; \quad J_{22} = \pi \int_{w} F^{2} \, d\eta \; ; \quad J_{33} = \pi \int_{a} d\eta \; ; \quad J_{44} = \pi \int_{t} d\eta \; ; \\ J_{12} &= J_{21} = \pi \int_{w} fF \, d\eta \; ; \quad J_{13} = J_{31} = \pi \int_{a} f \, d\eta \; ; \quad J_{14} = J_{41} = \pi \int_{t} f \, d\eta \; ; \\ J_{23} &= J_{32} = \pi \int_{a} F \, d\eta \; ; \quad J_{24} = J_{42} = \pi \int_{t} F \, d\eta \; ; \quad J_{34} = J_{43} = \pi \int_{t} d\eta \; ; \\ K_{12} &= \pi \int_{a} f(1 - F) \, d\eta \; ; \quad K_{22} = \pi \int_{a} F(1 - F) \, d\eta \; ; \\ K_{32} &= \pi \int_{a} (1 - F) \, d\eta \; ; \quad K_{42} = \pi \int_{t} (1 - F) \, d\eta \; . \end{split}$$

The numerical values of these integrals for aeroplane S are given by

J =	10.425	8.3441	3-7540	ړ 0 <b>∙7</b> 9684 [
	8.3441	6.8713	$3 \cdot 0588$	0.73005
	3.7540	$3 \cdot 0588$	$2 \cdot 0392$	0.63209
	0.79684	0.73005	0.63209	0.63209
		-		

and  $K_{12} = -2 \cdot 1627$ ;  $K_{22} = -1 \cdot 6992$ ;  $K_{32} = -1 \cdot 0196$ ;  $K_{42} = -0 \cdot 09796$ .

Tables 9 give the air-load coefficients calculated for aeroplane S on the foregoing basis. The asymptotic values for  $\omega \to \infty$  are as follows.

$\gamma \equiv -C/\omega^2 =$	$\lceil 2 \cdot 606 \rceil$	$0 \cdot 4079$	0.01617	0·00009084 ]	• •	(16)
	0.4079	$0 \cdot 1167$	0.005009	0.00003554		
	0.01617	$0 \cdot 005009$	0.0005383	$0.0_{5}6194$		
	0.00009084	$0 \cdot 00003554$	$0 \cdot 0_{5}6194$	$0.0_{6}5057$		
$B/\omega =$	$\lceil +5 \cdot 213 \rceil$	3.765	$0 \cdot 3452$	0.008407	••	(17)
$B/\omega =$	$\begin{bmatrix} +5 \cdot 213 \\ -0 \cdot 2138 \end{bmatrix}$	$3.765 \\ 0.6266$	$0.3452 \\ 0.09936$	0.008407 0.003236	••	(17)
$B/\omega =$	$ \begin{bmatrix} +5 \cdot 213 \\ -0 \cdot 2138 \\ +0 \cdot 009010 \end{bmatrix} $	3.765 0.6266 0.02145	0.3452 0.09936 0.009079	0.008407 0.003236 0.0005493		(17)

THIS DOCUMENT PROVIDED BY THE ABBOTT AEROSPACE

ECHNICAL LIBRARY

ABBOTTAEROSPACE.COM TABLE 1

Flexure–Torsion Flutter Characteristics of Aeroplane S

	UI	pper Critica	1	Lower Critical			Natural Frequencies (c.p.s.)				
j	Þ	<i>V</i> <sub>1</sub> (m.p.h.)	$f_1$	ω <sub>1</sub>	V <sub>2</sub> (m.p.h.)	$f_2$	$\omega_2$	$f_{1v}$	$f_{2v}$	f <sub>1a</sub>	$f_{2a}$
$0.2 \\ 0.1 \\ 0.05 \\ 0$	$ \begin{array}{c} 4 \cdot 39 \\ 2 \cdot 19 \\ 1 \cdot 10 \\ 0 \end{array} $	? 1868 1453 None	? 6∙69 8∙67 —	$\begin{array}{c} \begin{array}{c} \begin{array}{c} \begin{array}{c} \\ 0 \cdot 09 \\ 0 \cdot 15 \end{array} \end{array}$	649 665 778 None	$21 \cdot 7$ 17 · 9 16 · 6	0.84 0.675 0.535	9.60 9.89 9.97 10.0	$ \begin{array}{c} 48.7 \\ 30.9 \\ 28.6 \\ 28.0 \end{array} $	$9 \cdot 17 \\ 9 \cdot 43 \\ 9 \cdot 52 \\ 9 \cdot 56$	$42 \cdot 0$ $29 \cdot 9$ $27 \cdot 6$ $26 \cdot 7$

#### TABLE 2

Aileron-Tab Natural Frequencies with Spring Tab No. 2

#### (N = 3)

 $f_v, f_a$  denote frequencies (c.p.s.) corresponding to oscillations in vacuo and in still air

Description of system*		Control column locked (symmetrical oscillations			i .	Column free (antisymmetrical)		Column locked and	Column locked and	Column free and aileron
Aileron	Tab	$f_{1v}$	f <sub>2v</sub>	f <sub>1a</sub>	f <sub>2</sub> a	$f_{1v}$	f <sub>2v</sub>	aileron $(f_v)$	to wing $(f_v)$	wing $(f_v)$
F U F B F B	FU FU FB	$4 \cdot 25 \\ 3 \cdot 04 \\ 3 \cdot 03$	$288 \cdot 0 \\ 285 \cdot 0 \\ 134 \cdot 0$	$4 \cdot 05 \\ 2 \cdot 96 \\ 2 \cdot 95$	$270 \cdot 0$ $267 \cdot 0$ $132 \cdot 0$	$\begin{array}{c c} \cdot & 51 \cdot 2 \\ & 51 \cdot 4 \\ & 24 \cdot 2 \end{array}$	σ	$24 \cdot 2$ 17 · 1 17 · 0	$277 \cdot 0$ $277 \cdot 0$ $159 \cdot 0$	$50 \cdot 1 \\ 50 \cdot 1 \\ 28 \cdot 7$
F U F B F B	A U A U A B	$3 \cdot 72 \\ 2 \cdot 76 \\ 2 \cdot 77$	$   \begin{array}{r}     166 \cdot 0 \\     157 \cdot 0 \\     92 \cdot 3   \end{array} $	$3.58 \\ 2.70 \\ 2.71$	$162 \cdot 0$ $154 \cdot 0$ $91 \cdot 7$	$28 \cdot 4 \\ 27 \cdot 6 \\ 16 \cdot 4$		$22 \cdot 1$ 15 · 9 15 · 8	$     \begin{array}{r}       144 \cdot 0 \\       144 \cdot 0 \\       82 \cdot 7     \end{array} $	$26 \cdot 0$ $26 \cdot 0$ $15 \cdot 0$
A U A B A B	A U A U A B	$2 \cdot 21 \\ 1 \cdot 58 \\ 1 \cdot 57$	$159 \cdot 0$ $154 \cdot 0$ $71 \cdot 7$	$2 \cdot 18 \\ 1 \cdot 57 \\ 1 \cdot 57 \\ 1 \cdot 57$	$156 \cdot 0$ $151 \cdot 0$ $71 \cdot 4$	$ \begin{array}{c} 28 \cdot 3 \\ 27 \cdot 7 \\ 12 \cdot 9 \end{array} $		$     \begin{array}{r}       12 \cdot 6 \\       8 \cdot 87 \\       8 \cdot 86     \end{array} $	$     \begin{array}{r}       144 \cdot 0 \\       144 \cdot 0 \\       82 \cdot 7     \end{array} $	$26 \cdot 0 \\ 26 \cdot 0 \\ 15 \cdot 0$

\* F denotes fabric covering; A aluminium covering; U not mass-balanced; B uniformly statically balanced.

TECHNICAL LIBRARY ABBOTTAEROSPACE.COM

N = 2				N = 3		N = 6			N = 10		
Þ	$-W_{\rm max}$	1.05 <i>p</i>	$\bar{p}$	$-W_{\rm max}$	$1 \cdot 07 \bar{p}$	Þ	$-W_{\rm max}$	1 · 18p	Ē	- W <sub>max</sub>	$1\cdot 31ar{p}$
$0 \\ 0 \cdot 002 \\ 0 \cdot 0054 \\ 0 \cdot 010 \\ 0 \cdot 0125$	$\begin{array}{c} 0.00014\\ 0.00218\\ 0.00574\\ 0.0105\\ 0.0131\end{array}$	$\begin{array}{c} 0 \\ 0.00210 \\ 0.00567 \\ 0.0105 \\ 0.0131 \end{array}$	$\begin{array}{c} 0.00544\\ 0.006758\\ 0.01\\ 0.0125\\ 0.015\\ 0.02\\ 0.04\\ \end{array}$	$\begin{array}{c} 0{\cdot}00587\\ 0{\cdot}00741_{5}\\ 0{\cdot}0108\\ 0{\cdot}0135\\ 0{\cdot}0162_{5}\\ 0{\cdot}0215\\ 0{\cdot}0429 \end{array}$	$\begin{array}{c} 0.00582\\ 0.00723\\ 0.0107\\ 0.0134\\ 0.0161\\ 0.0214\\ 0.0428 \end{array}$	$\begin{array}{c} 0.006\\ 0.007155\\ 0.008\\ 0.01\\ 0.04 \end{array}$	0.00733 0.00869 0.00970 0.0122 0.0473	$\begin{array}{c} 0.00708\\ 0.00844\\ 0.00944\\ 0.0118\\ 0.0472 \end{array}$	0.01 0.04	0.0134 0.0524	0.0131 0.0524
<u>.</u>	· ·	M 1.05	·	1.07		_ 1.18	M	- 1.91	<u> </u>		

TABLE 3 Values of  $W_{max}$  for Aileron–Tab Flutter

TABLE 4Spring-Tab Constants (units : feet and pounds)(See Appendix I, para. 3 (b))

			R	r	$\binom{n}{(=R/r)}$	$(=\stackrel{N}{R'/r'})$	σ	$P_{0}$	$2\sigma_0 R'^2$	$2\sigma_0 R'r'$	$2\sigma_0 r'^2$	$\sigma r^2$
Short lever Long lever	•••	•••	0 0	$0.0609 \\ 0.113$	00	$5 \cdot 61 \\ 3 \cdot 03$	1068 1068	24 24	3650 3650	651 1205	116 398	$3.96 \\ 13.6$

46

.'

TECHNICAL LIBRARY ABBOTTAEROSPACE.COM

#### TABLE 5

Constants for Elastic Matrices e and  $\varepsilon$ 

(See Appendix I, para. 3 (b), and equations (2.10), (4.3))

		$rac{l_{\phi}}{ ho l^3}$	$\frac{m_{\theta}}{\rho l c_0^2}$	$\left  \begin{array}{c} \frac{2\sigma_0 R'^2}{\rho l c_0^2} \end{array} \right $	$\left  \frac{2\sigma_0 r'^2}{\rho l c_0^2} \right $	$\left  \frac{2\sigma_0 r'^2}{\rho l c_0^2} \right $	$\frac{\sigma r^2}{\rho l c_0^2}$	$\frac{\sigma R^2}{\rho l c_0{}^2}$	$\frac{\sigma Rr}{\rho lc_0^2}$
Short lever $(N = 5.61)$ Long lever $(N = 3.03)$	•••	 $egin{array}{c} 3\cdot74 imes10^6\ 3\cdot74 imes10^6 \end{array}$	$egin{array}{c} 1\cdot 16  imes 10^6 \ 1\cdot 16  imes 10^6 \end{array} \ 1\cdot 16  imes 10^6 \end{array}$	4227 4227	754 1395	134 461	$4.59 \\ 15.75$	000	0

 $1/\rho lc_0^2 = 1.158.$ 

47

#### TABLE 6

## Inertial Coefficients of Aileron and Tab\*

Coefficient	Case (U <sub>a</sub> , U <sub>t</sub> )	Case (B <sub>a</sub> , U <sub>t</sub> )	Case (B <sub>a</sub> , B <sub>t</sub> )
$a_{13} \varepsilon_t  imes 10^3 \ a_{23} \varepsilon_t  imes 10^3 \ a_{33} \varepsilon_t  imes 10^3 \ a_{14} \varepsilon_t  imes 10^3 \ a_{24} \varepsilon_t  imes 10^3 \ a_{34} \varepsilon_t  imes 10^3 \ a_{44} \varepsilon_t  imes 10^3$	$\begin{array}{l} 0.1488 + 5.020 \varDelta \\ 0.08692 + 2.2017 \varDelta \\ 0.02355 + 0.3064 \varDelta = H \\ 0.01348 \\ 0.007958 \\ 0.002220 \\ 0.0002884 \end{array}$	$ \begin{array}{c} 0 \\ H + \lambda_a (0 \cdot 02770 + 0 \cdot 6322  \Delta) = H_1 \\ H_1 \\ 0 \cdot 01348 \\ 0 \cdot 007958 \\ 0 \cdot 002220 \\ 0 \cdot 0002884 \end{array} $	$ \begin{vmatrix} 0 \\ H_2^* \\ H_2 \\ 0 \\ 0 \cdot 0002884(1+2\lambda_i) \\ 0 \cdot 0002884(1+2\lambda_i) \\ 0 \cdot 0002884(1+2\lambda_i) \end{vmatrix} $

$$* H_2 = H + \lambda_a \left( 0.02519 + 0.6322 \varDelta + \frac{0.008397}{\lambda_t} \right) + \frac{0.01091}{\lambda_t} (0.77 - 0.23 \lambda_t)^2$$

Note.—U denotes not mass balanced; B denotes uniformly statically balanced;  $\Delta = \sigma_a/\sigma_t$  and  $\varepsilon_t = \rho/\sigma_t$  (see Appendix II).

#### TABLE 7

#### Inertial Coefficients for Fabric or Metal Components (see Appendix II) (U denotes inertial un-balance : B denotes uniform static balance)

Description of System	10 <i>a</i> <sub>13</sub>	10a <sub>23</sub>	10 <i>a</i> <sub>33</sub>	$10^{3}a_{14}$	$10^4 a_{24}$	$10^4 a_{34}$	$10^{5}a_{44}$		
Fabric aileron (U); fabric tab (U) . ,, ,, (B); ,, ,, (U) . ,, ,, (B); ,, ,, (B) .	· · · ·		$\begin{array}{c} 0\cdot 836\\ 0\\ 0\end{array}$	$0.370 \\ 0.107 \\ 0.108$	$\begin{array}{c} 0 \cdot 0533 \\ 0 \cdot 107 \\ 0 \cdot 108 \end{array}$	$0.218 \\ 0.218 \\ 0$	$   \begin{array}{c}     1 \cdot 29 \\     1 \cdot 29 \\     0 \cdot 140   \end{array} $	$0.358 \\ 0.358 \\ 0.140$	$ \begin{array}{c} 0 \cdot 0463 \\ 0 \cdot 0463 \\ 0 \cdot 140 \end{array} $
Fabric aileron (U);         Al. tab (U)         .           ,,         ,,         (B);         ,,         (U)         .           ,,         ,,         (B);         ,,         (U)         .	· · · ·	  	$\begin{array}{c} 0.901 \\ 0 \\ 0 \end{array}$	$0.408 \\ 0.123 \\ 0.127$	$\begin{array}{c} 0.0636 \\ 0.123 \\ 0.127 \end{array}$	$     \begin{array}{c}       0 \cdot 806 \\       0 \cdot 806 \\       0     \end{array} $	$4.76 \\ 4.76 \\ 0.518$	$     \begin{array}{r}       1 \cdot 33 \\       1 \cdot 33 \\       0 \cdot 518     \end{array} $	$ \begin{array}{c} 0 \cdot 171 \\ 0 \cdot 171 \\ 0 \cdot 518 \end{array} $
Al. aileron (U); Al. tab (U) ,, ,, (B); ,, ,, (U) ,, ,, (B); ,, ,, (B)	· ·· · ··	· · · · · · · · · · · · · · · · · · ·	$\begin{array}{c} 3\cdot 09 \\ 0 \\ 0 \end{array}$	$1 \cdot 37 \\ 0 \cdot 395 \\ 0 \cdot 399$	$0.197 \\ 0.395 \\ 0.399$	$     \begin{array}{r}       0.807 \\       0.807 \\       0     \end{array} $	$\begin{array}{c} 4 \cdot 76 \\ 4 \cdot 76 \\ 0 \cdot 518 \end{array}$	$     \begin{array}{r}       1 \cdot 33 \\       1 \cdot 33 \\       0 \cdot 518     \end{array} $	$ \begin{array}{c} 0 \cdot 171 \\ 0 \cdot 171 \\ 0 \cdot 518 \end{array} $

Notes: (i) In all cases it is assumed that a<sub>11</sub> = 27 · 5, a<sub>22</sub> = 1 · 09, a<sub>12</sub> = 21 · 9j where jc denotes the distance of the inertia axis behind the flexural axis.
(ii) The density constants for fabric-covered and aluminium-covered components are taken respectively as σ = 0 · 03837(ε = 0 · 06197) and σ = 0 · 1151(ε = 0 · 01675).

(iii) Factors used in conversion to non-dimensional coefficients are  $1/\rho l^3 c^2 = 0.01043$ ;  $1/\rho l^2 c^3 = 0.01873$ ;  $1/\rho l c^4 = 0.03364$ .

TABLE	8
-------	---

Barred Inertial Co-efficients of Aileron and Tab with Spring Tab No. 2 (n = 0)

		N=2			N=3			N = 6		
Description of System		$10^3\overline{a}_{33}$	$10^{3}\overline{a}_{34}$	$10^3\overline{a}_{44}$	$10^{3}\overline{a}_{33}$	$10^{3}\bar{a}_{34}$	$10^{3}\overline{a}_{44}$	$10^{3}\bar{a}_{33}$	$10^3 \overline{a}_{ m 24}$	$10^3\overline{a}_{44}$
Fabric aileron (U); fabric tab (U)            ,,         ,,         (B);         ,,         ,(U)            ,,         ,,         (B);         ,,         ,(B)	1   1	$5 \cdot 33$ $10 \cdot 7$ $10 \cdot 8$	$5 \cdot 403 \\ 10 \cdot 74 \\ 10 \cdot 84$	$5 \cdot 49$ 10 \cdot 8 11 \cdot 0	$5 \cdot 33 \\ 10 \cdot 7 \\ 10 \cdot 8$	$5 \cdot 439 \\ 10 \cdot 78 \\ 10 \cdot 86$	$5 \cdot 59 \\ 10 \cdot 9 \\ 11 \cdot 1$	$5 \cdot 33 \\ 10 \cdot 7 \\ 10 \cdot 8$	$5 \cdot 547 \\ 10 \cdot 88 \\ 10 \cdot 9$	$5 \cdot 93$ 11 \cdot 3 11 \cdot 6
Fabric aileron (U); Al. tab (U)           ,, ,, (B); ,, ,, (U)           ,, ,, (B) ,, ,, (B)	 1 1	$6 \cdot 36 \\ 12 \cdot 3 \\ 12 \cdot 7$	$6 \cdot 624 \\ 12 \cdot 57 \\ 12 \cdot 80$	$6 \cdot 96 \\ 12 \cdot 9 \\ 13 \cdot 1$	$6 \cdot 36 \\ 12 \cdot 3 \\ 12 \cdot 7$	$6.757 \\ 12.70 \\ 12.85$	$7 \cdot 31 \\ 13 \cdot 2_5 \\ 13 \cdot 48$	$6 \cdot 36 \\ 12 \cdot 3 \\ 12 \cdot 7$	$7 \cdot 155 \\ 13 \cdot 10 \\ 13 \cdot 01$	$8 \cdot 57 \\ 14 \cdot 5 \\ 15 \cdot 2$
Al. aileron (U) Al. tab (U) ,, ,, (B); ,, ,, (U) ,, ,, (B); ,; ,, (B)	1 3 3	19·7 39·5 39·9	$     \begin{array}{r}       19 \cdot 99 \\       39 \cdot 75 \\       40 \cdot 00     \end{array} $	$20 \cdot 3$ $40 \cdot 1$ $40 \cdot 3$	$     \begin{array}{r}       19 \cdot 7 \\       39 \cdot 5 \\       39 \cdot 9     \end{array}   $	$   \begin{array}{c}     20 \cdot 13 \\     39 \cdot 88 \\     40 \cdot 06   \end{array} $	$20 \cdot 7$ $40 \cdot 4$ $40 \cdot 7$	$     \begin{array}{r}       19 \cdot 7 \\       39 \cdot 5 \\       39 \cdot 9     \end{array} $	$20 \cdot 52 \\ 40 \cdot 28 \\ 40 \cdot 21$	$21 \cdot 9$ $41 \cdot 7$ $42 \cdot 4$



# TABLE 9A

# Air-Load Coefficients $C_{1j}$ and $B_{1j}$ (see Appendix III)

						1		1
ω	<i>C</i> <sub>11</sub>	B <sub>11</sub>	C <sub>12</sub>	B <sub>12</sub>	C <sub>13</sub>	B <sub>13</sub>	C <sub>14</sub>	B <sub>14</sub>
$ \begin{array}{c} 0 \\ 0 \cdot 02 \\ 0 \cdot 04 \\ 0 \cdot 06 \\ 0 \cdot 06 \end{array} $	$ \begin{array}{c c} 0 \\ + 0.008476 \\ 0.02719 \\ 0.05186 \\ 0.05082 \end{array} $	$0 \\ 0.2048 \\ 0.4019 \\ 0.5911 \\ 0.7700$	$ \begin{array}{c} 7.064 \\ 6.942 \\ 6.817 \\ 6.695 \\ 6.570 \\ \end{array} $	$ \begin{array}{ c c c c c c c c c c c c c c c c c c c$	$ \begin{array}{ c c c c c c c c c c c c c c c c c c c$	$ \begin{array}{c} 0 \\ -0.09115 \\ -0.1468 \\ -0.1875 \\ 0.2181 \end{array} $	$\begin{array}{c} 0.2337 \\ 0.2296 \\ 0.2253 \\ 0.2209 \\ 0.2167 \end{array}$	$ \begin{array}{c} 0 \\ -0.01042 \\ -0.01708 \\ -0.02216 \\ 0.02615 \end{array} $
$ \begin{array}{c} 0.08 \\ 0.10 \\ 0.12 \\ 0.16 \\ 0.2 \\ 0.4 \end{array} $	$\begin{array}{c} 0.08008 \\ 0.1101 \\ 0.1408 \\ 0.2008 \\ 0.2550 \\ 0.3690 \end{array}$	$\begin{array}{c} 0.9476 \\ 1.115 \\ 1.435 \\ 1.735 \\ 3.034 \end{array}$	$ \begin{array}{c} 6.376\\ 6.463\\ 6.356\\ 6.158\\ 5.982\\ 5.342 \end{array} $	$\begin{array}{c} - 0.3970 \\ - 0.4011 \\ - 0.3885 \\ - 0.3259 \\ - 0.2284 \\ + 0.4967 \end{array}$	$2 \cdot 025$ $1 \cdot 989$ $1 \cdot 921$ $1 \cdot 861$ $1 \cdot 641$	$ \begin{array}{c} -0.2414 \\ -0.2589 \\ -0.2809 \\ -0.2904 \\ -0.2489 \end{array} $	$\begin{array}{c} 0.2126\\ 0.2086\\ 0.2013\\ 0.1947\\ 0.1684\end{array}$	$\begin{array}{c} -0.02935 \\ -0.03192 \\ -0.03566 \\ -0.03803 \\ -0.03995 \end{array}$
$0.6 \\ 0.8 \\ 1.0 \\ 1.2 \\ 1.4$	$\begin{array}{r} + & 0.1834 \\ - & 0.2919 \\ - & 1.035 \\ - & 2.029 \\ - & 3.263 \end{array}$	$\begin{array}{c} 4 \cdot 159 \\ 5 \cdot 212 \\ 6 \cdot 233 \\ 7 \cdot 240 \\ 8 \cdot 241 \end{array}$	$\begin{array}{c} 4 \cdot 932 \\ 4 \cdot 622 \\ 4 \cdot 350 \\ 4 \cdot 088 \\ 3 \cdot 818 \end{array}$	$     \begin{array}{r}       1 \cdot 343 \\       2 \cdot 201 \\       3 \cdot 048 \\       3 \cdot 880 \\       4 \cdot 699 \\     \end{array} $	$1 \cdot 510$ $1 \cdot 426$ $1 \cdot 366$ $1 \cdot 322$ $1 \cdot 286$	$-0.1564 \\ -0.0551 \\ +0.0449 \\ 0.1415 \\ 0.2344$	$0.1563 \\ 0.1471 \\ 0.1410 \\ 0.1366 \\ 0.1333$	$\begin{array}{c} -0.03603 \\ -0.03099 \\ -0.02599 \\ -0.02132 \\ -0.01701 \end{array}$
$1.6 \\ 1.8 \\ 2.0 \\ 2.2 \\ 2.4$	$ \begin{array}{r} 4.729 \\ 6.422 \\ 8.334 \\ -10.47 \\12.81 \end{array} $	$9 \cdot 242$ 10 \cdot 24 11 \cdot 25 12 \cdot 25 13 \cdot 26	$\begin{array}{c} 3 \cdot 532 \\ 3 \cdot 224 \\ 2 \cdot 891 \\ 2 \cdot 531 \\ 2 \cdot 143 \end{array}$	5.5086.3087.1017.8888.674	$ \begin{array}{r} 1 \cdot 256 \\ 1 \cdot 230 \\ 1 \cdot 205 \\ 1 \cdot 182 \\ 1 \cdot 159 \end{array} $	$\begin{array}{c} 0.3241 \\ 0.4111 \\ 0.4955 \\ 0.5781 \\ 0.6592 \end{array}$	$0.1308 \\ 0.1289 \\ 0.1274 \\ 0.1261 \\ 0.1251$	$\begin{array}{c} -0.01304 \\ -0.009379 \\ -0.005957 \\ -0.002748 \\ +0.0002837 \end{array}$
$   \begin{array}{c}     2 \cdot 6 \\     2 \cdot 8 \\     3 \cdot 0 \\     3 \cdot 2 \\     3 \cdot 4   \end{array} $	$-15:38 \\ -18:16 \\ -21:15 \\ -24:36 \\ -27:78$	$14 \cdot 27$ 15 \cdot 28 16 \cdot 29 17 \cdot 31 18 \cdot 33	$\begin{array}{c} \cdot \\ 1 \cdot 722 \\ 1 \cdot 273 \\ 0 \cdot 7934 \\ 0 \cdot 2815 \\ -0 \cdot 2622 \end{array}$	$\begin{array}{c} 9 \cdot 450 \\ 10 \cdot 22 \\ 11 \cdot 00 \\ 11 \cdot 77 \\ 12 \cdot 54 \end{array}$	$     \begin{array}{r}       1 \cdot 137 \\       1 \cdot 114 \\       1 \cdot 091 \\       1 \cdot 067 \\       1 \cdot 042     \end{array} $	$\begin{array}{c} 0.7386 \\ 0.8171 \\ 0.8946 \\ 0.9711 \\ 1.047 \end{array}$	$0.1242 \\ 0.1235 \\ 0.1228 \\ 0.1222 \\ 0.1217$	$\begin{array}{c} 0 \cdot 003164 \\ 0 \cdot 005916 \\ 0 \cdot 008558 \\ 0 \cdot 01111 \\ 0 \cdot 01357 \end{array}$
$3 \cdot 6 \\ 3 \cdot 8 \\ 4 \cdot 0 \\ 4 \cdot 2 \\ 4 \cdot 4$	$\begin{array}{r} -31 \cdot 41 \\ -35 \cdot 24 \\ -39 \cdot 29 \\ -43 \cdot 55 \\ -48 \cdot 02 \end{array}$	$     \begin{array}{r}       19 \cdot 35 \\       20 \cdot 37 \\       21 \cdot 39 \\       22 \cdot 41 \\       23 \cdot 44     \end{array} $	$\begin{array}{r} -0.8373 \\ -1.444 \\ -2.084 \\ -2.755 \\ -3.459 \end{array}$	$ \begin{array}{r} 13 \cdot 30 \\ 14 \cdot 07 \\ 14 \cdot 83 \\ 15 \cdot 60 \\ 16 \cdot 36 \end{array} $	$ \begin{array}{r} 1 \cdot 017 \\ 0 \cdot 9905 \\ 0 \cdot 9633 \\ 0 \cdot 9348 \\ 0 \cdot 9054 \end{array} $	$ \begin{array}{c} 1 \cdot 122 \\ 1 \cdot 197 \\ 1 \cdot 271 \\ 1 \cdot 345 \\ 1 \cdot 418 \end{array} $	0.1212 0.1208 0.1204 0.1200 0.1200 0.1196	$\begin{array}{c} 0 \cdot 01597 \\ 0 \cdot 01830 \\ 0 \cdot 02058 \\ 0 \cdot 02281 \\ 0 \cdot 02500 \end{array}$
$4 \cdot 6 \\ 4 \cdot 8 \\ 5 \cdot 0$	-52.70 -57.59 -62.69	$24 \cdot 46 \\ 25 \cdot 49 \\ 26 \cdot 52$	$-4.195 \\ -4.963 \\ -5.764$	$17 \cdot 12$ 17 · 88 +18 · 65	$0.8748 \\ 0.8431 \\ 0.8105$	$1 \cdot 491 \\ 1 \cdot 564 \\ +1 \cdot 636$	$0.1193 \\ 0.1190 \\ 0.1186$	$0.02715 \\ 0.02926 \\ +0.03135$

(1752)

D



## TABLE $9_B$

# Air-Load Coefficients $C_{2j}$ and $B_{2j}$ (see Appendix III)

ω	C <sub>21</sub>	B <sub>21</sub>	C <sub>22</sub>	$B_{22}$	C <sub>23</sub> .	$B_{23}$	C <sub>24</sub>	B <sub>24</sub>
$0 \\ 0 \cdot 02 \\ 0 \cdot 04 \\ 0 \cdot 06 \\ 0 \cdot 08$	$\begin{array}{c} 0 \\ -0.0005536 \\ -0.001940 \\ -0.003980 \\ -0.006578 \end{array}$	$0 \\ -0.008401 \\ -0.01648 \\ -0.02424 \\ -0.03169$	$\begin{array}{c} -0.4713 \\ -0.4662 \\ -0.4610 \\ -0.4561 \\ -0.4515 \end{array}$	$\begin{array}{c} 0 \\ 0 \cdot 02476 \\ 0 \cdot 04481 \\ 0 \cdot 06231 \\ 0 \cdot 07976 \end{array}$	0.2169 0.2185 0.2202 0.2219 0.2235	$\begin{array}{c} 0\\ 0{\cdot}006110\\ 0{\cdot}01072\\ 0{\cdot}01471\\ 0{\cdot}01828 \end{array}$	$\begin{array}{c} 0.03787\\ 0.03806\\ 0.03826\\ 0.03846\\ 0.03846\\ 0.03866\end{array}$	$\begin{array}{c} 0 \\ 0 \cdot 0005560 \\ 0 \cdot 0009377 \\ 0 \cdot 001246 \\ 0 \cdot 001503 \end{array}$
$\begin{array}{c} 0 \cdot 10 \\ \cdot 0 \cdot 12 \\ 0 \cdot 16 \\ 0 \cdot 2 \\ 0 \cdot 4 \end{array}$	$\begin{array}{c} -0.009665\\ -0.01319\\ -0.02142\\ -0.03105\\ -0.09759\end{array}$	$\begin{array}{c} -0.03887 \\ -0.04584 \\ -0.05881 \\ -0.07115 \\ -0.1243 \end{array}$	$-0.4471 \\ -0.4432 \\ -0.4363 \\ -0.4309 \\ -0.4196$	0.09565 0.1108 0.1397 0.1670 0.2935	0.2251 0.2266 0.2294 0.2319 0.2404	0.02154 0.02455 0.03003 0.03498 0.05601	0.03885 0.03903 0.03937 0.03968 0.04037	$\begin{array}{c} 0\cdot 001724\\ 0\cdot 001916\\ 0\cdot 002235\\ 0\cdot 002489\\ 0\cdot 003304\end{array}$
$0.6 \\ 0.8 \\ 1.0 \\ 1.2 \\ 1.4$	$-0.1928 \\ -0.3175 \\ -0.4724 \\ -0.6579 \\ -0.8747$	$\begin{array}{c} -0.1706 \\ -0.2138 \\ -0.2557 \\ -0.2971 \\ -0.3383 \end{array}$	$\begin{array}{r} -0.4291 \\ -0.4534 \\ -0.4902 \\ -0.5379 \\ -0.5962 \end{array}$	0.4148 0.5357 0.6571 0.7792 0.9013	0.2447 0.2468 0.2472 0.2465 0.2451	0.07489 0.09343 0.1120 0.1307 0.1496	$\begin{array}{c} 0 \cdot 04146 \\ 0 \cdot 04185 \\ 0 \cdot 04214 \\ 0 \cdot 04232 \\ 0 \cdot 04245 \end{array}$	0.003847 0.004339 0.004832 0.005341 0.005866
$1 \cdot 6 \\ 1 \cdot 8 \\ 2 \cdot 0 \\ 2 \cdot 2 \\ 2 - 4$	$-1 \cdot 124 -1 \cdot 405 -1 \cdot 717 -2 \cdot 062 -2 \cdot 438$	$\begin{array}{c} -0.3793 \\ -0.4205 \\ -0.4611 \\ -0.5030 \\ -0.5436 \end{array}$	$-0.6645 \\ -0.7425 \\ -0.8300 \\ -0.9278 \\ -1.034$	$1 \cdot 025$ 1 \cdot 148 1 · 271 1 · 395 1 · 520	$0.2429 \\ 0.2402 \\ 0.2369 \\ 0.2331 \\ 0.2288$	$0.1686 \\ 0.1877 \\ 0.2069 \\ 0.2262 \\ 0.2456$	$\begin{array}{c} 0 \cdot 04254 \\ 0 \cdot 04260 \\ 0 \cdot 04264 \\ 0 \cdot 04266 \\ 0 \cdot 04268 \end{array}$	0.006408 0.006962 0.007530 0.008104 0.008692
$2 \cdot 6 \\ 2 \cdot 8 \\ 3 \cdot 0 \\ 3 \cdot 2 \\ 3 \cdot 4$	$\begin{array}{c} -2 \cdot 849 \\ -3 \cdot 291 \\ -3 \cdot 765 \\ -4 \cdot 272 \\ -4 \cdot 812 \end{array}$	$\begin{array}{c} -0.5853 \\ -0.6268 \\ -0.6684 \\ -0.7100 \\ -0.7517 \end{array}$	$-1.151 \\ -1.276 \\ -1.411 \\ -1.556 \\ -1.710$	$     \begin{array}{r}       1 \cdot 644 \\       1 \cdot 768 \\       1 \cdot 892 \\       2 \cdot 017 \\       2 \cdot 142     \end{array} $	0.2241 0.2189 0.2133 0.2072 0.2007	$\begin{array}{c} 0.2650 \\ 0.2845 \\ 0.3041 \\ 0.3236 \\ 0.3432 \end{array}$	$\begin{array}{c} 0.04268\\ 0.04267\\ 0.04265\\ 0.04263\\ 0.04263\\ 0.04261\end{array}$	0.009281 0.009878 0.01048 0.01109 0.01170
$3.6 \\ 3.8 \\ 4.0 \\ 4.2 \\ 4.4$	$ \begin{array}{r} -5 \cdot 383 \\ -5 \cdot 988 \\ -6 \cdot 625 \\ -7 \cdot 294 \\ -7 \cdot 997 \end{array} $	$\begin{array}{c} -0.7935 \\ -0.8354 \\ -0.8774 \\ -0.9193 \\ -0.9613 \end{array}$	$-1.873 \\ -2.045 \\ -2.227 \\ -2.419 \\ -2.619$	$2 \cdot 266$ $2 \cdot 391$ $2 \cdot 516$ $2 \cdot 641$ $2 \cdot 766$	$0.1938 \\ 0.1865 \\ 0.1788 \\ 0.1707 \\ 0.1621$	$\begin{array}{c} 0.3628 \\ 0.3824 \\ 0.4020 \\ 0.4217 \\ 0.4414 \end{array}$	$\begin{array}{c} 0 \cdot 04257 \\ 0 \cdot 04253 \\ 0 \cdot 04249 \\ 0 \cdot 04244 \\ 0 \cdot 04239 \end{array}$	$\begin{array}{c} 0 \cdot 01231 \\ 0 \cdot 01293 \\ 0 \cdot 01355 \\ 0 \cdot 01417 \\ 0 \cdot 01479 \end{array}$
$4 \cdot 6 \\ 4 \cdot 8 \\ 5 \cdot 0$	-8.731 -9.498 -10.30	$-1.003 \\ -1.046 \\ -1.088$	$ \begin{array}{ } -2 \cdot 829 \\ -3 \cdot 049 \\ -3 \cdot 278 \end{array} $	$2.891 \\ 3.016 \\ 3.140$	$0.1532 \\ 0.1438 \\ 0.1341$	$0.4611 \\ 0.4809 \\ 0.5005$	$\begin{array}{c} 0 \cdot 04234 \\ 0 \cdot 04228 \\ 0 \cdot 04222 \end{array}$	$\begin{array}{c} 0 \cdot 01542 \\ 0 \cdot 01605 \\ 0 \cdot 01668 \end{array}$



## TABLE 9c

# Air-Load Coefficients $C_{3j}$ and $B_{3j}$ (see Appendix III)

ω	10C <sub>31</sub>	$10B_{31}$	10C <sub>32</sub>	10B <sub>32</sub>	10C <sub>33</sub>	10B <sub>33</sub>	$10^{2}C_{34}$	$10^2 B_{34}$
0	0	0	+0.06283	0	0.1680	0	0.7294	0
0.02	+0.00009983	0.003540	0.06080	-0.0004975	0.1670	-0.0007407	0.7281	-0.002933
0.04	0.000283	0.006945	0.05867	+0.0008560	0.1659	-0.000556	0 7265	-0.004435
0.00	0.0004764	0.01022	0.05655	0.002971	0.1648	+0.00001977	0.7248	-0.005331
0.08	0.000637	0.01336	0.05444	0.005586	0.1638	0.000856	0.7232	-0.002818
0.10	0.0007369	0.01638	0.05240	0.008567	0.1628	0.001886	0.7216	-0.006000
0.12	0.000755	0.01929	0.05044	0.01183	0.1618	0.003066	0.7201	-0.005945
0.16	+0.000484	0.02481	0.04667	0.01896	0.1600	0.005763	0.7174	-0.005297
0.2	-0.0002628	0.0300	0.04315	0.02668	0.1583	0.008789	0.7149	-0.004109
$0 \cdot 4$	-0.01228	0.05244	0.02737	0.06914	0.1520	0.02622	0.7054	+0.005499
0.6	-0.03885	0.07189	+0.01192	0.1136	0.1476	0.04501	0.6997	0.01732
°0·8	-0.07973	0.09009	-0.005302	0.1583	0.1440	0.06399	0.6966	0.02958
$1 \cdot 0$	-0.1346	0.1077	-0.02539	0.2027	0.1407	0.08295	0.6940	°0·04184
$1 \cdot 2$	-0.2031	0.1252	-0.04877	0.2469	0.1374	0.1018	0.6921	0.05398
$1 \cdot 4$	-0.2851	0.1425	-0.07577	0.2908	0.1339	0.1206	0.6902	0.06599
1.0	0.0000	0.1700	0 1005	0.0045	0 1001	0.1000	0.0000	0.05501
1.6	-0.3803	0.1598	-0.1065	0.3347	0.1301	0.1393	0.6890	0.07781
1.8	-0.4891	0.1771	-0.1410	0.3783	0.1260	0.1579	0.6877	0.08957
2.0	0.7455	0.1944	-0.1795	0.4220	0.1216	0.1765	0.6871	0.1013
2.4	-0.7433	0.2118	-0.2218	0.4055	0.1109	0.1930	0.0858	0.1128
2.4	-0.0334	0-2292	-0.2001	0.2021	0.1117	0.2134	0.0002	0.1243
$2 \cdot 6$	-1.055	0.2466	-0.3184	0.5521	0.1062	0.2319	0.6840	0.1358
$2 \cdot 8$	-1.229	0.2641	-0.3725	0.5954	0.1002	0.2503	0.6831	0.1472
$3 \cdot 0$	-1.416	0.2817 .	-0.4308	0.6386	0.09380	0.2687	0.6820	0.1585
$3 \cdot 2$	-1.616	0.2992	-0.4929	0.6817	0.08708 .	0.2871	0.6812	0.1698
$3 \cdot 4$	-1.829	0.3168	-0.5593	0.7248	0.07990	0.3054	0.6803	0.1811
2.6	. 9.055	0.9944	0.6900	0.7091	0.07020	0.0007	0.0709	0.1004
3.8	2,204	0.2591	-0.0292	0.0119	0.06497	0.3237 0.2490	0.6793	0.1924
4.0	2.546	0.3607	-0.7810	0.8542	0.05592	0.3420	0.6770	0.2030
4.0	-2.340 -2.811	0.3874	-0.8640	0.8075	0.04695	0.3786	0.6761	0.2140 0.2261
4.4	-3.089	0.4051	-0.9505	0.9404	0.03766	0.3969	0.6749	0.2201 0.2372
x . 1		0 1001	0 0004	TUTUT	0.00100	0.0009	0.0145	0.4012
$4 \cdot 6$	-3.380	0.4228	-1.040	0.9835	0.02794	0.4151	0.6737	0.2484
$4 \cdot 8$	-3.684	0.4406	-1.135	1.026	0.01779	0.4334	0.6725	0.2596
$5 \cdot 0$	-4.002	0.4584	1 233	+1.070	0.007220	+0.4516	0.6713	+0.2707
				<u>.</u>				

(1752)

D 2

#### THIS DOCUMENT PROVIDED BY THE ABBOTT AEROSPACE TECHNICAL LIBRARY ABBOTTAEROSPACE.COM

## TABLE 9D

# Air-Load Coefficients $C_{4j}$ and $B_{4j}$ (see Appendix III)

ω	10 <sup>3</sup> C <sub>41</sub>	$10^{3}B_{41}$	$10^{3}C_{42}$	$10^{3}B_{42}$	$10^{3}C_{43}$	$10^{3}B_{43}$	$10^{3}C_{44}$	$10^{3}B_{44}$
0	0	0	+0.06827	0	+0.1106	0	0.2547	0
0.02	0.00004857	0.001827	0.06668	-0.0001945	0.1100	-0.0002582	0.2545	-0.0002678
0.04	0.0001344	0.003585	0.06520	+0.0008457	0.1092	+0.0001815	0.2541	-0.0001880
0.06	0.0002193	0.005273	0.06380	0.002395	0.1084	0.0009152	0.2537	+0.00003881
0.08	0.0002816	0.006894	0.06238	0.004279	0.1076	0.001846	0.2533	0.0003652
0 00	0 0002010	0 00000		0 00				
0.10	0.0003065	0.008453	0.06104	0.006410	0.1069	0.002922	0.2529	0.0007655
0.12	0.0002831	0.009954	0.05970	0.008729	0.1061	0.004111	0.2525	0.001224
0.16	0.0000610	0.01280	0.05714	0.01378	0.1047	0.006745	0.2518	0.002270
$0.\overline{2}$	-0.0004781	0.01546	0.05468	0.01888	0.1037	0.009610	0.2513	0.003413
$0\cdot 4$	-0.007570	0.02701	0.04371	0.04915	0.09861	0.02579	0.2490	0.01024
							,	
0.6	-0.02271	0.03705	0.03298	0.08044	0.09481	0.04292	0.2478	0.01757
0.8	-0.04590	0.04646	0.02047	0.1116	0.09165	0.06024	0.2465	0.02497
1.0	-0.07690	0.05562	+0.006606	0.1435	0.08786	0.07775	0.2459	0.03224
$1 \cdot 2$	-0.1155	0.06462	-0.01021	0.1745	0.08470	0.09481	0.2453	0.03982
$1 \cdot 4$	-0.1618	0.07355	-0.02904	0.2050	0.08091	0.1119	0.2446	0.04715
$1 \cdot 6$	-0.2151	0.08207	-0.05091	0.2360	0.07648	0.1289	0.2440	0.05449
1.8	-0.2765	0.09164	-0.07570	0.2672	0.07206	0.1460	0.2434	0.06194
$2 \cdot 0$	-0.3450	0.1004	-0.1028	0.2976	0.06700	0.1631	0.2427	0.06890
$2 \cdot 2$	-0.4207	0.1092	-0.1327	0.3286	0.06194	0.1801	0.2427	0.07648
$2 \cdot 4$	-0.5036	0.1179	-0.1660	0.3590	0.05626	0.1972	0.2421	0.08344
$2 \cdot 6$	-0.5941	0.1273	-0.2014	0.3895	0.04970	0.2138	0.2414	0.09080
$2 \cdot 8$	-0.6919	0.1363	-0.2399	0.4200	0.04290	0.2306	0.2408	0.09800
$3 \cdot 0$	-0.7968	0.1450	-0.2815	0.4503	0.03565	0.2478	0.2402	0.1049
$3 \cdot 2$	-0.9094	0.1544	-0.3253	0.4810	0.02790	0.2643	0.2394	0.1124
$3 \cdot 4$	-1.029	0.1635	-0.3723	0.5114	0.01970	0.2812	0.2387	0.1196
$3 \cdot 6$	-1.156	0.1726	-0.4221	0 • 5418 •	0.01090	0.2980	0.2380	0.1268
$3 \cdot 8$	-1.290	0.1817	-0.4748	0.5723	+0.001700	0.3148	0.2372	0.1339
$4 \cdot 0$	-1.432	0.1904	-0.5305	0.6025	-0.008028	0.3318	0.2364	0.1410
$4 \cdot 2$	-1.581	0.1999	-0.5886	0.6331	-0.01810	0.3483	0.2356	0.1483
$4 \cdot 4$	-1.737	0.2091	-0.6497	0.6634	-0.02890	0.3652	0.2347	0.1555
	1 000	0.0700		0.0000	0.04000	0.0010	0.0007	0.1000
4.6	-1.900	0.2183	-0.7138	0.6938	-0.04000	0.3819	0.2337	0.1626
$4 \cdot 8$	-2.071	0.2273	-0.7806	0.7241	-0.02170	0.3987	0.2328	0.1698
$5 \cdot 0$	$ -2 \cdot 249$	0.2367	-0.8479	+0.7540	-0.06380	+0.4153	0.2320	+0.1770

TECHNICAL LIBRARY ABBOTTAEROSPACE.COM

#### TABLE 10

Barred Inertial Coefficients for Aileron–Tab with Spring Tab No. 1

	N = 3; n = 0.5		$N = 3; n = 1 \cdot 0$		N = 3;	N = 3	
Description of System	$10^{3}\bar{a}_{33}$	10³7⁄́́р	$10^{3}\overline{a}_{33}$	$10^{3}\overline{p}$	$10^{3}\bar{a}_{33}$	10³7	$10^{3}\bar{a}_{44}$
Fabric aileron (U); Fabric tab (U) ,, ,, (B); ,, ,, (U) ,, ,, (B); ,, ,, (B)	$5 \cdot 37$ 10 · 7 10 · 8	$     5 \cdot 462 \\     10 \cdot 83 \\     10 \cdot 87   $	$5 \cdot 41 \\ 10 \cdot 8 \\ 10 \cdot 8$	5.487 10.86 10.90	$5 \cdot 49 \\ 10 \cdot 9 \\ 10 \cdot 9$	5.537 10.91 10.95	$5 \cdot 59$ 10 · 90 11 · 10
Fabric aileron (U); Al.tab (U)            ,, ,, (B); ,, ,, (U)            ,, ,, (B); ,, ,, (B);	$6 \cdot 50 \\ 12 \cdot 4 \\ 12 \cdot 8$	$     \begin{array}{r}       6 \cdot 851 \\       12 \cdot 79 \\       12 \cdot 96     \end{array} $	$6 \cdot 64 \\ 12 \cdot 6 \\ 12 \cdot 9$	$ \begin{array}{r} 6 \cdot 943 \\ 12 \cdot 88 \\ 13 \cdot 06 \end{array} $	$6.96 \\ 12.9 \\ 13.1$	$7 \cdot 128 \\ 13 \cdot 07 \\ 13 \cdot 27$	$7 \cdot 31$ 13 · 25 13 · 48
Al. aileron (U); Al. tab (U) ,, ,, (B); ,, ,, (U) ,, ,, (B); ,, ,, (B)	19·8 39·6 40·0	$   \begin{array}{r}     20 \cdot 19 \\     39 \cdot 99 \\     40 \cdot 16   \end{array} $	$20 \cdot 0$ $39 \cdot 8$ $40 \cdot 1$	$20 \cdot 28 \\ 40 \cdot 08 \\ 40 \cdot 26$	$20 \cdot 3$ $41 \cdot 0$ $40 \cdot 3$	$   \begin{array}{r}     20 \cdot 47 \\     40 \cdot 27 \\     40 \cdot 47   \end{array} $	$20.70 \\ 40.40 \\ 40.70$

Al. denotes aluminium, U unbalanced, B uniform static balance.

.

.

#### TABLE 11A

## Flexure–Aileron–Tab Flutter (Aileron unbalanced)

			X	= 0			X	= 5			X =	= 10	
	Ŵ	Z <sub>1</sub>	Wi	$Z_2$	W <sub>2</sub>		<i>W</i> <sub>1</sub>	$Z_2$	W2	Z <sub>1</sub>	W <sub>1</sub>	$Z_2$	W2
54	$0.2 \\ 0.6 \\ 0.8 \\ 1.0 \\ 1.2$	$ \begin{array}{c} -0.002360 \\ -0.005161 \\ -0.005329 \\ -0.005397 \end{array} $	$ \begin{array}{r} -0.03184 \\ -0.008203 \\ -0.006419 \\ -0.006080 \\ \end{array} $	$\begin{vmatrix} +0.1884 \\ 0.01744 \\ -0.003195 \\ +0.0_37486 \end{vmatrix}$	$ \begin{array}{r} -0.27899 \\ -0.03703 \\ -0.01727 \\ -0.01390 \\ \end{array} $	+0.01590 +0.039515 -0.002338	$ \begin{array}{r} -0.03549 \\ -0.01504 \\ -0.01063 \end{array} $	$ \begin{array}{c} -0.005301 \\ -0.005488 \\ -0.00554 \end{array} $	-0.007895 -0.006050 -0.005702	$-0.005578 \\ -0.006793 \\ -0.005000 \\ -0.005190$	$ \begin{array}{c} -0.007346 \\ -0.003923 \\ -0.006912 \\ -0.006311 \end{array} $	$\begin{array}{r} -0.01248 \\ -0.0_35739 \\ +0.3092 \\ 0.008449 \end{array}$	-0.03217-0.01439-0.03789-0.01836
	$1 \cdot 4 \\ 1 \cdot 6 \\ 1 \cdot 8 \\ 2 \cdot 0 \\ 2 \cdot 4$	$\begin{array}{c} -0.005431 \\ -0.005464 \\ -0.005500 \\ -0.005537 \\ -0.005649 \end{array}$	$\begin{array}{c} -0.005886 \\ -0.005756 \\ -0.005652 \\ -0.005569 \\ -0.005412 \end{array}$	$\begin{array}{c} -0.0{}_{3}7491 \\ -0.001705 \\ -0.002353 \\ -0.002805 \\ -0.003394 \end{array}$	$ \begin{array}{c} -0.01186 \\ -0.01055 \\ -0.09676 \\ -0.00901 \\ -0.008379 \end{array} $	$\begin{array}{c} -0.004714 \\ -0.005105 \\ -0.005298 \\ -0.005317 \\ -0.005297 \end{array}$	$\begin{array}{c} -0.007021 \\ -0.006216 \\ -0.005797 \\ -0.005693 \\ -0.005633 \end{array}$	$\begin{array}{c} -0.006728 \\ -0.01980 \\ +0.008725 \\ +0.001135 \\ -0.001878 \end{array}$	$\begin{array}{c} -0.002812 \\ -0.03156 \\ -0.01336 \\ -0.01081 \\ -0.008844 \end{array}$	$\begin{array}{c} -0.005260 \\ -0.005288 \\ -0.005289 \\ -0.005283 \\ -0.005248 \end{array}$	$\begin{array}{c} -0.006018\\ -0.005851\\ -0.005764\\ -0.005703\\ -0.005667\end{array}$	$\begin{array}{r} 0 \cdot 002899 \\ + 0 \cdot 0_3 5848 \\ - 0 \cdot 0_3 7427 \\ - 0 \cdot 001605 \\ - 0 \cdot 002681 \end{array}$	$\begin{array}{c} -0.01411 \\ -0.01193 \\ -0.01057 \\ -0.009645 \\ -0.008457 \end{array}$
	$2 \cdot 6 \\ 3 \cdot 0 \\ 3 \cdot 4 \\ 3 \cdot 6 \\ 3 \cdot 8 \\ 3 \cdot 8 \\$	-0.005963 -0.006633 -0.008236	-0.005136 -0.005758 -0.004236	-0.003645 -0.003460 -0.002932 -0.002932	$ \begin{array}{c} -0.008219 \\ -0.009373 \\ -0.01468 \\ -$	$ \begin{array}{r} -0.005282 \\ -0.005241 \\ -0.005191 \\ -0.005135 \\ \end{array} $	$ \begin{array}{c} -0.005620 \\ -0.005626 \\ -0.005654 \\ -0.005697 \\ \end{array} $	$ \begin{array}{c} -0.002503 \\ -0.003269 \\ -0.003740 \\ -0.004072 \end{array} $	$ \begin{array}{r} -0.008315 \\ -0.007605 \\ -0.007137 \\ -0.006796 \\ \end{array} $	_0.005183 	0.005677 		
	$\begin{array}{c} 4 \cdot 0 \\ 4 \cdot 2 \\ 4 \cdot 6 \end{array}$			 		$-0.005062 \\ -0.004698$		$-0.004333 \\ -0.004561$	-0.006522 -0.006279	0.005024 	0.005805 	$\begin{array}{c} -0.004286\\\\\\\\\\\\\\\\\\\\ -$	0.006619 

THIS DOCUMENT PROVIDED BY THE ABBOTT AEROSPACE

TECHNICAL LIBRARY ABBOTTAEROSPACE.CAMPLE 11B

Flexure–Aileron–Tab Flutter (Aileron unbalanced)

		X =	- 3.0			X =	-2.5			X =	-1.0	
ω	Z1	· <i>W</i> <sub>1</sub>		W_2	Z <sub>1</sub>	$W_1$	Z <sub>2</sub>	$W_2$	Z <sub>1</sub>	W1	Z <sub>2</sub>	W2
$ \begin{array}{c} 0.6 \\ 0.8 \\ 1.0 \\ 1.2 \\ 1.4 \end{array} $	-0.005085 $-0.005441$ $-0.006026$	$-0.008399 \\ -0.006489 \\ -0.006014$	+0.01769 +0.003574 $-0.0_{3}4285$	$ \begin{array}{r} -0.03745 \\ -0.01796 \\ -0.01331 \\ \end{array} $	$ \begin{array}{ c c c c c c c c c c c c c c c c c c c$	$\begin{array}{c} -0.008359 \\ -0.007121 \\ -0.006553 \\ -0.006216 \\ -0.005963 \end{array}$	$\begin{array}{ } +0\cdot01770\\0\cdot008051\\0\cdot003493\\+0\cdot001034\\-0\cdot0_34255\end{array}$	$ \begin{array}{r} -0.03741 \\ -0.02400 \\ -0.01776 \\ -0.01446 \\ -0.01267 \end{array} $	$-0.005282 \\ -0.005342 \\ -0.005409 \\ -0.005476$	$-0.007020 \\ -0.006456 \\ -0.006127 \\ -0.005913$	$+0.0079350.003375+0.0_39130-0.0_35801$	$-0.02378 \\ -0.01749 \\ -0.01411 \\ -0.01209$
$     \begin{array}{r}       1 \cdot 6 \\       1 \cdot 8 \\       2 \cdot 0 \\       2 \cdot 2 \\       2 \cdot 6 \\       3 \cdot 0     \end{array} $	-0.002619-0.002930-0.003278-0.003782-0.003782	-0.008457 -0.008157 -0.007831 -0.007277 -0.006806	$-0.004046 \\ -0.004554 \\ -0.004661 \\ -0.004741 \\ -0.004668$	$-0.006721 \\ -0.006157 \\ -0.006116 \\ -0.006084 \\ -0.006146$	$ \begin{array}{c} -0.006460 \\$	-0.005629 $-0.007165$ $-0.006976$ $-0$	$ \begin{array}{c} -0.001224 \\ -0.004124 \\ -0.004502 \\ -0.004502 \end{array} $	-0.012340.0066320.006330	$ \begin{array}{c} -0.005566 \\ -0.005666 \\ -0.006143 \\ -0.01191 \\ \end{array} $	$ \begin{array}{c} -0.005750 \\ -0.005600 \\ -0.005218 \\ -0.003722 \\ \end{array} $	$ \begin{array}{c} -0.001519 \\ -0.002143 \\ -0.002793 \\ -0.002420 \\ \end{array} $	$ \begin{array}{c} -0.01083 \\ -0.01001 \\ -0.009336 \\ -0.01255 \\ \end{array} $

#### TABLE 11c

Flexure-Aileron-Tab Flutter (Aileron unbalanced)

		X =	— 10			<i>X</i> =	= — 5			X =	— 4	
ω	Z <sub>1</sub>	W <sub>1</sub>		W2	Z <sub>1</sub>	W <sub>1</sub>	. Z <sub>2</sub>	$W_2$	Z <sub>1</sub>	W1	Z <sub>2</sub>	W2
$ \begin{array}{c} 0.4 \\ 0.6 \\ 0.8 \\ 1.0 \\ 1.2 \\ 1.4 \\ 2.2 \\ 2.6 \\ 3.0 \\ \end{array} $	$\begin{array}{c} -0\cdot 004268\\ -0\cdot 003854\\ +0\cdot 01262\\ 0\cdot 005126\\ -\\ -\\ -\\ -\\ -\\ -0\cdot 001840\\ -0\cdot 002835\\ -0\cdot 003428\\ -0\cdot 003828\end{array}$	$\begin{array}{c} -0.01293 \\ -0.01221 \\ -0.02532 \\ -0.01807 \\ - \\ -0.009744 \\ -0.008494 \\ -0.007749 \\ -0.007251 \end{array}$	$\begin{array}{c} +0.04180 \\ +0.008017 \\ -0.005327 \\ -0.005229 \\$	$\begin{array}{c} -0.07394 \\ -0.03148 \\ -0.006156 \\ -0.006154 \\ -0.005832 \\ -0.005796 \\ -0.005766 \\ -0.005775 \\ -0.005851 \end{array}$	$\begin{array}{c} -0.005021\\ -0.005203\\ -0.005495\\ -0.003066\\ -0.0_{4}5265\\ -0.002044\\ -0.002999\\ -0.003951\end{array}$	$\begin{array}{c} -0.008560 \\ -0.007437 \\ -0.007275 \\ -0.01285 \\ -0.01155 \\ -0.009441 \\ -0.008287 \\ -0.007101 \end{array}$	$\begin{array}{r}$		$\begin{array}{c}$	$\begin{array}{c} - & - & - \\ - & 0 \cdot 008484 \\ - & - & 0 \cdot 006765 \\ - & 0 \cdot 006647 \\ - & 0 \cdot 009210 \\ - & 0 \cdot 008158 \\ - & 0 \cdot 007491 \\ - & 0 \cdot 007011 \end{array}$	$\begin{array}{c}$	$\begin{array}{c} - & - \\ - & 0 \cdot 03751 \\ - & 0 \cdot 01805 \\ - & 0 \cdot 01574 \\ - & 0 \cdot 005572 \\ - & 0 \cdot 005930 \\ - & 0 \cdot 005917 \\ - & 0 \cdot 005929 \\ - & 0 \cdot 005979 \end{array}$

THIS DOCUMENT PROVIDED BY THE ABBOTT AEROSPACE TECHNICAL LIBRARY ABBOTTAEROSPACE.COM

ę

# TABLE 12

# Binary Flutter (Aileron unbalanced)

		$Z = \infty$ ( $\overline{a}_1$	$_{1} = 0.0840$			$W = \infty \ (\overline{a}_{2})$	$_{13} = 0.0836)$	<i>.</i> .		$X = \infty \; (\overline{a}_{34}$	= 0.00540)	
a	X <sub>1</sub>	W <sub>1</sub>		W2	X1	Z <sub>1</sub>	$X_2$	Z <sub>2</sub>	Z <sub>1</sub>	W <sub>1</sub>		W2
0.2 0.2 0.6 0.6 56 1.0 1.2 1.4 1.6	$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$	$ \begin{array}{c} - & - & - & - & - & - & - & - & - & - &$	$ \begin{array}{c} - & - & - & - & - & - & - & - & - & - &$	0.0554072 $-0.0156952$ $0.0067231$	$   \begin{array}{r}     202 \cdot 9 \\     41 \cdot 44 \\     12 \cdot 61 \\     \hline     6 \cdot 996 \\     \overline{4 \cdot 817}   \end{array} $	$ \begin{array}{c} -0.4068 \\ -0.1078 \\ -0.0327 \\ -0.01786 \\ -0.01229 \end{array} $	$ \begin{array}{r} -29 \cdot 61 \\ -17 \cdot 06 \\ -7 \cdot 844 \\ -4 \cdot 516 \\ -2 \cdot 946 \\ \end{array} $	$ \begin{array}{c} -0.2893 \\ -0.05719 \\ -0.007563 \\ -0.001646 \\ -0.0_{3}6093 \end{array} $	$ \begin{array}{c} -0.00444 \\ -0.00516 \\ -0.00523 \\ -0.005265 \\ -$	$ \begin{array}{c}     -0 \cdot 01222 \\     -0 \cdot 00735 \\     -0 \cdot 00643 \\     -0 \cdot 00594 \\  \end{array} $	$\begin{array}{c}$	$ \begin{array}{c} -0.0930_{5} \\ -0.02658 \\ -0.01908 \\ -0.01266 \\ -0.001266 \\ -0.00$
$1 \cdot 8 \\ 2 \cdot 6$	$4 \cdot 590$	$\begin{array}{c c} 06 & -0.016240 \\ -0.00640 \\ -0.00640 \\ -0.00640 \\ -0.00640 \\ -0.00640 \\ -0.00640 \\ -0.00640 \\ -0.00640 \\ -0.00640 \\ -0.00640 \\ -0.00640 \\ -0.00600 \\ -0.00640 \\ -0$	$5 - 2 \cdot 40448$	-0.0038635	3.617	-0.009475	-1.982	-0.036250	-0.005225	-0.00574	-0.002155	-0.009265
$2 \cdot 4 \\ 2 \cdot 6 \\ 3 \cdot 6 \\ 3 \cdot 2 \\ 4 \cdot 6 \\ 4 \cdot 2 \\ 4 \cdot $	$ \begin{array}{c ccccccccccccccccccccccccccccccccccc$	$\begin{array}{cccccccccccccccccccccccccccccccccccc$	$7 - 1 \cdot 05762 \\ 7 - 0 \cdot 262334 \\ - 0 \cdot 485629 \\ 0 + 0 \cdot 485629 $	-0.0025141 -0.0026469 -0.0034600	$2 \cdot 850$ $2 \cdot 077$ $0 \cdot 9332$	$ \begin{array}{c} -0.007658 \\ -0.005974 \\ -0.003734 \\ \end{array} $	$ \begin{array}{c} - 1 \cdot 346 \\ - 0 \cdot 6330 \\ - 0 \cdot 4438 \\ - \end{array} $	$ \begin{array}{c} -0.0{}_{3}9375 \\ -0.001502 \\ -0.002911 \\ -0.002911 \end{array} $	-0.005053 $-0.00494$ $-0.00488$	$ \begin{array}{c}$	$ \begin{array}{c}$	-0.00729 -0.00655 -0.00641
Â.4									-0.00476	-0.00610	-0.00466	-0.00622

.



#### TABLE 13

## Flexural-Aileron-Tab Flutter (Aileron statically balanced)

	$X = \infty \ (\bar{a}_{34}$	= 0.01074)		= 10	X	= 0	X ==	- 5.0	Z ==	$\infty \ (\overline{a}_{14} = 0 \cdot 0$	<sub>3</sub> 436) $W = \infty$	
ω.	Ζ.	W	Z	W	Z	W	Z	W	X	W	X	Z
$ \begin{array}{c} 0.4 \\ 1.0 \\ 1.6 \\ 2.0 \\ 2.6 \\ 3.0 \\ 2.6 \\ 2.0 \\ 1.6 \\ \end{array} $	$\begin{array}{c} 0.06577 \\ + 0.001254 \\ - 0.005399 \\ - 0.006978 \\ - 0.008253 \\ - 0.008841 \\ - 0.009879 \\ - 0.01009 \\ - 0.01032 \\ - 0.01044 \end{array}$	$\begin{array}{c} -0.09888\\ -0.02511\\ -0.01705\\ -0.01512\\ -0.01356\\ -0.01285\\ -0.01166\\ -0.01145\\ -0.01127\\ -0.01127\end{array}$	$\begin{array}{c} +0.09266\\ +0.001734\\ -0.005360\\ -0.006983\\ -0.008271\\ -0.008852\\ -0.009911\\ -0.01011\\ -0.01033\\ -0.01044 \end{array}$	$ \begin{array}{ c c c c c c c c c c c c c c c c c c c$	$\begin{array}{c} 0.06672 \\ +0.001234 \\ -0.005589 \\ -0.007177 \\ -0.008484 \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\$	$\begin{array}{c} -0.09801 \\ -0.02480 \\ -0.01674 \\ -0.01484 \\ -0.01327 \\$	$\begin{array}{c} +0\cdot 06742 \\ +0\cdot 0_39559 \\ -0\cdot 005588 \\ -0\cdot 007022 \\ -0\cdot 008285 \\ \hline -0\cdot 008893 \\ -0\cdot 009805 \\ -0\cdot 01005 \\ -0\cdot 01031 \\ -0\cdot 01044 \\ \end{array}$	$\begin{array}{c} -0.09838\\ -0.02485\\ -0.01698\\ -0.01506\\ -0.01353\\ -0.01279\\ -0.01174\\ -0.01149\\ -0.01129\\ -0.01126\end{array}$	No	o real values	s for $\omega \ge 0$ .	4
$1 \cdot 0 \\ 0 \cdot 4$	-0.01054 -0.009848	-0.01171 -0.01741	$ \begin{vmatrix} -0 \cdot 01050 \\ -0 \cdot 008222 \end{vmatrix} $	-0.01181 -0.02087	$\begin{vmatrix} -0.01056 \\ -0.008984 \end{vmatrix}$	-0.01183 -0.01947	$ \begin{vmatrix} -0.01058 \\ -0.008969 \end{vmatrix} $	$ -0.01172 \\ -0.01950$				

THIS DOCUMENT PROVIDED BY THE ABBOTT AEROSPACE TECHNICAL LIBRARY ABBOTTAEROSPACE.COM

## TABLE 14A

## Torsion–Aileron–Tab. Flutter (Aileron unbalanced)

		Y	- 0			<i>Y</i> =	= 0.5			Y =	= 100	
ω	Z <sub>1</sub>	W <sub>1</sub>	Z <sub>2</sub>	W <sub>2</sub>	Z <sub>1</sub>	W1	Z <sub>2</sub>	W2	Z <sub>1</sub>	W <sub>1</sub>	Z <sub>2</sub>	W2
$0.2 \\ 0.6 \\ 0.8 \\ 1.0 \\ 1.4 \\ 1.8 \\ 2.2 \\ 2.6 \\ 3.0 \\ 3.4 \\ 3.8 \\ 4.2 \\ 4.6 \\ 1.4 \\ 1.8 \\ 1.4 $	$\begin{array}{c} +0\cdot2249\\ +0\cdot02280\\ -0\cdot01563\\ -0\cdot005284\\ -0\cdot005393\\ \hline -0\cdot005395\\ -0\cdot005370\\ -0\cdot005569\\ -0\cdot008741\\ -0\cdot001373\\ -0\cdot003758\\ -0\cdot004413\\ \hline \end{array}$	$\begin{array}{c} -0.3081 \\ -0.03885 \\ -0.05072 \\ -0.006807 \\ -0.005928_5 \\ \hline \\ -0.005709 \\ -0.005634 \\ -0.004399 \\ -0.007957 \\ -0.006939 \\ -0.006519 \\ -0.006219 \\ \hline \\ -0.006219 \\ \hline \\ \end{array}$	$\begin{array}{c} -0\cdot 004955\\ -0\cdot 005465\\ -0\cdot 006385\\ -0\cdot 0_4055\\ -0\cdot 002276\\ -0\cdot 003705\\ -0\cdot 004643\\ -0\cdot 005378\\ -0\cdot 005313\\ -0\cdot 005265\\ -0\cdot 005208\\ -0\cdot 005123\\ -0\cdot 005123\\$	$\begin{array}{c c} -0.02604 \\ -0.007197 \\ -0.0_39292 \\ -0.01552 \\ -0.01083 \\ -0.008580 \\ -0.007165 \\ -0.005457 \\ -0.005561 \\ -0.005590 \\ -0.005629 \\ -0.005697 \\ -0.0057697 \\ -0.0057697 \\ -0.0057697 \\ -0.00576$	$\begin{array}{c}$	$\begin{array}{c}\\\\\\\\\\\\\\\\\\$	$\begin{array}{c}$	$\begin{array}{c}$	$\begin{array}{c}$	$\begin{array}{c}\\\\\\\\\\\\ -0.01911\\0.01267\\\\ -0.008712\\\\ -0.007920\\\\ -0.0079393\\\\ 0.007013\\\\ -0.006719\\\\\\\\\\\\\\\\\\\\ -$	$\begin{array}{c}\\\\\\\\\\\\\\\\\\$	$\begin{array}{c}$

#### TABLE 14b

## Torsion-Aileron-Tab Flutter (Aileron unbalanced)

		Y =	- 0.05			Y =	-0.1			Y = -	- 0 • 15	
ω	Z <sub>1</sub>	W1	Z <sub>2</sub>	W_2	Z <sub>1</sub>	W <sub>1</sub>	Z <sub>2</sub>	W2	Z <sub>1</sub>	W <sub>1</sub>	$Z_2$	$W_2$
$   \begin{array}{c}     0 \cdot 2 \\     0 \cdot 6 \\     0 \cdot 8 \\     1 \cdot 0 \\     1 \cdot 2   \end{array} $	+0.2251 0.02230 +0.08353 -0.05254 -0.005378	$\begin{array}{c} -0.3083 \\ -0.03869 \\ -0.02775 \\ -0.007098 \\ -0.006261 \end{array}$	$ \begin{array}{c} -0.004943 \\ -0.005440 \\ -0.005717 \\ -0.0_36166 \\ -0.001205 \end{array} $	$ \begin{array}{ c c c c c c c c c c c c c c c c c c c$	+0.02192 0.02186 +0.005168 -0.005395	-0.03857-0.02561-0.007948-0.006375	-0.005418-0.005714-0.001971-0.001347	-0.007332-0.005495-0.01504-0.01327	$ \begin{array}{r} -0.02163 \\ +0.01527 \\ -0.005624 \\ \end{array} $	-0.03849-0.02468-0.006257	-0.005398 -0.005487 -0.001572	$ \begin{array}{c} -0.007385 \\ -0.005942 \\ -0.01412 \end{array} $
$1 \cdot 4$ $1 \cdot 8$ $2 \cdot 2$ $2 \cdot 6$ $2 \cdot 8$	$\begin{array}{c} -0.005406 \\ -0.005415 \\ -0.005402 \\ -0.005379 \\ -0.005373 \end{array}$	$\begin{array}{c} -0.005967 \\ -0.005722 \\ -0.005630 \\ -0.005626 \\ -0.005734 \end{array}$	$\begin{array}{c} -0.002167 \\ -0.003468 \\ -0.004248 \\ -0.004851 \\ -0.005184 \end{array}$	$ \begin{array}{c} -0.01112 \\ -0.008996 \\ -0.007902 \\ -0.007347 \\ -0.007774 \end{array} $	$ \begin{array}{c} -0.005430 \\ -0.005452 \\ -0.005456 \\ -0.005458 \\ -0.005458 \end{array} $	$ \begin{array}{c} -0.006014 \\ -0.005731 \\ -0.005613 \\ -0.005561 \\ \end{array} $	$ \begin{array}{c} -0.002114 \\ -0.003276 \\ -0.003943 \\ -0.004354 \\ -0.004354 \end{array} $	$ \begin{array}{c} -0.01146 \\ -0.009438 \\ -0.008572 \\ -0.008871 \\\end{array} $	$ \begin{array}{c} -0.005482 \\ -0.005523 \\ -0.005560 \\ -0.005613 \\ -0.005613 \end{array} $	$ \begin{array}{c} -0.006090 \\ -0.005736 \\ -0.005578 \\ -0.005482 \\ -\end{array} $	$\begin{array}{c} -0.002152 \\ -0.003118 \\ -0.003667 \\ -0.003897 \\ -\end{array}$	$\begin{array}{c} -0.01198 \\ -0.01007 \\ -0.009599 \\ -0.0127_5 \end{array}$
$3 \cdot 0$ $3 \cdot 4$ $3 \cdot 8$ $4 \cdot 2$	$\begin{array}{c} -0.005729 \\ -0.003205 \\ -0.004132 \\ -0.004715 \end{array}$	$ \begin{array}{c} -0.006489 \\ -0.006362 \\ -0.006159 \\ -0.005960 \end{array} $	$ \begin{array}{c} -0.005338 \\ -0.005305 \\ -0.005257 \\ -0.005176 \end{array} $	$ \begin{array}{ c c c c c c c c c c c c c c c c c c c$	$ \begin{array}{c} -0.005494 \\ -0.002091 \\ -0.004959 \\ -0.005156 \end{array} $	$ \begin{array}{c} -0.005539 \\ -0.005545 \\ -0.005686 \\ -0.005631 \end{array} $	$ \begin{array}{c} -0.004631 \\ -0.004877 \\ -0.005231 \\ -0.005177 \end{array} $	$-0.001672 \\ -0.005458 \\ -0.005547 \\ -0.005616$	0·005774  	-0·005378  	0·003532  	0·003972   

THIS DOCUMENT PROVIDED BY THE ABBOTT AEROSPACE

ABBOTTAEROSPACE.COM

							<b>`</b>					
		Y =	-0.2			Y =	-0.3			Y =	-0.5	
ω	Z <sub>1</sub>	W <sub>1</sub>	Z <sub>2</sub>	W2	Z1	W <sub>1</sub>	Z <sub>2</sub>	W <sub>2</sub>	Z <sub>1</sub>	W1	Z <sub>2</sub>	$W_2$
0.20.60.81.01.2	$\begin{array}{c}$	$-0.03843 \\ -0.02429 \\ -0.01738 \\ -0.007000$	$-0.005381 \\ -0.005443 \\ -0.005429 \\ -0.002843$	$\begin{array}{c} -0.007433 \\ -0.006134 \\ -0.004426 \\ -0.01668 \end{array}$	$\begin{array}{c} +0.2262 \\ 0.02108 \\ \\ 0.00673 \\ 0.005072 \end{array}$	$ \begin{array}{ c c c c c c c c c c c c c c c c c c c$	$ \begin{vmatrix} -0 \cdot 00491 \\ -0 \cdot 00535 \\ -0 \cdot 00535 \\ -0 \cdot 005373 \end{vmatrix} $	$ \begin{array}{c} -0.0262 \\ -0.00751 \\ -0.00570 \\ -0.00516 \end{array} $	$ \begin{array}{c}$	$ \begin{array}{c} -0.02385 \\ -0.001699 \\ \end{array} $	$ \begin{array}{c}$	$ \begin{array}{c}     -0.006542 \\     -0.006054 \\    \end{array} $
$1 \cdot 4 \\ 1 \cdot 8 \\ 2 \cdot 2 \\ 2 \cdot 6 \\ 2 \cdot 8$	$\begin{array}{c} -0.005626\\ -0.005693\\ -0.005834\\ -0.006234\\ -0.008546\end{array}$	$\begin{array}{c} -0.006260\\ -0.005739\\ -0.005497\\ -0.005258\\ -0.004860\end{array}$	$\begin{array}{c} -0.002401 \\ -0.002984 \\ -0.003309 \\ -0.002798 \\ -0.05285 \end{array}$	$\begin{array}{c} -0.01333 \\ -0.01166 \\ -0.01427 \\ -0.0_35621 \\ -0.004484 \end{array}$	+0.00332 -0.00283 	$ \begin{array}{c} -0.00945 \\ -0.00644 \\ \\ \\ \\ \\ \\ \\ \\ $	$ \begin{array}{c} -0.00487 \\ -0.00391 \\ \\ \\ \\ \\ \\ \\ \\ -$	$ \begin{array}{c} -0.005102 \\ -0.005770 \\ \\ \\ \\ \\ \\ \\ \\ -$	-0.034969 -0.002509 -0.003474 -0.004024	$\begin{array}{c} -0.01105 \\ -0.008742 \\ -0.007627 \\ -0.006981 \\ -\end{array}$	$\begin{array}{c} -0.005209 \\ -0.005111 \\ -0.005033 \\ -0.004966 \\ -\end{array}$	$ \begin{array}{c} -0.005776 \\ -0.005755 \\ -0.005796 \\ -0.005858 \\ \end{array} $
<b>3</b> ·0	_				_		·	· · · · · · · · · · · · · · · · · · ·	-0.004410	-0.006516	-0.004866	-0.005967

TABLE 14cTorsion-Aileron-Tab Flutter (Aileron unbalanced)

60

TABLE 15Binary Flutter (Aileron unbalanced)

		$Y = \infty$ ( $\overline{a}$	$a_{34} = 0.0054$			$Z = \infty \ (\overline{a}_2$	$_{24} = 0.0373)$			$W = \infty \ (\overline{a}_{23}$	= 0.0370)	
ω	Z <sub>1</sub>	W1	Z <sub>2</sub>	$W_2$	Y <sub>1</sub>	W <sub>1</sub>	Y2	$W_2$	Y <sub>1</sub>	Z <sub>1</sub>		
$\begin{array}{c} 0 \cdot 4 \\ 0 \cdot 2 \\ 0 \cdot 8 \\ 1 \cdot 0 \\ 1 \cdot 2 \\ 1 \cdot 4 \\ 1 \cdot 8 \\ 2 \cdot 0 \\ 2 \cdot 2 \\ 2 \cdot 6 \end{array}$	$ \begin{array}{c} -0.00444 \\ -0.00516 \\ -0.00523 \\ \\ -0.00526_{5} \\ -0.00522_{5} \\$	$ \begin{array}{c} -0.01222 \\ -0.00735 \\ -0.00643 \\ -0.005940 \\ -0.00574 \\ -0$	$ \begin{array}{c c} +0.07061 \\ \hline 0.01201 \\ 0.00591 \\ \hline \\ +0.0_36142 \\ \hline -0.002155 \\ \hline \\ \\$	$ \begin{array}{c} -0.0930_{5} \\ -0.02658 \\ -0.01908 \\ \\ -0.01266 \\ -0.009265 \\ \\ \\ \\ \\ \\ \\ \\ -$	$7 \cdot 5686$ $3 \cdot 4189$ $1 \cdot 98256$ $1 \cdot 30540$ $0 \cdot 92469$ $0 \cdot 68561$ $0 \cdot 40341$	$\begin{array}{c} -0.19537 \\ -0.092492 \\ -0.056145 \\ -0.0389624 \\ -0.029359 \\ -0.023374 \\ -0.016442 \\ -0.016442 \\$	$\begin{array}{c} +2\cdot 1296 \\ +0\cdot 41645 \\ -0\cdot 038268 \\ -0\cdot 197355 \\ -0\cdot 257846 \\ -0\cdot 27881 \\ -0\cdot 27536 \\ -0 \\ -0 \\ \\ \\ \\ \\ \\ -$	$\begin{array}{c} -0.14302 \\ -0.056279 \\ -0.028943 \\ -0.0174284 \\ -0.011739 \\ -0.008618 \\ -0.005728 \\ -0 \\ \\ \\ \\ \end{array}$	$2 \cdot 96957 \\1 \cdot 71775 \\1 \cdot 11770 \\ \\0 \cdot 561585 \\0 \cdot 303193 \\ \\0 \cdot 148744 \\0 \cdot 0330638 \\$	$\begin{array}{c} & & - \\ & & 0 \cdot 0487691 \\ - & 0 \cdot 0308518 \\ - & 0 \cdot 0222463 \\ & & - \\ & & - \\ & - & 0 \cdot 0142179 \\ - & 0 \cdot 0104444 \\ - & 0 \cdot 0104444 \\ - & 0 \cdot 0081852 \\ - & 0 \cdot 0064882 \end{array}$	$\begin{array}{c}$	$-0.021711 \\ -0.0104432 \\ -0.0061487 \\ -0.0033874 \\ -0.0028707 \\ -0.0030156 \\ -0.0035063 \\ -0.0$
3.0	-0.005053	-0.00582	-0.00376	-0.00729	0.040583	-0.008116	-0.17824	0.0045736	<u></u>		· .	

See results for  $X = \infty$  in Table 11

TABLE 16

# Torsion-Aileron-Tab Flutter (Aileron statically balanced)

THIS DOCUMENT PROVIDED BY THE ABBOTT AEROSPACE

 $\Delta$ 

ABBOTTAEROSPACE.COM

**THD** 

ΤE

(1)	Y =	= 1.0	Y =	0.5	Y =	· 0·2	Y =	= 0	Y = -	- 0.2
	Z	W	Z	W	Z	· W	Z	W	Z	· W
$0.6 \\ 0.8 \\ 1.0 \\ 1.2 \\ 1.4$	$\begin{array}{c} +0.02014\\ -0.01077\\ -0.03276\\ 0.002867\\ -0.002912\end{array}$	$\begin{array}{c} -0.04543 \\ -0.01152 \\ -0.03374 \\ -0.02152 \\ -0.01849 \end{array}$	$ \begin{array}{c} +0.01510 \\ +0.007878 \\ -0.01093 \\ -0.01074 \\ -0.01386 \end{array} $	$\begin{array}{c} -0.04414 \\ -0.03005 \\ -0.01353 \\ -0.01186 \\ -0.01344 \end{array}$	$ \begin{array}{c} +0.01503 \\ +0.0_31012 \\ -0.002615 $	$ \begin{array}{c} -0.04439 \\ -0.02293 \\ -0.01768 \\ \end{array} $	$\begin{array}{r} +0.01518 \\ +0.004648 \\ -0.0_33445 \\ -0.003234 \\ -0.005195 \end{array}$	$\begin{array}{c} -0.04461 \\ -0.03036 \\ -0.02355 \\ -0.01963 \\ -0.01701 \end{array}$	$ \begin{array}{c} +0.01538 \\ -0.032911 \\ -0.004856 \end{array} $	$ \begin{array}{c} -0.04483 \\ -0.02388 \\ -0.01789 \end{array} $
$1 \cdot 6 \\ 1 \cdot 8 \\ 2 \cdot 0 \\ 2 \cdot 2 \\ 2 \cdot 4$	-0.006200 -0.007990	-0.01567 -0.01377	$ \begin{array}{r} -0.003401 \\ -0.007344 \\ -0.008392 \\ \end{array} $	$ \begin{array}{c} -0.01462 \\ -0.01389 \\ -0.01311 \end{array} $	$\begin{array}{c} -0.01208 \\ -0.01161 \\ -0.01156 \\ -0.01182 \\ -\end{array}$	$ \begin{array}{c} -0.01075 \\ -0.01069 \\ -0.01058 \\ -0.01036 \\ -0.01036 \end{array} $	 	_0·01281 	-0.006907 -0.007552 	$ \begin{array}{c} -0.01525 \\ -0.01444 \\ \\ \\ \\ \\ \\ \\ \\$
$3 \cdot 0$ $3 \cdot 0$ $2 \cdot 4$ $2 \cdot 2$ $2 \cdot 0$	$ \begin{array}{c} -0.008921 \\ -0.009951 \\ -0.01021 \\                                    $	$ \begin{array}{c} -0.01272 \\ -0.01157 \\ -0.01132 \\ \\ \\ \\ \\ \\ \\ \\ -$	$ \begin{array}{c} -0.009300 \\ -0.009849 \\ -0.01013 \\ -0.01030 \end{array} $	$ \begin{array}{r} -0.01224 \\ -0.01165 \\ -0.01136 \\ -0.01122 \\ \end{array} $	$-1.3440 \\ +0.002639$	-0.006488 -0.002670			 	  
$1 \cdot 8$ $1 \cdot 6$ $1 \cdot 4$ $1 \cdot 2$ $1 \cdot 0$	-0.01042 $-0.01053$ $-0.01057$ $-0.01056$	$-0.01121 \\ -0.01127 \\ -0.01140 \\ -0.01178$	$-0.01033 \\ -0.01003 \\ -0.007605 \\ -0.009169$	$-0.01110 \\ -0.01030 \\ -0.03191 \\ +1.0194$	$ \begin{array}{r} -0.001197 \\ -0.001101 \\ -0.01025 \\ -0.01052 \\ \end{array} $	$ \begin{array}{r} +0.0_{3}8964 \\ -0.003216 \\ -0.01132 \\ -0.01157 \\ \end{array} $	$ \begin{array}{c} -0.008986 \\ -0.01026 \\ -0.01043 \\ -0.01053 \end{array} $	$-0.01243 \\ -0.01141 \\ -0.01143 \\ -0.01163$	$-0.01013 \\ -0.01038 \\ -0.01053$	$ \begin{array}{r} -0.01146 \\ -0.01137 \\ -0.01166 \\ \end{array} $
$\begin{array}{c} 0\cdot 8 \\ 0\cdot 6 \end{array}$	-0.007117 -0.01063	-0.02105 -0.01300	-0.01061 -0.01057	-0.01199 -0.01313		-0.01319	-0.01057 -0.01053	$-0.01212 \\ -0.01322$	-0.01051	-0.01325

TECHNICAL LIBRARY

.....

# TABLE 17

## Binary Flutter (Aileron statically balanced)

·	ω		$X  ext{ or } Y = \infty$	$(\overline{a}_{34} = 0.0107)$	74)		$W = \infty$ (ā	$\bar{b}_{23} = 0.0107$			$Z = \infty \ (\overline{a}_{24} =$	= 0 • 01096)	
	ω	Z <sub>1</sub>	W <sub>1</sub>	Z <sub>2</sub>	W2	Z <sub>1</sub>	$Y_1$	$Z_2$	$Y_2$	Y1	W <sub>1</sub>	$Y_2$	W2
62	$ \begin{array}{c} 0 \cdot 4 \\ 0 \cdot 6 \\ 0 \cdot 8 \\ 1 \cdot 0 \\ 1 \cdot 2 \end{array} $	+0.06577 	-0.09888 -0.02511	-0.009848 	$ \begin{array}{c} -0.01741 \\ -0.01171 \\ -0.01171 \\ -0.01171 \end{array} $	$\begin{array}{c} -0.08739 \\ -0.03889 \\ -0.02188 \\ -0.01394 \\ -0.009500 \end{array}$	$5 \cdot 8415$ 2 $\cdot 5623$ 1 $\cdot 4160$ 0 $\cdot 8793$ 0 $\cdot 5787$	$\begin{array}{c} -0.06624 \\ -0.02613 \\ -0.01405 \\ -0.009158 \\ -0.006861 \end{array}$	$3 \cdot 4741$ $1 \cdot 3868$ $0 \cdot 7600$ $0 \cdot 5003$ $0 \cdot 3767$	$3 \cdot \overline{051}$ $1 \cdot \overline{090}$	$ \begin{array}{c} -0.08208 \\ -0.03017 \\ -0.03017 \end{array} $	$1 \cdot 105$ $0 \cdot 4160$	$ \begin{array}{c c} -0.06071 \\ -0.02052 \\ -$
	$   \begin{array}{r}     1 \cdot 4 \\     1 \cdot 6 \\     1 \cdot 8 \\     2 \cdot 0 \\     2 \cdot 4 \\     2 \cdot 6 \\     3 \cdot 0 \\   \end{array} $	-0.005399 -0.006978 -0.008253 -0.008841	$ \begin{array}{c} -0.01705 \\ -0.01512 \\ -0.01356 \\ -0.01285 \\ \end{array} $	$ \begin{array}{c} -0.01044 \\ -0.01032 \\ -0.01009 \\ -0.009879 \end{array} $	-0.01127 $-0.01127$ $-0.01145$ $-0.00166$					0.5557 0.3294 0.2592 0.1996 	$ \begin{array}{c} -0.01581 \\ -0.009768 \\ -0.00794 \\ -0.00646 \\ \\ \\ \\ \\ \\ \\ \\ -$	0·2145 0·1475 0·1330 0·1306	$ \begin{array}{c} -0.01061 \\ -0.006986 \\ -0.00592 \\ -0.00535 \\ \\ \\ \\ \\ \\ \\ \\ -$

TECHNICAL LIBRARY ABBOTTAEROSPACE.COM

# TABLE 18

# Torsion–Aileron–Tab Flutter (Aileron dynamically balanced)

	Y	= 0	Y =	· 0·2	Y =	= 0.5	$Y = \infty \ (\overline{a}_{34}$	u = 0.01291)	$ Z = \infty \ (\overline{a}_{24}$	$= 0.0_{3}258)$	$W = \infty$	$(\bar{a}_{23} = 0)$
ω	Z	W	Z	W	Z	W	Z	W	Y	W	Y	Z
$ \begin{array}{c} 0 \cdot 4 \\ 0 \cdot 6 \\ 1 \cdot 0 \\ 1 \cdot 4 \\ 1 \cdot 8 \\ 2 \cdot 2 \\ 3 \cdot 0 \\ 3 \cdot 0 \\ 2 \cdot 2 \\ 1 \cdot 8 \end{array} $	$\begin{array}{c}$	$-0.04752 \\ -0.02676 \\ -0.02073 \\ -0.01816 \\ -0.01663 \\ \\ \\ \\ -0.01381 \\ -0.01362 $	$ \begin{array}{c} - 0 \cdot 01307 \\ - 0 \cdot 002218 \\ - 0 \cdot 006924 \\ - \\ - \\ - \\ - \\ - \\ - \\ - \\ - \\ - \\ -$	$ \begin{array}{c} -0.04722 \\ -0.02644 \\ -0.01994 \\ \\ \\ \\ \\ \\ \\ \\ -$	$\begin{array}{c}\\ +0 \cdot 01274\\ -0 \cdot 001980\\ -0 \cdot 007147\\ -0 \cdot 009541\\ -0 \cdot 01073\\\\ -0 \cdot 01165\\ -0 \cdot 01199 \end{array}$	$ \begin{array}{c} -0.04688 \\ -0.02540 \\ -0.01935 \\ -0.01626 \\ -0.01515 \\ -0.01418 \\ -0.01383 \end{array} $	$\begin{array}{c} +0.06381\\ +0.01967\\ -0.0_36566\\ -0.006036\\ -0.008299\\ -0.009537\\ -0.01117\\ -0.01157\\ -0.01223\\ -0.01243\end{array}$	$\begin{array}{c} -0\cdot 1013 \\ -0\cdot 05133 \\ -0\cdot 02754 \\ -0\cdot 01828 \\ -0\cdot 01828 \\ -0\cdot 01677 \\ -0\cdot 01481 \\ -0\cdot 01367 \\ -0\cdot 01354 \end{array}$	6.716 2.703 No values	$\begin{vmatrix} -0.1784 \\ -0.07545 \end{vmatrix}$ for $\omega > 0.8$	5·151 No values	$\left  -0.07893 \right $ for $\omega > 0.6$
$1 \cdot 4$ $1 \cdot 0$ $0 \cdot 6$ $0 \cdot 4$	$ \begin{array}{c c} -0.01250 \\ -0.01268 \\ -0.01264 \\ -\end{array} $	$ \begin{array}{c} -0.01363 \\ -0.01391 \\ -0.01552 \\ \end{array} $	$-0.01239 \\ -0.01268 \\ -0.01265 \\ -0$	$ \begin{array}{c} -0.01369 \\ -0.01391 \\ -0.01551 \\ - \\ - \\ \end{array} $	$-0.01216 \\ -0.01259 \\ -0.01266 \\ -$	$ \begin{array}{c} -0.01367 \\ -0.01401 \\ -0.01550 \\ \end{array} $	-0.01259-0.01269-0.01255-0.01204	$-0.01354 \\ -0.01388 \\ -0.01571 \\ -0.01951$	$1.830 \\ 3.895$	-0.06492 - 0.1512	$4 \cdot 422$	-0.07242

## TABLE 19

ECHNICAL LIBRARY ABBOTTAEROSPACE.COM

# Approximate Air-Load Coefficients\*

$C_{11} \\ C_{12} \\ C_{13} \\ C_{14}$	$\begin{array}{rrrr} 2 \cdot 090 & -2 \cdot 606  \omega^2 \\ 4 \cdot 523 & -0 \cdot 4079  \omega^2 \\ 1 \cdot 270 & -0 \cdot 01617  \omega^2 \\ 0 \cdot 1278 & -0 \cdot 0_4 9084  \omega^2 \end{array}$	$\begin{array}{c} B_{11} \\ B_{12} \\ B_{13} \\ B_{14} \end{array}$	$\begin{array}{rrrr} +0.8240 & +5.213\omega \\ -0.4290 & +3.765\omega \\ -0.1949 & +0.3452\omega \\ -0.02277 & +0.008407\omega \end{array}$
$C_{21} \\ C_{22} \\ C_{23} \\ C_{24}$	$\begin{array}{rrrr} -0.08540 & -0.4079\omega^2 \\ -0.3632 & -0.1167\omega^2 \\ +0.2569 & -0.005009\omega^2 \\ 0.04278 & -0.0_43554\omega^2 \end{array}$	$\begin{array}{c} \cdot & B_{21} \\ & B_{22} \\ & B_{23} \\ & B_{24} \end{array}$	$\begin{array}{rrrr} -0.03350 & +0.2138\omega \\ +0.01780 & +0.6266\omega \\ 0.008180 & +0.09936\omega \\ 0.001058 & +0.003236\omega \end{array}$
$C_{31} \\ C_{32} \\ C_{33} \\ C_{33} \\ C_{34}$	$\begin{array}{rrrr} 0 \cdot 003600 & -0 \cdot 01617  \omega^2 \\ 0 \cdot 002086 & -0 \cdot 005009  \omega^2 \\ 0 \cdot 01431 & -0 \cdot 0_3 5383  \omega^2 \\ 0 \cdot 006896 & -0 \cdot 0_5 6194  \omega^2 \end{array}$	$B_{31} \\ B_{32} \\ B_{33} \\ B_{34}$	$\begin{array}{rrrr} +0\cdot001420 & +0\cdot009010\omega \\ -0\cdot0_37000 & +0\cdot02145\omega \\ -0\cdot0_35080 & +0\cdot009079\omega \\ -0\cdot0_48560 & +0\cdot0_35493\omega \end{array}$
$C_{41} \\ C_{42} \\ C_{43} \\ C_{44}$	$\begin{array}{rrrr} 0 \cdot 0_4 1836 & -0 \cdot 0_4 9084  \omega^2 \\ 0 \cdot 0_4 3936 & -0 \cdot 0_4 3554  \omega^2 \\ 0 \cdot 0_4 9178 & -0 \cdot 0_5 6194  \omega^2 \\ 0 \cdot 0_3 2447 & -0 \cdot 0_6 50577  \omega^2 \end{array}$	$egin{array}{c} B_{41} \ B_{42} \ B_{43} \ B_{44} \end{array}$	$\begin{array}{rrrr} +0\cdot 0_57320 & +0\cdot 0_44654\omega \\ -0\cdot 0_54600 & +0\cdot 0_31511\omega \\ -0\cdot 0_53780 & +0\cdot 0_48344\omega \\ -0\cdot 0_52280 & +0\cdot 0_43559\omega \end{array}$

\* ' Barred ' coefficients are obtained by use of formula (5.4).

Ň



FIG. 1a. Diagram of non-preloaded spring tab No. 1.

(Note. Both the aileron and the tab are shown displaced from central position in the positive senses which are standard in flutter theory.)









65

E

(1752)

#### IS DOCUMENT PROVIDED BY THE ABBOTT AEROSPACE TECHNICAL LIBRARY ABBOTTAEROSPACE.COM



 $\label{eq:Fig.3.1} Fig. 3. \ \ Diagram \ of \ control \ circuit \ connections \ with \ spring \ tab \ No. \ 1.$  (System is shown with small general displacements. For convenience the levers  $L_{p}, \ L_{s}, \ and \ the \ control \ column \ C_{o} \ are \ drawn \ in \ the \ plane \ of \ the \ wings.)$ 











FIG. 5. Ternary inertia-stiffness diagram (para. 9).

*Explanation*:  $P_1$  lies on that base curve X = k for which  $P_1'M = k$ . The critical speed is then given by any of the relations

 $X' = \omega^2 P_1' N = \omega^2 (k + a_{11}), Z' = \omega^2 P_1 M, W' = \omega^2 I M.$ 

The appropriate value of  $\omega^2$  can be found from a supplementary frequency parameter diagram.

١



FIG. 6. Diagram of wing-aileron-tab combination.

更 2









FIG. 8a. Flexure-torsion inertia-stiffness diagram (para. 2). Base curves.





TECHNICAL LIBRARY ABBOTTAEROSPACE.COM



FIG. 9a. Flexure-aileron inertia-stiffness diagram (para. 13). Base curves.



FIG. 9b. Flexure-aileron inertia-stiffness diagram (para. 13). Frequency parameter curves.

÷







FIG. 11a. Torsion-aileron inertia-stiffness diagram (para. 14). Base curves.
ABBOTTAEROSPACE.COM







X

٠.

FIG. 13a. Aileron-tab inertia-stiffness diagram (para. 15). Base curves for N = 2 and  $\overline{p} = 0$  to 0.0125.





ECHNICAL LIBRARY

ABBOTTAEROSPACE.COM









74







Fig. 15b. Aileron-tab inertia-stiffness diagram (para. 15). Frequency parameter curves for N = 3.

75

.

TECHNICAL IBRARY ABBOTTAEROSPACE.COM









FIG. 17. Stability diagram for binary aileron-tab flutter (para. 16). Spring tab No. 2.





THIS DOCUMENT PROVIDED BY THE ABBOTT AEROSPACE TECHNICAL LIBRARY ABBOTTAEROSPACE.COM



FIG. 19. Base curves for normal aileron with elastically hinged tab (see end of para. 16).

**7**8

(12)



ABBOTTAEROSPACE.COM



TECHNICAL LIBRARY

ABBOTTAEROSPACE.COM



FIG. 23a. Flexure-aileron-tab inertia-stiffness.diagram (aileron unbalanced).



FIG. 23b. Flexure–aileron–tab inertia-stiffness diagram (aileron unbalanced).

ABBOTTAEROSPACE.COM



FIG. 24. Flexure-aileron-tab inertia-stiffness diagram (aileron statically balanced).



FIG. 25a. Torsion-aileron-tab inertia-stiffness diagram (aileron unbalanced).

82

ABBOTTAEROSPACE.COM

Z 6 0.01 Inertia Points -0-- Y= -0-1 Iat-0.00549,-0.00533. +-Y=-0.2 I'at-0.00549-1.095 -0.02 -0.03 -0.02 lo (2.42)-+ **\_(**2·90)**\_**@ (1.10)-(0-91)-0 -0-01 -0.02 (1:005) (0-86) (3·38)(2·795) -0-03

FIG. 25b. Torsion-aileron-tab inertia-stiffness diagram (aileron unbalanced)



FIG. 25c. Torsion-aileron-tab inertia-stiffness diagram (aileron unbalanced).

F 2

83

(1752)

TECHNICAL LIBRARY

ABBOTTAEROSPACE.COM



FIG. 26a. Torsion-aileron-tab inertia-stiffness diagram (aileron statically balanced).





ABBOTTAEROSPACE.COM

`



FIG. 27. Torsion-aileron-tab inertia-stiffness diagram (aileron dynamically balanced).



FIG. 28.—Flexure-torsion inertial-stiffness diagram with approximations.

CHNICAL LIBRARY E ABBOTTAEROSPACE.COM





86



FIG. 30a. Torsion-aileron inertia-stiffness diagram with approximations. Base curves.



ABBOTTAEROSPACE.COM



FIG. 31a. Aileron-tab inertia-stiffness diagram with approximations. Base curve.





#### TECHNICAL LIBRARY ABBOTTAEROSPACE.COM







# PART II

## Experiments on Binary Aileron-Tab Flutter

By

#### C. SCRUTON, B.Sc., J. WILLIAMS, B.Sc., and C. J. W. MILES

1. Summary:—A theoretical discussion of the effect of non-preloaded spring tab control on wing-aileron-tab flutter, in which the binary aileron-tab case is included, is given by Frazer and Jones in Part I. The experiments here described were made to test certain of their conclusions for binary aileron-tab flutter.

2. The Model.—The model was designed for tests in a 4-ft square wind tunnel. The wing (see Fig. 1), of 1.47-ft chord and 3-ft span and of NACA 2209 section, was rigidly constructed in wood. Fillets were fitted to the inboard end, where the wing was built into a plate for fixing to the tunnel floor.

Both aileron and tab were initially made of solid pine in order to obtain a density ratio  $(\Delta)^*$  of 1/1. Later this ratio was reduced by lightening holes in the aileron. The attachment of aileron to wing was by two small journal hinges and that of tab to aileron by two point and cup hinges. Balance arms, which were offset from the chord lines, were fitted to the aileron and to the tab, but subsequently that of the tab was changed to an arm with no offset and the necessary recess was cut from the aileron.

Details of the model representation of the elastic characteristics of the spring control are shown in Fig. 2. Here the flat spring (a), which represents the stiffness of the control circuit  $(2\sigma_0)$ , is earthed at one end to the wing by an adjustable mounting and is fixed at the other end to the floating arm (b). The arm (b) is pivoted at the aileron hinge axis and is elastically connected to the aileron by means of the adjustable clamping link (d) and the piano-wire spring (c). Spring (c), which represents the stiffness of the tab mechanism spring ( $\sigma$ ), is built into the aileron on the hinge axis. Connection between F at the top of arm (b) to M on the tab lever was made by a link of hypodermic tubing which was pin-jointed to F and M. It can easily be shown by comparison of the strain energies that this system is elastically equivalent to the spring tab control system of Fig. 1a, Part I. The equivalent leverages AF, AI and TM are similarly denoted in Fig. 2 of this Part and in Fig. 1a of Part I. For the model AF and TM were of fixed length such that N = 6, AI was variable to give values of n between 0 and 2.

No measurements of the inertial values were made when the aileron was of solid pine. After the aileron was lightened and without any additional masses the aileron and tab had the following inertial values.

> $\mu_a = 0.39 \text{ lb}$   $\mu_t = 0.02 \text{ lb}$   $A_{33} = 0.93 \text{ lb/in.}^2$   $A_{44} = 1.6 \times 10^{-3} \text{ lb/in.}^2$  $P = 3.0 \times 10^{-3} \text{ lb/in.}^2$

3. Results.—Tests of Recommendations of Part I.—(a) The Effect of Density Ratio  $\Delta$ .—No systematic variation of  $\Delta$  was attempted. Before the aileron was lightened the density ratio was approximately unity. No flutter within the speed range of the tunnel could then be obtained

<sup>\*</sup> The symbols used accord with those used in Part I.



but successive additions of masses to the trailing edge of the tab progressively lowered the critical speed. The aileron was then lightened in order to obtain flutter without addition of mass to the tab and a critical speed within the tunnel range obtained. If the lightened aileron can be regarded as homogeneous the density ratio was then about 1/3.

(b) The Effect of Addition of Mass to the Aileron (see Table).—Addition of mass to the aileron invariably increased the critical speed. A comparison was made of the effect of equal additions to the moment of inertia of the aileron by masses—added firstly to the aileron balancing arm and then to the trailing edge. The first method was slightly more effective than the second. This may have been due to very slight movements of the main wing.

(c) The Effect of the Location of the Tab Balancing Mass.—Tests were made with an offset balancing arm before the disadvantageous nature of such an arrangement was realised. In the Appendix it is shown that the neutral point (*i.e.*, the position forward of the hinge axis behind which mass has to be placed in order to be advantageous) recedes as the offset increases. The offset for the model arm was such that the neutral point was behind the rearmost tab balancing position available (D/21). It was found that any addition of mass to the arm reduced the critical speed.

The results of tests for n = 0 and n = 2 with the non-offset balancing arm are given in Fig. 3 and Fig. 4. Here the neutral point was distance D/7 forward of the tab hinge axis and the curves show that for n = 2 addition of mass was advantageous only when placed behind this position and that the addition of a mass at the neutral point which statically balanced the tab did not appreciably affect the critical speed. This conforms well with the theory but heavier masses added at the neutral point tended to decrease the critical speed. This decrease is more marked when n = 0 although the curves show the same general characteristics as those for n = 2. In both cases no flutter occurred within the tunnel speed range when the tab was statically mass balanced at position 2D/21. Unfortunately no position intermediate between 2D/21 and D/7could be used but from the asymptotic trend of the curves it is probable that the system would be stable for all wind speeds if the tab were statically balanced by a mass rearward of the 2D/21

Fig. 4 shows the rate of increase of the critical speed with the addition of mass at the 2D/21 position. If, as is deduced from Fig. 3, the system is stable when the tab is balanced by mass at the 2D/21 position then it appears that a close approach to static mass balance is necessary to raise the critical speed appreciably.

Tests with Fluid Damping and Solid Friction.—Fluid damping and solid friction were applied separately between the floating arm (b) and the wing to represent such dampings on the spring casing of spring tab No. 1 of Part I.

Increase in damping or friction invariably increased the critical speed. The largest amount of fluid damping applied, that due to a 0.5 sq in. vane attached to the outer end of arm (b) and moving in heavy gear oil, only increased the critical speed from 44 to 48 feet per second. Solid friction, provided by a felt pad attached to the arm (b) and rubbing on a brass plate, was more effective. The critical speed increased with the pressure on the felt pad until there was no movement between the felt pad and the brass plate. In this condition flutter at a high speed was still possible because of flexibility in the connection of the felt pad to the arm.

4. Conclusions.—The recommendations (a), (b), (c) and (d) of para. 16 of Part I are confirmed by the model tests. In the application of recommendation (c) it is important to consider the dependence of the position of the neutral point on the offset of the balancing mass.



#### TABLE

#### The Effect of Addition of Mass to the Aileron

The inertial condition of model before the addition of masses is as stated in para. 3 for the lightened aileron

п	Mass added to aileron (lb) at		Added moment	Critical speed
	Balancing arm	Trailing edge	(lb in. <sup>2</sup> )	(feet per second)
0 0 0	0 0 · 070 0	$0 \\ 0 \\ 0 \cdot 012$	0 0 · 177 0 · 177	$47 \cdot 5 \\ 52 \cdot 0 \\ 52 \cdot 2$
2 2 2 2 2 2 2 2 2 2 2	$ \begin{array}{c} 0 \\ 0 \cdot 037 \\ 0 \\ 0 \cdot 70 \\ 0 \\ 0 \cdot 079 \\ 0 \end{array} $	$ \begin{array}{c} 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \\ 0 \\$	$\begin{matrix} 0 \\ 0 \cdot 177 \\ 0 \cdot 177 \\ 0 \cdot 333 \\ 0 \cdot 333 \\ 0 \cdot 374 \\ 0 \cdot 374 \end{matrix}$	$52 \cdot 4 \\ 61 \cdot 2 \\ 59 \cdot 7 \\ 72 \cdot 1 \\ 67 \cdot 4 \\ 76 \cdot 6 \\ 70 \cdot 6 $

#### APPENDIX

### The Position of the Neutral Point for an Offset Balancing Arm

Let a mass *m* be added to the tab at a distance  $\lambda$  forward of the tab hinge axis (*i.e.*, at a distance  $D - \lambda$  behind the aileron hinge axis) but offset by a perpendicular distance  $\lambda \tan \theta$  from the tab chord line produced, where  $\theta$  is the angle between this line and the line which joins the tab hinge to the mass (*see* sketch which follows).

Then

$$\begin{aligned} \delta A_{33} &= m(D^2 - 2\lambda D + \lambda^2 \sec^2 \theta) , \\ \delta A_{44} &= m\lambda^2 \sec^2 \theta , \\ \delta P &= m(\lambda^2 \sec^2 \theta - \lambda D) . \end{aligned}$$
 (1)

Hence

$$\delta \bar{A}_{44} = m\{\lambda^2 \sec^2 \theta (N+1)^2 - 2\lambda D(N+1) + D^2\} \quad \dots \quad \dots \quad (2)$$

$$\partial P = m\{\lambda^2 \sec^2 \theta (N+1)(n+1) - \lambda D(N+n+2) + D^2\}.$$
 (3)

From para. 16, Part I, the loading will be advantageous if  $\delta \tilde{a}_{44}/\delta \bar{p} < 1$  and  $\delta \bar{p}$  is positive.  $(\delta \bar{a}_{44} \text{ is always positive since sec}^2 \theta > 1.)$ 

From (2) and (3)  $\delta \bar{a}_{44}/\delta \bar{p} < 1$  if

$$\lambda^{2} \sec^{2} \theta(N+1)(N-n) - \lambda D[N-n] < 0. \qquad \dots \qquad \dots \qquad (4)$$

For positions forward of the tab hinge axis  $\lambda(N - n)$  is positive and condition (4) becomes

This condition determines the neutral point, provided  $\delta \bar{p}$  is positive between  $\lambda = 0$  and  $\lambda = \{D/(N+1)\} \cos^2 \theta$ . This is so since if the case of  $\theta = 0$  is considered it is easily shown that  $\delta \bar{p}$  is positive when  $\lambda < D/(N+1)$  (or > D/(n+1)) and the effect of offset is to make  $\delta \bar{p}$  more positive.



Thus, for a particular spring tab a circle  $\lambda = \{D/(N+1)\}\cos^2\theta$  (as in sketch below) can be drawn which is the locus of the neutral points. Any tab balancing mass which is placed outside this circle will be disadvantageous.



The following physical explanation of this rearward movement of the neutral point can be given. When  $\lambda$  is constant  $\delta A_{44}$  is increased by offset without any change in the mass moment about the hinge axis. The effect on the barred coefficients is immediately seen if equations (2) and (3) are written :—

 $\delta \bar{A}_{44} = (N+1)^2 \delta A_{44} - 2(N+1)Dm\lambda + mD^2 \qquad \dots \qquad \dots \qquad \dots \qquad (2a)$ 

$$\delta \bar{P} = (N+1)(n+1)\delta A_{44} - (N+n+2)Dm\lambda + mD^2. \quad .. \quad (3a)$$

Hence, since N > n,  $\delta A_{44}/\delta \bar{P}$  would increase with offset if  $\lambda$  were constant and to compensate it is necessary to reduce the value of  $\lambda$ .

In the case of a spring tab control on a *Spitfire* aileron the tab was fitted with balancing arms on the upper and lower surfaces of which the angular offsets were 60 deg and 50 deg respectively. The distance forward of the neutral point was thus only about one-quarter of the maximum possible distance. TECHNICAL LIBRARY ABBOTTAEROSPACE.COM



Fig. 1.





<sup>-</sup> Fig. 3.







(1752) Wt. 18/9296 K5 12/55 Hw.

95

PRINTED IN GREAT BRITAIN

# R. & M. No. 2952



ECHNICAL LIBRARY

ABBOTTAEROSPACE.COM

S.O. Code No. 23-2952

R. & M. No. 2952