



ICAO ENGINE EXHAUST EMISSIONS DATA BANK

SUBSONIC ENGINES

** DATA SUPERSEDED ** SEE SHEET: 8AL025

ENGINE IDENTIFICATION: AE3007C BYPASS RATIO: 5.2 UNIQUE ID NUMBER: 6AL021 PRESSURE RATIO (π_{oo}) : 15.8 ENGINE TYPE: MTF RATED OUTPUT (F_{oo}) (kN): 29.62

REGULATORY DATA

| CHARACTERISTIC VALUE: | НС | СО | NOx | SMOKE NUMBER |
|----------------------------|--------|--------|--------|--------------|
| D_p/F_{oo} (g/kN) or SN | 14.0 | 65.2 | 39.0 | 1.2 |
| AS % OF ORIGINAL LIMIT | 71.6 % | 55.2 % | 54.5 % | 3.5 % |
| AS % OF CAEP/2 LIMIT (NOx) | | | 68.1 % | |
| AS % OF CAEP/4 LIMIT (NOx) | | | 68.8 % | |
| AS % OF CAEP/6 LIMIT (NOx) | | | 69.1 % | |
| AS % OF CAEP/8 LIMIT (NOx) | | | 73.2 % | |

DATA STATUS

- PRE-REGULATION

x CERTIFICATION

- REVISED (SEE REMARKS)

TEST ENGINE STATUS

- NEWLY MANUFACTURED ENGINES

x DEDICATED ENGINES TO PRODUCTION STANDARD

- OTHER (SEE REMARKS)

EMISSIONS STATUS

x DATA CORRECTED TO REFERENCE

(ANNEX 16 VOLUME II)

CURRENT ENGINE STATUS

(IN PRODUCTION, IN SERVICE UNLESS OTHERWISE NOTED)

x OUT OF PRODUCTION (DATE: -)

- OUT OF SERVICE

MEASURED DATA

| | POWER | TIME | FUEL FLOW | EMI | SSIONS INDICES | (g/kg) | |
|--|---------------------|---------|-----------|-------|----------------|--------|--------------|
| MODE | SETTING | minutes | kg/s | HC | CO | NOx | SMOKE NUMBER |
| | (%F ₀₀) | | | | | | |
| TAKE-OFF | 100 | 0.7 | 0.301 | 0.254 | 0.94 | 16.88 | 1 |
| CLIMB OUT | 85 | 2.2 | 0.253 | 0.291 | 1.16 | 14.57 | 0.01 |
| APPROACH | 30 | 4.0 | 0.094 | 0.696 | 4.28 | 6.78 | 0.01 |
| IDLE | 7 | 26.0 | 0.038 | 4.953 | 26.32 | 3.36 | 0.01 |
| LTO TOTAL FUEL (kg) or EMISSIONS (g) 127 | | | 320 | 1695 | 1050 | - | |
| NUMBER OF ENGINES | | | 2 | 2 | 2 | 2 | |
| NUMBER OF TESTS | | | 3 | 3 | 3 | 3 | |
| AVERAGE D _p /F _{oo} (g/kN) or AVERAGE SN (MAX) | | | 10.79 | 57.18 | 35.47 | 0 | |
| SIGMA $(D_p/F_{oo} \text{ in } g/kN, \text{ or } SN)$ | | | - | - | - | - | |
| RANGE $(D_p/F_{oo} \text{ in g/kN, or SN})$ | | | _ | - | _ | _ | |

ACCESSORY LOADS

POWER EXTRACTION 0 (kW) AT - POWER SETTINGS STAGE BLEED 0 % CORE FLOW AT - POWER SETTINGS

ATMOSPHERIC CONDITIONS

| BAROMETER (kPa) | 0 |
|----------------------|---|
| TEMPERATURE (K) | 0 |
| ABS HUMIDITY (kg/kg) | 0 |

| Ľί | JĿ | ш |
|----|----|---|

| SPEC | Jet A | |
|----------|---------|--|
| H/C | 1.9 | |
| AROM (%) | 16 - 20 | |

MANUFACTURER: Rolls-Royce Corporation
TEST ORGANIZATION: Rolls-Royce Corporation
TEST LOCATION: Indianapolis, Indiana, USA

TEST DATES: FROM 03 Mar 94 TO 19 Apr 95

REMARKS

1. For effectivity see Rolls-Royce Notice to Operators No. AE3007A-076

2. Results based on Rolls-Royce report EDR 15171B