

INCH-POUND

MIL-PRF-22885F
AMENDMENT 2
9 August, 2000
SUPERSEDING
AMENDMENT 1
25 June 1998

PERFORMANCE SPECIFICATION

SWITCHES, PUSH BUTTON, ILLUMINATED, GENERAL SPECIFICATION FOR

This amendment forms a part of MIL-PRF-22885F, dated 23 January 1998, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 7

3.6.2.3 delete and substitute:

"3.6.2.3 Plug-in terminations (not applicable to printed circuit boards). Plug-in terminations shall be treated to facilitate contact. Gold plating, .00003 inch minimum (0.00076 mm minimum) may be used and shall be over a diffusion barrier such as nickel or palladium. For additional information and guidance on plating see 6.13."

PAGE 13

4.4.1 delete and substitute:

"4.4.1 Sample Size. The number of switches to be subjected to qualification inspection shall be as specified in table XI."

Custodian:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Preparing activity:
DLA - CC

(Project 5930-1711)

Review activities:
Army - AR, AV, MI
Navy - AS, MC, OS, SH
Air Force - 19, 99

AMSC N/A

1 of 1

FSC 5930

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.