

MIL-STD-726H  
 NOTICE 2  
 8 April 1988

MILITARY STANDARD  
 PACKAGING REQUIREMENT CODES

TO ALL HOLDERS OF MIL-STD-726H:

1. THE FOLLOWING PAGES OF MIL-STD-726H HAVE BEEN REVISED AND SUPERSEDE PAGES LISTED:

| NEW PAGE | DATE         | SUPERSEDED PAGE | DATE                     |
|----------|--------------|-----------------|--------------------------|
| 9        | 31 July 1985 | 9               | REPRINTED WITHOUT CHANGE |
| 10       | 8 April 1988 | 10              | 31 July 1985             |
| 11       | 8 April 1988 | 11              | 22 January 1986          |
| 12       | 8 April 1988 | 12              | 22 January 1986          |
| 15       | 8 April 1988 | 15              | 31 July 1985             |
| 16       | 31 July 1985 | 16              | REPRINTED WITHOUT CHANGE |
| 19       | 8 April 1988 | 19              | 31 July 1985             |
| 20       | 8 April 1988 | 20              | 31 July 1985             |
| 23       | 8 April 1988 | 23              | 31 July 1985             |
| 24       | 8 April 1988 | 24              | 31 July 1985             |
| 27       | 31 July 1985 | 27              | REPRINTED WITHOUT CHANGE |
| 28       | 8 April 1988 | 28              | 31 July 1985             |
| 33       | 8 April 1988 | 33              | 31 July 1985             |
| 34       | 31 July 1985 | 34              | REPRINTED WITHOUT CHANGE |
| 35       | 8 April 1988 | 35              | 22 January 1986          |
| Blank    |              |                 |                          |
| 35a      | 8 April 1988 | 35a             | 22 January 1986          |
| 36       | 8 April 1988 | 36              | 22 January 1986          |
| 36a      | 8 April 1988 | Added           |                          |
| 36b      | 8 April 1988 | Added           |                          |
| 39       | 31 July 1985 | 39              | REPRINTED WITHOUT CHANGE |
| 40       | 8 April 1988 | 40              | 31 July 1985             |
| 41       | 8 April 1988 | 41              | 22 January 1986          |
| 42       | 8 April 1988 | 42              | 22 January 1986          |
| 43       | 8 April 1988 | 43              | 22 January 1986          |
| 44       | 8 April 1988 | 44              | 22 January 1986          |
| 44a      | 8 April 1988 | Added           |                          |
| Blank    |              |                 |                          |
| 47       | 8 April 1988 | 47              | 31 July 1985             |
| Blank    |              |                 |                          |
| 47a      | 8 April 1988 | Added           |                          |
| 48       | 8 April 1988 | 48              | 31 July 1985             |
| 49       | 8 April 1988 | 49              | 31 July 1985             |
| 50       | 8 April 1988 | 50              | 31 July 1985             |
| 51       | 8 April 1988 | 51              | 31 July 1985             |
| 52       | 8 April 1988 | 52              | 31 July 1985             |
| 52a      | 8 April 1988 | Added           |                          |
| Blank    |              |                 |                          |
| 53       | 8 April 1988 | 53              | 31 July 1985             |

MIL-STD-726H  
 NOTICE 2

| NEW PAGE | DATE            | SUPERSEDED PAGE | DATE                     |
|----------|-----------------|-----------------|--------------------------|
| 54       | 8 April 1988    | 54              | 31 July 1985             |
| 54a      | 8 April 1988    | Added           |                          |
| Blank    |                 |                 |                          |
| 59       | 8 April 1988    | 59              | 31 July 1985             |
| 60       | 8 April 1988    | 60              | 31 July 1985             |
| 61       | 8 April 1988    | 61              | 31 July 1985             |
| 62       | 31 July 1987    | 62              | REPRINTED WITHOUT CHANGE |
| 81       | 8 April 1988    | 81              | 31 July 1985             |
| 82       | 8 April 1988    | 82              | 31 July 1985             |
| 85       | 8 April 1988    | 85              | 31 July 1985             |
| 86       | 8 April 1988    | 86              | 31 July 1985             |
| 87       | 8 April 1988    | 87              | 31 July 1985             |
| 88       | 31 July 1987    | 88              | REPRINTED WITHOUT CHANGE |
| 89       | 8 April 1988    | 89              | 31 July 1985             |
| 90       | 8 April 1988    | 90              | 31 July 1985             |
| 91       | 8 April 1988    | 91              | 22 January 1986          |
| 92       | 8 April 1988    | 92              | 22 January 1986          |
| 93       | 8 April 1988    | 93              | 22 January 1986          |
| 94       | 8 April 1988    | 94              | 22 January 1986          |
| 95       | 8 April 1988    | 95              | 22 January 1986          |
| 96       | 8 April 1988    | 96              | 22 January 1986          |
| 97       | 8 April 1988    | 97              | 22 January 1986          |
| Blank    |                 |                 |                          |
| 97a      | 8 April 1988    | Added           |                          |
| 98       | 8 April 1988    | 98              | 22 January 1986          |
| 99       | 22 January 1986 | 99              | REPRINTED WITHOUT CHANGE |
| 100      | 8 April 1988    | 100             | 22 January 1986          |
| 101      | 8 April 1988    | 101             | 31 July 1985             |
| 102      | 8 April 1988    | 102             | 31 July 1985             |

2. RETAIN THIS NOTICE AND INSERT BEFORE TABLE OF CONTENTS.

3. Holders of MIL-STD-726H will verify that page changes and additions indicated above have been entered. This notice page will be retained as a check sheet. This issuance, together with appended pages, is a separate publication. Each notice is to be retained by stocking points until the military standard is completely revised or canceled.

MIL-STD-726H  
NOTICE 2

Custodians:

Army - SM  
Navy - AS  
Air Force - 43  
DLA - ES

Preparing Activity:

Navy - AS  
(Project PACK-0844)

Review Activities:

Army - AT, CR, GL, AV  
Navy - EC, SA  
Air Force - 99  
DLA - IS, GS

User Activities:

Army - MI  
Navy - YD, SH

MIL-STD-726H  
31 JULY 1985

SPECIFICATIONS (Continued)

MILITARY (Continued)

|               |                                                                                                                |
|---------------|----------------------------------------------------------------------------------------------------------------|
| MIL-C-22235   | Corrosion Preventive Oil, Nonstaining                                                                          |
| MIL-P-23199   | Packaging and Packing Requirements for Special Purpose Components and Repair Parts                             |
| MIL-S-23665   | Sonobuoys, Detection Devices, Preservation, Packaging and Packing Procedures for                               |
| MIL-L-23699   | Lubricating Oil, Aircraft Turbine Engine, Synthetic Base                                                       |
| MIL-G-23827   | Grease, Aircraft and Instrument, Gear and Actuator Screw                                                       |
| * MIL-G-25537 | Grease, Aircraft, Helicopter, Oscillating Bearing                                                              |
| MIL-P-25621   | Preservation, Packaging and Packing of Rubber and Nylon Fuel, Oil and Water-Alcohol Cells                      |
| MIL-C-25731   | Crates, Wood, for Domestic and Overseas Shipment of Airframe Components (2000-Pound Maximum Net Load)          |
| MIL-C-26094   | Can, Hermetic Sealing, Aluminum, Two-Piece                                                                     |
| MIL-B-26195   | Boxes, Wood-Cleated, Skidded, Load-Bearing Base                                                                |
| MIL-P-26514   | Polyurethane Foam, Rigid or Flexible for Packaging                                                             |
| MIL-S-28786   | Switches, Packaging of                                                                                         |
| MIL-B-38721   | Boxes, Consolidation, Fiberboard and Polyolefin                                                                |
| MIL-C-39028   | Capacitors, Packing of                                                                                         |
| * MIL-R-39032 | Resistors, Packaging of                                                                                        |
| MIL-B-43666   | Boxes, Shipping Consolidation                                                                                  |
| MIL-T-45542   | Tool Sets, Shop Sets and Kits, Maintenance, Modification and Tool, Packaging of                                |
| * MIL-V-45554 | Vulcanizing Equipment, Including Related Items, Tire and Tube, Rebuild and Repair, Preparation for Delivery of |
| MIL-B-45977   | Bins Cabinets, Shelving and Worktables, Packaging of                                                           |

\* Changed

MIL-STD-726H  
NOTICE 2

SPECIFICATIONS (Continued)

MILITARY (Continued)

|                   |                                                                                                    |
|-------------------|----------------------------------------------------------------------------------------------------|
| MIL-L-46002       | Preservative Oil, Contact and Volatile Corrosion-Inhibited                                         |
| MIL-P-46093       | Primer Coating, Synthetic (for Brake Drums)                                                        |
| MIL-P-46161       | Plastic Molding Material, Polyterephthalate Thermoplastic, Glass Fiber Reinforced                  |
| MIL-H-46170       | Hydraulic Fluid, Rust Inhibited, Fire Resistant, Synthetic Hydrocarbon Base                        |
| MIL-B-46176       | Brake Fluid, Silicone, Automotive All Weather, Operational and Preservative                        |
| MIL-C-52950       | Crates, Wood, Open and Covered                                                                     |
| MIL-C-55330       | Connectors, Electrical and Fiber Optic, Packaging of                                               |
| MIL-C-55442       | Cable Assemblies and Cord Assemblies, Packaging of                                                 |
| MIL-B-55521       | Batteries, Nonrechargeable, Packaging of                                                           |
| MIL-M-55565       | Microcircuits, Packaging of                                                                        |
| ** MIL-E-55585    | Electronics Equipment and Parts, Packaging of                                                      |
| MIL-V-62038       | Vehicles Wheeled Preparation for Shipment and Storage of                                           |
| MIL-G-81322       | Grease, Aircraft, General Purpose Wide Temperature Range                                           |
| MIL-F-81334       | Foam, Plastic, Flexible, Open Cell, Polyester Type, Polyurethane                                   |
| MIL-G-81559       | Gyroscope Assemblies and Attitude and Directional Reference Instruments for Aircraft, Packaging of |
| MIL-B-81705       | Barrier Materials, Flexible, Electrostatic-Free Heat Sealable                                      |
| MIL-B-81916       | Barrier Material, Watervaporproof, Flexible, Heat Sealable, Flame Resistant                        |
| MIL-H-83282       | Hydraulic Fluid, Fire Resistant, Synthetic Hydrocarbon Base, Aircraft                              |
| MIL-C-0083933(MR) | Corrosion Preventive Compound, Cold Application (for Motor Vehicles)                               |

\*\* Added

Supersedes page 10 of MIL-STD-726H

MIL-STD-726H  
NOTICE 2

STANDARDS (Continued)

MILITARY (Continued)

|                 |                                                                                                   |
|-----------------|---------------------------------------------------------------------------------------------------|
| MIL-F-87090     | Foam, Combustion Retardant, for Cushioning Supply Items Aboard Navy Ships                         |
| MIL-F-83671     | Foam-In-Place Packaging Materials, General Specification for                                      |
| MIL-STD-129     | Marking for Shipment and Storage                                                                  |
| MIL-STD-163     | Steel Mill Products, Preparation for Shipment and Storage                                         |
| MIL-STD-281     | Automobiles, Trucks, Truck-Tractors, Trailers and Trailer Dollies, Preservation and Packaging of  |
| MIL-STD-649     | Aluminum and Magnesium Products, Preparation for Shipment and Storage                             |
| MIL-STD-758     | Packaging Procedures for Submarine Repair Parts                                                   |
| MIL-STD-767     | Cleaning Requirements for Special Purpose Equipment, Including Piping System                      |
| MIL-STD-794     | Parts and Equipment, Procedures for Packaging of                                                  |
| MIL-STD-1169    | Packaging, Packing and Marking for Shipment of Inert Ammunition Components                        |
| MIL-STD-1186    | Cushioning, Anchoring, Bracing, Blocking, and Waterproofing, With Appropriate Test Methods        |
| ** MIL-STD-1190 | Minimum Guidelines for Level C Preservation, Packing and Marking                                  |
| MIL-STD-2073    | DOD Materiel, Procedures for Development and Application of Packaging Requirements                |
| MS 18011        | Containers, Reusable, Aluminum, Hand Portable-Assembly for Shipping                               |
| MS 90363        | Box, Fiberboard, With Cushioning for Special, Minimum Cube Storage and Limited Reuse Applications |

FEDERAL MANUALS

M1-7 Federal Manual for Supply Cataloging, Chapter 7

2.2 Other government publications. The following documents form a part of this standard to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

Title 49CFR Code of Federal Regulation (Hazardous Material)

(Copies of specifications, standards and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

\*\* Added

Supersedes page 11 of MIL-STD-726H, NOTICE 1

\* 2.3 Other publications. The following document forms a part of this standard to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. The issues of documents which have not been adopted shall be those in effect on the date of the cited DODISS.

ASTM D 3951

Packaging, Commercial

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

3. DEFINITIONS. For definitions of packaging terminology refer to Section 3 of MIL-STD-794.

#### 4. GENERAL REQUIREMENTS

##### 4.1 General.

4.1.1 Code system. The code system established herein is a position and sequence code. Coded data used under this system shall always appear in the sequence and in the number of positions specified herein regardless of the manner by which it is published. By means of this code lengthy identifying and descriptive data is reduced to a convenient form capable of being stored and manipulated by existing electronic data processing methods and equipment or by manual means. The digits of this code shall not be used for purposes other than those specified herein. Digit positions 1 through 17 are mandatory in acquisition documents. Digit positions 18 through 28 are optional for use. If digits 18 through 28 are not used for purposes stated herein, zeros shall be placed in these positions and not used for any other purpose.

4.2 Essential elements. For the purpose of uniformity the following are established as the minimum essential elements which will be used for acquisition purposes:

- Method of Preservation
- Quantity per Unit Pack
- Cleaning and Drying Procedure
- Preservative Material
- Wraps, Cushioning and Dunnage
- Unit Container
- Intermediate Container Quantity
- Intermediate Container
- Level of Preservation

4.3 Alternate elements. In addition to the basic packaging information set forth above, codes are provided for including the following items of logistical information:

- a. Allowable maximum weight and cube of the unit container or allowable maximum inside dimensions (length, width and depth) of the unit container.

\* Changed

MIL-STD-726H  
 NOTICE 2

4.13.3 Coordinating procedures. Revisions that affect the application of the established codes or that delete or revise existing codes shall be coordinated in accordance with regularly prescribed standardization procedures prior to publication.

5. DETAILED REQUIREMENTS

5.1 Relations of tables to code fields. The tables in this section of the standard are associated with the code fields indicated in Table I and Table Ia as follows:

| <u>Digit Positions</u>       | <u>Code Fields</u>              | <u>Tables</u>        |
|------------------------------|---------------------------------|----------------------|
| 1 and 2                      | Method of preservation          | II, IIa, IIb and IIc |
| 3                            | Quantity per unit pack          | III                  |
| 4                            | Cleaning and drying procedure   | IV                   |
| 5 and 6                      | Preservative material           | V                    |
| 7 and 8                      | Wraps                           | VI                   |
| 9 and 10                     | Cushioning and dunnage          | VIa                  |
| 11                           | Cushioning thickness            | VIb                  |
| 12 and 13                    | Unit container                  | VII                  |
| 14                           | Intermediate container quantity | VIII                 |
| 15 and 16                    | Intermediate container          | VII                  |
| 17                           | Level of protection             | IX                   |
| 18, 19, 20, 21, 22, 23 or 24 | Length, width, depth            | X                    |
| 18 and 19                    | Weight                          | XI, XIa              |
| 20 and 21                    | Cube                            | XII, XIIa            |
| 24                           | Level A packing                 | XIII                 |
| 25                           | Level B packing                 | XIII                 |
| 26                           | Level C packing                 | XIII                 |
| 26                           | Commercial packing              | XIII                 |
| 27 and 28                    | Special marking                 | XIV                  |

\* 5.1.1 General code requirements. The requirements cited in the tables of this standard will be invoked by use of the associated codes. When using these codes, a symbol must be used in each digit space in every field of the total code. To distinguish between alphabetical and numerical "0", numeric "0" shall be designated as "Ø" and alphabetical "0" shall be designated as "O". When none of the requirements of a table apply, one of the following codes shall be used:

a. Use the numerical code "Ø" or "ØØ" (dependent upon the number of digit spaces in code field) to indicate that the field does not apply to the package described by the code.

b. Use the code "Y" or "YY" (dependent upon the number of digit spaces in the code field) to indicate that the packager (contractor) is responsible for selecting the appropriate requirement. When this code is

\* Changed

MIL-STD-726H

31 JULY 1985

used, the packager is required to limit his selection to requirements included in the tables of this standard unless prior written permission to use unlisted materials has been obtained from contracting officer.

c. Use the code "Z" or "ZZ" (dependent upon the number of digit spaces in the code field) to indicate that special requirements apply which are not represented by the code symbols. When the "Z" or "ZZ" symbols are used in a procurement document, details of the requirement shall be provided with the document.

d. Use of code "X" or "XX" will normally indicate that the requirement in a field is included as part of the requirements defined for the preservation method codes. (See corresponding tables.)

5.2 Method of preservation (1st & 2nd Digit). The 1st and 2nd digit positions of the packaging requirement codes shall indicate the method of preservation for the item being packaged.

5.2.1 Preservation methods. The preservation methods cited in Table II are those methods established by and described in MIL-P-116. When the preservation methods of this specification are invoked, the packages presented shall be capable of meeting the applicable test requirements of the specification. When the method of preservation specifically requires the use of a particular material in fabrication of the package, this material shall not be identified in other fields of the code.

5.2.2 Methods and submethods of preservation. Table IIa lists codes which allow the user limited selection among the methods and submethods of MIL-P-116.

5.2.3 Packaging documents. Table IIb lists codes that indicate specifications and standards that are referenced regularly in specifying the packaging requirements for certain groups of items. These codes should not be used unless the referenced document, supplemented by information provided in the additional fields of the total code, adequately describes the packaging needed for the item being considered.

5.2.4 Special methods. Table IIc lists codes that indicate preservation procedures which are regularly used but which cannot be conveniently or adequately described without amplification of the basic method and material symbols.

5.3 Quantity per unit pack (3rd Digit). Table III lists the codes to be used in designating the quantity per unit pack. Quantity per unit pack for ammunition and other hazardous material will be the quantity in that package configuration which meets the packaging requirements of Title 49 of the Code of Federal Regulations. This is normally the quantity in the exterior shipping container.

5.3.1 Unusual quantities. When a quantity other than any listed in Table III is desired, a "Z" will be used. In this case the desired quantity must be provided by supplemental instructions. When the quantity per unit

\* 5.7.2 Container groups. Container codes listed in table VII are grouped as follows:

|                             |                          |
|-----------------------------|--------------------------|
| General Requirements        | 01 through 19            |
| Bags and Sacks              | First digit A or B       |
| Barrels and Kegs            | First digit C            |
| Boxes, Paper and Fiber      | First digit D, E, N or P |
| Boxes, Wood                 | First digit F or G       |
| Cans, Metal and Fiber       | First digit H or J       |
| Cases and Containers        | First digit K or L       |
| Crates                      | First digit M            |
| Drums, Fiberboard           | First digit C            |
| Drums, Metal                | First digit R            |
| Miscellaneous, Unclassified | First digit W            |
| Referral Codes              | 00, XX, YY, ZZ           |

5.7.3 Approximate weight and thickness information. The weight and thickness information in table VII should not be considered as requirements for these materials. They are solely approximations and are offered to assist users in calculating the approximate weight using the bill of materials formulas contained in table VI, appendix D of MIL-STD-794.

5.8 Intermediate container quantity (14th Digit). Table VIII lists codes that indicate the number of unit packs to be in the intermediate container.

5.9 Intermediate container (15th & 16th Digit). Table VII lists the codes that indicate the intermediate container; they are the same as the codes used to specify the unit container.

\*\* 5.9.1 Intermediate container limitations. Refer to Appendix F of MIL-STD-2073-1A, paragraph 20.4.1.3.

5.10 Level of protection (17th Digit). Table IX lists the codes that indicate the unit pack level of protection provided for the item. (For a description of levels of protection see MIL-STD-794.)

5.11 Weight, cube or dimensions. Either the maximum allowable unit container weight and cube, or the maximum allowable unit container (outside) dimensions may be prescribed. Weight and cube codes will be given digit positions 18 through 21; dimension codes will be given digit positions 18 through 23.

5.11.1 Options in selecting materials. In the interest of reducing transportation and storage costs, packages having the minimum practical weight and cube are desired. When the coded requirements allow the packager leeway in selecting packaging materials and containers, the choice should be made in favor of products which will provide the lightest and smallest package that is practical to produce and still provide the protection required.

5.11.2 Dimensions (18th through 23rd Digit). Table X lists the codes for indicating maximum allowable outside length, width and depth of the unit container.

\* Changed

\*\* Added

Supersedes page 19 of MIL-STD-726H

5.11.3 Weight and cube. At the discretion of the using agency, the 18th through the 21st digit of the code may be used to prescribe the maximum allowable weight and cube of the unit container in lieu of the container dimensions.

5.11.3.1 Weight (18th & 19th Digit). Table XI lists the maximum unit package weight with the corresponding code in the adjacent column. Packagers are encouraged to utilize materials and containers which will provide the required protection in the minimum volume. Table XIa lists the weight codes in alphanumeric order with the corresponding weights in the adjacent columns.

5.11.3.2 Cube (20th & 21st Digit). Table XII lists the maximum unit package cube with the corresponding code in the adjacent column. Packagers are encouraged to utilize materials and containers which will provide the required protection in the minimum volume. Table XIIa lists the cube codes in alphanumeric order with the corresponding cubes in the adjacent columns.

5.12 Packing (24th, 25th & 26th Digit). Table XIII lists codes that indicate the type of shipping container suitable for Level A, Level B, Level C and Commercial packing. Codes "Y" or "Z" may be entered as required in one or more of these digital positions in accordance with the general requirements in 5.1.1.

\*\* 5.12.1 Exterior packing requirements. Refer to Appendix F of MIL-STD-2073-T, paragraph 20.5.

\*\* 5.12.2 Hazardous materials shipment. Refer to Appendix F of MIL-STD-2073-T, paragraph 20.8.

5.13 Special markings (27th & 28th Digit). At the discretion of the using agency, the 27th and 28th digits are to be used to prescribe unit pack special markings. Table XIV contains the codes and corresponding explanations of the special markings. The special markings are considered an integral part of the total package required to protect the contained item during packaging, storage, transit and removal from the package and must be applied to the containers according to MIL-STD-129. The codes should be used only as they apply to items enclosed within the approved packaging and must be compatible with the prescribed packaging data.

\*\* Added

MIL-STD-726H  
 NOTICE 2

TABLE II. Preservation Method Codes (Digit Positions 1 and 2)  
 (PCAM Columns 47, 48, MIL-STD-834) (See 5.2 and 5.2.1).

| Method of preservation codes for the preservation methods and submethods established by MIL-P-116; Preservation, Methods of |        |      |          |                           |      |          |      |
|-----------------------------------------------------------------------------------------------------------------------------|--------|------|----------|---------------------------|------|----------|------|
| Code to method conversion                                                                                                   |        |      |          | Method to code conversion |      |          |      |
| Code                                                                                                                        | Method | Code | Method   | Method                    | Code | Method   | Code |
| 1Ø                                                                                                                          | III    | 3Q   | IA-14    | III                       | 1Ø   | IC-3     | 2D   |
| 11                                                                                                                          | I      | 3T   | IA-13    | I                         | 11   | IC-4     | 2S   |
| 2A                                                                                                                          | IC-7   | 3V   | IA-5     | IA (2)                    | 3Y   | IC-7     | 2A   |
| 2B                                                                                                                          | IC-9   | 3W   | IA-6     | IA-5                      | 3V   | IC-9     | 2B   |
| 2C                                                                                                                          | IC-1Ø  | 3Y   | IA (2)   | IA-6                      | 3W   | IC-1Ø    | 2C   |
| 2D                                                                                                                          | IC-3   | 4G   | IIC      | IA-8                      | 3G   | II (2)   | 4Y   |
| 2E                                                                                                                          | IC-1   | 4H   | Ila      | IA-13                     | 3T   | Ila      | 4H   |
| 2M                                                                                                                          | IC-2   | 4P   | Ile      | IA-14                     | 3Q   | Ilb      | 4Q   |
| 2S                                                                                                                          | IC-4   | 4Q   | Ilb      | IA-15                     | 3P   | IIC      | 4G   |
| 2Y                                                                                                                          | IC (2) | 4T   | IIf      | IA-16                     | 3H   | IId      | 4V   |
| 3G                                                                                                                          | IA-8   | 4V   | IId      | IC (2)                    | 2Y   | Ile      | 4P   |
| 3H                                                                                                                          | IA-16  | 4Y   | II (2)   | IC-1                      | 2E   | IIf      | 4T   |
| 3P                                                                                                                          | IA-15  | ZZ   | Note (1) | IC-2                      | 2M   | Note (1) | ZZ   |

Note 1: See paragraph 5.1.1

Note 2: Submethod is the choice of the contractor.

TABLE IIa. Optional Preservation Method Codes (Digit Positions 1 and 2)  
 (PCAM Columns 47, 48, MIL-STD-834) (See 5.2 and 5.2.2).

| Method of preservation codes which allow the user a limited choice between certain preservation methods and submethods of MIL-P-116. |                                                                         |      |                               |
|--------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------|------|-------------------------------|
| Code                                                                                                                                 | Method of preservation                                                  | Code | Method of preservation        |
| 6F                                                                                                                                   | Method IA-13 or IA-15 optional                                          | 6P   | Method IId (preferred) or Ila |
| 6L                                                                                                                                   | Method I or III in plastic containers of minimum practical size         | 6Q   | Method IId (preferred) or Ilb |
| 6M                                                                                                                                   | Method I or III selected in accordance with the guidelines of MIL-P-116 | 6R   | Method IId or IIf optional    |

Methods IB, IB-1, IB-2 deleted (Codes 1Y, 12, 1B)

MIL-STD-726H  
 NOTICE 2

TABLE IIb. Procedural Specification Codes (Digit Positions 1 & 2)  
 (PCAM Columns 47, 48, MIL-STD-834) (See 5.2 and 5.2.3).

Method of preservation codes referencing documents which establish packaging requirements for products or item groups.

| Code | Products or item groups                        | Procedure   |
|------|------------------------------------------------|-------------|
| 15   | Aluminum and magnesium                         | MIL-STD-649 |
| 17   | Batteries                                      | MIL-B-208   |
| 18   | Batteries, dry                                 | MIL-B-55521 |
| 19   | Batteries, storage, aircraft                   | MIL-P-6063  |
| 20   | Batteries, storage, industrial                 | PPP-B-140   |
| 21   | Bearings, antifriction                         | MIL-B-197   |
| 22   | Cable, cord, and wire, electric                | MIL-C-12000 |
| 23   | Chemicals, liquid, dry and paste               | PPP-C-2020  |
| 25   | Cordage                                        | MIL-C-3131  |
| 26   | Capstans, winches, etc.                        | MIL-P-3184  |
| 27   | Cable assemblies and cord assemblies           | MIL-C-55442 |
| 28   | Copper                                         | MIL-C-3993  |
| 29   | Electric machines                              | MIL-E-16298 |
| 30   | Printing, duplicating & reproduction equipment | MIL-P-3684  |
| 33   | Electronic equipment                           | MIL-E-17555 |
| 34   | Engine Repair Parts                            | MIL-R-196   |
| 35   | Engines, gas turbine                           | MIL-E-5607  |
| 36   | Engines, aircraft reciprocating                | MIL-E-6058  |
| 37   | Engines other than aircraft                    | MIL-E-10062 |
| 42   | Hardware                                       | PPP-H-1581  |
| 45   | Hoists                                         | MIL-H-3280  |
| 47   | Hose                                           | MIL-H-775   |
| 48   | Optical elements                               | MIL-O-16898 |
| 49   | Machinery, metal, and wood working             | MIL-M-18058 |
| 52   | Nails                                          | FF-N-105    |
| 53   | Preformed packing, "O" rings                   | MIL-P-4861  |
| 54   | Paint and related products                     | PPP-P-1892  |
| 56   | Parachutes                                     | MIL-P-5610  |
| 66   | Propellers                                     | MIL-P-6074  |
| 67   | Pumps                                          | MIL-P-10603 |
| 70   | Rubber, nylon fuel, oil & water alcohol cells  | MIL-P-25621 |
| 71   | Steel mill products                            | MIL-STD-163 |
| 73   | Tires and tubes                                | MIL-T-4     |
| 74   | Tools                                          | PPP-P-40    |
| 75   | Electron tubes                                 | MIL-E-75    |
| *76  | Valves, fittings and flanges                   | MIL-V-3     |
| 78   | Welding rods                                   | MIL-W-10430 |
| 81   | Abrasives and abrasive products                | MIL-A-3816  |

\* Changed  
 Code 38 deleted

MIL-STD-726H  
 31 JULY 1985

TABLE IIc. Specialized Preservation Procedure Codes Digit  
 Positions 1 & 2) (PCAM Columns 47, 48, MIL-STD-  
 834) (See 5.2 and 5.2.4) (Continued).

| Code | Packaging procedure                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| AJ   | Preserve Method I as follows: Place preserved item in fold of MIL-B-121, grade A material, and fasten with pressure sensitive tape to a rectangle of rigid, corrugated fiberboard of minimum practicable dimension.                                                                                                                                                                                                                                                                                                                                                             |
| AK   | Preserve Method I as follows: Flush or fog spray internal water passages with preservative conforming to P-3 of MIL-P-116. Flush or fog spray internal oil passages with preservative conforming to P-7, P-9, or P-10 of MIL-P-116. All internal surfaces must be thoroughly covered with preservative. Plug or seal all openings to prevent entrance of dirt and moisture. Coat all external ferrous metal surfaces with nontacky, cold application, preservative compound conforming to P-19 of MIL-P-116, or paint with suitable enamel. (Used for pumps and similar items.) |
| AL   | Preserve Method I as follows: Unit container shall conform to PPP-B-636, type CF, Class weather-resistant. Seal all seams and joints with PPP-T-76 tape, not less than two inches wide.                                                                                                                                                                                                                                                                                                                                                                                         |
| AM   | Preserve in manufacturer's standard metal container, sealed with waterproof tape conforming to PPP-T-60.                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| AN   | Preserve Method IA as follows: Clean each item with chemically neutral detergent, wrap in nonabrasive chemically inert tissue, and overwrap with cushioning material conforming to PPP-C-843, or as an alternate, nonabrasive cushioning conforming to PPP-C-843 to a minimum thickness of twice the thickness of the item. Seal each cushioned item within a bag made of material conforming to MIL-B-131. (Used for items of glass and similar material which have critical surfaces.)                                                                                        |
| AP   | Preserve Method IA-8 using MIL-B-131, class 1 barrier. Place each packaged item in an individual corrugated carton, folder or sleeve meeting weight limitations of PPP-B-636. Use sufficient cushioning within corrugated container for package to pass free fall drop test of MIL-P-116.                                                                                                                                                                                                                                                                                       |
| AQ   | Preserve by Method IIa, IIb, or IIc. If IIa is selected, place item in a nailed wood box conforming to table III or IV of PPP-B-621, after sealing of barrier.                                                                                                                                                                                                                                                                                                                                                                                                                  |
| AR   | Preserve by Method II (specific submethod optional) except that items inherently fungusproof or completely treated with fungus resistant compound or varnish (such as MIL-V-173) shall be packaged by Method III.                                                                                                                                                                                                                                                                                                                                                               |
| AT   | Preserve in accordance with MIL-P-23199, Level A. Need for purging shall be determined by criteria specified in MIL-P-23199, Level A.                                                                                                                                                                                                                                                                                                                                                                                                                                           |

MIL-STD-726H  
 NOTICE 2

TABLE IIc. Specialized Preservation Procedure Codes Digit  
Positions 1 & 2 (PCAM Columns 47, 48, MIL-STD-  
834) (See 5.2 and 5.2.4) (Continued).

| Code | Packaging procedure                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
|------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| AU   | Preservative compounds shall not be applied to windings, commutators or peripheries or armatures or rotors. Shafts shall be coated with type P-2 preservative and wrapped with MIL-B-121, grade A material, secured in place with PPP-T-60 tape. Commutators shall be wrapped with MIL-B-121, grade A material, held in place with PPP-T-60 tape. Exposed surfaces of steel collector rings shall be coated with Type P-2 preservative. No preservative is required for bronze, brass or other corrosion resisting metals. All collector rings shall be wrapped with MIL-B-121, grade A material, secured in place with PPP-T-60 tape. Corrodible surfaces, except shafts, commutators, and collector rings, may be preserved by the use of insulating varnish applied during the manufacturing process. In addition to the foregoing requirements, armatures and rotors shall be wrapped with MIL-B-121, grade A material, secured with PPP-T-60 tape. |
| AW   | Preserve in accordance with any of the following alternate methods (Used for gaskets and similar items):<br>a. Seal in bags conforming to class B, C or E of MIL-B-117, using stiffening material internally if needed to maintain rigidity.<br>b. Method 1A-13 or 1A-15 of MIL-P-116.<br>c. Place between sheets of, in fold of, or in a sheet of corrugated fiberboard of sufficient stiffness to resist bending, overwrap with waterproofed wrapping paper conforming to PPP-B-1055 and seal with pressure sensitive tape conforming to PPP-T-76 or PPP-T-60, or adhesive conforming to MMM-A-260. Authorization to use other waterproof barrier materials may be granted upon request.                                                                                                                                                                                                                                                              |
| *#AY | Preserve by Method 1A-8, 1A-14, 1A-15 or 1A-16 using bags conforming to MIL-B-117, type I, class G, style 1.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| BA   | Assemble nonferrous accessories on shaft. Fasten nonferrous keys in keyways with pressure sensitive tape having non-corrosive properties of PPP-T-60. Preserve all ferrous parts and accessories in accordance with Method 1A-8 (using preservative conforming to P-2) and fasten them to shaft with pressure sensitive tape conforming to PPP-T-60. Pack assemblies individually (one per box) but otherwise in accordance with figure I of MIL-P-2845, except that tops and bottoms of boxes may be made of 1" nominal thickness lumber. (Used for shaft assemblies and similar items, nonferrous.)                                                                                                                                                                                                                                                                                                                                                   |

\* Changed  
 # Fire retardant

MIL-STD-726H  
 NOTICE 2

TABLE IIc. Specialized Preservation Procedure Codes Digit Positions 1 & 2) (PCAM Columns 47, 48, MIL-STD-834) (See 5.2 and 5.2.4) (Continued).

| Code | Packaging procedure                                                                                                                                                                                                                                                                                                                                                                               |
|------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| DY   | Preserve in accordance with MIL-STD-794, except that packaging shall be converted to the minimum cube methods in accordance with MIL-STD-758 when nonrepairable items do not exceed 40 pounds and repairable items do not exceed 100 pounds. All items exceeding 40 pounds shall be packed Level A in individual shipping containers in accordance with MIL-STD-794 or MIL-STD-758 as applicable. |
| EA   | Preserve Method IIc using MIL-B-131, class 1 barrier. Place each preserved item in an individual folding, paperboard box or set-up, paperboard box conforming to PPP-B-566 or PPP-B-676. Use sufficient cushioning within paperboard container for pack to pass the free fall drop test of MIL-P-116.                                                                                             |
| EB   | Preserve Method IC-3 using MIL-B-121, type I barrier. Place each pack item in an individual folding paperboard box or set-up paperboard box conforming to PPP-B-566 or PPP-B-676. Use sufficient cushioning within paperboard container for pack to pass the free fall test of MIL-P-116.                                                                                                         |
| EK   | Preserve Method III as follows: Each bolt shall have the shank and threads protected by means of a sleeve extending over the full length of the shank and thread. The sleeve shall be manufactured from paperboard, asphalt impregnated chipboard or spiral wrap of kraft paper over chipboard, lined with material conforming to MIL-B-121. Plastic sleeve coverings may also be used.           |
| EL   | Preserve Method IC-1 using MIL-B-121, type I barrier. Place each preserved item in an individual fiberboard box meeting the weight limitations of PPP-B-636. Use sufficient cushioning within container for pack to pass the free fall drop test of MIL-P-116.                                                                                                                                    |
| FA   | Method of preservation shall be in accordance with Method Symbol A of MIL-B-197. (See Note 1.)                                                                                                                                                                                                                                                                                                    |
| FB   | Method of preservation shall be in accordance with Method Symbol B of MIL-B-197. (See Note 1.)                                                                                                                                                                                                                                                                                                    |
| FC   | Method of preservation shall be in accordance with Method Symbol C of MIL-B-197. (See Note 1.)                                                                                                                                                                                                                                                                                                    |
| FF   | Method of preservation shall be in accordance with Method Symbol F of MIL-B-197. (See Note 1.)                                                                                                                                                                                                                                                                                                    |
| FG   | Method of preservation shall be in accordance with Method Symbol G of MIL-B-197. (See Note 1.)                                                                                                                                                                                                                                                                                                    |
| FH   | Method of preservation shall be in accordance with Method Symbol H of MIL-B-197. (See Note 1.)                                                                                                                                                                                                                                                                                                    |
| FJ   | Method of preservation shall be in accordance with Method Symbol J of MIL-B-197. (See Note 1.)                                                                                                                                                                                                                                                                                                    |
| FK   | Method of preservation shall be in accordance with Method Symbol K of MIL-B-197. (See Note 1.)                                                                                                                                                                                                                                                                                                    |
| FL   | Method of preservation shall be in accordance with Method Symbol L of MIL-B-197. (See Note 1.)                                                                                                                                                                                                                                                                                                    |
| *FM  | Method of preservation shall be in accordance with Method Symbol A, C, G or L of MIL-B-197, as applicable. (See Note 1.)                                                                                                                                                                                                                                                                          |

\* Changed

MIL-STD-726H  
 31 JULY 1985

TABLE IIc. Specialized Preservation Procedure Codes Digit  
 Positions 1 & 2) (PCAM Columns 47, 48, MIL-STD-  
 834) (See 5.2 and 5.2.4) (Continued).

| Code  | Packaging procedure                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| FN    | Method of preservation shall be in accordance with MIL-B-197, Method Symbol L for open bearings and Method Symbol C or L for closed bearings. (See Note 1.)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| FP    | Method of preservation shall be in accordance with Method Symbol A or L of MIL-B-197. (See Note 1.)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| FO    | Preserve in accordance with MIL-E-75, Package Group 1.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| FS    | Preserve in accordance with MIL-E-75, Package Group 4.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| FT    | Preserve in accordance with MIL-E-75, Package Group 9. Appropriate magnetic cautionary markings shall be determined in accordance with MIL-S-4473.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| FU    | Preserve in accordance with MIL-E-75, Package Group 23.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| FV    | Preserve in accordance with MIL-E-75, Package Group 24.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| FX    | Preserve in accordance with MS90363-4.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| FY    | Preserve in accordance with MS90363-5.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| GA    | Preserve in accordance with MS90363-6.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| GB    | Preserve in accordance with MS90363-7.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| GC    | Preserve in accordance with MS90363-8.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| GP    | Preserve in accordance with MS90363-3.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| GQ    | Preserve in accordance with MS90363-1.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| GR    | Preserve in accordance with MS90363-2.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| GS    | Preserve by Method IC-1 (modified) of MIL-P-116 in a transparent, flexible, sealable, volatile corrosion inhibitor treated bag conforming to MIL-B-22020. The interleaf furnished inside each class 2, cold sealable bag shall be withdrawn after inserting item and prior to final sealing in accordance with MIL-B-22020. Items with sharp edges or protrusions shall be wrapped with sufficient layers of transparent, flexible, pressure (cold) sealable volatile corrosion inhibitor barrier material conforming to MIL-B-22019, type II to prevent bag puncture. The latex coated (nonprinted) side of the barrier material shall always be facing the item. Alternately, the item may be completely wrapped with transparent, flexible, pressure (cold) sealable volatile corrosion inhibitor barrier material conforming to MIL-B-22019, type II as indicated above and further preserved in transparent barrier bag conforming to type I, class C, style 2 of MIL-B-117. Closure shall be heat-sealing when this alternate method is used. In addition to markings required elsewhere in the contract, unit identification and caution labels shall be in accordance with MIL-STD-129. |
| GV    | Preserve Method III. Unit container shall conform to PPP-B-636, type CF, class weather-resistant. Seal all seams and joints with tape, not less than two inches wide, conforming to PPP-T-76.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
| **#GW | Preserve by Method IIa modified as follows: Pack in flexible, reusable watervaporproof container conforming to MIL-C-9959, Type I, grade A, flame resistant.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |

Deleted: FR, FW (use 96, table IIb)

\*\* Added

# Fire retardant

MIL-STD-726H  
 NOTICE 2

TABLE IIc. Specialized Preservation Procedure Codes Digit  
Positions 1 & 2) (PCAM Columns 47, 48, MIL-STD-  
834) (See 5.2 and 5.2.4) (Continued).

| Code | Packaging procedure                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| *GX  | Preserve by Method IA-8 as follows: Items subject to damage by electromagnetic and electrostatic field forces shall be initially wrapped in material conforming to MIL-B-81705, type II, or cushioned in material conforming to PPP-C-1842, type III, style A or B, or PPP-C-795 class 2, or PPP-C-1752 type VII, class 1, grade B, or PPP-C-1797, type II, to prevent bag puncture, and unit packed in a heat-sealed bag conforming to MIL-B-117, type I, class F, style 1. Alternate cushioning materials are acceptable if certified as having physical properties equal to or better than similarly constructed material(s) covered by a government packaging specification and such materials satisfy the electrostatic decay rate requirement of MIL-B-81705. Lead or terminal configurations for all items shall be maintained as manufactured without causing loads of stresses capable of causing damage to the item. Materials used to maintain item position and lead or terminal configuration shall permit item removal without damage to the item. Sensitive electronic device caution labels shall be applied in accordance with MIL-STD-129, Appendix C, paragraph 20.30. |
| GZ   | Preserve by Method IC-1 or IA-8 modified as follows: Preserve in a transparent barrier bag conforming to type I, class C, style 2 of MIL-B-117. To prevent bag puncture, wrap or cushion with sufficient layers of MIL-B-22191 or L-P-378 barrier material, PPP-C-1842 or PPP-C-795 cushioning, or otherwise protect sharp edges and protrusions with caps, covers, plugs, or rigid plastic foam in accordance with MIL-P-26514. If a contact preservative has been applied to the item, MIL-B-22191, type II barrier material is required as wrap or cushioning and initial wrap prior to application of cushioning. The bag closure shall be made by heat sealing.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| JF   | Preserve Method III - Items shall be preserved in a vacuum formed skin pack, formed from either cellulose acetate, cellulose butyrate or cellulose propionate. The material shall be 10 to 15 mils minimum thickness prior to draw and 2 to 4 mils minimum thickness after draw. PPP-F-320, class - domestic fiberboard shall be used as a stiffener.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |
| JG   | Preserve Method IA-8 using MIL-B-131, class 1 or 2 barrier material.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| JH   | Preserve Method IA-8 using MIL-B-22191, type I film. Sharp edges and protrusions shall be sufficiently cushioned to protect the item and barrier.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |
| *JK  | Preserve Submethod IA-8 for semiconductor devices and resistors in accordance with Level A provisions of MIL-S-19491 and MIL-B-39032, respectively, utilizing the field force protection (shielding).                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |

\* Changed

MIL-STD-726H  
 NOTICE 2

TABLE IIc. Specialized Preservation Procedure Codes Digit Positions 1 & 2) (PCAM Columns 47, 48, MIL-STD-834) (See 5.2 and 5.2.4) (Continued).

| Code | Packaging procedure                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |
|------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| JL   | <p>requirements as well as insuring that all other applicable requirements (including packing, marking and quality assurance) of these specifications are met. All other items shall be preserved submethod IA-8 as follows: These items shall be wrapped in material conforming to MIL-B-81705, type II, or cushioned in material conforming to PPP-C-795, class 2; PPP-C-1752, type VII, class 1, grade B; PPP-C-1797, type II, or PPP-C-1842, type III. Lead or terminal configurations for all items shall be maintained as manufactured without causing loads or stresses capable of causing item damage. Materials used to protect lead or terminal configurations shall permit item removal without damage to the item. The unit container shall consist of a heat sealed bag conforming to MIL-B-117, type I, class F, style 1. All containers used shall be marked as specified for sensitive electronic devices in MIL-STD-129.</p> <p>Preserve Method IC-3 using MIL-B-22191 type III film. Sharp edges and protrusions shall be sufficiently cushioned with transparent material to protect the item and barrier.</p> |

TABLE IIc. Specialized Preservation Procedure Codes Digit Positions 1 & 2) (PCAM Columns 47, 48, MIL-STD-834) (See 5.2 and 5.2.4) (Continued).

| Code | Packaging procedure                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
|------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| JM   | Preserve Method III as follows: Unit container shall consist of one piece of 3/8-inch plywood and one piece of double wall fiberboard, PPP-F-320, each 4 inches longer and wider than the item dimensions. Place item on plywood, cover with fiberboard and staple fiberboard to plywood on sides and ends. For items longer than 96 inches, frame panel in accordance with PPP-B-601 (used for backing boards and similar flat items).                                                                                                      |
| JN   | Preserve in accordance with MIL-P-23199, Level B.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |
| JR   | Preserve Method III. Preserve technical literature Method IC-1 and place on top of contents prior to closure of unit container.                                                                                                                                                                                                                                                                                                                                                                                                              |
| JS   | Preserve Method IA-14. Preserve technical literature Method IC-1 and place on top of contents prior to closure of unit container.                                                                                                                                                                                                                                                                                                                                                                                                            |
| JT   | Preserve Method IIb. Preserve technical literature Method IC-1 and place on top of contents prior to closure of unit container.                                                                                                                                                                                                                                                                                                                                                                                                              |
| **JU | Cable Assemblies - Wrap and cushion connector end in accordance with procedure specified in MIL-P-116. Seal connector ends in MIL-B-22191 or MIL-B-117. Coil where possible to minimum cube and secure with dry common cord. Secure items weighing over ten pounds (coiled where possible) to corrugated, solid fiberboard or other rigid material. Preserve Method III in a fiberboard box conforming to PPP-B-636 weather resistant, sealing all seams with PPP-T-60 or PPP-T-76 tape.                                                     |
| **JV | Cable Assemblies - Wrap and cushion connector end in accordance with procedure specified in MIL-P-116. Seal connector ends in MIL-B-22191 or MIL-B-117. Coil where possible to minimum cube and secure with dry common cord. Preserve Method IC-1 in bag conforming to MIL-B-117, type I, class B.                                                                                                                                                                                                                                           |
| **JW | Cushion the item with antistatic material conforming to PPP-C-795, class 2 (air cap); PPP-C-1842, type III, style A or B open cell, or PPP-C-1797, type II. Place the wrapped or cushioned item in a bag made from material conforming to MIL-B-81705, type I (MIL-B-117, type I, class F, style 1). Heat seal the bag on all four edges. Place a MIL-STD-129 ESD caution label on the unit pack. Place the bagged item into an antistatic cushioned PPP-B-1672, Type II, container. Place a MIL-STD-129 ESD caution label on the container. |
| **JX | Package in accordance with MIL-STD-1169 using a watervaporproof enclosure with desiccant (Method II of MIL-P-116).                                                                                                                                                                                                                                                                                                                                                                                                                           |
| **JY | Package in accordance with MIL-STD-1169 using a watervaporproof enclosure (Method IA of MIL-P-116).                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| **JZ | Package in accordance with MIL-STD-1169 using a waterproof or water-proof, greaseproof enclosure (Method IC of MIL-P-116).                                                                                                                                                                                                                                                                                                                                                                                                                   |
| **KA | Package in accordance with MIL-STD-1169 providing physical and mechanical protection (Method III of MIL-P-116).                                                                                                                                                                                                                                                                                                                                                                                                                              |

\*\* Added

MIL-STD-726H  
 NOTICE 2

TABLE IIc. Specialized Preservation Procedure Codes Digit  
Positions 1 & 2) (PCAM Columns 47, 48, MIL-STD-  
834) (See 5.2 and 5.2.4) (Continued).

| Code | Packaging procedure                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| **KB | Place the item in an antistatic pouch conforming to MIL-P-81997, type I or II or bags constructed from MIL-B-81705, type II material, with or without a zipper closure and seal the pouch. Place the bagged item into an antistatic cushioned PPP-B-1672, type II container. Place a MIL-STD-129 ESD caution label on the container.                                                                                                                                                                                                                                                                                                                                                     |
| **KC | Preserve Method IC-1. Apply P-9 preservative. Place item in a bag conforming to MIL-B-22019, type II, or MIL-B-22020, class 2.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |
| **KD | Preserve Method IC-1. Apply P-9 preservative. Place item in a bag conforming to MIL-B-22020 and place bagged item into a weather resistant fiberboard box conforming to PPP-B-636. Fill voids with PPP-F-320 or PPP-C-843 material as required.                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| **KE | Wrap the item with barrier material conforming to MIL-B-81705, type II (MIL-B-117, type I, class A, style 2). Place the wrapped or cushioned item in a bag made from material conforming to MIL-B-81705, type I (MIL-B-117, type I, class F, style 1). Heat seal the bag on all four edges. Place a MIL-STD-129 ESD caution label on the unit pack. Place the bagged item into an antistatic cushioned PPP-B-1672, type II, container. Place a MIL-STD-129 ESD caution label on the container.                                                                                                                                                                                           |
| **KF | Clean each item in accordance with Method C-1 of MIL-P-116. Apply to the clean, dry metal surface and any crevice, hole or cavity with a transparent coating compound (hot dipping) conforming to MIL-P-149, type II (transparent cellulose, acetate, butyrate variety, or equivalent). Apply as many layers as necessary to protect the item from contact damage and to seal the item from moisture. Apply the compound in such a manner that upon removal no compound will be retained in the voids. Wrap the individually coated items in barrier material conforming to MIL-B-121, types I or II, grade A. (A preservation procedure for labyrinth rings and similar items in sets.) |

Note 1. Preservation and packing shall be in accordance with Level A requirements of MIL-B-197. In reference to Code "FM," the method of preservation described by symbol "G" (IA-8) of MIL-B-197 shall not exceed ten pounds, and symbol "A" may only be used for bearings exceeding an o.d. of 4.86 inches.

\*\* Added

Added page

MIL-STD-726H  
 NOTICE 2

TABLE III. Quantity Per Unit Pack Code (Digit Position 3)  
(PCAM Column 49, MIL-STD-883A) (See 5.3).

| Code | Quantity    | Code | Quantity | Code | Quantity                                                                 |
|------|-------------|------|----------|------|--------------------------------------------------------------------------|
| 1    | 1           | E    | 18       | U    | 250                                                                      |
| 2    | 2           | F    | 20       | V    | 500                                                                      |
| 3    | 3           | G    | 24       | W    | 1000                                                                     |
| 4    | 4           | H    | 25       | X    | Bulk                                                                     |
| 5    | 5           | J    | 32       | Y    | Packager's option so long as all other contractual requirements are met. |
| 6    | 6           | K    | 36       |      | Special requirement refer to special instruction or drawings provided.   |
| 7    | 7           | L    | 48       |      |                                                                          |
| 8    | 8           | M    | 50       |      |                                                                          |
| 9    | 9           | N    | 72       | Z    |                                                                          |
| Ø    | (See 5.3.1) | P    | 75       |      |                                                                          |
| A    | 10          | Q    | 100      |      |                                                                          |
| B    | 12          | R    | 120      |      |                                                                          |
| C    | 15          | S    | 144      |      |                                                                          |
| D    | 16          | T    | 200      |      |                                                                          |

MIL-STD-726H  
 31 JULY 1985

TABLE V. Preservative Material Codes  
 (Digit Positions 5 & 6) (PCAM Columns 51, 52, MIL-STD-834)  
 (see 5.5) (Continued).

| Code  | Material                                                                                                                                                                                                    |
|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 38    | MIL-P-149, plastic compounds, strippable coating (hot dipping).                                                                                                                                             |
| 43    | MIL-G-25537; grease, aircraft, helicopter.                                                                                                                                                                  |
| 49    | Vendor's protective grease or oil coating.                                                                                                                                                                  |
| 50    | MIL-L-7870, lubricating oil, general purpose, low temperature.                                                                                                                                              |
| 51    | MIL-L-6081, lubricating oil, jet engine, grade 1010.                                                                                                                                                        |
| 52    | MIL-C-8188, corrosion-preventive oil, gas turbine, engine, aircraft, synthetic base.                                                                                                                        |
| **#53 | MIL-L-6082, lubricating oil, aircraft, reciprocating engine (piston) (fire retardant).                                                                                                                      |
| 56    | MIL-L-23699, lubricating oil, aircraft turbine engines, synthetic base.                                                                                                                                     |
| 57    | MIL-L-21260, lubricating oil, internal combustion engine, preservative and break-in, grade 1, light viscosity oil.                                                                                          |
| 58    | MIL-L-21260, grade 2, medium viscosity oil.                                                                                                                                                                 |
| 59    | MIL-L-21260, grade 3, heavy viscosity oil.                                                                                                                                                                  |
| ##*65 | MIL-H-83282, hydraulic fluid, synthetic hydrocarbon, fire retardant.                                                                                                                                        |
| 71    | MIL-P-3420, inhibitor, corrosion, volatile treated carrier type, type I, for general application.                                                                                                           |
| 72    | MIL-P-3420, type II, for limited application.                                                                                                                                                               |
| **73  | P-9, lubricating oil, general purpose, preservative (water displacing, low temperature) overwrapped with MIL-P-3420 type I material.                                                                        |
| 78    | MIL-B-22019, barrier materials, transparent, flexible, sealable, volatile corrosion inhibitor treated.                                                                                                      |
| 79    | MIL-B-46176, brake fluid, silicone, automotive, operational and preservative.                                                                                                                               |
| 80    | MIL-P-46093, primer coating, synthetic (for brake drums).                                                                                                                                                   |
| 83    | P-9 applied to operating parts with P-1 applied to external non-critical surfaces.                                                                                                                          |
| 89    | Preserve with normal operating lubricant.                                                                                                                                                                   |
| 92    | MIL-H-6083, hydraulic fluid petroleum base, preservative applied to interior surfaces; P-6 applied to critical external ferrous metal surfaces; P-1 applied to external noncritical ferrous metal surfaces. |
| 95    | MIL-C-22235, corrosion preventive, oil, nonstaining.                                                                                                                                                        |
| **AA  | Preservative used shall be in accordance with the general provisions of MIL-P-116.                                                                                                                          |
| XX    | See method of preservation code (1st and 2nd digits) for this requirement.                                                                                                                                  |
| YY    | Packager's option so long as all other contractual requirements are met.                                                                                                                                    |
| ZZ    | Special requirement - See specific instructions or drawings provided.                                                                                                                                       |

\*\* Added

# Fire retardant

MIL-STD-726H  
 NOTICE 2

TABLE VI. Wrapping Material Codes  
 (Digit Positions 7 & 8) (PCAM Columns 53, 54, MIL-STD-834) (See 5.6).

| Code | Material                                                                              | Weight<br>lbs/sq. in. |
|------|---------------------------------------------------------------------------------------|-----------------------|
| **00 | No requirement.                                                                       | 0.00025               |
| AA   | Material used shall be in accordance with the requirements of MIL-P-116.              |                       |
| *#AB | MIL-B-131, type II, barrier watervaporproof, flexible heat sealable, flame resistant. | 0.00020               |
| BA   | QQ-A-1876, Aluminum Foil, 0.0025".                                                    | 0.00006               |
| CA   | UU-P-268, Paper, Kraft, Wrapping.                                                     | 0.00010               |
| CB   | UU-P-268, type I, grade B, 30 pound basis weight.                                     | 0.00013               |
| CC   | UU-P-268, type I, grade B, 40 pound basis weight.                                     | 0.00003               |
| CD   | UU-P-268, type I, grade B, 60 pound basis weight.                                     |                       |
| #CE  | UU-P-268, type II, grade C, 60 pound basis weight, fire retardant.                    |                       |
| #CF  | UU-P-268, type II, grade D, 55 pound basis weight, fire retardant.                    | 0.00003               |
| DA   | UU-P-553, Paper Wrapping tissue.                                                      | 0.00003               |
| DB   | UU-P-553, type I.                                                                     | 0.00003               |
| DC   | UU-P-553, type II.                                                                    | 0.00007               |
| EA   | MIL-P-17667, Chemically Neutral Wrapping Paper.                                       | 0.00007               |
| EB   | MIL-P-17667, type I.                                                                  | 0.00007               |
| EC   | MIL-P-17667, type II, class 1.                                                        | 0.00007               |
| ED   | MIL-P-17667, type II, class 2.                                                        | 0.00035               |
| FA   | MIL-P-130, Laminated and Creped Wrapping Paper.                                       | 0.00035               |
| FB   | MIL-P-130, type I, 150# basis weight.                                                 | 0.00029               |
| FC   | MIL-P-130, type II, 125# basis weight.                                                | 0.00023               |
| FD   | MIL-P-130, type III, 100# basis weight.                                               | 0.00025               |
| GA   | MIL-B-121, Greaseproof, Waterproof Barrier.                                           | 0.00025               |
| GB   | MIL-B-121, grade A.                                                                   | 0.00025               |
| GC   | MIL-B-121, type I, heavy duty, grade A.                                               | 0.00022               |
| GD   | MIL-B-121, type I, grade A, class 1, heat sealable.                                   | 0.00025               |
| GE   | MIL-B-121, type I, grade A, class 2, non heat sealable.                               | 0.00025               |
| GF   | MIL-B-121, type II, medium duty.                                                      | 0.00017               |
| GG   | MIL-B-121, type II, class 1, heat sealable, grade A.                                  | 0.00020               |
| GH   | MIL-B-121, type II, class 2, nonheat sealable, grade A.                               | 0.00025               |
| GK   | MIL-B-121, grade A, overwrap with MIL-B-130, secure wrap.                             | 0.00035               |
| GM   | MIL-B-131, class 1, general.                                                          | 0.00028               |
| GN   | MIL-B-131, class 2, limited.                                                          | 0.00035               |
| GP   | MIL-B-131, class 3, scrim.                                                            | 0.0004                |
| HC   | PPP-B-1055, barrier material, waterproofed, flexible.                                 | 0.00017               |
| JA   | L-P-378, plastic sheet & strip, thin gauge, polyolefin, 2 mil.                        |                       |

\* Changed  
 \*\* Added  
 # Fire retardant

MIL-STD-726H  
 NOTICE 2

TABLE VI. Wrapping Material Codes  
 (Digit Positions 7 & 8) (PCAM Columns 53, 54, MIL-STD-B34) (See 5.6).  
 (Continued).

| Code | Material                                                                                                                                            | Weight<br>lbs/sq. in. |
|------|-----------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|
| JB   | PPP-C-795, cushioning material, flexible, cellular plastic film for packaging applications, class 1, thin, up to 1/4 inch.                          | 0.00017               |
| JL   | MIL-B-22019, barrier materials, transparent, flexible, heat sealable, volatile corrosion inhibitor treated.                                         | 0.00010               |
| JV   | MIL-B-22191, barrier materials, transparent, flexible, heat sealable, type III.                                                                     | 0.00017               |
| JW   | PPP-C-795, cushioning material, flexible, cellular, plastic film for packaging applications, class 1, medium, 1/4 to 3/8 inch.                      | 0.00023               |
| JX   | PPP-C-795, class 1, thick, greater than 3/8 inch.                                                                                                   | 0.00025               |
| K3   | MIL-B-81705, type II barrier materials, flexible electrostatic free, heat sealable.                                                                 | 0.00030               |
| LA   | NNN-P-40, paper, lens, type II.                                                                                                                     | 0.00002               |
| MA   | PPP-P-291, paperboard, wrapping & cushioning.                                                                                                       | 0.00043               |
| N1   | PPP-C-795, cushioning material, flexible, cellular, plastic film for packaging applications, class 2, antistatic, pink tinted, thin up to 1/4 inch. | 0.00017               |
| N2   | PPP-C-795, class 2, antistatic, pink tinted, medium, 1/4 inch to 3/8 inch.                                                                          | 0.00023               |
| N3   | PPP-C-795, thick, greater than 3/8 inch.                                                                                                            | 0.00023               |
| N4   | PPP-C-1797, cushioning material, resilient, low density, unicellular, polypropylene foam, 1/16 inch.                                                | 0.00004               |
| N5   | PPP-C-1797, 3/32 inch.                                                                                                                              | 0.00004               |
| N6   | PPP-C-1797, 1/8 inch.                                                                                                                               | 0.00004               |
| N7   | PPP-C-1797, 1/4 inch.                                                                                                                               | 0.00004               |
| N8   | MIL-B-81705, type I barrier materials, flexible, electrostatic free, heat sealable.                                                                 | 0.00030               |
| *#PA | PPP-C-795, cushioning material, fire retardant, flexible, cellular, plastic film for packaging application, class 3.                                |                       |
| XX   | See Method of Preservation Code (1st and 2nd digits) for this requirement.                                                                          |                       |
| YY   | Packager's option so long as all other contractual requirements are met.                                                                            |                       |
| ZZ   | Special requirements - See specific instructions or drawings provided.                                                                              |                       |

Code 00 changed to Code 00 and transferred to the first listing of Table VI.

\* Changed

# Fire retardant

Supersedes page 41 of MIL-STD-726H, NOTICE 1

MIL-STD-726H  
 NOTICE 2

TABLE VIa. Cushioning and Dunnage Materials Codes  
 (Digit Positions 9 & 10) (PCAM Columns 55, 56, MIL-STD-834) (See 5.6).

| Code  | Material                                                                                                                                                                            | Weight<br>lbs/sq. in. |
|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|
| **00  | No requirement.                                                                                                                                                                     |                       |
| AA    | Any cushioning and dunnage which will meet the general requirements of MIL-P-116.                                                                                                   |                       |
| AB    | Cushioning and dunnage used within the unit container shall be treated latex or sponge rubber, cellulosic preforms, rubberized hair, or cane fiber inserts.                         |                       |
| AC    | Provide cushioning outside of the transparent unit pack when packing within the shipping container. Any cushioning which meets the general requirements of MIL-P-116 is acceptable. |                       |
| AD    | Cushion, anchor, block or brace in accordance with MIL-STD-1186.                                                                                                                    |                       |
| **#AE | Cushion, anchor, block or brace in accordance with MIL-STD-1186 using fire retardant materials.                                                                                     |                       |
| AF    | Cushioning conforming to the general requirements of MIL-P-116 shall be located between the barrier and outer container.                                                            | 0.0020                |
| #AG   | MIL-F-87090, class 1, combustion retardant foam for cushioning supply items aboard Navy ships (sheet stock).                                                                        |                       |
| #AH   | MIL-F-81334, foam, plastic, flexible, open cell, polyester type, polyurethane grades 1 and 2, sheet and strip, fire retardant.                                                      |                       |
| #AJ   | MIL-F-87090, class 2, combustion retardant foam for cushioning supply items aboard Navy ships (die cuts).                                                                           |                       |
| 1/ BA | PPP-C-843, Cellulosic Cushioning Material.                                                                                                                                          | 0.0015                |
| 1/ BB | PPP-C-843, in PPP-B-566 or PPP-B-676 Box (see Note 3).                                                                                                                              | 0.0026                |
| BC    | PPP-C-843 in PPP-B-636 class domestic (see Note 1).                                                                                                                                 | 0.0025                |
| 1/ RD | PPP-C-843, type I                                                                                                                                                                   | 0.0004                |
| BE    | PPP-C-843, type I in PPP-B-566 or PPP-B-676 Box (see Note 1).                                                                                                                       | 0.0015                |
| BF    | PPP-C-843, type I, in PPP-B-636 class domestic (see Note 1).                                                                                                                        | 0.0018                |
| 1/ BG | PPP-C-843, type II.                                                                                                                                                                 | 0.0008                |
| BH    | PPP-C-843, type II, in PPP-B-566 or PPP-B-676 Box (see Note 1).                                                                                                                     | 0.00195               |
| BJ    | PPP-C-843, type II, in PPP-B-636 class domestic (see Note 1).                                                                                                                       | 0.0023                |
| #BL   | PPP-C-850, cushioning material, polystyrene expanded, resilient, type I (sheet form) and type 2 (roll form) grade SE flame resistant.                                               |                       |
| BN    | PPP-C-850, Cushioning Material, Polystyrene, Expanded, Resilient (For Packaging Use).                                                                                               | 0.00122               |
| DA    | PPP-P-291, Paperboard, Wrapping & Cushioning.                                                                                                                                       | 0.00043               |

1/ Not to be used for Army aircraft or Army aircraft components.

\*\* Added

# Fire retardant

Supersedes page 42 of MIL-STD-726H, NOTICE 1

MIL-STD-726H  
 NOTICE 2

TABLE VIa. Cushioning and Dunnage Materials Codes  
 (Digit Positions 9 & 10) (PCAM Columns 55, 56, MIL-STD-834) (See 5.6).  
 (Continued).

| Code | Material                                                                                | Weight<br>lbs/sq. in. |
|------|-----------------------------------------------------------------------------------------|-----------------------|
| DB   | PPP-P-291, in PPP-B-566 or PPP-B-676 Box (see Note 1).                                  | 0.00043               |
| **DC | PPP-B-291, in PPP-B-636 or class domestic box (see Note 1).                             |                       |
| #DD  | MIL-R-5001, rubber cellular sheet, latex foam, type I and II, grade A (flame resistant) |                       |
| *#DF | Oil and flame retardant in accordance with para. 1.2.2, MIL-R-6130, type I, grade A.    |                       |
| #DG  | Oil and flame retardant in accordance with para. 1.2.2, MIL-R-6130, type II, grade A.   |                       |
| #DH  | MIL-R-0020092, type I, class 5, fire retardant shipboard.                               |                       |
| #DJ  | MIL-R-0020092, type II, class 5, fire retardant shipboard.                              |                       |
| EA   | PPP-B-566 or PPP-B-676 Box (see Note 3).                                                | 0.00043               |
| EB   | Vendor's setup or folding box (see Note 3).                                             | 0.00043               |
| EC   | PPP-B-636 class domestic (see Note 3).                                                  | 0.0017                |
| ED   | Vendor's fiberboard box (see Note 3).                                                   | 0.0017                |
| EG   | PPP-T-495, Mailing Tube (see Note 3).                                                   | 0.0034                |
| EM   | PPP-C-1120, class B (not necessarily water resistant).                                  | 0.00064               |
| EN   | PPP-C-1120, type I (soft density), class B.                                             | 0.00064               |
| EQ   | PPP-C-1120, type I, class B, in PPP-B-636, class domestic (see Note 1).                 | 0.00064               |
| ER   | PPP-C-1120, type II (medium soft density), class B.                                     | 0.00097               |
| ET   | PPP-C-1120, type II, class B, in PPP-B-636, class domestic (see Note 1).                | 0.00097               |
| EU   | PPP-C-1120, type III (medium firm density), class B.                                    | 0.00147               |
| EW   | PPP-C-1120, type III, class B, in PPP-B-636, class domestic (see Note 1).               | 0.0025                |
| EX   | PPP-C-1120, type IV (firm density), class B.                                            | 0.0022                |
| EZ   | PPP-C-1120, type IV, class B, in PPP-B-636, class domestic (see Note 1).                | 0.0036                |
| FA   | PPP-C-1120, class A (water resistant), cushioning material, bound fiber.                | 0.00067               |
| FB   | PPP-C-1120, type I (soft density), class A.                                             | 0.00064               |
| FC   | PPP-C-1120, type I, class A, in PPP-B-566 or PPP-B-676 box (see Note 1).                | 0.0018                |
| FD   | PPP-C-1120, type I, class A, in PPP-B-636 class domestic (see Note 1).                  | 0.00207               |
| FE   | PPP-C-1120, type II (medium soft density), class A.                                     | 0.00097               |
| FF   | PPP-C-1120, type II, class A, in PPP-B-566 or PPP-B-676 box (see Note 1).               | 0.00207               |
| FG   | PPP-C-1120, type II, class A, in PPP-B-636, class domestic (see Note 1).                | 0.00237               |

\* Changed  
 \*\* Added  
 # Fire retardant

Supersedes page 43 of MIL-STD-726H, NOTICE 1

MIL-STD-726H  
 NOTICE 2

TABLE VIa. Cushioning and Dunnage Materials Codes  
 (Digit Positions 9 & 10) (PCAH Columns 55, 56, MIL-STD-834) (See 5.6).  
(Continued).

| Code  | Material                                                                                                             | Weight<br>lbs/sq. in. |
|-------|----------------------------------------------------------------------------------------------------------------------|-----------------------|
| FH    | PPP-C-1120, type III (medium firm density), class A.                                                                 | 0.00147               |
| FJ    | PPP-C-1120, type III, class A, in PPP-B-566 or<br>PPP-B-676 box (see Note 1).                                        | 0.00257               |
| FK    | PPP-C-1120, type III, class A, in PPP-B-636, class<br>domestic (see Note 1).                                         | 0.00287               |
| FL    | PPP-C-1120, type IV (firm density), class A.                                                                         | 0.00220               |
| FM    | PPP-C-1120, type IV, class A, in PPP-B-566 or<br>PPP-B-676 box (see Note 1).                                         | 0.0033                |
| FN    | PPP-C-1120, type IV, class A, in PPP-B-636, class<br>domestic (see Note 1).                                          | 0.0036                |
| *#FP  | PPP-C-1120, cushioning material, uncompressed bound<br>fiber, type I, class A, grade 1, fire retardant.              |                       |
| **#FQ | PPP-C-1120, cushioning material, uncompressed bound<br>fiber, type II, class A, grade 1, fire retardant.             |                       |
| **#FR | PPP-C-1120, cushioning material, uncompressed bound<br>fiber, type III, class A, grade 1, fire retardant.            |                       |
| **#FT | PPP-C-1120, cushioning material, uncompressed bound<br>fiber, type IV, class A, grade 1, fire retardant.             |                       |
| GA    | PPP-C-1752, cushioning material, packaging, unicellular,<br>polyethylene foam, flexible, 2 pounds per cubic<br>foot. | 0.0010                |
| #GB   | MIL-F-83671, class 3, semirigid, foam-in-place, fire<br>retardant (see Note 2).                                      | 0.0002                |
| GC    | MIL-P-19644, Plastic, Molding Material.                                                                              |                       |
| #GD   | MIL-P-26514, type I, class 1, polyurethane, prefoamed,<br>rigid, fire retardant.                                     |                       |
| #GE   | MIL-P-26514, type I, class 2, grade A, polyurethane,<br>prefoamed, flexible, light load range, fire<br>retardant.    | 0.0012                |
| #GF   | MIL-P-26514, type I, class 2, grade B, polyurethane,<br>prefoamed, flexible medium load range, fire<br>retardant.    | 0.0013                |
| #GG   | MIL-P-19644, plastic molding material (polystyrene<br>foam, expanded) fire retardant.                                |                       |
| #GH   | MIL-P-26514, type I, class 2, grade C, polyurethane,<br>prefoamed, flexible, medium load range, fire<br>retardant.   | 0.00166               |

\* Changed  
 \*\* Added  
 # Fire retardant

MIL-STD-726H  
NOTICE 2

TABLE VIa. Cushioning and Dunnage Materials Codes  
(Digit Positions 9 & 10) (PCAM Columns 55, 56, MIL-STD-834) (See 5.6).  
(Continued).

| Code | Material                                                                                                                    | Weight<br>lbs/sq. in. |
|------|-----------------------------------------------------------------------------------------------------------------------------|-----------------------|
| #GJ  | MIL-P-26514, type I, class 2, grade C, polyurethane, prefoamed, flexible, heavy load range, 65 g's or less, fire retardant. | 0.020                 |
| #GK  | MIL-F-83671, class 2, grade A, foam-in-place, fire retardant (see Note 2).                                                  |                       |
| #GL  | MIL-F-83671, class 2, grade B, foam-in-place, fire retardant (see Note 2).                                                  |                       |
| #GM  | MIL-F-83671, class 3, foam-in-place, fire retardant (see Note 2).                                                           |                       |

# Fire retardant

Added page

MIL-STD-726H

NOTICE 2

TABLE VIa. Cushioning and Dunnage Materials Codes  
 (Digit Positions 9 & 10) (PCAM Columns 55, 56, MIL-STD-834) (See 5.6).  
 (Continued).

| Code  | Material                                                                                                                                                                                                                                                                                                                               | Weight<br>lbs/sq. in. |
|-------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|
| **#JP | PPP-C-1120, cushioning material, uncompressed bound fiber, type V, class A, grade 1, fire retardant.                                                                                                                                                                                                                                   | 0.0029                |
| JQ    | Fiberboard triple-wall cells, pads, sleeves or die-cuts, made of materials used in the fabrication of PPP-B-640 boxes.                                                                                                                                                                                                                 |                       |
| **#JR | Wood blocking and bracing, fire retardant and/or fasteners (and/or steel strapping, for tie-down purposes). Rubber tired wheels shall be blocked clear of the floor of the crate or skid and shall not be load bearing. Wood blocking and bracing shall be of wood treated with nonleachable compounds in accordance with MIL-L-19140. | 0.001                 |
| LB    | MIL-F-2312, felt, hair or wool.                                                                                                                                                                                                                                                                                                        |                       |
| LC    | PPP-C-795, Cushioning Material, Flexible, Cellular, Plastic Film, for Packaging Applications, class 1, thin, up to 1/4 inch.                                                                                                                                                                                                           | 0.00017               |
| LD    | PPP-C-795, class 1, greater than 1/4".                                                                                                                                                                                                                                                                                                 | 0.00020               |
| #LE   | MIL-P-26514, Polyurethane Foam, Rigid or Elastic, for Packaging, type 1, class 2 used as corner pads, fire retardant.                                                                                                                                                                                                                  |                       |
| LF    | MIL-C-3955, spirally wound fiber cans (material used as tubing without metal ends).                                                                                                                                                                                                                                                    | 0.0029                |
| LG    | PPP-F-320, type CF, class domestic, fiberboard discs, faced on both sides with MIL-B-121, grade A, barrier material (cushioning inside fiber cans).                                                                                                                                                                                    |                       |
| LH    | Utilize the chest or carrying case of the item as the inner container (see Note 3).                                                                                                                                                                                                                                                    | 0.018                 |
| LJ    | PPP-T-60, tape, pressure-sensitive adhesive, water-proof for packaging applied to exposed threads.                                                                                                                                                                                                                                     |                       |
| LK    | Wood blocking and bracing, and/or fasteners, and/or steel strapping, for tie-down purposes. Rubber tired wheels shall be blocked clear of the floor of the crate or skid, and shall not be load bearing.                                                                                                                               | 0.00122               |
| LN    | Plastic containers (vials, boxes, etc.) shall be constructed of rigid, transparent material and, if applicable, resistant to lubricant or preservative being used.                                                                                                                                                                     |                       |
| LP    | NN-P-530, plywood padded as required; used as a pressure strip, block, brace or pallet.                                                                                                                                                                                                                                                | 0.01925               |

\*\* Added

# Fire retardant

MIL-STD-726H  
 NOTICE 2

TABLE VIa. Cushioning and Dunnage Materials Codes  
 (Digit Positions 9 & 10) (PCAM Columns 55, 56, MIL-STD-834) (See 5.6).  
 (Continued).

| Code  | Material                                                                                                                        | Weight<br>lbs/sq. in. |
|-------|---------------------------------------------------------------------------------------------------------------------------------|-----------------------|
| LR    | PPP-C-795, Cushioning Material, Flexible, Cellular, Plastic Film, for Packaging Applications, class 1, medium, 1/4 to 3/8 Inch. | 0.00023               |
| LS    | PPP-C-795, class 1, thick, greater than 3/8 inch.                                                                               | 0.00023               |
| LT    | PPP-C-795, class 2, antistatic, pink, thin, up to 1/4 inch.                                                                     | 0.00017               |
| LU    | PPP-C-795, class 2, antistatic, pink, medium, 1/4 to 3/8 inch.                                                                  | 0.00022               |
| LV    | PPP-C-795, class 2, antistatic, pink, thick, greater than 3/8 inch.                                                             | 0.00023               |
| **#LW | PPP-C-795, class 3, cushioning material, fire retardant, flexible, cellular, plastic film for packaging application.            |                       |
| LX    | PPP-C-795, in PPP-B-636 class, domestic box.                                                                                    |                       |
| **MA  | MIL-F-83671, class 2, polyurethane, flexible foamed-in-place (see Note 2).                                                      |                       |
| **MB  | MIL-F-83671, class 1, polyurethane, rigid, foamed-in-place (see Note 2).                                                        |                       |
| **MC  | MIL-F-83671, class 1, polyurethane, density 0.5 through 1.0 lb per cubic foot (see Note 2).                                     |                       |

\*\* Added

# Fire retardant

Added page

MIL-STD-726H  
 NOTICE 2

TABLE VIa. Cushioning and Dunnage Materials Codes  
 (Digit Positions 9 & 10) (PCAM Columns 55, 56, MIL-STD-834) (See 5.6).  
 (Continued).

| Code | Material                                                                                                                                                                                                                                                                                                                                                                                                   | Weight<br>lbs/sq. in. |
|------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|
| NA   | PPP-C-795, cushioning material, flexible, cellular, plastic film, for packaging applications, or PPP-C-1842, cushioning material, plastic, open cell for packaging applications or PPP-C-1797, cushioning material, resilient, low density, unicellular, polypropylene foam or PPP-C-1752, cushioning material, packaging, unicellular polyethylene foam.                                                  | 0.0004                |
| *NB  | PPP-C-1842, type III, style A or B, or PPP-C-1797, type I, polypropylene foam (antistatic). Other electrostatic free cushioning material is acceptable provided it meets the static decay rate test requirement of PPP-C-1842.                                                                                                                                                                             |                       |
| ND   | PPP-C-795 or PPP-C-1842 or PPP-C-1797 or PPP-C-1752 in a PPP-B-636 box, class domestic (see Note 2).                                                                                                                                                                                                                                                                                                       |                       |
| NG   | PPP-C-1842, cushioning material, plastic, open cell.                                                                                                                                                                                                                                                                                                                                                       | 0.00017               |
| NR   | PPP-F-320, class domestic, fiberboard used as pads, cells, sleeves, or die cuts in PPP-B-636, class domestic box or cushioning material conforming to MIL-P-19644 or polyurethane foam conforming to MIL-P-26514 in PPP-B-636, class domestic box.                                                                                                                                                         |                       |
| NS   | PPP-F-320, class weather resistant used as pads, cells, sleeves or die-cuts or plastic molding material conforming to MIL-P-19644 or polyurethane foam conforming to MIL-P-26514.                                                                                                                                                                                                                          |                       |
| NU   | PPP-C-795, Cushioning Material, Flexible, Cellular, Plastic Film, for Packaging Application or PPP-C-1842, Cushioning Material, Plastic, Open Cell for Packaging Application or PPP-C-1797, Cushioning Material, Resilient, Low Density, Unicellular Polypropylene Foam or PPP-C-1752, Cushioning Material, Packaging, Unicellular Polyethylene Foam, Flexible in PPP-B-566 or PPP-B-676 Box (see Note 3). |                       |
| NV   | PPP-C-1842, Cushioning Material, type III, Plastic Open Cell for Packaging Application or PPP-C-1797, Cushioning Material, Resilient, Low Density, Unicellular Polypropylene Foam in PPP-B-566 or PPP-B-676 Box (see Note 3).                                                                                                                                                                              |                       |
| NW   | PPP-C-1842, cushioning material, type III, plastic open cell for packaging application or PPP-C-1797, cushioning material, resilient, low density, unicellular polypropylene foam in PPP-B-636, class domestic box (see Note 3).                                                                                                                                                                           |                       |
| **NX | PPP-C-1752, type VII, grade C, class 1 or 3.                                                                                                                                                                                                                                                                                                                                                               |                       |

Code 00 changed to Code 00 and transferred to the first listing in Table VIa.

\* Changed

\*\* Added

MIL-STD-726H  
 NOTICE 2

TABLE VIa. Cushioning and Dunnage Materials Codes  
 (Digit Positions 9 & 10) (PCAM Columns 55, 56, MIL-STD-834) (See 5.6).  
(Continued).

| Code  | Material                                                                                                     | Weight<br>lbs/sq. in. |
|-------|--------------------------------------------------------------------------------------------------------------|-----------------------|
| **#P1 | Cushion, anchor, block or brace in accordance with MIL-STD-1186 using fire retardant varieties of materials. |                       |
| **#P2 | PPP-F-320, class domestic, fire retardant.                                                                   |                       |
| **#P3 | PPP-F-320, class weather-resistant, fire retardant.                                                          |                       |
| XX    | See Method of Preservation Code (1st and 2nd digits) for this requirement.                                   |                       |
| YY    | Packager's option so long as all other contractual requirements are met.                                     |                       |
| ZZ    | Special requirements. See specific instructions or drawing provided.                                         |                       |

Note 1. The use of this code does not require an additional container within a barrier to satisfy the method.

Note 2. Application of these materials (foamed-in-place) shall be in such a manner as to facilitate ease of removal and insure the reusability of the cushioning dunnage.

Note 3. Cushioning thickness shall apply to cushioning only and does not include thickness of the container.

\*\* Added  
 # Fire retardant

Supersedes page 49 of MIL-STD-726H

MIL-STD-726H  
 NOTICE 2

TABLE VIb. Cushioning Thickness Codes  
 (Digit Position 11) (PCAM Column 57, MIL-STD-883A) (See 5.6.7).

| Code | Minimum thickness   | Code | Minimum thickness                                                              |
|------|---------------------|------|--------------------------------------------------------------------------------|
| **Ø  | Not applicable.     | P    | 3-1/2 inches thick.                                                            |
| A    | 1/4 inch thick.     | Q    | 3-3/4 inches thick.                                                            |
| B    | 1/2 inch thick.     | R    | 4 inches thick.                                                                |
| C    | 3/4 inch thick.     | S    | 4-1/4 inches thick.                                                            |
| D    | 1 inch thick.       | T    | 4-1/2 inches thick.                                                            |
| E    | 1-1/4 inches thick. | U    | 4-3/4 inches thick.                                                            |
| F    | 1-1/2 inches thick. | V    | 5 inches thick.                                                                |
| G    | 1-3/4 inches thick. | W    | 5-1/4 inches thick.                                                            |
| H    | 2 inches thick.     | X    | As required to protect<br>the item or elements of<br>the package.              |
| J    | 2-1/4 inches thick. | Y    | Packager's option so long<br>as all other contractual<br>requirements are met. |
| K    | 2-1/2 inches thick. | Z    | Special requirements - See<br>specific instructions or<br>drawing provided.    |
| L    | 2-3/4 inches thick. |      |                                                                                |
| M    | 3 inches thick.     |      |                                                                                |
| N    | 3-1/4 inches thick. |      |                                                                                |

\*\* Added

MIL-STD-726H  
 NOTICE 2

TABLE VII. Unit and Intermediate Container Codes  
 (Digit Positions 12 & 13 or 15 & 16)  
 (PCAM Columns 58, 59 or 61, 62, MIL-STD-834) (see 5.7 or 5.9).

| Code | Container                                                                                                                                                                                                                                                                                                | Weight<br>lbs/sq. in. | Wall<br>Thickness<br>(Inch) |
|------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|-----------------------------|
| **00 | No requirement.                                                                                                                                                                                                                                                                                          |                       |                             |
| 10   | Any suitable container included in this table may be used (see 5.7.1).                                                                                                                                                                                                                                   |                       |                             |
| 11   | Unit or shipping container is not required. Preparation for shipment shall be accomplished in a manner which will insure safe delivery at destination, and shall comply with the Uniform Freight Classification Rules or Regulations, or other regulations, as applicable to the mode of transportation. |                       |                             |
| #12  | Bag conforming to requirements of UU-B-23 (flame retardant).                                                                                                                                                                                                                                             |                       |                             |
| A1   | Bags made of material conforming to MIL-P-130, MIL-P-17667, MIL-B-121, grade A; or MIL-B-117. Closure may be by staples, tape, adhesive or heat seal.                                                                                                                                                    | 0.0003                | .006                        |
| A2   | Any bag or sack used by the vendor.                                                                                                                                                                                                                                                                      | 0.0002                | .006                        |
| A3   | Bags made of material conforming to MIL-B-121, grade A or L-P-378, type I or II. Closure shall be heat sealed only.                                                                                                                                                                                      | 0.00017               | .004                        |
| #A4  | Bags made of material conforming to MIL-B-117, type I, class G, style 1 (flame resistant).                                                                                                                                                                                                               |                       |                             |
| AA   | PPP-B-20, mailing bags.                                                                                                                                                                                                                                                                                  |                       |                             |
| AC   | PPP-S-30, sacks, shipping, paper (cushioned or reinforced).                                                                                                                                                                                                                                              |                       |                             |
| AD   | PPP-S-30, type I, exterior packaging bags.                                                                                                                                                                                                                                                               |                       |                             |
| AE   | PPP-S-30, type II, interior packaging bags.                                                                                                                                                                                                                                                              |                       |                             |
| AH   | PPP-B-35, bags, textile, shipping.                                                                                                                                                                                                                                                                       |                       |                             |
| AJ   | PPP-B-35, type I, standard burlap bag.                                                                                                                                                                                                                                                                   |                       |                             |
| AK   | PPP-B-35, type II, standard cotton bag.                                                                                                                                                                                                                                                                  |                       |                             |
| AL   | PPP-B-35, type III, laminated textile bags.                                                                                                                                                                                                                                                              |                       |                             |
| AN   | UU-B-36, bags, paper, grocers.                                                                                                                                                                                                                                                                           | 0.0002                | 0.006                       |
| AO   | Any suitable bag or sack included in this table may be used.<br>(See 5.7.1)                                                                                                                                                                                                                              |                       |                             |

\*\* Added

# Fire retardant

MIL-STD-726H  
 NOTICE 2

TABLE VII. Unit and Intermediate Container Codes  
 (Digit Positions 12 & 13 or 15 & 16)  
 (PCAM Columns 58, 59 or 61, 62, MIL-STD-834) (see 5.7 or 5.9) (Continued).

| Code  | Container                                                                                                                                                  | Weight<br>lbs/sq. in. | Wall<br>Thickness<br>(Inch) |
|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|-----------------------------|
| *B1   | MIL-B-117, type I, class B, style 3,<br>heavy duty, waterproof, opaque and<br>transparent.                                                                 | 0.0003                |                             |
| B2    | MIL-B-117, type I, class C, style 3,<br>heavy duty, waterproof, greaseproof,<br>opaque and transparent bag.                                                | 0.0003                |                             |
| B3    | MIL-B-117, type I, class E, style 3,<br>heavy duty, greaseproof, waterproof,<br>watervaporproof, opaque and trans-<br>parent bag.                          | 0.0003                |                             |
| B4    | MIL-B-117, type II, class E, style 3,<br>medium duty, greaseproof, waterproof,<br>watervaporproof, opaque and trans-<br>parent bag.                        | 0.00025               |                             |
| B7    | MIL-B-117 bags or bags made of<br>L-P-378 material, fabricated in<br>accordance with MIL-B-117,<br>closure may be staples, tape,<br>adhesive or heat seal. | 0.00017               | 0.004                       |
| B8    | MIL-B-117, type I, class A, style 2,<br>heavy duty, waterproof, electro-<br>static free.                                                                   | 0.00035               | 0.006                       |
| B9    | MIL-B-117, type I, class F, style 1,<br>heavy duty, watervaporproof,<br>electrostatic free.                                                                | 0.00035               | 0.006                       |
| **#BC | PPP-B-640, class 4, weather resistant,<br>fire retardant.                                                                                                  |                       |                             |
| BD    | MIL-B-117, bags, interior packaging.                                                                                                                       | 0.00017               | 0.006                       |
| *BE   | MIL-B-117, type I, class C, style 1,<br>heavy duty, waterproof, greaseproof,<br>and opaque.                                                                | 0.00025               | 0.006                       |
| **#BG | MIL-C-104, type II, bolted, class 2, ply-<br>wood treated with nonleachable compounds<br>in accordance with MIL-L-19140.                                   |                       |                             |
| **#BJ | Any suitable wood crate, included in this<br>table and made with wood treated with<br>unleachable compounds in accordance<br>with MIL-L-19140.             |                       |                             |
| *BL   | MIL-B-117, type I, class B, style 2,<br>heavy duty, waterproof and trans-<br>parent.                                                                       | 0.00017               | 0.004                       |

\* Changed

\*\* Added

# Fire retardant

Codes B6, BQ deleted

Supersedes page 52 of MIL-STD-726H

MIL-STD-726H  
 NOTICE 2

TABLE VII. Unit and Intermediate Container Codes  
 (Digit Positions 12 & 13 or 15 & 16)  
 (PCAM Columns 58, 59 or 61, 62, MIL-STD-834) (see 5.7 or 5.9) (Continued).

| Code  | Container                                                                             | Weight<br>lbs/sq. in. | Wall<br>Thickness<br>(Inch) |
|-------|---------------------------------------------------------------------------------------|-----------------------|-----------------------------|
| **#BM | PPP-B-636, class domestic, fire retardant.                                            |                       |                             |
| **#BN | PPP-B-636, class weather resistant, fire retardant.                                   |                       |                             |
| **#BP | PPP-B-640, class 3, nonweather resistant, fire retardant.                             |                       |                             |
| BR    | MIL-B-117, type I, class C, heavy duty, greaseproof waterproof bag.                   | 0.0003                |                             |
| BS    | MIL-B-117, type I, class E, heavy duty, greaseproof, waterproof, watervaporproof bag. | 0.0003                |                             |

\*\* Added  
 # Fire retardant

Added page

MIL-STD-726H

NOTICE 2

TABLE VII. Unit and Intermediate Container Codes  
 (Digit Positions 12 & 13 or 15 & 16)  
 (PCAM Columns 58, 59 or 61, 62, MIL-STD-834) (see 5.7 or 5.9) (Continued).

| Code | Container                                                                                                    | Weight<br>lbs/sq. in. | Wall<br>Thickness<br>(Inch) |
|------|--------------------------------------------------------------------------------------------------------------|-----------------------|-----------------------------|
| BT   | MIL-B-22020, bag, transparent,<br>sealable VCI, treated.                                                     | 0.00020               | 0.004                       |
| *BU  | MIL-B-117, type II, class C, style 1,<br>medium duty, waterproof, grease-<br>proof and opaque.               |                       |                             |
| BV   | MIL-B-117, type II, class C, medium<br>type, greaseproof, waterproof bag.                                    | 0.00035               |                             |
| BW   | MIL-B-117, type II, class E, medium<br>type, greaseproof waterproof,<br>watervaporproof bag.                 | 0.00017               |                             |
| *BX  | MIL-B-117, type I, class C, style 3,<br>heavy duty, waterproof, greaseproof,<br>opaque and transparent.      |                       |                             |
| CA   | PPP-B-1806, barrels and kegs, wood<br>slack.                                                                 |                       |                             |
| CF   | PPP-D-723, drum, fiber.                                                                                      | 0.00430               | 0.12                        |
| CG   | PPP-D-723, type I, domestic type.                                                                            | 0.00430               | 0.12                        |
| CH   | PPP-D-723, type II, normal overseas<br>type.                                                                 | 0.00430               | 0.12                        |
| CJ   | PPP-D-723, type III, military over-<br>seas type.                                                            | 0.00430               | 0.12                        |
| CO   | Any suitable fiber drum included in<br>this table may be used. (See 5.7.1)                                   |                       |                             |
| CR   | PPP-D-723, type I, grade A, class 2.                                                                         |                       |                             |
| CT   | PPP-B-566, variety 2, process II.                                                                            | 0.0017                | 0.045                       |
| CU   | PPP-B-566, variety 2, process II or<br>PPP-B-665, class 2.                                                   | 0.0017                | 0.045                       |
| CV   | PPP-B-566, variety 2, process II or<br>PPP-B-665, class 2 or PPP-B-636,<br>type CF, class weather-resistant. | 0.0017                | 0.045                       |
| CW   | PPP-B-665, class 2, box, paperboard<br>metal edge and components.                                            | 0.0017                | 0.045                       |
| D1   | PPP-B-566 or PPP-B-676, folding or<br>setup boxes.                                                           | 0.0017                | 0.045                       |
| D2   | PPP-B-566, PPP-B-665 or PPP-B-676,<br>folding, metal-stayed or setup<br>boxes.                               | 0.0017                | 0.045                       |
| D3   | PPP-B-566, PPP-B-665, PPP-B-676,<br>PPP-B-636, folding, metal-stayed,<br>setup or fiberboard boxes.          | 0.0017                | 0.045                       |
| D4   | Vendor's setup or folding boxes.                                                                             | 0.0017                | 0.045                       |
| D6   | Variety 1, PPP-B-566 or PPP-B-676 boxes.                                                                     | 0.0017                | 0.045                       |
| D7   | Variety 2, PPP-B-566 or PPP-B-676 boxes.                                                                     | 0.0017                | 0.045                       |
| DA   | PPP-B-566, boxes, folding paperboard.                                                                        | 0.0011                | 0.045                       |

\* Changed

MIL-STD-726H  
 NOTICE 2

TABLE VII. Unit and Intermediate Container Codes  
 (Digit Positions 12 & 13 or 15 & 16)  
 (PCAM Columns 58, 59 or 61, 62, MIL-STD-834) (see 5.7 or 5.9) (Continued).

| Code   | Container                                                                                                                                                             | Weight<br>lbs/sq. in. | Wall<br>Thickness<br>(Inch) |
|--------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|-----------------------------|
| DB     | MIL-B-43666, type III.                                                                                                                                                | 0.00297               | 0.375                       |
| DC     | MIL-B-38721, boxes, consolidated,<br>fiberboard.                                                                                                                      | 0.0011                | 0.040                       |
| DE     | PPP-B-676 box.                                                                                                                                                        | 0.0012                | 0.040                       |
| DJ     | PPP-B-665 box.                                                                                                                                                        |                       |                             |
| DO     | Any suitable fiber box, included<br>in this table may be used.<br>(See 5.7.1)                                                                                         |                       |                             |
| DP     | PPP-B-640, box, triple wall.                                                                                                                                          | 0.00297               | 0.375                       |
| DQ     | PPP-B-640, class 1.                                                                                                                                                   | 0.00297               | 0.375                       |
| DR     | PPP-B-640, class 2.                                                                                                                                                   | 0.00297               | 0.375                       |
| **#DS  | MIL-C-104, crate, wood, lumber or ply-<br>wood sheathed, nailed or bolted made<br>with wood treated with nonleachable<br>compounds in accordance with<br>MIL-L-19140. |                       |                             |
| ***#DT | MIL-C-104, type I, nailed, class 2, ply-<br>wood treated with nonleachable com-<br>pounds in accordance with MIL-L-19140.                                             |                       |                             |
| DU     | PPP-B-591, boxes, fiberboard,<br>wood-cleated.                                                                                                                        | 0.0043                | 0.750                       |
| DV     | PPP-B-591, domestic type.                                                                                                                                             | 0.0043                | 0.75                        |
| DW     | PPP-B-591, overseas type.                                                                                                                                             | 0.0043                | 0.75                        |
| E1     | PPP-B-636, type CF or type SF,<br>class domestic.                                                                                                                     | 0.00126               | 0.187                       |
| E2     | PPP-B-636, type CF or type SF,<br>class, weather-resistant.                                                                                                           |                       | 0.187                       |
| E3     | PPP-B-636, W5c or W6c.                                                                                                                                                |                       |                             |
| E4     | PPP-B-636, W5s or W6s.                                                                                                                                                |                       |                             |
| E5     | PPP-B-636, any desired option.                                                                                                                                        |                       |                             |
| E6     | Vendor's fiberboard box.                                                                                                                                              | 0.00126               |                             |
| E7     | PPP-B-636, type CF, class domestic,<br>variety SW.                                                                                                                    |                       |                             |
| E8     | PPP-B-636, type CF, class domestic,<br>variety DW.                                                                                                                    | 0.00126               | 0.375                       |
| E9     | PPP-B-636, type CF, class weather<br>resistant or water resistant<br>PPP-B-566 or PPP-B-676.                                                                          |                       |                             |
| EB     | PPP-B-636, type CF.                                                                                                                                                   |                       |                             |
| EC     | PPP-B-636, type CF, class domestic.                                                                                                                                   | 0.00136               | 0.187                       |
| ED     | PPP-B-636, type CF, class weather<br>resistant.                                                                                                                       | 0.00126               | 0.187                       |

\*\* Added

# Fire retardant

MIL-STD-726H  
 NOTICE 2

TABLE VII. Unit and Intermediate Container Codes  
 (Digit Positions 12 & 13 or 15 & 16)  
 (PCAM Columns 58, 59 or 61, 62, MIL-STD-834) (see 5.7 or 5.9) (Continued).

| Code | Container                                   | Weight<br>lbs/sq. in. | Wall<br>Thickness<br>(Inch) |
|------|---------------------------------------------|-----------------------|-----------------------------|
| EE   | PPP-B-636, grade V3c.                       | 0.00136               | 0.187                       |
| EF   | PPP-B-636, W5c.                             |                       |                             |
| EG   | PPP-B-636, W6c.                             |                       |                             |
| EN   | PPP-B-636, type SF, class domestic.         | 0.00126               | 0.187                       |
| *EP  | PPP-B-636, type SF, class weather resistant | 0.00126               | 0.187                       |
| EQ   | PPP-B-636, V3s.                             |                       |                             |
| ER   | PPP-B-636, W5s.                             |                       |                             |
| ES   | PPP-B-636, W6s.                             |                       |                             |

\* Changed  
 Added page

MIL-STD-726H  
 NOTICE 2

TABLE VII. Unit and Intermediate Container Codes  
 (Digit Positions 12 & 13 or 15 & 16)  
 (PCAM Columns 58, 59 or 61, 62, MIL-STD-834) (see 5.7 or 5.9) (Continued).

| Code | Container                                                                                                                                                                                                                                                                                                           | Weight<br>lbs/sq. in. | Wall<br>Thickness<br>(Inch) |
|------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|-----------------------------|
| JM   | PPP-C-96, type V, class 5, round, square, oval or oblong, both ends crimped or double-seamed on, with snap-on closure.                                                                                                                                                                                              |                       |                             |
| JN   | PPP-C-96, type V, class 6, round, square, oval or oblong, both ends crimped or double-seamed on, with spout closure.                                                                                                                                                                                                |                       |                             |
| K1   | Each unit shall be packaged in a reusable metal container of minimum practicable size conforming to MIL-D-6054, MIL-D-6055 or MIL-C-4150, depending upon size or capacity of container required. This container will be used to accomplish the preservation method indicated by the 1st and 2nd digits of the code. |                       |                             |
| KA   | MIL-C-4150, case, carrying and storage, cushioned within a PPP-B-636, box class domestic.                                                                                                                                                                                                                           |                       |                             |
| #KB  | MIL-C-9959, container, flexible, reusable, watervaporproof, flame resistant, type I, grade A.                                                                                                                                                                                                                       |                       |                             |
| KE   | MIL-D-6054, drum, metal, shipping and storage, reusable.                                                                                                                                                                                                                                                            |                       |                             |
| KF   | MIL-D-6055, drums, metal, reusable, shipping and storage (capacity from 88 to 510 cubic inches).                                                                                                                                                                                                                    |                       |                             |
| KO   | Any suitable rigid case or container, included in this table, may be used. (See 5.7.1)                                                                                                                                                                                                                              |                       |                             |
| KP   | MIL-C-5584, Container, shipping and storage, metal, reusable.                                                                                                                                                                                                                                                       |                       |                             |
| LO   | MS18011-21 (See Note 1).                                                                                                                                                                                                                                                                                            |                       |                             |
| *M1  | MIL-C-9897, Crate, Slotted Angle, Steel or Aluminum, for Lightweight Airframe Components and Bulky Items, type I, style A, 500 lbs maximum weight.                                                                                                                                                                  |                       |                             |

\* Changed

# Fire retardant

MIL-STD-726H  
 NOTICE 2

TABLE VII. Unit and Intermediate Container Codes  
 (Digit Positions 12 & 13 or 15 & 16)  
 (PCAM Columns 58, 59 or 61, 62, MIL-STD-834) (see 5.7 or 5.9) (Continued).

| Code  | Container                                                                                                                                                                                                                                                                                           | Weight<br>lbs/sq. in. | Wall<br>Thickness<br>(Inch) |
|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|-----------------------------|
| M2    | MIL-C-9897, type II, style A, 500 lbs<br>maximum gross weight.                                                                                                                                                                                                                                      |                       |                             |
| M3    | MIL-C-9897, type I, style B, 3000 lbs<br>gross weight.                                                                                                                                                                                                                                              |                       |                             |
| M4    | MIL-C-9897, type II, style B, 3000 lbs<br>gross weight.                                                                                                                                                                                                                                             |                       |                             |
| M5    | Vendor's open wood crate.                                                                                                                                                                                                                                                                           |                       |                             |
| MA    | MIL-C-104, Crate, Wood, Lumber or<br>Plywood Sheathed, Nailed or Bolted.                                                                                                                                                                                                                            |                       |                             |
| MB    | MIL-C-104, type I, nailed, class 1, lumber.                                                                                                                                                                                                                                                         |                       |                             |
| MC    | MIL-C-104, type II, bolted, class 1, lumber.                                                                                                                                                                                                                                                        |                       |                             |
| **#ME | PPP-B-621, class 1 (domestic) or class 2<br>(overseas), fire retardant treated, non-<br>leachable compounds in accordance with<br>MIL-L-19140.                                                                                                                                                      |                       |                             |
| MF    | MIL-C-104, type I, nailed, class 2, plywood.                                                                                                                                                                                                                                                        |                       |                             |
| MG    | MIL-C-104, type II, bolted, class 2, plywood.                                                                                                                                                                                                                                                       |                       |                             |
| MH    | MIL-C-104, type II, bolted, class 1 or 2,<br>provided with lifting attachments and an<br>inspection port (Method IIa packages<br>only). The top, one side and one end of<br>the crate shall be marked "REUSABLE CON-<br>TAINER USE FOR RETURN OF NFRI ASSEMBLY."<br>Black letters, minimum 2" high. |                       |                             |
| MJ    | MIL-C-3774, crate, wood, open 12,000 to<br>16,000 lbs capacity.                                                                                                                                                                                                                                     |                       |                             |
| **#ML | PPP-B-576, fire retardant treated non-<br>leachable compounds, in accordance with<br>MIL-L-19140.                                                                                                                                                                                                   |                       |                             |
| MO    | Any suitable wood crate, included in this<br>table may be used. (See 5.7.1)                                                                                                                                                                                                                         |                       |                             |
| **#MP | MIL-B-26195, fire retardant treated with<br>nonleachable compounds in accordance<br>with MIL-L-19140                                                                                                                                                                                                |                       |                             |
| **#MS | PPP-B-621, class 2, overseas, constructed<br>with lumber and plywood treated with<br>nonleachable compounds in accordance<br>with MIL-L-19140.                                                                                                                                                      |                       |                             |
| MU    | MIL-C-25731, types VI or VII as applicable.                                                                                                                                                                                                                                                         |                       |                             |
| MV    | MIL-C-52950, crates, wood, open and<br>covered, style A, heavy duty.                                                                                                                                                                                                                                |                       |                             |
| MW    | MIL-C-25731, crate, wood, for lightweight<br>aircraft components.                                                                                                                                                                                                                                   |                       |                             |
| MX    | MIL-C-52950, crates, wood, open and<br>covered, style B, light duty.                                                                                                                                                                                                                                |                       |                             |

\*\* Added

# Fire retardant

Supersedes page 60 of MIL-STD-726H

MIL-STD-726H

NOTICE 2

TABLE VII. Unit and Intermediate Container Codes  
 (Digit Positions 12 & 13 or 15 & 16)  
 (PCAM Columns 58, 59 or 61, 62, MIL-STD-834) (see 5.7 or 5.9) (Continued).

| Code | Container                                                                                        | Weight<br>lbs/sq. in. | Wall<br>Thickness<br>(Inch) |
|------|--------------------------------------------------------------------------------------------------|-----------------------|-----------------------------|
| MY   | Naval Aviation Supply Office Dwg. No. 15024, for shipping and storage of gyroscopic instruments. |                       |                             |
| NO   | PPP-B-636, variety double wall, grade V11C.                                                      | 0.026                 |                             |
| NP   | PPP-B-636, variety double wall, grade V13c.                                                      | 0.026                 |                             |
| NQ   | PPP-B-636, variety double wall, grade V15c.                                                      | 0.026                 |                             |
| NR   | PPP-B-1672, vertical star pack, type I, includes internal cushioning.                            | 0.001                 |                             |
| NS   | PPP-B-1672, folded convoluted pack, type II, includes internal cushioning.                       | 0.0004                |                             |
| NT   | PPP-B-636, type CF or type SF, class domestic, style FTC.                                        | 0.014                 |                             |
| NU   | PPP-B-636, type CF or type SF, class weather resistant, style FTC.                               | 0.015                 |                             |
| NV   | PPP-B-1672, telescoping encapsulated pack, type III, includes internal cushioning.               |                       |                             |
| NW   | PPP-B-1672, horizontal star pack type IV, includes internal cushioning.                          |                       |                             |
| NY   | Naval Aviation Supply Office Dwg. No. P069, molded, reusable for circuit cards and modules.      |                       |                             |
| NZ   | Naval Aviation Supply Office Dwg. No. 13414, modular, reusable, for packaging major repairables. |                       |                             |

Code 00 changed to Code 00 and transferred to first listing of Table VII.

MIL-STD-726H  
 31 JULY 1985

TABLE VII. Unit and Intermediate Container Codes  
 (Digit Positions 12 & 13 or 15 & 16)  
 (PCAM Columns 58, 59 or 61, 62, MIL-STD-834) (see 5.7 or 5.9) (Continued).

| Code | Container                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Weight<br>lbs/sq. in. | Wall<br>Thickness<br>(Inch) |
|------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|-----------------------------|
| PK   | MIL-P-9902 demountable box, type II, class 1, style A; PPP-B-601, box, wood, cleated-plywood, overseas type, PPP-B-621; box wood, nailed, class 2 or PPP-B-640, fiberboard box, triple-wall, class 2. Provide with nominal 2"x4" skids. See box specifications for weight limitations. The packaged item shall be centered and cushioned on all surfaces between the unit package and the shipping container with cushioning conforming to PPP-C-1120, type III or IV, class C; PPP-C-1752, PPP-C-850, type I, MIL-P-26514 or MIL-R-20092, type II, class 4 as required. Close, seal and reinforce the fiberboard boxes in accordance with the appendix to the box specification. Steel banding is not permitted. Wood and plywood boxes shall have top panels secured with wood screws and boxes banded. The top, one side and one end of the box shall be marked "REUSABLE CONTAINER AND CUSHIONING-USE FOR RETURN OF NRFI ASSEMBLY." Black letters, minimum 2" high. In addition, mark box, "TO OPEN - USE SCREW DRIVER," minimum 1" high. |                       |                             |
| RS   | PPP-P-704, type I, 5 gallon, tight head, steel shipping pail.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                       |                             |
| RT   | PPP-P-704, type II, steel shipping pails (1 through 12 gallons), lug cover.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                       |                             |
| RU   | PPP-D-705, type III, steel shipping drum, full removable lug cover.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | 0.01430               |                             |
| W1   | PPP-T-495, tubes, mailing and filing, styles A or B.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                       |                             |
| W2   | PPP-T-495, style C.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                       |                             |

MIL-STD-726H  
 NOTICE 2

TABLE XII. Maximum Code Cubes (Digit Positions 20 & 21)  
 (PCAM Columns 66, 67, MIL-STD-834) (See 5.11 and 5.11.3.2) (Continued).

| Cubic feet | Code | Cubic feet | Code | Cubic feet | Code | Cubic feet                       | Code | Cubic feet                                     | Code |
|------------|------|------------|------|------------|------|----------------------------------|------|------------------------------------------------|------|
| 7,150      | MV   | 7,890      | NC   | 8,710      | NH   | 9,620                            | NN   | Packager's<br>option<br>Special<br>requirement | YY   |
| 7,290      | MW   | 8,050      | ND   | 8,890      | NJ   | 9,810                            | NP   |                                                | ZZ   |
| 7,440      | MX   | 8,210      | NE   | 9,060      | NK   | 10,000                           | NQ   |                                                |      |
| 7,580      | NA   | 8,370      | NF   | 9,240      | NL   | No<br>established<br>requirement | *ØØ  |                                                |      |
| 7,750      | NB   | 8,540      | NG   | 9,430      | NM   |                                  |      |                                                |      |

\* Changed from 00 to ØØ

MIL-STD-726H  
 NOTICE 2

TABLE XIIa. Maximum Cube Codes (Digit Positions 20 & 21)  
 (PCMA Columns 66, 67, MIL-STD-834) (See 5.11 and 5.11.3.2)  
 (Table lists codes in alphanumeric order).

| Code | Cubic feet | Cubic inches | Code | Cubic feet | Cubic inches | Code | Cubic feet | Cubic inches |
|------|------------|--------------|------|------------|--------------|------|------------|--------------|
| AA   | 0.003      | 2.5          | AJ   | 0.115      | 200          | AS   | 0.579      | 1,000        |
| AB   | 0.003      | 5            | AK   | 0.174      | 300          | AT   | 0.636      | 1,100        |
| AC   | 0.009      | 15           | AL   | 0.231      | 400          | AU   | 0.706      | 1,210        |
| AD   | 0.017      | 30           | AM   | 0.289      | 500          | AV   | 0.779      | 1,330        |
| AE   | 0.029      | 50           | AN   | 0.347      | 600          | AW   | 0.845      | 1,460        |
| AF   | 0.046      | 80           | AP   | 0.405      | 700          | AX   | 0.926      | 1,600        |
| AG   | 0.069      | 120          | AQ   | 0.463      | 800          |      |            |              |
| AH   | 0.087      | 150          | AR   | 0.521      | 900          |      |            |              |

| Code | Cubic feet | Code | Cubic feet | Code | Cubic feet | Code | Cubic feet | Code | Cubic feet |
|------|------------|------|------------|------|------------|------|------------|------|------------|
| A1   | 2.10       | BX   | 5.00       | CW   | 23.30      | DV   | 64.80      | EK   | 116        |
| A2   | 2.30       | B1   | 3.70       | CX   | 24.40      | DW   | 68.10      | EL   | 122        |
| A3   | 2.50       | B2   | 3.80       | C1   | 4.90       | DX   | 71.50      | EM   | 128        |
| A4   | 2.70       | B3   | 4.00       | C2   | 5.10       | D1   | 6.10       | EN   | 135        |
| A5   | 2.90       | B4   | 4.10       | C3   | 5.20       | D2   | 6.20       | EP   | 142        |
| A6   | 3.10       | B5   | 4.30       | C4   | 5.30       | D3   | 6.30       | EQ   | 148        |
| A7   | 3.20       | B6   | 4.40       | C5   | 5.40       | D4   | 6.40       | ER   | 156        |
| A8   | 3.40       | B7   | 4.50       | C6   | 5.60       | D5   | 6.50       | ES   | 164        |
| A9   | 3.50       | B8   | 4.70       | C7   | 5.70       | D6   | 6.70       | ET   | 172        |
| BA   | 1.00       | B9   | 4.80       | C8   | 5.80       | D7   | 6.80       | EU   | 181        |
| BB   | 1.10       | CA   | 5.50       | C9   | 5.90       | D8   | 6.90       | EV   | 190        |
| BC   | 1.20       | CB   | 6.00       | DA   | 25.70      | D9   | 7.00       | EW   | 199        |
| BD   | 1.30       | CC   | 6.60       | DB   | 26.90      | E1   | 7.10       | EX   | 209        |
| BE   | 1.40       | CD   | 7.20       | DC   | 28.30      | E2   | 7.40       | FA   | 220        |
| BF   | 1.50       | CE   | 7.90       | DD   | 29.70      | E3   | 7.50       | FB   | 230        |
| BG   | 1.60       | CF   | 8.70       | DE   | 31.20      | E4   | 7.60       | FC   | 242        |
| BH   | 1.70       | CG   | 9.50       | DF   | 32.70      | E5   | 7.70       | FD   | 254        |
| BJ   | 1.80       | CH   | 10.40      | GG   | 34.40      | E6   | 7.80       | FE   | 267        |
| BK   | 1.90       | CJ   | 11.40      | DH   | 36.10      | E7   | 8.00       | FF   | 280        |
| BL   | 2.00       | CK   | 12.50      | DJ   | 37.90      | E8   | 8.10       | FG   | 294        |
| BM   | 2.20       | CL   | 13.70      | DK   | 39.80      | E9   | 8.20       | FH   | 309        |
| BN   | 2.40       | CM   | 15.00      | DL   | 41.80      | EA   | 75.00      | FJ   | 324        |
| BP   | 2.60       | CN   | 15.80      | DM   | 43.90      | EB   | 78.80      | FK   | 340        |
| BQ   | 2.80       | CP   | 16.50      | DN   | 46.10      | EC   | 82.70      | FL   | 358        |
| BR   | 3.00       | CQ   | 17.40      | DP   | 48.46      | ED   | 86.90      | FM   | 375        |
| BS   | 3.30       | CR   | 18.20      | DQ   | 50.80      | EE   | 91.20      | FN   | 394        |
| BT   | 3.60       | CS   | 19.10      | DR   | 53.30      | EF   | 95.80      | FP   | 414        |
| BU   | 3.90       | CT   | 20.10      | DS   | 56.00      | EG   | 100        | FQ   | 435        |
| BV   | 4.20       | CU   | 21.10      | DT   | 58.80      | EH   | 106        | FR   | 456        |
| BW   | 4.60       | CV   | 22.20      | DU   | 61.70      | EJ   | 111        | *FS  | 479        |

\* Changed

MIL-STD-726H  
 NOTICE 2

TABLE XIIa. Maximum Cube Codes (Digit Positions 20 & 21)  
 (PCMA Columns 66, 67, MIL-STD-834) (See 5.11 and 5.11.3.2)  
 (Table lists codes in alphanumeric order) (continued).

| Code | Cubic<br>feet | Code | Cubic<br>feet | Code | Cubic<br>feet | Code | Cubic<br>feet | Code | Cubic<br>feet |
|------|---------------|------|---------------|------|---------------|------|---------------|------|---------------|
| 4R   | 244           | 6P   | 381           | 8M   | 543           | 10   | 653           | 56   | 805           |
| 4S   | 246           | 6Q   | 384           | 8N   | 547           | 11   | 655           | 57   | 813           |
| 4T   | 248           | 6R   | 388           | 8P   | 549           | 12   | 657           | 58   | 817           |
| 4U   | 250           | 6S   | 391           | 8Q   | 551           | 13   | 660           | 59   | 821           |
| 4V   | 252           | 6T   | 398           | 8R   | 553           | 14   | 622           | 60   | 823           |
| *4W  | 256           | 6U   | 401           | 8S   | 555           | 15   | 666           | 61   | 830           |
| 4X   | 258           | 6V   | 404           | 8T   | 558           | 16   | 668           | 62   | 833           |
| 4Y   | 260           | 6W   | 407           | 8U   | 560           | 17   | 670           | 63   | 837           |
| 4Z   | 263           | 6X   | 411           | 8V   | 562           | 18   | 673           | 64   | 840           |
| 5A   | 265           | 6Y   | 417           | 8W   | 564           | 19   | 675           | 65   | 846           |
| 5B   | 269           | 6Z   | 421           | 8X   | 566           | 20   | 679           | 66   | 849           |
| 5C   | 271           | 7A   | 424           | 8Y   | 569           | 21   | 681           | 67   | 853           |
| 5D   | 273           | 7B   | 427           | 8Z   | 571           | 22   | 683           | 68   | 856           |
| 5E   | 275           | 7C   | 431           | 9A   | 573           | 23   | 685           | 69   | 862           |
| 5F   | 277           | 7D   | 438           | 9B   | 575           | 24   | 687           | 70   | 866           |
| 5G   | 283           | 7E   | 441           | 9C   | 577           | 25   | 693           | 71   | 869           |
| 5H   | 285           | 7F   | 444           | 9D   | 580           | 26   | 696           | 72   | 873           |
| 5J   | 287           | 7G   | 447           | 9E   | 582           | 27   | 698           | 73   | 880           |
| 5K   | 289           | 7H   | 451           | 9F   | 584           | 28   | 701           | 74   | 883           |
| 5L   | 292           | 7J   | 460           | 9G   | 586           | 29   | 707           | 75   | 887           |
| 5M   | 297           | 7K   | 464           | 9H   | 588           | 30   | 710           | 76   | 890           |
| 5N   | 300           | 7L   | 468           | 9J   | 592           | 31   | 713           | 77   | 897           |
| 5P   | 302           | 7M   | 472           | 9K   | 594           | 32   | 716           | 78   | 901           |
| 5Q   | 303           | 7N   | 476           | 9L   | 596           | 33   | 722           | 79   | 904           |
| 5R   | 306           | 7P   | 484           | 9M   | 598           | 34   | 725           | 80   | 908           |
| 5S   | 312           | 7Q   | 488           | 9N   | 600           | 35   | 728           | 81   | 914           |
| 5T   | 315           | 7R   | 492           | 9P   | 603           | 36   | 730           | 82   | 918           |
| 5U   | 318           | 7S   | 496           | 9Q   | 605           | 37   | 736           | 83   | 922           |
| 5V   | 321           | 7T   | 500           | 9R   | 607           | 38   | 739           | 84   | 926           |
| 5W   | 323           | 7U   | 505           | 9S   | 610           | 39   | 742           | 85   | 934           |
| 5X   | 327           | 7V   | 507           | 9T   | 612           | 40   | 745           | 86   | 937           |
| 5Y   | 331           | 7W   | 509           | 9U   | 615           | 41   | 751           | 87   | 941           |
| 5Z   | 334           | 7X   | 511           | 9V   | 617           | 42   | 754           | 88   | 944           |
| 6A   | 337           | 7Y   | 512           | 9W   | 619           | 43   | 757           | 89   | 952           |
| 6B   | 339           | 7Z   | 515           | 9X   | 620           | 44   | 760           | 90   | 955           |
| 6C   | 343           | 8A   | 517           | 9Y   | 624           | 45   | 766           | 91   | 959           |
| 6D   | 347           | 8B   | 519           | 9Z   | 628           | 46   | 769           | 92   | 962           |
| 6E   | 349           | 8C   | 521           | 01   | 630           | 47   | 772           | 93   | 965           |
| 6F   | 352           | 8D   | 523           | 02   | 632           | 48   | 775           | 94   | 972           |
| 6G   | 356           | 8E   | 526           | 03   | 634           | 49   | 781           | 95   | 976           |
| 6H   | 361           | 8F   | 528           | 04   | 636           | 50   | 784           | 96   | 979           |
| 6J   | 364           | 8G   | 530           | 05   | 640           | 51   | 787           | 97   | 983           |
| 6K   | 368           | 8H   | 532           | 06   | 642           | 52   | 790           | 98   | 992           |
| 6L   | 370           | 8J   | 536           | 07   | 644           | 53   | 796           | 99   | 998           |
| 6M   | 373           | 8K   | 538           | 08   | 646           | 54   | 799           |      |               |
| 6N   | 378           | 8L   | 540           | 09   | 649           | 55   | 802           |      |               |

\*Changed

Supersedes page 85 of MIL-STD-726H

MIL-STD-726H  
 NOTICE 2

TABLE XIII. Level of Packing Codes (Digit Positions 24, 25, 26)  
(See 4.8.2 and 5.12).

| Code | Requirement                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
|------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| A    | Packing shall be accomplished using fiberboard boxes, weather resistant class; conforming to PPP-B-636 or triple-wall, corrugated fiberboard boxes, class 2, conforming to PPP-B-640.                                                                                                                                                                                                                                                                                   |
| *B   | Packing shall be accomplished using paper overlaid, veneer, cleated, wood boxes, class 2, conforming to PPP-B-576, or wirebound wood boxes, class 3 conforming to PPP-B-585 or wood-cleated, fiberboard boxes, class 2, conforming to PPP-B-591.                                                                                                                                                                                                                        |
| C    | Packing shall be accomplished using cleated-plywood, wood boxes, grade A of PPP-B-601 or nailed and lock-corner, wood boxes, class 2, conforming to PPP-B-621 or covered, wood crates, style A or B, conforming to MIL-C-52950 or lumber and plywood sheathed, wood crates, conforming to MIL-C-104 or steel or aluminum, slotted angle crates, type I, conforming to MIL-C-9897 or load-bearing base, skidded, wood-cleated boxes, type II, conforming to MIL-B-26195. |
| D    | Packing shall be accomplished using open wood crates, conforming to MIL-C-3774 or steel or aluminum, slotted angle crates, type I, conforming to MIL-C-9897 or open wood crates, type A or B open, conforming to MIL-C-52950.                                                                                                                                                                                                                                           |
| E    | Packing shall be accomplished in accordance with MIL-STD-794, table I as specified for Level A. Closure, sealing and reinforcement shall be in accordance with applicable specification for shipping container.                                                                                                                                                                                                                                                         |
| F    | Packing is not required; the unit container shall also serve as the shipping container. Closure sealing and reinforcement shall be in accordance with applicable specification for shipping containers.                                                                                                                                                                                                                                                                 |
| G    | Packing shall be accomplished in accordance with requirements in the applicable commodity of procedural packaging/packing specification for Level A.                                                                                                                                                                                                                                                                                                                    |
| H    | Packing shall be in accordance with MIL-STD-794 using weather resistant boxes. Boxes conforming to PPP-B-636, special requirements, shall be used up to size and weight limitation. When size and weight are exceeded, a suitable container shall be selected from table I.                                                                                                                                                                                             |

\* Changed

MIL-STD-726H  
 31 JULY 1985

TABLE XIII. Level of Packing Codes (Digit Positions 24, 25, 26)  
(See 4.8.2 and 5.12) (Continued).

| Code | Requirement                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |
|------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| U    | <p>Items or packages that require packing for acceptance by the carrier shall be packed in exterior type shipping containers in a manner that will ensure safe transportation at the lowest rate to the point of delivery and shall meet, as a minimum, the requirements of the following rules and regulations, as applicable to the mode(s) of transportation to be utilized:</p> <ul style="list-style-type: none"> <li>(a) Postal Regulations</li> <li>(b) Department of Transportation Regulations</li> <li>(c) Civil Air Regulations</li> <li>(d) Uniform Freight Classification Rules</li> <li>(e) National Motor Freight Classification Rules</li> <li>(f) American Truckers' Association Rules</li> <li>(g) Other applicable carriers' rules</li> <li>(h) Military Air Regulations for dangerous materials</li> </ul> <p>Consolidation of Shipments - All exterior packs of 1.5 cubic feet or less, having no single dimension (length, width, height) exceeding 40 inches (and when the total number of such containers in any individual shipment exceeds 25), shall be consolidated, using flat pallets, box pallets or containers as the consolidating media.</p> <p>Hazardous Material Shipment - By military air (including Logair and Quicktrans). Hazardous materials required to be shipped by military air or delivered to an airport of embarkation for shipment by military air shall be prepared for shipment according to provisions of AFR-71-4, DSAM 4145.3, TM38-250, NAVSUP Pub 505, MCO P4030.19, Packaging and Handling of Dangerous Materials for Transportation by Military Aircraft.</p> <p>Other than by military air - Dangerous materials required to be shipped by a mode of transportation other than military air shall be prepared for shipment according to applicable Department of Transportation (DOT) Regulations in effect at time of shipment. Shipments by parcel post must comply with Postal Regulations.</p> |

MIL-STD-726H  
 NOTICE 2

TABLE XIII. Level of Packing Codes (Digit Positions 24, 25, 26)  
(See 4.8.2 and 5.12) (Continued).

| Code | Requirement                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| L    | Packing shall be accomplished using fiberboard boxes conforming to PPP-B-636, class domestic or PPP-B-640, class 1.                                                                                                                                                                                                                                                                                                                                                                                                                               |
| *M   | Packing shall be accomplished using paper overlaid, cleated, wood boxes, class 1, conforming to PPP-B-576 or wirebound wood boxes, class 1, conforming to PPP-B-585 or wood-cleated fiberboard boxes, class 1, conforming to PPP-B-591 or load-bearing base, skidded, wood-cleated boxes, type I, conforming to MIL-B-26195.                                                                                                                                                                                                                      |
| N    | Packing shall be accomplished using cleated-plywood, wood boxes, domestic type, conforming to PPP-B-601 or nailed and lock-corner, wood boxes, class 1, conforming to PPP-B-621 or covered wood crates style A or B (sheathed) domestic class conforming to MIL-C-52950 or nailed and bolted, sheathed, lumber and plywood, wood crates, non-weather resistant/domestic class, conforming to MIL-C-104 or for lightweight airframe components and bulky items, steel or aluminum, slotted angle crates, domestic class, conforming to MIL-C-9897. |
| P    | Packing shall be accomplished using open wood crates, non-weather resistant/domestic class, style A or B conforming to MIL-C-52950 or open wood crates non-weather resistant/domestic class conforming to MIL-C-3774 or for lightweight airframe, steel or aluminum, slotted angle, crates, type I, domestic class, conforming to MIL-C-9897.                                                                                                                                                                                                     |
| Q    | Packing shall be accomplished in accordance with MIL-STD-794, Table II as specified. Closure sealing and reinforcement shall be in accordance with applicable specifications for shipping containers.                                                                                                                                                                                                                                                                                                                                             |
| R    | Packing shall be accomplished in accordance with the requirements in the applicable commodity or procedural packaging/packing specification for Level B.                                                                                                                                                                                                                                                                                                                                                                                          |
| S    | Packing shall be accomplished in accordance with the requirements in MIL-STD-794, table II using domestic class. Boxes conforming to PPP-B-636, special requirements, shall be used up to size and weight limitations. When size and weight are exceeded, a suitable container shall be selected from table I or MIL-STD-794.                                                                                                                                                                                                                     |
| T    | Packing shall be accomplished by use of fiberboard containers conforming to weather-resistant class of PPP-B-636 or PPP-B-640; or whenever practicable by means of shrink-film conforming to L-P-378, type 4.                                                                                                                                                                                                                                                                                                                                     |

\* Changed

MIL-STD-726H  
 NOTICE 2

TABLE XIII. Level of Packing Codes (Digit Positions 24, 25, 26)  
(See 4.8.2 and 5.12) (Continued).

| Code | Requirement                                                                                                                                                                                                                                                          |
|------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| X    | Packing shall be accomplished in accordance with ASTM D3951.                                                                                                                                                                                                         |
| Y    | Packager's option, provided all other contractual requirements are met.                                                                                                                                                                                              |
| Z    | Special requirement. See specific instructions or drawings provided.                                                                                                                                                                                                 |
| 2    | Packing shall be accomplished using cleated-plywood boxes, overseas type conforming to PPP-B-601 or nailed wood boxes conforming to PPP-B-621, class 2, style 4.                                                                                                     |
| *3   | Packing shall be accomplished using cleated-plywood boxes, overseas type, conforming to PPP-B-601 or nailed wood boxes conforming to PPP-B-621, class 2, style 4 or wirebound wood boxes conforming to PPP-B-585, class 3, style 2 or 3.                             |
| *5   | Packing shall be accomplished using cleated-plywood boxes, domestic type, conforming to PPP-B-601 or nailed wood boxes conforming to PPP-B-621, class 1, style 4 or wirebound wood boxes conforming to PPP-B-585, class 2, style 2 or 3.                             |
| 6    | Packing shall be in accordance with the requirements of the applicable commodity or procedural packing specification for level C.                                                                                                                                    |
| *7   | Packing shall be accomplished using cleated-plywood boxes, domestic type, conforming to PPP-B-601 or nailed wood boxes conforming to PPP-B-621, class 1, style 4, or fiberboard boxes conforming to PPP-B-640, class 2, style E or PPP-B-585, class 3, style 2 or 3. |
| **8  | Packing shall be accomplished in accordance with MIL-E-55585.                                                                                                                                                                                                        |
| **9  | Packing shall be accomplished in accordance with MIL-STD-1190.                                                                                                                                                                                                       |
| **Ø  | Packing not authorized.                                                                                                                                                                                                                                              |

\* Changed  
 \*\* Added

MIL-STD-726H  
 NOTICE 2

TABLE XIV. Special Marking Codes (Digit Positions 27 & 28)  
(PCAM Columns 44, 45, MIL-STD-834) (See 5.13).

| Code | Explanation of Code              | Code | Explanation of Code                                                                                                             |
|------|----------------------------------|------|---------------------------------------------------------------------------------------------------------------------------------|
| ZZ   | Special requirements             | 20   | Do not bend                                                                                                                     |
| 01   | Fragile                          | 21   | Do not sling                                                                                                                    |
| 02   | Arrow up                         | 23   | Perishable biologicals, do not freeze                                                                                           |
| 03   | Method II                        | 24   | Open for inspection or use only                                                                                                 |
| 04   | Fragile, Arrow up and Method II  | 25   | Box _____ of _____                                                                                                              |
| 05   | Delicate instrument              | 26   | Load bearing area                                                                                                               |
| 06   | Delicate instrument and arrow up | 28   | Do not drop or throw                                                                                                            |
| 07   | Glass - do not drop              | 29   | Do not hump                                                                                                                     |
| 08   | Keep dry                         | 30   | Top heavy                                                                                                                       |
| 09   | Perishable - Keep frozen         | 31   | Center of gravity                                                                                                               |
| 10   | Keep at 40 degree temperature    | 32   | Type I, shelf life                                                                                                              |
| 11   | Sling Point                      | 33   | Type II, shelf life                                                                                                             |
| 12   | Fragile, Method II               | 34   | Manufacturer's part number                                                                                                      |
| 13   | Open this side                   | 36   | Fragile, arrow up, and glass                                                                                                    |
| 14   | Center of balance                | 37   | Fragile, arrow up                                                                                                               |
| 15   | Use no hooks                     | *39  | Sensitive electronic device requirements of MIL-STD-129 (Appendix C, 20.30) apply                                               |
| 16   | Top                              | 40   | Omission of marking for sensitive, controlled or pilferable items per MIL-STD-129                                               |
| 17   | Reusable container               | **50 | Marking shall be accomplished in accordance with the marking requirements in the applicable commodity specification             |
| 18   | Remove top first                 | **51 | Marking shall be accomplished in accordance with the marking requirements in the applicable procedural packaging specification. |
| 19   | Method II reusable container     | 99   | No codes in this table apply; only MIL-STD-129 markings apply                                                                   |

6. NOTES

6.1 Intended use. The position and sequence data code system established in this standard is to be used for expressing the essential elements of the required preservation and packing methods for acquired Department of Defense items. The purpose of the code system is to present a convenient form of storing and being manipulated by electronic data processing methods or by manual means. The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

\* Changed

\*\* Added

Supersedes page 90 of MIL-STD-726H

MIL-STD-726H  
 NOTICE 2

APPENDIX A

CROSS REFERENCE INDEX

10. SCOPE

10.1 This index lists the table(s) and code(s) that each document is referenced in.

| <u>Document No.</u> | <u>Table</u>             | <u>Code</u>                                                                             |
|---------------------|--------------------------|-----------------------------------------------------------------------------------------|
| L-P-378             | IIc<br>VI<br>VII<br>XIII | BG, DB, DC, DD, DG, GY, GZ<br>JA<br>A3, B7, WQ<br>T                                     |
| O-M-232             | IV                       | C                                                                                       |
| FF-N-105            | IIb                      | 52                                                                                      |
| NN-P-530            | VIa                      | LP                                                                                      |
| QQ-A-1876           | VI                       | BA                                                                                      |
| RR-C-271            | IIb                      | D7                                                                                      |
| UU-B-23             | VII                      | 12                                                                                      |
| UU-B-36             | VII                      | AN                                                                                      |
| UU-C-282            | VIa                      | HA, HB, HC, HD, HE, HF, HG, HH, HJ, HK, HL, HM                                          |
| UU-P-268            | VI<br>VII                | CA, CB, CC, CD, CE, CF<br>WP                                                            |
| UU-P-553            | VI                       | DA, DB, DC                                                                              |
| VV-L-800            | V                        | Ø9                                                                                      |
| MMM-A-260           | IIc                      | AW                                                                                      |
| NNN-P-40            | VI                       | LA                                                                                      |
| PPP-B-20            | VII                      | AA                                                                                      |
| PPP-B-35            | VII                      | AH, AJ, AK, AL                                                                          |
| PPP-B-140           | IIb                      | 2Ø                                                                                      |
| PPP-B-566           | IIc<br>VIa               | CE, DX, EA, EB<br>BB, BE, BH, DB, FC, FF, FJ, FM, HE, HF, HG, HH,<br>JD, JE, JF, NU, NV |
| *PPP-B-576          | VII<br>XIII              | CT, CU, CV, D1, D2, D3, D6, D7, DA<br>F1, FK, FL, FM, ML**<br>B, M                      |
| **PPP-B-585         | XIII                     | B, M, 3, 5, 7                                                                           |
| PPP-B-591           | VII<br>XIII              | DU, DV, DW<br>B, M, 5                                                                   |
| PPP-B-601           | IIc<br>VII<br>XIII       | JM<br>F1, F2, F3, F4, F6, F7, FD, FF, FG, FH, PK<br>C, N, 2, 3, 4, 5, 7                 |
| *PPP-B-621          | IIc<br>VII               | AQ<br>EX, EY, F2, F3, F7, F9, FA, FB, FC, ME**, MS**,<br>PK                             |
|                     | XIII                     | C, N, 2, 3, 4, 5, 7                                                                     |

\* Changed

\*\* Added

Code BL, Table VII, L-P-378 deleted

MIL-STD-726H  
 NOTICE 2

| <u>Document No.</u> | <u>Table</u>                                            | <u>Code</u>                                                                                                                                                                                                                                                                                                        |
|---------------------|---------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| *PPP-B-636          | IIC<br>VIa<br><br>VII<br><br>XIII<br>VIa<br>VII<br>XIII | AL, AP, CH, CM, DR, DS, DW, EL, GV, JU**, KD**<br>BC, BF, BJ, DC, EC, EQ, ET, EW, EZ, FD, FG, FK,<br>FN, HJ, HK, HL, HM, JG, JH, JJ, LX, ND, NR<br>BM**, BN**, CV, D3, E1, E2, E3, E4, E5, E7, E8,<br>E9, EB, EC, ED, EE, EF, EG, EN, EP, EQ, ER, ES,<br>ET, EU, EW, KA, NO, NP, NQ, NT, NU<br>A, H, L, S, T<br>JQ |
| *PPP-B-640          | VIa<br>VII<br>XIII                                      | BC**, BP**, DP, DQ, DR, PK<br>A, L, T, 7                                                                                                                                                                                                                                                                           |
| PPP-B-665           | VII                                                     | CU, CV, CW, D2, D3, DJ                                                                                                                                                                                                                                                                                             |
| PPP-B-676           | IIC<br>VIa<br><br>VII                                   | CE, DX, EA, EB<br>BH, DB, EA, FC, FF, FJ, FM, HE, HF, HH, JD, JE,<br>JF, NU, NV<br>D1, D2, D3, D6, D7, DE                                                                                                                                                                                                          |
| PPP-B-1055          | IIC<br>VI<br>VII                                        | AW<br>HC<br>EV                                                                                                                                                                                                                                                                                                     |
| PPP-B-1364          | VII                                                     | JW, KB, KE                                                                                                                                                                                                                                                                                                         |
| *PPP-B-1672         | IIC<br>VII                                              | NR, NS, NV, NW                                                                                                                                                                                                                                                                                                     |
| PPP-B-1806          | VII                                                     | CA                                                                                                                                                                                                                                                                                                                 |
| PPP-C-96            | VII                                                     | HA, HB, HC, HD, HE, HF, HG, HH, HJ, HK, JH, JJ,<br>JK, JL, JM, JN                                                                                                                                                                                                                                                  |
| *PPP-C-795          | IIC<br>VI<br>VIa                                        | DB, DC, GX, GY, GZ, JK, JW**<br>JB, JW, JX, N1, N2, N3, PA<br>LC, LD, LR, LS, LT, LU, LV, LX, LW, NA, ND, NU                                                                                                                                                                                                       |
| PPP-C-843           | IIC<br>VIa                                              | AC, AN, KD**<br>BA, BB, BC, BE, BF, BH, BJ                                                                                                                                                                                                                                                                         |
| PPP-C-850           | VIa<br>VII                                              | BL, BN<br>PK                                                                                                                                                                                                                                                                                                       |
| *PPP-C-1120         | VIa                                                     | EM, EN, EQ, ER, ET, EU, EW, EZ, FA, FB, FC, FD,<br>FE, FF, FG, FH, FJ, FK, FL, FM, FN, FP, FQ**,<br>FR**, FT**, JP**                                                                                                                                                                                               |
|                     | VII                                                     | PK                                                                                                                                                                                                                                                                                                                 |
| *PPP-C-1752         | IIC<br>VIa<br>VII                                       | GX, JK<br>GA, GP, HN, NA, ND, NU, NX**<br>PK                                                                                                                                                                                                                                                                       |
| *PPP-C-1797         | IIC<br>VI<br>VIa                                        | GX, JK, JW**<br>N4, N5, N6, N7, PA<br>GT, GU, GV, GW, GY, NA, NB, ND, NU, NV, NW                                                                                                                                                                                                                                   |
| *PPP-C-1842         | IIC<br>VIa                                              | DB, DC, GX, GY, GZ, JK, JW**<br>NG, NA, ND, NB, NU, NV, NW                                                                                                                                                                                                                                                         |
| PPP-C-2020          | IIB                                                     | 23                                                                                                                                                                                                                                                                                                                 |
| PPP-D-705           | VII                                                     | RU                                                                                                                                                                                                                                                                                                                 |
| PPP-D-723           | VII                                                     | CF, CG, CH, CJ, CR                                                                                                                                                                                                                                                                                                 |
| *PPP-F-320          | IIC<br>VIa<br><br>VII                                   | JF, JM, KD**<br>JA, JB, JC, JD, JE, JF, JG, JH, JJ, JL, JM, JN,<br>LG, NR, NS, P2**, P3**<br>WS                                                                                                                                                                                                                    |

\* Changed

\*\* Added

MIL-STD-726H  
 NOTICE 2

| <u>Document No.</u> | <u>Table</u> | <u>Code</u>                                    |
|---------------------|--------------|------------------------------------------------|
| PPP-H-1581          | IIb          | 42                                             |
| PPP-P-40            | IIb          | 74                                             |
| PPP-P-291           | VI           | MA                                             |
|                     | VIa          | DA, DB, DC                                     |
|                     | VII          | WR                                             |
| PPP-P-704           | VII          | RS, RT                                         |
| PPP-P-1132          | IIb          | B6                                             |
| PPP-P-1133          | IIb          | B7                                             |
| PPP-P-1134          | IIb          | B8                                             |
| PPP-P-1135          | IIb          | B9                                             |
| PPP-P-1136          | IIb          | C1                                             |
| PPP-P-1892          | IIb          | 54                                             |
| PPP-S-30            | VII          | AC, AD, AE                                     |
| PPP-T-45            | IIC          | BJ                                             |
| PPP-T-60            | IIC          | AM, AU, AW, BA, BJ, DH, DR, JU**               |
|                     | VIa          | LJ                                             |
| PPP-T-76            | IIC          | AL, AW, CH, CM, DR, GV, JU**                   |
| PPP-T-360           | IIb          | A2                                             |
| PPP-T-495           | VIa          | EG                                             |
|                     | VII          | WM, W1, W2, W3                                 |
| MIL-V-3             | IIb          | 76                                             |
| MIL-T-4             | IIb          | 73                                             |
| MIL-E-75            | IIb          | 75                                             |
|                     | IIC          | FQ, FS, FT, FU, FV                             |
| *MIL-C-104          | VII          | BG, DS, DT, F7, GB, MA, MB, MC, MF, MG, MH     |
|                     | XIII         | C, N                                           |
| *MIL-P-116          | IIC          | JU**, JV**                                     |
| Method I            | II           | 11                                             |
|                     | IIa          | 6L, 6M                                         |
|                     | IIC          | AH, AJ, AK, AL, BC, BL, BN, DC, DH, DK, DN     |
| Method IA           | II           | 3Y                                             |
|                     | IIC          | AN, BD, DQ, JX, JY                             |
| Submethod IA-5      | II           | 3V                                             |
| Submethod IA-6      | II           | 3W                                             |
| Submethod IA-8      | II           | 3G                                             |
|                     | IIC          | AP, BA, BD, CG, DD, DX, GX, GY, GZ, JG, JH, JK |
| Submethod IA-13     | II           | 3T                                             |
|                     | IIa          | 6F                                             |
|                     | IIC          | AW                                             |
| Submethod IA-14     | II           | 3Q                                             |
|                     | IIC          | CH, JS                                         |
| Submethod IA-15     | II           | 3P                                             |
|                     | IIa          | 6F                                             |
|                     | IIC          | AW, CJ                                         |
| Submethod IA-16     | II           | 3H                                             |
|                     | IIC          | DT, DU                                         |

Methods IB, IB-1 and IB-2 deleted

\* Changed

\*\* Added

MIL-STD-726H  
 NOTICE 2

| <u>Document No.</u>           | <u>Table</u> | <u>Code</u>                                                            |
|-------------------------------|--------------|------------------------------------------------------------------------|
| * Method IC                   | II           | 2Y                                                                     |
|                               | IIC          | DP, DR, JZ**, KD**                                                     |
| * Submethod IC-1              | II           | 2E                                                                     |
|                               | IIC          | CE, DD, EL, GS, GZ, JR, JS, JT, KC**, KD**, KF**                       |
| Submethod IC-2                | II           | 2M                                                                     |
|                               | IIC          | JP                                                                     |
| Submethod IC-3                | II           | 2D                                                                     |
|                               | IIC          | EB, JL                                                                 |
| Submethod IC-4                | II           | 2S                                                                     |
| Submethod IC-7                | II           | 2A                                                                     |
| Submethod IC-9                | II           | 2B                                                                     |
| Submethod IC-10               | II           | 2C                                                                     |
| * Method II                   | II           | 4Y                                                                     |
|                               | IIC          | AR, JX**                                                               |
| Submethod IIa                 | II           | 4H                                                                     |
|                               | IIa          | 6P                                                                     |
|                               | IIC          | AQ, DV, GW                                                             |
| Submethod IIb                 | II           | 4Q                                                                     |
|                               | IIa          | 6Q                                                                     |
|                               | IIC          | AQ, CA, CM, DW, JT                                                     |
| Submethod IIc                 | II           | 4G                                                                     |
|                               | IIC          | DG, EA, JO                                                             |
| Submethod IId                 | II           | 4V                                                                     |
|                               | IIa          | 6P, 6Q, 6R                                                             |
|                               | IIC          | AQ, CB                                                                 |
| Submethod IIe                 | II           | 4P                                                                     |
|                               | IIC          | CP                                                                     |
| Submethod II f                | II           | 4T                                                                     |
|                               | IIa          | 6R                                                                     |
| * Method III                  | II           | 10                                                                     |
|                               | IIa          | 6L, 6M                                                                 |
|                               | IIC          | AE, AF, AG, AR, BM, CQ, DA, DB, EK, GV, JF, JM, JR, KA                 |
| Cleaning Procedures (C-types) | IV           | 1, 3, 5, 6, 7, 8, A, C, D, G, H, K, L, M, P, Q                         |
| * Preservatives               | IIb          | 76                                                                     |
|                               | IIC          | KF**                                                                   |
| (P-types)                     | V            | 01, 02, 03, 06, 07, 09, 10, 11, 12, 13, 15, 17, 18, 19, 20, 21, 83, AA |
| General Requirements          | VI           | AA                                                                     |
| *MIL-B-117                    | VIa          | AA, AC, AF                                                             |
|                               | IIC          | AW, AY, CQ, DC, DS, GS, GX, GY, GZ, JK, JU**, JV**, JW**, KE**         |
|                               | VII          | A1, A4, B1, B2, B3, B4, B7, B8, B9, BD, BE**, BL**, BR                 |
|                               |              | BS, BU, BV, BW, BX                                                     |
| *MIL-B-121                    | IIC          | AF, AJ, AU, BG, CE, CQ, DA, DH, DR, EB, EK, EL, KF**                   |
|                               | VI           | GA, GB, GC, GD, GE, GF, GG, GH, GK                                     |
|                               | VIa          | LG                                                                     |
|                               | VII          | A1, A3                                                                 |
| *MIL-P-130                    | IIC          | CQ, DA                                                                 |
|                               | VI           | FA, FB, FC, FD, GK                                                     |
|                               | VII          | A1                                                                     |

\* Changed \*\* Added  
 Codes BE, R1, BU, BX, Table VII, MIL-B-121 deleted  
 Supersedes page 94 of MIL-STD-726H, NOTICE 1

MIL-STD-726H  
 NOTICE 2

| <u>Document No.</u> | <u>Table</u> | <u>Code</u>                                          |
|---------------------|--------------|------------------------------------------------------|
| *MIL-B-131          | IIc<br>VI    | AN, AP, CG, DV, DW, DX, EA, JG<br>AB, GM, GN, GP     |
| *MIL-P-149          | IIc<br>V     | KF**<br>38                                           |
| MIL-V-173           | IIc          | AR                                                   |
| MIL-R-196           | IIb          | 34                                                   |
| MIL-B-197           | IIb<br>IIc   | 21<br>FA, FB, FC, FF, FG, FH, FJ, FK, FL, FM, FN, FP |
| MIL-B-208           | IIb          | 17                                                   |
| MIL-H-775           | IIb          | 47                                                   |
| MIL-F-2312          | VIa          | LB                                                   |
| MIL-P-2845          | IIb          | B5                                                   |
| MIL-C-3131          | IIb          | 25                                                   |
| MIL-L-3150          | V            | 07                                                   |
| MIL-B-3180          | IIb          | A5                                                   |
| MIL-P-3184          | IIb          | 26                                                   |
| MIL-H-3280          | IIb          | 45                                                   |
| MIL-P-3420          | V            | 18, 71, 72, 73                                       |
| MIL-C-3600          | IIb          | 94                                                   |
| MIL-P-3684          | IIb          | 30                                                   |
| MIL-C-3774          | VII<br>XIII  | MJ<br>D, P                                           |
| MIL-A-3816          | IIb          | 81                                                   |
| MIL-B-3865          | IIb          | B1                                                   |
| MIL-W-3903          | IIb          | D6                                                   |
| MIL-N-3944          | IIb<br>VIa   | 89<br>LF                                             |
| *MIL-C-3955         | VIa<br>VII   | LF<br>JC, JD, JE, JF, JG                             |
| MIL-C-3993          | IIb          | 28                                                   |
| MIL-C-4150          | VII          | KA, K1, WB                                           |
| MIL-S-4473          | IIc          | FT                                                   |
| MIL-P-4861          | IIb          | 53                                                   |
| MIL-R-5001          | VIa          | DD                                                   |
| MIL-C-5501          | IIc          | DR                                                   |
| MIL-C-5584          | VII          | KP, WB                                               |
| MIL-E-5607          | IIb          | 35                                                   |
| MIL-P-5610          | IIb          | 56                                                   |
| MIL-B-5806          | VII          | WU                                                   |
| MIL-D-6054          | VII          | K1, KE                                               |
| MIL-D-6055          | VII          | K1, KF                                               |
| MIL-E-6058          | IIb          | 36                                                   |
| MIL-P-6063          | IIb          | 19                                                   |
| MIL-P-6074          | IIb          | 66                                                   |
| MIL-L-6081          | V            | 32, 51                                               |
| MIL-L-6082          | V            | 53                                                   |
| MIL-H-6083          | V            | 92                                                   |
| MIL-L-6085          | V            | 17                                                   |
| MIL-R-6130          | VIa          | DF, DG                                               |

\* Changed

\*\* Added

MIL-STD-726H  
 NOTICE 2

| <u>Document No.</u> | <u>Table</u> | <u>Code</u>                                          |
|---------------------|--------------|------------------------------------------------------|
| MIL-C-6529          | V            | 31, 32                                               |
| MIL-L-7808          | V            | 33                                                   |
| MIL-L-7870          | V            | 50                                                   |
| MIL-C-8188          | V            | 52                                                   |
| MIL-L-8937          | V            | 30                                                   |
| MIL-B-9361          | VII          | WC                                                   |
| MIL-C-9897          | VII          | M1, M2, M3, M4                                       |
|                     | XIII         | C, D, N, P                                           |
| MIL-P-9902          | VII          | PK                                                   |
| MIL-M-9950          | IV           | E                                                    |
| MIL-C-9959          | IIC          | GW                                                   |
|                     | VII          | KB                                                   |
| MIL-E-10062         | IIB          | 37                                                   |
| MIL-W-10430         | IIB          | 78                                                   |
| MIL-P-10603         | IIB          | 67                                                   |
| MIL-G-10924         | V            | 13                                                   |
| MIL-C-11796         | V            | 06                                                   |
| MIL-C-12000         | IIB          | 22                                                   |
| MIL-S-12134         | IIB          | 97                                                   |
| MIL-R-12323         | IIB          | B4                                                   |
| MIL-C-16173         | V            | 01, 02, 03, 19, 21                                   |
| MIL-E-16298         | IIB          | 29                                                   |
| MIL-C-16555         | V            | 27, 28, 29                                           |
| MIL-P-16789         | IIB          | B3                                                   |
| *MIL-O-16898        | IIB          | 48                                                   |
|                     | IV           | B**                                                  |
| MIL-E-17555         | IIB          | 33                                                   |
| MIL-P-17667         | IIC          | AF, DA, CQ                                           |
|                     | VI           | EA, EB, EC, ED                                       |
|                     | VII          | A1                                                   |
| MIL-M-18058         | IIB          | 49                                                   |
| *MIL-L-19140        | VIa          | JR**                                                 |
|                     | VII          | BG**, BJ**, DS**, DT**, FH**, ME**, ML**, MS**, MP** |
| MIL-S-19491         | IIB          | 96                                                   |
|                     | IIC          | JK                                                   |
| MIL-P-19644         | VIa          | GC, GG, GZ, NR                                       |
| MIL-R-0020092       | VIa          | DH, DJ                                               |
|                     | VII          | PK                                                   |
| MIL-L-21260         | V            | 10, 57, 58, 59                                       |
| *MIL-B-22019        | IIC          | GS, KC**, KD**                                       |
|                     | V            | 18, 78                                               |
|                     | VI           | JL                                                   |
| *MIL-B-22020        | IIC          | GS, KC**                                             |
|                     | VII          | BT                                                   |
| *MIL-F-22191        | IIC          | DB, DC, DD, DS, DV, GY, GZ, JH, JL, JU**, JV**       |
|                     | VI           | JV                                                   |
| MIL-C-22235         | V            | 95                                                   |
| MIL-P-23199         | IIC          | AT, JN                                               |
| MIL-S-23665         | IIB          | C3                                                   |
| MIL-L-23699         | V            | 56                                                   |
| MIL-G-23827         | V            | 11                                                   |
| MIL-G-25537         | V            | 43                                                   |

\* Changed \*\* Added

MIL-P-14232 deleted

Supersedes page 96 of MIL-STD-726H, NOTICE 1

MIL-STD-726H  
 NOTICE 2

| <u>Document No.</u> | <u>Table</u> | <u>Code</u>                              |
|---------------------|--------------|------------------------------------------|
| MIL-P-25621         | IIb          | 70                                       |
| MIL-C-25731         | VII          | MW                                       |
| MIL-C-26094         | VII          | HU                                       |
| *MIL-B-26195        | VII          | FU, FV, FW, GB, MP**                     |
|                     | XIII         | C, M                                     |
| *MIL-P-26514        | IIc          | DD, DG, GY, GZ                           |
|                     | VIa          | GD, GE, GF, GH, GJ, GQ, GR, LE, NR, NS** |
|                     | VII          | PK                                       |
| MIL-S-28786         | IIb          | C8                                       |
| MIL-B-38721         | VII          | DC                                       |
| MIL-C-39028         | IIb          | A9                                       |
| MIL-R-39032         | IIb          | C2                                       |
|                     | IIc          | JK                                       |
| MIL-B-43666         | VII          | DB                                       |
| MIL-T-45542         | IIb          | A3                                       |
| MIL-V-45554         | IIb          | E3                                       |
| MIL-B-45997         | IIb          | A1                                       |
| MIL-L-46002         | V            | 20                                       |
| MIL-P-46093         | V            | 80                                       |
| MIL-P-46161         | VII          | GC                                       |
| MIL-H-46170         | V            | 15                                       |
| MIL-B-46176         | V            | 79                                       |
| MIL-C-52950         | VII          | MV, MX                                   |
|                     | XIII         | C, D, N, P                               |
| MIL-C-55330         | IIb          | C7                                       |
| MIL-C-55442         | IIb          | 27                                       |
| MIL-B-55521         | IIb          | 18                                       |
| MIL-M-55565         | IIb          | C4                                       |
| **MIL-E-55585       | XIII         | 8                                        |
| MIL-V-62038         | IIb          | E4                                       |
| MIL-G-81322         | V            | 12                                       |
| MIL-F-81334         | VIa          | AH                                       |
| MIL-G-81559         | IIb          | C6                                       |
| *MIL-B-81705        | IIc          | GX, JK, JW**, KB**, KE**                 |
|                     | VI           | K3, N8                                   |
| **MIL-P-81997       | IIc          | KB                                       |
| MIL-H-83282         | V            | 65                                       |
| *MIL-F-83671        | VIa          | GB, GK, GL, GM, MA**, MB**, MC**         |
| MIL-C-0083933(MR)   | V            | 26                                       |
| MIL-F-87090         | VIa          | AG, AJ                                   |
| *MIL-STD-129        | IIc          | BC, GS, GX, JK, JW**, KB**, KE**         |
|                     | XIV          | 39, 40, 99                               |
| MIL-STD-163         | IIb          | 71                                       |
| MIL-STD-281         | IIb          | A8                                       |
| MIL-STD-649         | IIb          | 15                                       |
| MIL-STD-758         | IIc          | DY                                       |
| MIL-STD-767         | IV           | N                                        |

\* Changed  
 \*\* Added

MIL-STD-726H  
NOTICE 2

THIS PAGE INTENTIONALLY LEFT BLANK

MIL-STD-726H  
NOTICE 2

| <u>Document No.</u> | <u>Table</u>                  | <u>Code</u>                    |
|---------------------|-------------------------------|--------------------------------|
| MIL-STD-794         | IIb<br>IIc<br>XIII            | C9, C5<br>DY<br>E, H, Q, S     |
| **MIL-STD-1169      | IIc                           | JX, JY, JZ, KA                 |
| *MIL-STD-1186       | VIa                           | AD, AE**, P1**                 |
| **MIL-STD-1190      | XIII                          | 9                              |
| MIL-STD-2073-1      | para 5.9a,<br>5.12a,<br>5.12b |                                |
| MS18011             | VII                           | LQ                             |
| MS90363             | IIc                           | FX, FY, GA, GB, GC, GP, GQ, GR |
| **ASTM D3951        | XIII                          | X                              |
| * Changed           |                               |                                |
| ** Added            |                               |                                |

MIL-STD-726H  
 NOTICE 2

APPENDIX B

DELETED, CHANGED AND RESTORED CODES

10. SCOPE

10.1 This appendix contains the deleted, changed and restored codes of MIL-STD-726. The revision and/or change notice of MIL-STD-726 is specified for each affected code to facilitate the location of the issue in which the action occurred.

10.2 The reason for the affected codes may be ascertained by referring to the specified revision or change notice.

10.3 Deleted Codes

| <u>Code</u>         | <u>Table</u> | <u>MIL-STD-726</u>   |
|---------------------|--------------|----------------------|
| 3U                  | II           | Rev. B, Change No. 1 |
| 2F, 2L, 3A          | II           | Rev. C, Change No. 1 |
| 12**, 1B**, 1Y**    | II           | Rev. H, Change No. 2 |
| 6G                  | IIa          | Rev. A               |
| 6A                  | IIa          | Rev. B, Change No. 1 |
| 3U, 3N              | IIa          | Rev. C, Change No. 1 |
| 6B, 6C, 6D, 6E, 6H  | IIa          | Rev. D               |
| 6K, 6N              | IIa          | Rev. D               |
| 41, 57, 78, 82      | IIb          | Rev. A               |
| 31                  | IIb          | Rev. A, Change No. 3 |
| 61                  | IIb          | Rev. B, Change No. 2 |
| 43, 44, 68, 72, 93  | IIb          | Rev. C               |
| 10, 11, 12          | IIb          | Rev. C, Change No. 2 |
| 69, 79              | IIb          | Rev. C, Change No. 3 |
| 85, 95              | IIb          | Rev. D               |
| 51                  | IIb          | Rev. F               |
| 24, 32, 38, 40, 46, | IIb          | Rev. G               |
| 50, 55, 62, 63, 64, |              |                      |
| 65, 86, 87, 91, A4, |              |                      |
| B2, D1, D2, D3, D4  | IIb          | Rev. H               |
| 16, 39, 59, 60, 63, |              |                      |
| 77, 80, 83, 84, 88, |              |                      |
| 90, 92, 98, 99, A6, |              |                      |
| B2, D8, D9, E1      |              |                      |
| **38                | IIb          | Rev. H, Change No. 2 |
| D5, E2, AV, AX      | IIc          | Rev. A               |
| AS                  | IIc          | Rev. A, Change No. 4 |
| BQ, CF              | IIc          | Rev. B, Change No. 1 |
| ED, EE, EF, EG, ES  | IIc          | Rev. C, Change No. 2 |
| CN, DG, DJ          | IIc          | Rev. C, Change No. 3 |
| CK, CL, CR          | IIc          | Rev. C, Change No. 5 |
| EC, EH              | IIc          | Rev. D               |
| DE, DF              | IIc          | Rev. F, Change No. 2 |

\*\* Added to the list of deletions



MIL-STD-726H  
 NOTICE 2

| <u>Code</u>         | <u>Table</u> | <u>MIL-STD-726</u>   |
|---------------------|--------------|----------------------|
| ME, ML, MP          | VII          | Rev. A, Change No. 4 |
| BC, MM, MS          | VII          | Rev. B               |
| KT                  | VII          | Rev. B, Change No. 1 |
| DS, DT              | VII          | Rev. C               |
| BG, BJ, BM, BN, BP  | VII          | Rev. C, Change No. 3 |
| D5                  | VII          | Rev. C, Change No. 4 |
| KL, KT, KU, N1, N2  | VII          | Rev. D               |
| N3, N4, N5, N6, N7, |              |                      |
| N8, N9, NA, NB, NC, |              |                      |
| ND, NE, NF, NG, NH, |              |                      |
| NJ, NK, NL, NM, NN, |              |                      |
| WF                  |              |                      |
| BF, BH              | VII          | Rev. E               |
| B5, FN              | VII          | Rev. F               |
| EM, JA, NX, RA, WT  | VII          | Rev. G               |
| AP, CB, CS, D8, D9, | VII          | Rev. H               |
| FE, FP, FQ, FR, FS, |              |                      |
| FT, FX, GA, HO, HP, |              |                      |
| HR, HQ, JP, KC,     |              |                      |
| KM, KN, KQ, KR, KS, |              |                      |
| LA, LB, LC, LD, LE  |              |                      |
| LF, LG, LH, LJ, LK, |              |                      |
| LL, LM, LN, LO, LP, |              |                      |
| LR, LS, LT, LU, LV, |              |                      |
| LW, LX, L1, L2, L3, |              |                      |
| L4, L5, MR, MT, PA, |              |                      |
| PB, PC, PD, PE, PF, |              |                      |
| PG, PH, PJ, P1, P2, |              |                      |
| P3, P4, P5, P6, P7, |              |                      |
| P8, P9, RD, RE, RF, |              |                      |
| RJ, RK, RL, RM, RN, |              |                      |
| RO, RI, R2, WE      |              |                      |
| B6**, BQ**          | VII          | Rev. H, Change No. 2 |
| WG                  |              |                      |
| Alpha 0             | VIII         | Rev. D               |
| C                   | IX           | Rev. F               |
| SA                  | VII          | Rev. F, Change No. 1 |
| K                   | XIII         | Rev. G               |
| 35, 38 40           | XIV          | Rev. G               |

10.4 Restored Codes

| <u>Code</u>         | <u>Table</u> | <u>MIL-STD-726</u>   |
|---------------------|--------------|----------------------|
| 38, 63              | I Ib         | Rev. G, Change No. 2 |
| CE, CG, CH, CM, DB, | I Ic         | Rev. G, Change No. 2 |
| FK, GV              |              |                      |
| JK**                | I Ic         | Rev. H, Change No. 1 |

\*\* Added to the list of deleted or restored codes

MIL-STD-726H  
 NOTICE 2

Code

CD, FD, GD, GG, GK,  
 JX, N1, N2, N3,  
 N4, N5, N6, N7  
 BC, BE, BF, BH, BJ,  
 DB, DC, EQ, ET, EW,  
 EZ, FC, FD, FF, FG,  
 FJ, FK, FM, FN, GJ,  
 GN, GQ, GR, GU, GV,  
 GW, GY, HE, HF, HG,  
 HH, HJ, HK, HL, HM,  
 JD, JE, JF, JG, JH,  
 JJ, LF, LS, LU, LV,  
 LX, MC, ME  
 AD, AE, AJ, AK, B1,  
 B2, B3, B4, B6, BQ,  
 BR, BS, BU, BV, BW,  
 BX, CR, E3, E4, E5,  
 E7, E9, EB, EF, EG,  
 EQ, ER, ES, EU, FE

\*\*10.5 Changed Codes

\*\*Code

\*\*76  
 AY, FM, GX\*\*  
 \*\*PA  
 \*\*FP, GK, GL, GM, NB  
 \*\*B1, BE, BL, BU, BX  
 \*\*FS

Table

VI

Via

VII

MIL-STD-726

Rev. G, Change No. 2

Rev. G, Change No. 2

Rev. G, Change No. 2

Table

IIb

IIc

VI

Via

VII

XIIa

MIL-STD-726

Rev. H, Change No. 2

Rev. H, Change No. 2

Rev. H, Change No. 2

Rev. H, Change No. 2

Rev. H, Change No. 2

Rev. H, Change No. 2

\*\* Added to the list of restored or changed codes

MIL-STD-726H  
NOTICE 2

Custodians:

\*Army - SM  
Navy - AS  
Air Force - 43  
DLA - ES

Preparing Activity:

Navy - AS  
(Project PACK-0762)

Review Activities:

\*Army - AT, AV, CR, GL  
Navy - EC, SA  
Air Force - 99  
\*DLA - IS, GS

User Activities:

Army - MI  
Navy - YD, SH

\* Changed