

MS28775 REV E NOTICE 1 53 ■ 9999912 0009845 8 ■

INCH-POUND

**NOTICE OF INACTIVATION
FOR NEW DESIGN**

**MS28775E
NOTICE 1
15 November 1989**

MILITARY STANDARD

**PACKING PREFORMED, HYDRAULIC
+275°F ("O" RING)**

**This notice should be filed in front of MS28775E
dated 23 March 1989**

**MS28775 is inactive for new design and is no longer used by the
Department of Defense except in procurement of replenishment spares as
necessary to maintain equipment in the field until obsolescence or wear
out.**

**Future designs should use MIL-P-83461/1, Packing, Preformed,
Petroleum Hydraulic Fluid Resistant, Improved Performance at 275°F
(135°C) Sizes and Tolerances.**

**Preparing Activity
Air Force - 11**

(Project 5330-0656)

AMSC N/A



FSC 5330

**DISTRIBUTION STATEMENT A: Approved for public release; distribution is
unlimited.**

THIS DOCUMENT CONTAINS 1 PAGES.

MS28775 REV E 53 9999912 0005438 8

E-53-03



SECTION A-A

FED. SUP CLASS
8330

TABLE I DYNAMIC OR STATIC USE

PART NUMBER	ID IN.		ID (mm)		T IN.		T (mm)		APPROX MASS	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	LB/100	Kg/100
HS28775-001	0.025	0.033	0.635	0.838	0.037	0.043	0.940	1.072	.001	.0004
HS28775-002	0.038	0.044	0.965	1.168	0.047	0.053	1.194	1.366	.003	.0014
HS28775-003	0.052	0.060	1.321	1.524	0.057	0.063	1.448	1.600	.005	.0023
HS28775-004	0.065	0.075	1.65	1.90	0.067	0.073	1.702	1.854	.008	.0036
HS28775-005	0.096	0.106	2.44	2.69	0.067	0.073	1.702	1.854	.010	.0045
HS28775-006	0.109	0.119	2.77	3.02	0.067	0.073	1.702	1.854	.010	.0045
HS28775-007	0.140	0.150	3.56	3.81	0.067	0.073	1.702	1.854	.012	.0054
HS28775-008	0.171	0.181	4.34	4.60	0.067	0.073	1.702	1.854	.014	.0064
HS28775-009	0.203	0.213	5.16	5.41	0.067	0.073	1.702	1.854	.016	.0073
HS28775-010	0.234	0.244	5.94	6.20	0.067	0.073	1.702	1.854	.017	.0077
HS28775-011	0.296	0.306	7.52	7.77	0.067	0.073	1.702	1.854	.021	.0095
HS28775-012	0.359	0.369	9.12	9.37	0.067	0.073	1.702	1.854	.024	.011
HS28775-110	0.357	0.367	9.07	9.32	0.100	0.106	2.540	2.692	.036	.025
HS28775-111	0.419	0.429	10.64	10.90	0.100	0.106	2.540	2.692	.063	.029
HS28775-112	0.482	0.492	12.24	12.50	0.100	0.106	2.540	2.692	.071	.032
HS28775-113	0.544	0.554	13.82	14.07	0.100	0.106	2.540	2.692	.079	.036
HS28775-114	0.607	0.617	15.42	15.67	0.100	0.106	2.540	2.692	.086	.039
HS28775-115	0.669	0.679	16.99	17.25	0.100	0.106	2.540	2.692	.093	.042
HS28775-116	0.732	0.742	18.59	18.85	0.100	0.106	2.540	2.692	.101	.046
HS28775-210	0.728	0.740	18.49	18.80	0.135	0.143	3.429	3.632	.191	.087
HS28775-211	0.790	0.802	20.07	20.37	0.135	0.143	3.429	3.632	.205	.093
HS28775-212	0.853	0.865	21.67	21.97	0.135	0.143	3.429	3.632	.219	.099
HS28775-213	0.915	0.927	23.24	23.55	0.135	0.143	3.429	3.632	.232	.105
HS28775-214	0.978	0.990	24.84	25.15	0.135	0.143	3.429	3.632	.246	.112
HS28775-215	1.040	1.052	26.42	26.72	0.135	0.143	3.429	3.632	.260	.118
HS28775-216	1.103	1.115	28.02	28.32	0.135	0.143	3.429	3.632	.274	.124
HS28775-217	1.165	1.177	29.59	29.90	0.135	0.143	3.429	3.632	.287	.130
HS28775-218	1.228	1.240	31.19	31.50	0.135	0.143	3.429	3.632	.302	.137
HS28775-219	1.290	1.302	32.77	33.07	0.135	0.143	3.429	3.632	.315	.143
HS28775-220	1.353	1.365	34.37	34.67	0.135	0.143	3.429	3.632	.328	.149
HS28775-221	1.415	1.427	35.94	36.25	0.135	0.143	3.429	3.632	.342	.155
HS28775-222	1.478	1.490	37.54	37.85	0.135	0.143	3.429	3.632	.356	.161
HS28775-325	1.465	1.485	37.21	37.72	0.205	0.215	5.21	5.46	.843	.382
HS28775-326	1.590	1.610	40.39	40.89	0.205	0.215	5.21	5.46	.906	.411
HS28775-327	1.715	1.735	43.56	44.07	0.205	0.215	5.21	5.46	.969	.440
HS28775-328	1.840	1.860	46.74	47.24	0.205	0.215	5.21	5.46	1.031	.468
HS28775-329	1.965	1.985	49.91	50.42	0.205	0.215	5.21	5.46	1.094	.496
HS28775-330	2.090	2.110	53.09	53.59	0.205	0.215	5.21	5.46	1.156	.524
HS28775-331	2.215	2.235	56.26	56.77	0.205	0.215	5.21	5.46	1.219	.553
HS28775-332	2.340	2.360	59.44	59.94	0.205	0.215	5.21	5.46	1.282	.582
HS28775-333	2.465	2.485	62.61	63.12	0.205	0.215	5.21	5.46	1.344	.610
HS28775-334	2.590	2.610	65.79	66.29	0.205	0.215	5.21	5.46	1.407	.638
HS28775-335	2.710	2.740	68.83	69.60	0.205	0.215	5.21	5.46	1.469	.666
HS28775-336	2.835	2.865	72.01	72.77	0.205	0.215	5.21	5.46	1.532	.695
HS28775-337	2.960	2.990	75.18	75.95	0.205	0.215	5.21	5.46	1.594	.723
HS28775-338	3.085	3.115	78.36	79.12	0.205	0.215	5.21	5.46	1.657	.752
HS28775-339	3.210	3.240	81.53	82.30	0.205	0.215	5.21	5.46	1.719	.780
HS28775-340	3.335	3.365	84.71	85.47	0.205	0.215	5.21	5.46	1.782	.808

(E) ENTIRE STANDARD REVISED

P.A. AIR FORCE 8 Other Civil ARMY-AV NAVY-AS AF-99	INTERNATIONAL INTEREST ABCC 17/87	TITLE PACKING, PREFORMED, HYDRAULIC, +275°F ("O" RING)	MILITARY STANDARD MS 28775
	(E)		
PROCUREMENT SPECIFICATION MIL-P-28732	SUPERSEDES MS28764	SHEET 1 OF 7	

DD FORM 1 SEP 77 672-1 (Coordinated)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

APPROVED 12 JUL 57 REVISED (A) 23 JUN 59 (B) 6 JUL 65 (C) 22 AUG 68 (D) 1 SEP 75 (E) 23 MAR 84

This military standard is approved by the Department and Agencies of the Department of Defense. Selection for all manufacturing and design applications and for repetitive use shall be made from this document.

User activities:

DSA-CS-
ARMY-AT

Review activities: ARMY-MI,AR
AIR FORCE-II
DSA-15

MS28775 REV E 53 9999912 0005439 T

FED. SUP CLASS
8880

TABLE I DYNAMIC OR STATIC USE

PART NUMBER	ID IN.		ID (mm)		T IN.		T (mm)		APPROX MASS	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	LB/100	Kg/100
MS28775-341	3.460	3.490	87.88	88.63	0.203	0.215	5.21	5.46	1.845	.837
MS28775-342	3.585	3.615	91.06	91.82	0.203	0.215	5.21	5.46	1.907	.865
MS28775-343	3.710	3.740	94.23	95.00	0.203	0.215	5.21	5.46	1.970	.894
MS28775-344	3.835	3.865	97.41	98.17	0.203	0.215	5.21	5.46	2.032	.922
MS28775-345	3.960	3.990	100.58	101.35	0.203	0.215	5.21	5.46	2.095	.950
MS28775-346	4.085	4.115	103.76	104.52	0.203	0.215	5.21	5.46	2.157	.978
MS28775-347	4.210	4.240	106.93	107.70	0.203	0.215	5.21	5.46	2.220	1.007
MS28775-348	4.335	4.365	110.11	110.87	0.203	0.215	5.21	5.46	2.282	1.035
MS28775-349	4.460	4.490	113.28	114.05	0.203	0.215	5.21	5.46	2.345	1.064
MS28775-425	4.460	4.490	113.28	114.05	0.269	0.281	6.83	7.14	4.077	1.849
MS28775-426	4.585	4.615	116.46	117.22	0.269	0.281	6.83	7.14	4.185	1.898
MS28775-427	4.710	4.740	119.63	120.40	0.269	0.281	6.83	7.14	4.292	1.947
MS28775-428	4.835	4.865	122.81	123.57	0.269	0.281	6.83	7.14	4.399	1.995
MS28775-429	4.960	4.990	125.98	126.75	0.269	0.281	6.83	7.14	4.506	2.044
MS28775-430	5.077	5.123	128.96	130.12	0.269	0.281	6.83	7.14	4.614	2.093
MS28775-431	5.202	5.248	132.13	133.30	0.269	0.281	6.83	7.14	4.721	2.141
MS28775-432	5.327	5.373	135.31	136.47	0.269	0.281	6.83	7.14	4.828	2.190
MS28775-433	5.452	5.498	138.48	139.65	0.269	0.281	6.83	7.14	4.935	2.239
MS28775-434	5.577	5.623	141.66	142.82	0.269	0.281	6.83	7.14	5.042	2.287
MS28775-435	5.702	5.748	144.83	146.00	0.269	0.281	6.83	7.14	5.150	2.336
MS28775-436	5.827	5.873	148.01	149.17	0.269	0.281	6.83	7.14	5.257	2.393
MS28775-437	5.952	5.998	151.18	152.35	0.269	0.281	6.83	7.14	5.364	2.433
MS28775-438	6.202	6.248	157.53	158.70	0.269	0.281	6.83	7.14	5.579	2.531
MS28775-439	6.452	6.498	163.88	165.06	0.269	0.281	6.83	7.14	5.794	2.628
MS28775-440	6.702	6.748	170.23	171.40	0.269	0.281	6.83	7.14	6.008	2.725
MS28775-441	6.952	6.998	176.58	177.75	0.269	0.281	6.83	7.14	6.223	2.823
MS28775-442	7.195	7.255	182.75	184.28	0.269	0.281	6.83	7.14	6.438	2.920
MS28775-443	7.445	7.505	189.10	190.63	0.269	0.281	6.83	7.14	6.652	3.017
MS28775-444	7.695	7.755	195.45	196.98	0.269	0.281	6.83	7.14	6.867	3.115
MS28775-445	7.945	8.005	201.80	203.33	0.269	0.281	6.83	7.14	7.081	3.212
MS28775-446	8.445	8.505	214.50	216.03	0.269	0.281	6.83	7.14	7.510	3.407
MS28775-447	8.945	9.005	227.20	228.73	0.269	0.281	6.83	7.14	7.940	3.602
MS28775-448	9.445	9.505	239.90	241.43	0.269	0.281	6.83	7.14	8.369	3.796
MS28775-449	9.945	10.005	252.60	254.13	0.269	0.281	6.83	7.14	8.798	3.991
MS28775-450	10.445	10.505	265.30	266.83	0.269	0.281	6.83	7.14	9.227	4.185
MS28775-451	10.945	11.005	278.00	279.53	0.269	0.281	6.83	7.14	9.656	4.380
MS28775-452	11.445	11.505	290.70	292.23	0.269	0.281	6.83	7.14	10.086	4.575
MS28775-453	11.945	12.005	303.40	304.93	0.269	0.281	6.83	7.14	10.515	4.770
MS28775-454	12.445	12.505	316.10	317.63	0.269	0.281	6.83	7.14	10.944	4.964
MS28775-455	12.945	13.005	328.80	330.33	0.269	0.281	6.83	7.14	11.373	5.159
MS28775-456	13.445	13.505	341.50	343.03	0.269	0.281	6.83	7.14	11.802	5.353
MS28775-457	13.945	14.005	354.20	355.73	0.269	0.281	6.83	7.14	12.231	5.548
MS28775-458	14.445	14.505	366.90	368.43	0.269	0.281	6.83	7.14	12.660	5.742
MS28775-459	14.945	15.005	379.60	381.13	0.269	0.281	6.83	7.14	13.090	5.933
MS28775-460	15.445	15.505	392.30	393.83	0.269	0.281	6.83	7.14	13.519	6.132

(E) ENTIRE STANDARD REVISED

P.A. AIR FORCE 62 Other Code ARMY - AV NAVY - AS AF - 99	INTERNATIONAL INTEREST ABCC 17/87 (E)	TITLE PACKING, PREFORMED, HYDRAULIC, + 275° F ("O" RING)	MILITARY STANDARD MS28775
PROCUREMENT SPECIFICATION MIL-P-20782	SUPERSEDES: MS28784	SHEET 2 OF 7	

DD FORM 672-1 (Coordinated)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

APPROVED 12 JUL 87 REVISED (E) FOR CHANGES SEE PAGES 1 THRU 7.

Dear activities: DSA-C3
ARMY-AT
Review activities: ARMY - MI, AR
AIR FORCE-11
DSA - 15

This military standard is approved by the Department and Agencies of the Department of Defense. Solicitation for all new engineering and design applications and for revisions shall be made from this document.

MS28775 REV E 53 999912 0005440 6

FED. SUP CLASS
8330

User activities: DSA-CS
ARMY-AI

Review activities: ARMY-MI, AR
AIR FORCE-II
DSA-IS

This military standard is approved by the Department and Agencies of the
Department of Defense. Selection for all manufacturing and design
applications and for repetitive use shall be made from this document.

TABLE H DYNAMIC OR STATIC USE (SEE NOTE 5)										
PART NUMBER	ID IN.		ID (mm)		T IN.		T (mm)		APPROX MASS	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	LB/100	Kg/100
MS28775-102	0.044	0.054	1.12	1.37	0.100	0.106	2.540	2.692	.018	.008
MS28775-103	0.076	0.086	1.93	2.18	0.100	0.106	2.540	2.692	.022	.010
MS28775-104	0.107	0.117	2.72	2.97	0.100	0.106	2.540	2.692	.026	.012
MS28775-105	0.138	0.148	3.51	3.76	0.100	0.106	2.540	2.692	.029	.013
MS28775-106	0.169	0.179	4.29	4.55	0.100	0.106	2.540	2.692	.034	.015
MS28775-107	0.201	0.211	5.11	5.36	0.100	0.106	2.540	2.692	.037	.017
MS28775-108	0.232	0.242	5.89	6.15	0.100	0.106	2.540	2.692	.041	.019
MS28775-109	0.294	0.304	7.47	7.72	0.100	0.106	2.540	2.692	.048	.022
MS28775-201	0.166	0.176	4.22	4.47	0.135	0.143	3.429	3.632	.068	.031
MS28775-202	0.229	0.239	5.82	6.07	0.135	0.143	3.429	3.632	.082	.037
MS28775-203	0.291	0.301	7.39	7.65	0.135	0.143	3.429	3.632	.095	.043
MS28775-204	0.354	0.364	8.99	9.25	0.135	0.143	3.429	3.632	.109	.049
MS28775-205	0.416	0.426	10.57	10.82	0.135	0.143	3.429	3.632	.123	.056
MS28775-206	0.479	0.489	12.17	12.42	0.135	0.143	3.429	3.632	.137	.062
MS28775-207	0.541	0.551	13.74	14.00	0.135	0.143	3.429	3.632	.150	.068
MS28775-208	0.604	0.614	15.34	15.60	0.135	0.143	3.429	3.632	.164	.074
MS28775-209	0.666	0.676	16.92	17.17	0.135	0.143	3.429	3.632	.178	.081
MS28775-309	0.407	0.417	10.34	10.59	0.205	0.215	5.21	5.46	.311	.141
MS28775-310	0.470	0.480	11.94	12.19	0.205	0.215	5.21	5.46	.343	.155
MS28775-311	0.532	0.542	13.51	13.77	0.205	0.215	5.21	5.46	.374	.170
MS28775-312	0.595	0.605	15.11	15.37	0.205	0.215	5.21	5.46	.405	.184
MS28775-313	0.657	0.667	16.69	16.94	0.205	0.215	5.21	5.46	.436	.198
MS28775-314	0.719	0.731	18.26	18.57	0.205	0.215	5.21	5.46	.468	.212
MS28775-315	0.781	0.793	19.84	20.14	0.205	0.215	5.21	5.46	.499	.226
MS28775-316	0.844	0.856	21.44	21.74	0.205	0.215	5.21	5.46	.530	.241
MS28775-317	0.906	0.918	23.01	23.32	0.205	0.215	5.21	5.46	.562	.255
MS28775-318	0.969	0.981	24.61	24.92	0.205	0.215	5.21	5.46	.593	.269
MS28775-319	1.031	1.043	26.19	26.49	0.205	0.215	5.21	5.46	.624	.283
MS28775-320	1.094	1.106	27.79	28.09	0.205	0.215	5.21	5.46	.656	.297
MS28775-321	1.156	1.168	29.36	29.67	0.205	0.215	5.21	5.46	.687	.312
MS28775-322	1.219	1.231	30.96	31.27	0.205	0.215	5.21	5.46	.718	.326
MS28775-323	1.281	1.293	32.54	32.84	0.205	0.215	5.21	5.46	.749	.340
MS28775-324	1.344	1.356	34.14	34.44	0.205	0.215	5.21	5.46	.781	.354

(E) ENTIRE STANDARD REVISED

P.A. AIR FORCE-82 Other Civil ARMY -AV NAVY-AS AF-88	INTERNATIONAL INTEREST	TITLE	MILITARY STANDARD	
	ABCC 17/87 (E)	PACKING, PREFORMED, HYDRAULIC, + 250° F ("O" RING)	MS28775	
	PROCUREMENT SPECIFICATION MIL-P-25732	SUPERSEDES	MS28764	SHEET 3 OF 7

DD FORM 672-1 (Coordinated)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

APPROVED 12 JUL 87 REVISED (E) FOR CHANGES SEE PAGES 1 THRU 7

MS28775 REV E 53 9999912 0005441 8

FED. SUP CLASS
5330

TABLE III STATIC USE ONLY (SEE NOTE 1)

PART NUMBER	ID IN.		ID (mm)		T IN.		T (mm)		APPROX MASS	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	LB/100	Kg/100
MS28775-013	0.421	0.431	10.69	10.93	0.067	0.073	1.702	1.854	.028	.013
MS28775-014	0.484	0.494	12.29	12.55	0.067	0.073	1.702	1.854	.031	.014
MS28775-015	0.546	0.556	13.87	14.12	0.067	0.073	1.702	1.854	.034	.015
MS28775-016	0.609	0.619	15.47	15.72	0.067	0.073	1.702	1.854	.034	.017
MS28775-017	0.671	0.681	17.04	17.30	0.067	0.073	1.702	1.854	.041	.019
MS28775-018	0.734	0.744	18.64	18.90	0.067	0.073	1.702	1.854	.045	.020
MS28775-019	0.795	0.807	20.19	20.50	0.067	0.073	1.702	1.854	.048	.022
MS28775-020	0.858	0.870	21.79	22.10	0.067	0.073	1.702	1.854	.052	.024
MS28775-021	0.920	0.932	23.37	23.67	0.067	0.073	1.702	1.854	.055	.025
MS28775-022	0.983	0.995	24.97	25.27	0.067	0.073	1.702	1.854	.059	.027
MS28775-023	1.045	1.057	26.54	26.85	0.067	0.073	1.702	1.854	.062	.028
MS28775-024	1.108	1.120	28.14	28.45	0.067	0.073	1.702	1.854	.066	.030
MS28775-025	1.170	1.182	29.72	30.02	0.067	0.073	1.702	1.854	.069	.031
MS28775-026	1.233	1.245	31.32	31.62	0.067	0.073	1.702	1.854	.073	.033
MS28775-027	1.295	1.307	32.89	33.20	0.067	0.073	1.702	1.854	.076	.034
MS28775-028	1.358	1.370	34.49	34.80	0.067	0.073	1.702	1.854	.080	.036
MS28775-117	0.793	0.805	20.14	20.45	0.100	0.106	2.540	2.692	.108	.049
MS28775-118	0.856	0.868	21.74	22.05	0.100	0.106	2.540	2.692	.116	.053
MS28775-119	0.918	0.930	23.32	23.62	0.100	0.106	2.540	2.692	.124	.056
MS28775-120	0.981	0.993	24.92	25.22	0.100	0.106	2.540	2.692	.131	.059
MS28775-121	1.043	1.055	26.49	26.80	0.100	0.106	2.540	2.692	.139	.063
MS28775-122	1.106	1.118	28.09	28.40	0.100	0.106	2.540	2.692	.146	.066
MS28775-123	1.168	1.180	29.67	29.97	0.100	0.106	2.540	2.692	.154	.070
MS28775-124	1.231	1.243	31.27	31.57	0.100	0.106	2.540	2.692	.161	.073
MS28775-125	1.293	1.305	32.84	33.15	0.100	0.106	2.540	2.692	.169	.077
MS28775-126	1.356	1.368	34.44	34.75	0.100	0.106	2.540	2.692	.176	.080
MS28775-127	1.418	1.430	36.02	36.32	0.100	0.106	2.540	2.692	.184	.083
MS28775-128	1.481	1.493	37.62	37.92	0.100	0.106	2.540	2.692	.191	.087
MS28775-129	1.539	1.559	39.09	39.60	0.100	0.106	2.540	2.692	.199	.090
MS28775-130	1.602	1.622	40.69	41.20	0.100	0.106	2.540	2.692	.207	.094
MS28775-131	1.664	1.684	42.27	42.77	0.100	0.106	2.540	2.692	.214	.097
MS28775-132	1.727	1.747	43.87	44.37	0.100	0.106	2.540	2.692	.222	.101
MS28775-133	1.789	1.809	45.44	45.95	0.100	0.106	2.540	2.692	.230	.104
MS28775-134	1.852	1.872	47.04	47.55	0.100	0.106	2.540	2.692	.236	.107
MS28775-135	1.915	1.935	48.64	49.15	0.100	0.106	2.540	2.692	.244	.111
MS28775-136	1.977	1.997	50.22	50.72	0.100	0.106	2.540	2.692	.252	.114
MS28775-137	2.040	2.060	51.82	52.32	0.100	0.106	2.540	2.692	.259	.117
MS28775-138	2.102	2.122	53.39	53.90	0.100	0.106	2.540	2.692	.267	.121
MS28775-139	2.165	2.185	54.99	55.50	0.100	0.106	2.540	2.692	.274	.124
MS28775-140	2.227	2.247	56.57	57.07	0.100	0.106	2.540	2.692	.282	.128
MS28775-141	2.290	2.310	58.17	58.67	0.100	0.106	2.540	2.692	.289	.131
MS28775-142	2.352	2.372	59.74	60.25	0.100	0.106	2.540	2.692	.297	.135
MS28775-143	2.415	2.435	61.34	61.85	0.100	0.106	2.540	2.692	.304	.138
MS28775-144	2.477	2.497	62.92	63.42	0.100	0.106	2.540	2.692	.312	.142
MS28775-145	2.540	2.560	64.52	65.02	0.100	0.106	2.540	2.692	.319	.145
MS28775-146	2.602	2.622	66.09	66.60	0.100	0.106	2.540	2.692	.327	.148
MS28775-147	2.660	2.690	67.56	68.33	0.100	0.106	2.540	2.692	.334	.152
MS28775-148	2.722	2.752	69.14	69.90	0.100	0.106	2.540	2.692	.342	.155
MS28775-149	2.785	2.815	70.74	71.50	0.100	0.106	2.540	2.692	.350	.159
MS28775-223	1.599	1.619	40.61	41.12	0.135	0.143	3.429	3.632	.383	.174
MS28775-224	1.724	1.744	43.79	44.30	0.135	0.143	3.429	3.632	.411	.186
MS28775-225	1.849	1.869	46.96	47.47	0.135	0.143	3.429	3.632	.438	.199
MS28775-226	1.974	1.994	50.14	50.65	0.135	0.143	3.429	3.632	.466	.211
MS28775-227	2.099	2.119	53.31	53.82	0.135	0.143	3.429	3.632	.493	.224
MS28775-228	2.224	2.244	56.49	57.00	0.135	0.143	3.429	3.632	.529	.240
MS28775-229	2.349	2.369	59.66	60.17	0.135	0.143	3.429	3.632	.543	.249
MS28775-230	2.474	2.494	62.84	63.35	0.135	0.143	3.429	3.632	.575	.261
MS28775-231	2.599	2.619	66.01	66.52	0.135	0.143	3.429	3.632	.603	.274
MS28775-232	2.719	2.749	69.06	69.82	0.135	0.143	3.429	3.632	.630	.286
MS28775-233	2.844	2.874	72.24	73.00	0.135	0.143	3.429	3.632	.657	.298
MS28775-234	2.969	2.999	75.41	76.17	0.135	0.143	3.429	3.632	.685	.311
MS28775-235	3.094	3.124	78.59	79.35	0.135	0.143	3.429	3.632	.712	.323
MS28775-236	3.219	3.249	81.76	82.52	0.135	0.143	3.429	3.632	.740	.336
MS28775-237	3.344	3.374	84.94	85.70	0.135	0.143	3.429	3.632	.767	.348
MS28775-238	3.469	3.499	88.11	88.87	0.135	0.143	3.429	3.632	.794	.360

P.A.
AIR FORCE - 8
Other Code
ARMY - AV
NAVY - AS
AF - 99

INTERNATIONAL
INTEREST
ASCC 17/87
(E)

TITLE
PACKING, PREFORMED,
HYDRAULIC, +275° F ("O" RING)

MILITARY STANDARD

MS28775

PROCUREMENT SPECIFICATION
MIL-P-26732

SUPERSEDES
MS28784

SHEET 4 OF 7

DD FORM 672-1 (Coordinated)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

(E) ENTIRE STANDARD REVISED

APPROVED 12 JUL 87 REVISED (E) FOR CHANGES SEE PAGES 1 THRU 7.

This military standard is approved by the Department and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

MS28775 REV E 53 9999912 0005442 T

FED. SUP CLASS
5330

TABLE III STATIC USE ONLY (SEE NOTE 1)

PART NUMBER	ID IN.		ID (mm)		T IN.		T (mm)		APPROX MASS	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	LB/100	Kg/100
MS28775-239	3.594	3.624	91.29	92.05	0.135	0.143	3.429	3.612	.822	.373
MS28775-240	3.719	3.749	94.46	95.22	0.135	0.143	3.429	3.612	.849	.385
MS28775-241	3.844	3.874	97.64	98.40	0.135	0.143	3.429	3.612	.877	.398
MS28775-242	3.969	3.999	100.81	101.57	0.135	0.143	3.429	3.612	.904	.411
MS28775-243	4.094	4.124	103.99	104.75	0.135	0.143	3.429	3.612	.932	.423
MS28775-244	4.219	4.249	107.16	107.92	0.135	0.143	3.429	3.612	.959	.435
MS28775-245	4.344	4.374	110.34	111.10	0.135	0.143	3.429	3.612	.986	.447
MS28775-246	4.469	4.499	113.51	114.27	0.135	0.143	3.429	3.612	1.014	.460
MS28775-247	4.594	4.624	116.69	117.45	0.135	0.143	3.429	3.612	1.041	.472

TABLE III STATIC USE ONLY (SEE NOTE 5)

PART NUMBER	ID-IN.		ID-(mm)		T-IN.		T-(mm)		APPROX MASS	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	LB/100	Kg/100
MS28775-029	1.479	1.499	37.57	38.07	0.067	0.073	1.702	1.854	.086	.039
MS28775-030	1.604	1.624	40.74	41.25	0.067	0.073	1.702	1.854	.094	.043
MS28775-031	1.729	1.749	43.92	44.42	0.067	0.073	1.702	1.854	.101	.046
MS28775-032	1.854	1.874	47.09	47.60	0.067	0.073	1.702	1.854	.108	.049
MS28775-033	1.979	1.999	50.27	50.77	0.067	0.073	1.702	1.854	.114	.052
MS28775-034	2.104	2.124	53.44	53.95	0.067	0.073	1.702	1.854	.121	.055
MS28775-035	2.229	2.249	56.62	57.12	0.067	0.073	1.702	1.854	.128	.058
MS28775-036	2.354	2.374	59.79	60.30	0.067	0.073	1.702	1.854	.135	.061
MS28775-037	2.479	2.499	62.97	63.47	0.067	0.073	1.702	1.854	.142	.064
MS28775-038	2.604	2.624	66.14	66.65	0.067	0.073	1.702	1.854	.149	.068
MS28775-039	2.724	2.754	69.19	69.95	0.067	0.073	1.702	1.854	.156	.071
MS28775-040	2.849	2.879	72.36	73.13	0.067	0.073	1.702	1.854	.163	.074
MS28775-041	2.974	3.004	75.54	76.30	0.067	0.073	1.702	1.854	.170	.077
MS28775-042	3.224	3.254	81.89	82.65	0.067	0.073	1.702	1.854	.184	.083
MS28775-043	3.474	3.504	88.24	89.00	0.067	0.073	1.702	1.854	.198	.090
MS28775-044	3.724	3.754	94.59	95.35	0.067	0.073	1.702	1.854	.212	.096
MS28775-045	3.974	4.004	100.94	101.70	0.067	0.073	1.702	1.854	.226	.102
MS28775-046	4.224	4.254	107.29	108.05	0.067	0.073	1.702	1.854	.240	.109
MS28775-047	4.474	4.504	113.64	114.40	0.067	0.073	1.702	1.854	.254	.115
MS28775-048	4.724	4.754	119.99	120.75	0.067	0.073	1.702	1.854	.267	.121
MS28775-049	4.966	5.012	126.14	127.30	0.067	0.073	1.702	1.854	.281	.127
MS28775-050	5.216	5.262	132.49	133.65	0.067	0.073	1.702	1.854	.295	.134
MS28775-150	2.847	2.877	72.31	73.08	0.100	0.106	2.540	2.692	.357	.162
MS28775-151	2.972	3.002	75.49	76.25	0.100	0.106	2.540	2.692	.372	.169
MS28775-152	3.222	3.252	81.84	82.60	0.100	0.106	2.540	2.692	.402	.181
MS28775-153	3.472	3.502	88.19	88.95	0.100	0.106	2.540	2.692	.462	.210
MS28775-154	3.722	3.752	94.54	95.30	0.100	0.106	2.540	2.692	.462	.210
MS28775-155	3.972	4.002	100.89	101.65	0.100	0.106	2.540	2.692	.492	.224
MS28775-156	4.222	4.252	107.24	108.00	0.100	0.106	2.540	2.692	.523	.237
MS28775-157	4.472	4.502	113.59	114.35	0.100	0.106	2.540	2.692	.553	.250
MS28775-158	4.722	4.752	119.94	120.70	0.100	0.106	2.540	2.692	.583	.264
MS28775-159	4.972	5.002	126.29	127.05	0.100	0.106	2.540	2.692	.613	.277
MS28775-160	5.214	5.260	132.44	133.60	0.100	0.106	2.540	2.692	.643	.290
MS28775-161	5.464	5.510	138.79	139.95	0.100	0.106	2.540	2.692	.673	.303
MS28775-162	5.714	5.760	145.14	146.30	0.100	0.106	2.540	2.692	.703	.316
MS28775-163	5.964	6.010	151.49	152.65	0.100	0.106	2.540	2.692	.733	.330
MS28775-164	6.214	6.260	157.84	159.00	0.100	0.106	2.540	2.692	.763	.343
MS28775-165	6.464	6.510	164.19	165.35	0.100	0.106	2.540	2.692	.793	.356
MS28775-166	6.714	6.760	170.54	171.70	0.100	0.106	2.540	2.692	.823	.370
MS28775-167	6.964	7.010	176.89	178.05	0.100	0.106	2.540	2.692	.853	.383
MS28775-168	7.207	7.267	183.06	184.58	0.100	0.106	2.540	2.692	.883	.400
MS28775-169	7.457	7.517	189.41	190.93	0.100	0.106	2.540	2.692	.913	.413
MS28775-170	7.707	7.767	195.76	197.28	0.100	0.106	2.540	2.692	.943	.426
MS28775-171	7.957	8.017	202.11	203.63	0.100	0.106	2.540	2.692	.973	.440
MS28775-172	8.207	8.267	208.46	209.98	0.100	0.106	2.540	2.692	1.003	.453
MS28775-173	8.457	8.517	214.81	216.33	0.100	0.106	2.540	2.692	1.033	.466
MS28775-174	8.707	8.767	221.16	222.68	0.100	0.106	2.540	2.692	1.064	.479
MS28775-175	8.957	9.017	227.51	229.03	0.100	0.106	2.540	2.692	1.094	.492
MS28775-176	9.207	9.267	233.86	235.38	0.100	0.106	2.540	2.692	1.124	.505
MS28775-177	9.457	9.517	240.21	241.73	0.100	0.106	2.540	2.692	1.154	.518
MS28775-178	9.707	9.767	246.56	248.08	0.100	0.106	2.540	2.692	1.184	.531

MS28775 REV E 53 9999912 0005443 1

FED. SUP CLASS
8880

TABLE IV STATIC USE ONLY (SEE NOTE 5)

PART NUMBER	ID IN.		ID (mm)		T IN.		T (mm)		APPROX MASS	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	LB/100	Kg/100
HS28775-248	4.719	4.749	119.86	120.62	0.135	0.143	3.429	3.632	1.068	.484
HS28775-249	4.844	4.874	123.04	123.80	0.135	0.143	3.429	3.632	1.076	.497
HS28775-250	4.969	4.999	126.21	126.97	0.135	0.143	3.429	3.632	1.123	.509
HS28775-251	5.086	5.132	129.18	130.35	0.135	0.143	3.429	3.632	1.151	.522
HS28775-252	5.211	5.257	132.36	133.53	0.135	0.143	3.429	3.632	1.178	.534
HS28775-253	5.336	5.382	135.53	136.70	0.135	0.143	3.429	3.632	1.206	.547
HS28775-254	5.461	5.507	138.71	139.88	0.135	0.143	3.429	3.632	1.233	.559
HS28775-255	5.586	5.632	141.88	143.05	0.135	0.143	3.429	3.632	1.260	.572
HS28775-256	5.711	5.757	145.06	146.23	0.135	0.143	3.429	3.632	1.288	.584
HS28775-257	5.836	5.882	148.23	149.40	0.135	0.143	3.429	3.632	1.315	.596
HS28775-258	5.961	6.007	151.41	152.58	0.135	0.143	3.429	3.632	1.343	.609
HS28775-259	6.211	6.257	157.76	158.93	0.135	0.143	3.429	3.632	1.397	.634
HS28775-260	6.461	6.507	164.11	165.28	0.135	0.143	3.429	3.632	1.452	.659
HS28775-261	6.711	7.757	170.46	171.63	0.135	0.143	3.429	3.632	1.507	.684
HS28775-262	6.961	7.007	176.81	177.98	0.135	0.143	3.429	3.632	1.562	.708
HS28775-263	7.204	7.264	182.98	184.51	0.135	0.143	3.429	3.632	1.617	.733
HS28775-264	7.454	7.514	189.33	190.86	0.135	0.143	3.429	3.632	1.672	.758
HS28775-265	7.704	7.764	195.68	197.21	0.135	0.143	3.429	3.632	1.726	.783
HS28775-266	7.954	8.014	202.03	203.56	0.135	0.143	3.429	3.632	1.781	.808
HS28775-267	8.204	8.264	208.38	209.91	0.135	0.143	3.429	3.632	1.836	.833
HS28775-268	8.454	8.514	214.73	216.26	0.135	0.143	3.429	3.632	1.891	.858
HS28775-269	8.704	8.764	221.08	222.61	0.135	0.143	3.429	3.632	1.946	.883
HS28775-270	8.954	9.014	227.43	228.96	0.135	0.143	3.429	3.632	2.000	.907
HS28775-271	9.204	9.264	233.78	235.31	0.135	0.143	3.429	3.632	2.055	.932
HS28775-272	9.454	9.514	240.13	241.66	0.135	0.143	3.429	3.632	2.110	.957
HS28775-273	9.704	9.764	246.48	248.01	0.135	0.143	3.429	3.632	2.165	.982
HS28775-274	9.954	10.014	252.83	254.36	0.135	0.143	3.429	3.632	2.220	1.007
HS28775-275	10.454	10.514	265.53	267.06	0.135	0.143	3.429	3.632	2.329	1.056
HS28775-276	10.954	11.014	278.23	279.76	0.135	0.143	3.429	3.632	2.439	1.106
HS28775-277	11.454	11.514	290.93	292.46	0.135	0.143	3.429	3.632	2.549	1.156
HS28775-278	11.954	12.014	303.63	305.16	0.135	0.143	3.429	3.632	2.658	1.206
HS28775-279	12.954	13.014	329.03	330.56	0.135	0.143	3.429	3.632	2.878	1.305
HS28775-280	13.954	14.014	354.43	355.96	0.135	0.143	3.429	3.632	3.097	1.405
HS28775-281	14.954	15.014	379.83	381.36	0.135	0.143	3.429	3.632	3.317	1.505
HS28775-282	15.910	16.000	404.11	406.40	0.135	0.143	3.429	3.632	3.531	1.602
HS28775-283	16.910	17.000	429.51	431.80	0.135	0.143	3.429	3.632	3.751	1.701
HS28775-284	17.910	18.000	454.91	457.20	0.135	0.143	3.429	3.632	3.968	1.800
HS28775-350	4.585	4.615	116.46	117.22	0.205	0.215	5.21	5.46	2.412	1.094
HS28775-351	4.710	4.740	119.63	120.40	0.205	0.215	5.21	5.46	2.474	1.122
HS28775-352	4.835	4.865	122.81	123.57	0.205	0.215	5.21	5.46	2.537	1.151
HS28775-353	4.960	4.990	125.98	126.75	0.205	0.215	5.21	5.46	2.600	1.179
HS28775-354	5.077	5.123	128.96	130.12	0.205	0.215	5.21	5.46	2.662	1.207
HS28775-355	5.202	5.248	132.13	133.30	0.205	0.215	5.21	5.46	2.725	1.236
HS28775-356	5.327	5.373	135.31	136.47	0.205	0.215	5.21	5.46	2.788	1.265
HS28775-357	5.452	5.498	138.48	139.65	0.205	0.215	5.21	5.46	2.851	1.293
HS28775-358	5.577	5.623	141.66	142.82	0.205	0.215	5.21	5.46	2.913	1.321
HS28775-359	5.702	5.748	144.83	146.00	0.205	0.215	5.21	5.46	2.976	1.350
HS28775-360	5.827	5.873	148.01	149.17	0.205	0.215	5.21	5.46	3.038	1.378
HS28775-361	5.952	5.998	151.18	152.35	0.205	0.215	5.21	5.46	3.101	1.407
HS28775-362	6.202	6.248	157.53	158.70	0.205	0.215	5.21	5.46	3.226	1.463
HS28775-363	6.452	6.498	163.88	165.06	0.205	0.215	5.21	5.46	3.352	1.520
HS28775-364	6.702	6.748	170.23	171.40	0.205	0.215	5.21	5.46	3.477	1.577
HS28775-365	6.952	6.998	176.58	177.75	0.205	0.215	5.21	5.46	3.603	1.634
HS28775-366	7.195	7.255	182.76	184.28	0.205	0.215	5.21	5.46	3.728	1.691
HS28775-367	7.445	7.505	189.10	190.63	0.205	0.215	5.21	5.46	3.854	1.748
HS28775-368	7.695	7.755	195.45	196.98	0.205	0.215	5.21	5.46	3.979	1.805
HS28775-369	7.945	8.005	201.80	203.33	0.205	0.215	5.21	5.46	4.104	1.862
HS28775-370	8.195	8.255	208.15	209.68	0.205	0.215	5.21	5.46	4.229	1.918
HS28775-371	8.445	8.505	214.50	216.03	0.205	0.215	5.21	5.46	4.355	1.975
HS28775-372	8.695	8.755	220.85	222.38	0.205	0.215	5.21	5.46	4.480	2.032
HS28775-373	8.945	9.005	227.20	228.73	0.205	0.215	5.21	5.46	4.605	2.089
HS28775-374	9.195	9.255	233.55	235.08	0.205	0.215	5.21	5.46	4.731	2.146
HS28775-375	9.445	9.505	239.90	241.43	0.205	0.215	5.21	5.46	4.856	2.203

ENTIRE STANDARD REVISED

P.A. AIR FORCE-82 Other Cust ARMY-AV NAVY-AB AF-99	INTERNATIONAL INTEREST ABCC 17/87 (E)	TITLE PACKING, PREFORMED, HYDRAULIC, +275°F ("O" RING)	MILITARY STANDARD	
			MS28775	
PROCUREMENT SPECIFICATION MIL - P - 28782		SUPERSEDES: MS28784	SHEET 6 OF 7	

DD FORM 672-1 (Coordinated)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

APPROVED 12 JUL 57 REVISED (E) FOR CHANGES SEE PAGES 1 THRU 7.

Activities: DSA - CS
ARMY - AT
DSA - IS
Review activities: ARMY - MI, AR
AIR FORCE - II

This entry is approved by the Department and ADDRESS OF THE
SUBMITTER OF THE ENTRY. Selection for all engineering and design
applications and for retention use shall be made from this document.

MS28775 REV E 53 9999912 0005444 3

FED. SUP CLASS
5330

TABLE IV STATIC USE ONLY (SEE NOTE 5)

PART NUMBER	ID IN.		ID (mm)		T IN.		T (mm)		APPROX MASS	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	LB/100	Kg/100
MS28775-376	9.695	9.755	244.25	247.78	0.205	0.215	5.21	5.46	4.981	2.259
MS28775-377	9.945	10.006	252.60	254.13	0.205	0.215	5.21	5.46	5.107	2.317
MS28775-378	10.445	10.505	265.30	266.83	0.205	0.215	5.21	5.46	5.358	2.430
MS28775-379	10.945	11.006	278.00	279.53	0.205	0.215	5.21	5.46	5.608	2.544
MS28775-380	11.445	11.505	290.70	292.23	0.205	0.215	5.21	5.46	5.859	2.658
MS28775-381	11.945	12.005	303.40	304.93	0.205	0.215	5.21	5.46	6.110	2.771
MS28775-382	12.445	12.505	316.10	317.63	0.205	0.215	5.21	5.46	6.361	2.884
MS28775-383	12.945	13.005	328.80	330.33	0.205	0.215	5.21	5.46	6.611	2.997
MS28775-384	13.445	13.505	341.50	343.03	0.205	0.215	5.21	5.46	6.861	3.110
MS28775-385	13.945	14.005	354.20	355.73	0.205	0.215	5.21	5.46	7.111	3.223
MS28775-386	14.445	14.505	366.90	368.43	0.205	0.215	5.21	5.46	7.361	3.336
MS28775-387	14.945	15.005	379.60	381.13	0.205	0.215	5.21	5.46	7.611	3.449
MS28775-388	15.445	15.505	392.30	393.83	0.205	0.215	5.21	5.46	7.861	3.562
MS28775-389	15.945	16.005	405.00	406.53	0.205	0.215	5.21	5.46	8.111	3.675
MS28775-390	16.445	16.505	417.70	419.23	0.205	0.215	5.21	5.46	8.361	3.788
MS28775-391	16.945	17.005	430.40	431.93	0.205	0.215	5.21	5.46	8.611	3.901
MS28775-392	17.445	17.505	443.10	444.63	0.205	0.215	5.21	5.46	8.861	4.014
MS28775-393	17.945	18.005	455.80	457.33	0.205	0.215	5.21	5.46	9.111	4.127
MS28775-394	18.445	18.505	468.50	470.03	0.205	0.215	5.21	5.46	9.361	4.240
MS28775-395	18.945	19.005	481.20	482.73	0.205	0.215	5.21	5.46	9.611	4.353
MS28775-461	19.445	19.505	493.90	495.43	0.269	0.281	6.83	7.14	10.111	4.586
MS28775-462	19.945	20.005	506.60	508.13	0.269	0.281	6.83	7.14	10.361	4.700
MS28775-463	20.445	20.505	519.30	520.83	0.269	0.281	6.83	7.14	10.611	4.813
MS28775-464	20.945	21.005	532.00	533.53	0.269	0.281	6.83	7.14	10.861	4.926
MS28775-465	21.445	21.505	544.70	546.23	0.269	0.281	6.83	7.14	11.111	5.039
MS28775-466	21.945	22.005	557.40	558.93	0.269	0.281	6.83	7.14	11.361	5.152
MS28775-467	22.445	22.505	570.10	571.63	0.269	0.281	6.83	7.14	11.611	5.265
MS28775-468	22.945	23.005	582.80	584.33	0.269	0.281	6.83	7.14	11.861	5.378
MS28775-469	23.445	23.505	595.50	597.03	0.269	0.281	6.83	7.14	12.111	5.491
MS28775-470	23.945	24.005	608.20	609.73	0.269	0.281	6.83	7.14	12.361	5.604
MS28775-471	24.445	24.505	620.90	622.43	0.269	0.281	6.83	7.14	12.611	5.717
MS28775-472	24.945	25.005	633.60	635.13	0.269	0.281	6.83	7.14	12.861	5.830
MS28775-473	25.445	25.505	646.30	647.83	0.269	0.281	6.83	7.14	13.111	5.943
MS28775-474	25.945	26.005	659.00	660.53	0.269	0.281	6.83	7.14	13.361	6.056
MS28775-475	26.445	26.505	671.70	673.23	0.269	0.281	6.83	7.14	13.611	6.169

- (1) O-RING SIZES -.013 THROUGH -.28, -.117 THROUGH -.149 AND -.223 THROUGH -.247 ARE INTENDED ONLY FOR USE AS STATIC SEALS, AND ARE NOT TO BE USED IN APPLICATIONS WITH RECIPROCATING OR ROTARY INVOLVEMENT.
 - (2) EXAMPLE OF PART NO. MS28775-211 - PACKING WITH NOMINAL ID DIA .796 IN., T DIA .139 IN., OR 20.22 MM ID DIA, 3.530 MM T DIA.
 - (3) RINGS MAY BE OFF-REGISTER, DUE TO HOLD MISALIGNMENT, NOT TO EXCEED 0.003 INCH, PROVIDED ALL CROSS-SECTIONAL DIAMETERS, INCLUDING THE PROTRUSIONS (FLASH EXCLUDED) OF BOTH HALVES, WHERE APPLICABLE, SATISFY "T" DIMENSIONS.
 - (4) CERTAIN PROVISION (DIMENSIONS FOR SIZES -.001 THRU -.050, -.106 THRU -.178, -.210 THRU -.281, -.325 THRU -.349, -.425 THRU -.460) OF THIS STANDARD ARE THE SUBJECT OF INTERNATIONAL STANDARDIZATION AGREEMENT ASQC AIR STD 17/27 AND NATO STANAG 3444. WHEN REVISION OR CANCELLATION OF THIS STANDARD IS PROPOSED WHICH WILL EFFECT OR VIOLATE THE INTERNATIONAL AGREEMENT CONCERNED, THE PREPARING ACTIVITY WILL TAKE APPROPRIATE RECONCILIATION ACTION THROUGH INTERNATIONAL CHANNELS, INCLUDING DEPARTMENTAL STANDARDIZATION OFFICES, IF REQUIRED.
 - (5) THESE O-RING SIZES DO NOT MEET THE STANDARDS OF MIL-G-5514 AND ARE INTENDED FOR NON-STANDARD APPLICATIONS. THEY ARE INACTIVE FOR NEW DESIGN.
- FOR DESIGN PURPOSES, THIS STANDARD TAKES PRECEDENCE OVER PROCUREMENT DOCUMENTS REFERENCED HEREIN. REFERENCED DOCUMENTS SHALL BE OF THE ISSUE IN EFFECT ON DATE OF INVITATIONS FOR BID OR REQUEST FOR PROPOSAL, EXCEPT THAT REFERENCED ADOPTED INDUSTRY DOCUMENTS SHALL GIVE THE DATE OF THE ISSUE ADOPTED.

ENTIRE STANDARD REVISED

P.A. AIR FORCE 62 Other Code ARMY-AV NAVY-AS AF-99	INTERNATIONAL INTEREST ASQC 17/87 E	TITLE PACKING, PREFORMED, HYDRAULIC, +275°F ("O" RING)	MILITARY STANDARD MS28775 SHEET 7 OF 7
PROCUREMENT SPECIFICATION MIL-P-26732		SUPERMODEL MS28784	

DD FORM 672-1 (Coordinated)

PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE.

PROJECT 5330-0568

U.S. GOVERNMENT PRINTING OFFICE: 1984 - 706-040/A

Information Handling Services
July 22, 1999 05:24:30

APPROVED 12 JUL 97 REVISED (E) FOR CHANGES SEE PAGES 1 THRU 7.

This military standard is approved by the Department and members of the Department of Defense. Submission for all engineering and design applications and for repetitive use shall be made from this document.

User activities: DSA-CS
ARMY-AI

Review activities: ARMY-MI,AR
AIR FORCE-11
DSA-15